DST #1 EUMONT QUEEN 3440-3550.
TOOL OPEN 60 FT PU DST. REC 603. SW. NO GAS X NO OIL.
INITIAL HYDRO 1844 5" PREFLOW 118 PSI TO 203#.
90" ISIP 520#. 60" FFP 225#-339#.
120" FSIP 412#. FINAL HYDRO 1833#. REC IN BTM HOLE
SAMPLES. 2000 CC SW. PRS 260#. 0.3 CU FT GAS.
SW RESISTIVITY .05 AT 75. CHLORIDES 140000 PPM.
PIT MUD SAMPLE .04 AT 75 CHLORIDES 155000 PPM.

LAND OFFICE			State
PERATOR			3, State Cit & Gds Ledse No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM & A PROPOSALS TO BRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. SE MAPPLICATION FOR PERM Y - 11 (FORM C-101) FOR SUCH PHOPOSALS.)			7, Unit Agreement Name
OIL X CAS C	OTHER•		7. CHIC Adirement Isdine
. Name of Sperator Amoco Production Company			8. Farm or Lease Name McQuatters
. Attiress of C; erator			9. Well No.
P. O. Box 68, Hobbs, NM 88240			3 10. Field and Pool, or Wildcat
	North North	LINE AND 2230 FEET FROM	Hardy Blinebry
East LINE, SECTIO		RANGE 36-E NAPAL	
	15, Elevation (Show whethe 3538 GR	er DF, RT, GR, etc.)	12. County Lea
Check A	111111	Nature of Notice, Report or Oth	
NOTICE OF IN	ITENTION TO:	SUBSEQUENT	REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
PULL OR ALTER CASING	CHANGE PLANS	COMMENCE DRILLING OPNS X	PLUG AND ABANDONMENT
POLL ON ALTER CASING		OTHER	
] [
OTHER			
	erations (Clearly state all pertinent de	etails, and give pertinent dates, including e	estimated date of starting any proposed
. T. Descrite Fragosed or Completed Op worky SEE RULE 1103.		Letails, and give pertinent dates, including of the let at 9:30	
On 7-4-79 Verna Drill	ing Co. (Rig #12) spudd		a.m. Drilled to a TD
On 7-4-79 Verna Drill of 1264' and ran 13-3	ing Co. (Rig #12) spudd /8" 48# casing set at 1	led a 17-1/2" hole at 9:30	a.m. Drilled to a TD
On 7-4-79 Verna Drill of 1264' and ran 13-3	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1	led a 17-1/2" hole at 9:30	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m.	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1 7-5-79. WOC 18 hrs. T	led a 17-1/2" hole at 9:30 263'. Cemented with 700: 50 SX Incor with 2% CACL.	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1 7-5-79. WOC 18 hrs. T	led a 17-1/2" hole at 9:30 263'. Cemented with 700: 50 SX Incor with 2% CACL.	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m.	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1 7-5-79. WOC 18 hrs. T	led a 17-1/2" hole at 9:30 263'. Cemented with 700: 50 SX Incor with 2% CACL.	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m.	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1 7-5-79. WOC 18 hrs. T	led a 17-1/2" hole at 9:30 263'. Cemented with 700: 50 SX Incor with 2% CACL.	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m.	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1 7-5-79. WOC 18 hrs. T	led a 17-1/2" hole at 9:30 263'. Cemented with 700: 50 SX Incor with 2% CACL.	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m.	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1 7-5-79. WOC 18 hrs. T	led a 17-1/2" hole at 9:30 263'. Cemented with 700: 50 SX Incor with 2% CACL.	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m.	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1 7-5-79. WOC 18 hrs. T	led a 17-1/2" hole at 9:30 263'. Cemented with 700: 50 SX Incor with 2% CACL.	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m.	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nac1/SX. Tailed in 1 7-5-79. WOC 18 hrs. T nd resumed drilling.	led a 17-1/2" hole at 9:30 263'. Cemented with 700 50 SX Incor with 2% CACL. ested casing with 1000# fo	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m. Reduced hole to 11" a	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nacl/SX. Tailed in 1 7-5-79. WOC 18 hrs. T nd resumed drilling.	led a 17-1/2" hole at 9:30 263'. Cemented with 700 50 SX Incor with 2% CACL. ested casing with 1000# for the formy knowledge and belief.	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX.
On 7-4-79 Verna Drill of 1264' and ran 13-3 35 SX Econolite and 6 Plug down 10:25 p.m. Reduced hole to 11" at	ing Co. (Rig #12) spudd /8" 48# casing set at 1 # Nacl/SX. Tailed in 1 7-5-79. WOC 18 hrs. T nd resumed drilling.	led a 17-1/2" hole at 9:30 263'. Cemented with 700 50 SX Incor with 2% CACL. ested casing with 1000# fo	a.m. Drilled to a TD SX Class C cement with Circulated 25 SX. or 30 min. Test OK.

0+4-NMOCD, H; 1-Hou; 1-Susp; 1-BD