

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
 State Fee
 5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE APPLICATION FOR PERMIT TO DRILL C-101 FOR SUCH PROPOSALS.)

1. OIL WELL GAS WELL OTHER- **South Penrose Skelly Unit**

2. Name of Operator **Gulf Oil Corporation**

3. Address of Operator **Box 670, Hobbs, New Mexico 88240**

4. Location of Well
 UNIT LETTER **H** **1980** FEET FROM THE **North** LINE AND **660** FEET FROM
 THE **East** LINE, SECTION **9** TOWNSHIP **22-S** RANGE **37-E** N.M.P.M.

7. Unit Agreement Name
 8. Form or Lease Name
 9. Well No. **163**
 10. Field and Pool, or Wildcat **Penrose Skelly**

15. Elevation (Show whether DF, RT, CR, etc.) **3431' GL**

12. County **Lea**

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
FULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Revised C-103 to Plug & Abandon</u> <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3739' TD.
 Pull producing equipment. Set CI BP at approximately 3575' and cap with 7 sacks, 35', of cement to 3740'. Load hole with abandonment mud. Perforate 7" casing at 1300' and squeeze with a minimum of 260 sacks of cement and attempt to circulate cement to surface outside 7" casing. Spot 10 sack cement plug from 50' to surface. Install dry hole marker and clean location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED G. F. Berlin TITLE Area Engineer DATE December 20, 1976

APPROVED BY Geologist TITLE Geologist DATE DEC 21 1976

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

1912 575

OLYMPIA, WASH. DIST. DIV.
MAY 11 1912