

**INSTRUCTIONS**

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

**INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE**

**Southeastern New Mexico**

**Northwestern New Mexico**

T. Anhy _____ 1180'	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____ 1274'	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____ 2496'	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2629'	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____ 2780'	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____ 3170'	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

**FORMATION RECORD (Attach additional sheets if necessary)**

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
1180'	1274'	94'	Anhydrite.				
1274'	2496'	1222'	Salt w/Anhydrite stringers.				
2496'	2629'	133'	Sdy. Dolomite and Anhydrite.				
2629'	2780'	151'	Dolomite w/Sand Stringers (Yates).				
2780'	3170'	390'	Dolomite, Anhydrite, and Sand (Seven Rivers).				
3170'	3571'	401'	Sdy. Dolomite, Anhydrite and Sand (Queen).				
3571'	3675'	104'	Dolomitic and Anhydritic Sand (Penrose).				
All measurements RKB.							