

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oils. Div.  
P.O. Box 1980  
Hobbs, NM 88241

FORM APPROVED  
Bureau No. 1004-0135  
Expires: March 31, 1993  
5. Lease Designation and Serial No.  
8910084910 - NMLCO62368

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

Oil Well  Gas Well  Other

2. Name of Operator

OXY USA Inc.

16696

3. Address and Telephone No.

P.O. Box 50250 Midland, TX 79710-0250

915-685-5717

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2323 FSL 990 FEL NESE (I) Sec 5 T25S R38E

7. If Unit or CA, Agreement Designation

W. Dollarhide Qn Sd Unit  
008596

8. Well Name and No.

64

9. API Well No.

30-025-12392

10. Field and Pool, or Exploratory Area

Dollarhide Queen

11. Country or Parish, State

Lea NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- Notice of Intent  
 Subsequent Report  
 Final Abandonment Notice

TYPE OF ACTION

- Abandonment  
 Recompletion  
 Plugging Back  
 Casing Repair  
 Altering Casing  
 Other \_\_\_\_\_  
 Change of Plans  
 New Construction  
 Non-Routine Fracturing  
 Water Shut-Off  
 Conversion to Injection  
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD - 3746'

NOTIFY BLM OF P&A. MIRU PU 3/13/96, ND WH, NU BOP. RIH & TAG CIBP @ 3540', POOH TO 3510', SPOT 10sx CL C CMT, M&P 9.5# MUD-LADEN BW, POOH TO 2606'. SPOT 25sx CL C CMT PLUG @ 2606-2506', POOH TO 2500', M&P 9.5# MUD-LADEN BW. POOH TO 1325', SPOT 25sx CL C CMT PLUG @ 1325-1225', M&P 9.5# MUD-LADEN BW. POOH TO 415', SPOT 35sx CL C CMT PLUG @ 415-315', POOH, WOC. RIH & TAG CMT @ 300', POOH TO 50', SPOT 10sx CL C CMT PLUG TO SURF. NDBOP, RDP-3/14/96, CUTOFF WH, CLEAN LOCATION & BACKFILL ALL PITS, INSTALL DH MARKER. ANDY CORTEZ W/ BLM WITNESSED PLUGGING PROCEDURES.

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed David Stewart Title Regulatory Analyst Date 3/7/97

(This space for Federal or State office use)

Approved by (ORIG. SGD.) DAVID R. GLASS Title PETROLEUM ENGINEER Date MAR 13 1997

Conditions of approval, if any:

*[Handwritten signature]*

