

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUBMIT IN THIS (Other Instructions apply side)

11

Form Approval: Bureau Form No. 47-11111-1 5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

LC-030168 (b)

6. DEED, ASSIGNMENT OR TRUST NAME

1. OIL WELL [X] GAS WELL [] OTHER []

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR Continental Oil Company

8. FARM OR LEASE NAME

EAVES B-1

3. ADDRESS OF OPERATOR P. O. Box 460, Hobbs, New Mexico 88240

9. WELL NO.

10

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface

10. FIELD AND FOOT, OR WILDCAT

SCARBOROUGH VATES 7BIVE

660' FNL + 1980' FWL of Sec 31, T-265,

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 31, T-265, R-37E

R-37E, in Lea County, N. Mex.

14. PERMIT NO.

15. FINANCINGS (Show whether DF, EF, CR, etc.)

2935' DF

12. COUNTY OR PARISH

Lea

13. STATE

N. MEX.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF []

PULL OR ALTER CASING []

WATER SHUT-OFF []

REPAIRING WELL []

FRACURE TREAT []

MULTIPLE COMPLETION []

FRACURE TREATMENT []

ALTERING CASING []

SHOOT OR ACIDIZE []

ABANDON* []

SHOOTING OR ACIDIZING [X]

ABANDONMENT* []

REPAIR WELL []

CHANGE PLANS []

(Other) Perforate add. pay [X]

(Other)

(NOTE: Report results of multiple completion on Well Completion or Reconpletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following work was performed on this well.

Perforated 4 1/2" casing with one SSPF at 3170', 83, 92, 96, 3202, 19 + 24. Treated perms with 5,500 gals 15% LSTNE. Found 4 1/2" casing parted at 1267'. Ran C.I.B.P and set at 3210' with 1/2 sack cement on top. Perforated casing at 1277' with 2 holes, squeezed perms + casing leak with 200 sacks class C cement. Drilled out cement and cleaned out to 3210' PBD. Placed well on test. Treated well from 11-10-69 to 2-5-70. Final test - pumped 580 + 233 Bu in 24 hrs. well shut-in on 2-10-70

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Adm. Section Chief

DATE 2-11-70

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

TITLE

USGS-5 FILE

77 24, Part 1

*See Instructions on Reverse Side

