

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-10272

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name West Dollarhide Queen Sand Unit
2. Name of Operator Sirgo-Collier, Inc.	8. Farm or Lease Name
3. Address of Operator P. O. Box 3531, Midland, Texas 79702	9. Well No. 116
4. Location of well UNIT LETTER <u>A</u> <u>100</u> FEET FROM THE <u>North</u> LINE AND <u>50</u> FEET FROM THE <u>East</u> LINE, SECTION <u>6</u> TOWNSHIP <u>25S</u> RANGE <u>38E</u> NMPM.	10. Field and Pool, or WHdcat Dollarhide Queen
15. Elevation (Show whether DF, RT, GR, etc.) 3125' GL 3136.5' KB	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Spud, cement surface & prod. casing</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-17-88 Spudded with 12-1/4" bit to TD of 410'. Ran 10 joints 8-5/8" 24# casing to 405'. Cemented with 250 sx Class "C" with 2% CaCl2. PD 3:00 pm. Circulated 56 sx.

4-18-88 WOC 18 hours. Tested BOP and casing to 800# for 30 minutes. Tested okay. Drilled out with 7-7/8" bit.

4-22-88 TD 3904'

4-23-88 Ran 181 joints of 5-1/2" 17# casing to 3904'. Cemented with 560 sx Western Light cement with 1/4# flocele + 15# salt, tailed with 200 sx Class "C" with 2% CaCl2. PD 4:15 am. Circulated 115 sx.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Amy L. Whitley TITLE Agent DATE May 3, 1988

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE MAY 10 1988

CONDITIONS OF APPROVAL, IF ANY: