

COBRA OIL & GAS CORPORATION
 STATE 30 #1 – WELLBORE SCHEMATIC
 UNIT B, 660' FNL & 1,980' FEL
 SECTION 30, T24S–R33E
 LEA COUNTY, NEW MEXICO

Set 10 sx plug
 @ surface

Set 50 sx plug
 700' – 600'

16" csg set @ 645' with 680 sx of cmt
 Hole size: 20" – TOC @ surface by circ.

Set 50 sx plug
 2600' – 2500'

Set 50 sx plug
 5050' – 4950'

10 3/4" csg set @ 5000' with 3535 sx of cmt
 Hole size: 14 3/4" – TOC @ surface by circ.

Cut off 7 5/8"
 csg @ +/- 9500'
 set 35 sx plug
 9550' – 9450'

Set 35 sx plug
 7500' – 7400'

Set 25 sx plug
 10200' – 10100'

Perf 10284' – 10326'

Cut off tbg @ 10642' – Set 26 sx cmt plug from
 10642' – 10512' – Tag PBTD @ 10567'

7 5/8" csg set @ 13135' with 1600 sx of cmt
 Hole size: 9 1/2" – TOC +/- 10110' by CBL

Set CIBP @ 13150' w/25' cmt on top
 Perf 13218' – 13338'

Set CIBP @ 14700' w/25' cmt on top
 Perf 14788' – 14795'

Set CIBP @ 15400', w/27' cmt on top
 Perf 15431' – 15530'

Total depth – 15585'. 2 7/8" tbg set
 @ 15556' with 675 sacks of cmt.
 TOC +/- 11000'

