

RECORD OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3554 feet, and from _____ feet to _____ feet.
 Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing Sept. 11, 1957
 OIL WELL: The production during the first 24 hours was 62.4 barrels of liquid of which 62 % was oil; 10 % was emulsion; 19 % water; and _____ % was sediment. A.P.I. Gravity 28.9
 GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of liquid Hydrocarbon. Shut in Pressure _____ lbs.
 Length of Time Shut in _____

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy.....	<u>1090</u>	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	<u>1190</u>	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	<u>2705</u>	T. Montoya.....	T. Farmington.....
T. Yates.....	<u>2885</u>	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	<u>3170</u>	T. McKee.....	T. Menefee.....
T. Queen.....	<u>3502</u>	T. Ellenburger.....	T. Point Lookout.....
T. Grayburg.....		T. Gr. Wash.....	T. Mancos.....
T. San Andres.....		T. Granite.....	T. Dakota.....
T. Glorieta.....		T.	T. Morrison.....
T. Drinkard.....		T.	T. Penn.....
T. Tubbs.....		T.	T.
T. Abo.....		T.	T.
T. Penn.....		T.	T.
T. Miss.....		T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	100	100	Surface gravel				
100	1090	990	Red beds				
1090	1190	100	Anhydrite				
1190	2705	1015	Salt & anhydrite				
2705	2885	180	Anhydrite & dolomite				
2885	3050	165	Sand w/dolomite streaks				
3050	3170	120	Dolomite & sand				
3170	3295	125	Dolomite w/trace sand				
3295	3400	105	Sand w/dolomite streaks				
3400	3425	15	Dolomite				
3425	3440	25	Sand w/ tr. dolomite				
3440	3465	25	Dolomite				
3465	3475	10	Sand				
3475	3502	27	Dolomite w/shale streaks				
3502	3510	8	Sand				
3510	3525	15	Dolomite				
3525	3554	29	Sand w/dolomite, tr.				
T.D.	3554						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

9-23-57
(Date)

Company or Operator SOUTHERN CALIFORNIA PETROLEUM CORPORATION Address Box 1071, Midland, Texas
 Name Jawar Position or Title Division Engineer