

NEW MEXICO OIL CONSERVATION COMMISSION

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
27197

SUNDRY NOTICES AND REPORTS ON WELLS  
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.

1.  OIL WELL  GAS WELL  OTHER-

7. Unit Agreement Name Unit  
West Dollarhide Devonian

8. Form of Lease Name

2. Name of Operator  
Gulf Oil Corporation

9. Well No.  
106

3. Address of Operator  
P. O. Box 670, Hobbs, NM 88240

4. Location of Well  
UNIT LETTER K 1980 FEET FROM THE South LINE AND 781 FEET FROM  
THE East LINE, SECTION 33 TOWNSHIP 24-S RANGE 38-E NMPM.

10. Field and Pool, or Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)  
3173' GL

12. County  
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <u>Reenter, Abandon Well and Plug and Abandon</u> <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7995' PB.

Remove dry hole marker.  
Drill out surface plug in 7" casing and clean out to 1100'.  
Perforate 7" casing at 1050' with 4 or 5 circulation holes.  
Set cement retainer at 950' and cement with 250 sacks Class C cement.  
Circulate cement to surface.  
Spot 100', 17 sacks cement plug on top of retainer.  
Spot 50' cement plug from 50' to surface.  
Clean location.  
Install dry hole marker.

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE APPROVED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED D. F. Berlin TITLE Area Engineer DATE 3-22-77

APPROVED BY [Signature] TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: