

Form 9-331
(May 1963)
5 - USGS
1 - File

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved,
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032650 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

A. B. Coates "C"

9. WELL NO.

29

10. FIELD AND POOL, OR WILDCAT

Justis Ellenberger

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 24, T25S, R37E

12. COUNTY OR PARISH

Lea

13. STATE

N. Mex.

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

Box 249, Hobbs, New Mexico

4. LOCATION OF WELL. (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1650' FNL & 330' FEL, Sec. 24

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3068.3

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Casing Test & cement job

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded @ 8:00 PM 8-17-72. Drilled 17-1/2" hole to 567'. Set 13-3/8" 48# H-40 Casing at 560'. Cemented with 580 sacks Class "C" with 2% Cacl. Cement circulated. W.O.C. 18 hours. Tested casing and BOP with 1,000# for 30 minutes, no drop in pressure.

18. I hereby certify that the foregoing is true and correct

SIGNED ORIGINAL SIGNED BY:
C. L. Wade

TITLE Area Supt.

DATE 8-22-72

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

AUG 23 1972

*See Instructions on Reverse Side. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO