

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NO DATA TO BE REPORTED
OTHER THAN ON THE
VERSE SIDE

LEASE DESIGNATION AND SERIAL

LC-067968

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)

6 IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

West Dollarhide Queen
WDQSU *Sand Tract*

8. FARM OR LEASE NAME

9. WELL NO.

~~30-80~~

10. FIELD AND POOL, OR WILDCAT

Dollarhide Queen

11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA

Sec 30, T-24-S, R-38-E

12. COUNTY OR PARISH 13. STATE

Lea

NM

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
3. ADDRESS OF OPERATOR
Sirgo-Collier, Inc.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

Unit G, 1650' FNL 1600' FEL, Sec 30, T-24-S, R-38-E

14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, CR, etc.)

GL 3165' KB 3176.5'

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

DESIGN WATER SHUT OFF
FRACURE TREAT
SHOOTING OR ACIDIZING
PLUG WELL
OTHER

PULL OR ALTER CASING
MULTIPLE COMPLETION
ABANDON*
PLUG LEASE

SUBSEQUENT REPORT OF:

WATER SHUT OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
Other Spud, cement surface & prod string

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. PURPOSE, SCOPE, OR COMPLETE OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 8-22-87 Spudded with 12-1/4" bit to TD of 433' KB. Ran 429' 8-5/8" 24# J grade casing, type M slotted shoe and 3 centralizers. Cemented 250 sx Class C cement + 5 sx 2% CaCl2 and circulated 45 sx to pit.
- 8-23-87 Tested 8-5/8" 600#. Test okay.
- 8-28-87 TD 3955' KB
- 8-28-87 Ran 3955' of 5-1/2" 15.50# J grade casing. Cemented with 950 sx Halliburton Light cement + 200 sx Class C + 15# salt + 1/4# Flocele + 2% CaCl2. Circulated 85 sx to pit.

ACCEPTED FOR RECORD

SJS
SEP 10 1987

CARLSBAD, NEW MEXICO

SEP 1 10 56 AM '87
CARLSBAD, NEW MEXICO
APPLICABLE AGENCIES

RECEIVED

18. I hereby certify that the foregoing is true and correct

BY: *Amy L. Whitley* TITLE: Agent

DATE: 8-31-87

(Check space for Federal or State office use)

APPROVED BY: TITLE: DATE:

*See Instructions on Reverse Side