



Western Refining Southwest, Inc.

A subsidiary of Marathon Petroleum Corporation

92 Giant Crossing Road
Jamestown, NM 87347
Tel: 505.722.3833

December 15, 2020

Mr. Kevin Pierard, Chief
New Mexico Environmental Department
Hazardous Waste Bureau
2905 Rodeo Park Drive East, Building 1
Santa Fe, New Mexico 87505

**RE: French Drain Soil Sampling Investigation Work Plan
Western Refining Southwest Inc., Gallup Refinery
EPA ID #NMD000333211
HWB-WRG-18-014**

Dear Mr. Pierard,

Attached please find an Investigation Work Plan for the Sanitary Treatment Pond (STP-1) French Drain area. If you have any questions or comments regarding the information contained herein, please do not hesitate to contact Mr. John Moore at (505) 879-7643.

Certification

I certify under penalty of law that this document and all attachments were prepared under my direction of supervision according to a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Sincerely,
Marathon Petroleum Company LP, Gallup Refinery

Robert S. Hanks

Robert S. Hanks
Refinery General Manager

Enclosure

cc: D. Cobrain, NMED HWB
M. Suzuki, NMED HWB
C. Chavez, NMOCD
L. King, EPA Region 6
G. McCartney, Marathon Petroleum Company
J. Moore, Marathon Gallup Refinery
H. Jones, Trihydro Corporation



MARATHON PETROLEUM CORPORATION

GALLUP REFINING DIVISION

FRENCH DRAIN SOIL SAMPLING INVESTIGATION

WORK PLAN

HWB-WRG-18-014



Gallup Refining Division French Drain Soil Sampling
Investigation Work Plan

Approval to Proceed

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision according to a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

John Moore

Name: John Moore

12/15/20

Date

Title: Environmental Supervisor



Gallup Refining Division French Drain Soil Sampling
Investigation Work Plan

Executive Summary

The Marathon Petroleum Company (MPC), Gallup Refining Division is submitting this Investigation Work Plan for the investigation of hydrocarbon impacts to soils in the Sanitary Treatment Pond (STP-1) French Drain area.

Hydrocarbon impacts were discovered in the drain line of the STP-1 French Drain on February 6, 2018.

Subsequent investigation efforts were completed on February 8 and 10, 2018. This Investigation Work Plan was developed to investigate and sample the underlying soils to further delineate the potential impacts to the subsurface.

Initial investigation efforts included borehole installations and soil excavations in February 2018. As a result of the investigation, six deep soil boring locations were converted into groundwater monitoring wells and have been added to the annual groundwater sampling schedule since April 2018.

This Investigation Work Plan describes the proposed installation of soil borings and sample collection further north, east and west of the STP-1 French Drain and north of the wastewater treatment plant. This investigation is intended to reduce data gaps and will be utilized to determine if additional remediation or investigation is warranted.



Gallup Refining Division French Drain Soil Sampling
Investigation Work Plan

Table of Contents

Approval to Proceed.....	2
Executive Summary	3
Introduction	5
Background	5
Site Conditions	6
Surface Conditions	6
Subsurface Conditions.....	6
Scope of Activities	6
Investigation Methods	7
Sample Collection Procedures	7
Sample Frequency	8
Data Quality and Validation	9
Data Evaluation	9
Monitoring and Sampling Program	9
Schedule	9
References.....	9

List of Figures

1. Facility Location. Marathon Petroleum Corp. Gallup Refining Division. Gallup, New Mexico
2. French Drain Location. Marathon Petroleum Corp. Gallup Refining Division. Gallup, New Mexico
3. Proposed Soil Boring Locations. Marathon Petroleum Corp. Gallup Refining Division. Gallup, New Mexico

List of Appendices

- A. WELL LOGS
- B. STANDARD OPERATING PROCEDURE – SOIL SAMPLING

Gallup Refining Division French Drain Soil Sampling
Investigation Work Plan

Introduction

The MPC, Gallup Refining Division (Refinery) is located approximately 17 miles east of Gallup, McKinley County, New Mexico along the north side of Interstate Highway I-40 (Figure 1). The physical address is I-40, Exit #39 Jamestown, New Mexico 87347. The Refinery property covers approximately 810 acres.

Trihydro Corporation prepared this Investigation Work Plan for the investigation of soils contained in and around the STP-1 French Drain, located on the northwestern portion of the Refinery. The French Drain is located on the east side of STP-1 (Figure 2).

The Refinery is a petroleum oil refinery that processes crude oil received by pipeline or tanker truck from the Four Corners region. The Refinery is currently transitioning to idle mode. Various process units that have operated at the Refinery, and include crude distillation, reformer, fluidized catalytic cracker, alkylation, sulfur recovery, mercox treater, and hydrotreater. Past operations have produced gasoline, diesel fuels, jet fuels, kerosene, propane, butane, and residual fuel.

Background

As detailed in MPC's Response to Comment No. 39 on 2017 Annual Groundwater Monitoring Report (Marathon 2019a), a hydrocarbon release from the drain line of the STP-1 French Drain was discovered on February 6, 2018. Efforts to pinpoint the source of the hydrocarbon release included borehole installation and soil excavations conducted on February 8 and February 10, 2018, respectively. Investigation activities are detailed in the Second Response to Comments No. 39 on 2017 Annual Groundwater Monitoring Report from MPC (Marathon 2019b). Borehole and soil excavation locations of the February 2018 investigation are shown on Figure 3. Hydrocarbons were identified in the shallow subsurface in BH#1, #2, and #3 near the southeast corner of STP-1. Borehole depths were not recorded but are estimated to reach 6 to 8 feet below ground surface (ft bgs). Hydrocarbons were also visually identified in soil at excavation #9 located between the wastewater treatment plant and STP-1. Excavations #4, #5, #6, #7, #8, #10, and #11 showed no visible signs of hydrocarbon contamination.

Smaller hand excavations were also completed to the east of STP-1, where hydrocarbons were identified at approximately 3 ft bgs. Hand excavations completed on the northwest sides of Tanks 569, 570, 571, and 572 showed no visible evidence of a release. Fluid levels were monitored in Tanks 570, 571, and 345 to determine if a potential leak was responsible for the release. A static level test of Tank 570 in 2019 showed a

Gallup Refining Division French Drain Soil Sampling
Investigation Work Plan

loss of product, which lead to the tank being taken out of service. There were no indications of leaks in Tanks 571 and 345.

On March 5, 2019, six deep soil borings were installed throughout the tank farm and north of STP-1: SB-FD-1, OW-61, OW-62, OW-63, OW-64, and OW-65. These locations are shown on Figure 2 of this report and boring/well logs can be found in Appendix A. Hydrocarbon impacts were identified at OW-61 at depths ranging from 10 to 26 ft bgs. Elevated photoionization detector (PID) readings were identified at OW-62 (18-20 ft bgs), OW-63 (18-24 ft bgs), OW-64 (10-24 ft bgs), and OW-65 (14-20 ft bgs) which could suggest hydrocarbon contamination in the area.

The purpose of this Investigation Work Plan is to further identify and delineate horizontal and vertical soil impacts from a potential hydrocarbon release near the STP-1 French Drain. This investigation will evaluate the need for any further investigation and/or remediation.

Site Conditions

Surface Conditions

Local site topographic features include high ground in the southeast gradually decreasing to a lowland fluvial plain to the northwest. Elevations on the refinery property range from 7,040 feet (ft) to 6,860 ft. The area near STP-1 and the French Drain is approximately 6,910 ft above mean sea level.

Subsurface Conditions

The shallow subsurface soil (alluvium) is comprised of clay and silt with some inter-bedded sand layers. Beneath the alluvium is the Petrified Forest Member of the Chinle Group, which primarily consists of interbedded mudstone, siltstone, and sandstone. The Alluvium/Chinle interface ranges from 15 ft bgs to more than 32 ft bgs.

Scope of Activities

The investigative activities of the STP-1 French Drain will be initiated to further delineate horizontal and vertical hydrocarbon impacts to soil and to confirm data previously collected. The sampling activities will be conducted per the Resource Conservation and Recovery Act (RCRA) Post-Closure Permit Section IV.J.2.ii. Pending New Mexico Environmental Department (NMED) approval, MPC anticipates investigation work to be completed in 2021.

Gallup Refining Division French Drain Soil Sampling
Investigation Work Plan

A Geoprobe drill rig will be used to advance soil borings and up to two discrete soil samples will be collected at each boring location. Based upon prior investigations completed by MPC, hydrocarbon impacts around the STP-1 French Drain area were observed at approximately 8 ft bgs. To delineate vertical distribution, soil borings will be advanced to at least 5 ft below the deepest detected contamination based on PID field screening and field observation results.

Soil samples will be analyzed for hydrocarbon impacts via Method 8270 (semi-volatile organic compounds [SVOCs]), Method 8260 (volatile organic compounds [VOCs]), and Method 8015M (total petroleum hydrocarbons [TPH] gasoline range organics [GRO] and diesel range organics [DRO]). Analytical results will be screened by comparison to NMED Industrial Soil Screening Levels (SSLs).

After the investigation has been completed, MPC will prepare an investigation report summarizing analytical results from the soil sampling. The investigation will be submitted to NMED.

Investigation Methods

The proposed sampling locations are shown on Figure 3. The proposed locations include six boreholes around the STP-1 French Drain area.

Soils obtained will be visually inspected and classified in general accordance with ASTM D2487 (Unified Soil Classification System) and D2488 (Description and Identification of Soils). Detailed soil boring logs will be completed in the field by qualified field staff. Soil samples will be field screened at regular intervals via PID for evidence of contaminants and will be recorded in the boring logs.

Sample Collection Procedures

Samples will be collected in accordance with the soil sampling Standard Operating Procedure (Appendix B). Details related to sample collection will be documented on the confirmation sampling field forms. General observations recorded on the field forms for each soil sample location will include sampling start and end times, weather, site conditions, sampling team members, and other affiliations present. Sample-specific information will include: field sample identification, sample start and end depth, collection method, sample type (i.e., composite or aliquot), soil classification and characteristics, deviations or clarification of sampling procedures, and other observations. Field techniques will be applied consistently across the STP-1 French Drain area by a team of dedicated sampling personnel who may be assisted by site supervisors. A summary of the sampling activities is shown below:

Gallup Refining Division French Drain Soil Sampling
Investigation Work Plan

1. Install six soil borings to observe and collect soil samples from the borings in order to delineate horizontal and vertical extent of hydrocarbon impacts.
2. Analyze soil samples for:
 - pH
 - SVOCs, Method 8270
 - VOCs, Method 8260
 - TPH GRO and DRO
 - Density
3. Screen analytical data by comparing with NMED SSLs.

Soil sampling equipment will be decontaminated before collecting each sample, and equipment decontamination will be noted on the field forms. Immediately after collection, soil samples will be placed into a clean, sealable plastic bag labeled with the field sample identification. Sample jars will be filled, labeled, and placed in a cooler. Before shipment, coolers will be packed with additional ice and one temperature blank per cooler. A chain of custody (CoC) form will accompany each sample shipment. Coolers will be sealed and shipped overnight to the Eurofins TestAmerica Analytical Laboratory in Pensacola, FL.

Sample Frequency

Soil sample collection will be taken at a frequency in accordance with the RCRA Post-Closure Permit Section IV.J.2.d.ii (Soil and Rock Sampling) and will include the following applicable intervals and depths:

- At the surface of the proposed boring locations;
- At 2.5-ft intervals;
- At the maximum depth of each boring; and
- At intervals suspected of being source or contaminated zones.



Data Quality and Validation

Quality assurance/quality control (QA/QC) samples will be collected during sampling to monitor the validity of the sample collection procedures. Field duplicates will be collected at a rate of ten percent of all samples collected. Equipment blanks will be collected from re-usable equipment at a rate of ten percent; if disposable sampling equipment is used, the blanks shall be collected at a frequency of one per day. Field blank samples will also be collected once a day. The field duplicate and blank samples will be submitted to the laboratory along with the soil samples.

QA/QC samples will be recorded on the field forms and CoCs. All data will undergo Tier II data validation.

Data Evaluation

Analytical results will be compared to NMED SSLs, and the chosen disposal facility's waste acceptance criteria. Soil recovered during sampling will be placed in containers within the area of the STP-1 French Drain and characterized prior to disposal.

Monitoring and Sampling Program

Monitoring wells OW-61 through OW-65 were added to the routine quarterly groundwater sampling event beginning in April 2018 and have been sampled quarterly since that time.

Schedule

Pending NMED approval, MPC anticipates the investigation to begin in early 2021. After the investigation has been completed, MPC will prepare an investigation report summarizing the sampling results.

References

- Marathon. 2019a. Response to Comment No. 39 on 2017 Annual Groundwater Monitoring Report (dated March 21, 2019), Marathon Petroleum Company LP, Gallup Refinery, (dba Western Refining Southwest, Inc.), EPA ID# NMD000333211, HWB-WRG-18-014. May 23, 2019.
- Marathon. 2019b. Second Response to Comment No. 39 on 2017 Annual Groundwater Monitoring Report (dated March 21, 2019), Marathon Petroleum Company LP, Gallup Refinery, (dba Western Refining Southwest, Inc.), EPA ID# NMD000333211, HWB-WRG-18-014. August 23, 2019.

Figures



Image Cite: DigitalGlobe © CNES (2020) Distribution Airbus DS © Microsoft Corporation, BING Imagery

EXPLANATION

 INTERSTATE HIGHWAY



0 2,000'



Trihydro
CORPORATION
1252 Commerce Drive
Laramie, Wyoming 82070
www.trihydro.com
(P) 307/745.7474 (F) 307/745.7729

FIGURE 1

FACILITY LOCATION

**MARATHON PETROLEUM CORP.
GALLUP REFINING DIVISION
GALLUP, NEW MEXICO**

Drawn By: REP	Checked By: JP	Scale: 1" = 2,000'	Date: 9/14/20	File: 697-FD-FACILITYLOC_202009
---------------	----------------	--------------------	---------------	---------------------------------


\\TRIHYRO.COM\CLIENTS\TOM VARRATHON\CADD\GALLUP\REPORTS\FRENCHDRAIN\WP\697-FD-FRENCHDRAINLOC_202009



Image Cite: DigitalGlobe © CNES (2020) Distribution Airbus DS © Microsoft Corporation, BING Imagery

EXPLANATION

- OW-65 MONITORING WELL AND DESIGNATION (APPROXIMATE)
- FRENCH DRAIN
- SD-2 STORM DRAIN AND DESIGNATION





1252 Commerce Drive
Laramie, Wyoming 82070
www.trihydro.com
(P) 307/745.7474 (F) 307/745.7729

Drawn By: REP Checked By: JP Scale: 1" = 200' Date: 9/14/20 File: 697-FD-FRENCHDRAINLOC_202009

FIGURE 2

FRENCH DRAIN LOCATION

MARATHON PETROLEUM CORP.
GALLUP REFINING DIVISION
GALLUP, NEW MEXICO


\\TRIHYRO.COM\CLIENTS\ITOM\MARATHON\CADD\GALLUP\REPORTS\FRENCHDRAIN\WP\697-FD-PROPSOILLOC_202009



Image Cite: DigitalGlobe © CNES (2020) Distribution Airbus DS © Microsoft Corporation, BING Imagery

EXPLANATION

- PROPOSED SOIL BORING
- BORING AND DESIGNATION (INSTALLED FEBRUARY 2018)
- FRENCH DRAIN
- HYDROCARBON IMPACTS (EXCAVATION INSTALLED FEBRUARY 2018)
- HYDROCARBON ABSENT (EXCAVATION INSTALLED FEBRUARY 2018)



Trihydro
CORPORATION
1252 Commerce Drive
Laramie, Wyoming 82070
www.trihydro.com
(P) 307/745.7474 (F) 307/745.7729

Drawn By: REP Checked By: JP Scale: 1" = 200' Date: 9/14/20 File: 697-FD-PROPSOILLOC_202009

FIGURE 3

PROPOSED SOIL BORING LOCATIONS

MARATHON PETROLEUM CORP.
GALLUP REFINING DIVISION
GALLUP, NEW MEXICO

Appendix A

Well Logs



Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Augers
Sampling Method : Split Spoon 2'
Comments :
Total Depth : 32'
Ground Water : 18' BGL
Start Date : 3-13-2018
Finish Date : 3-13-2018

WELL NO. OW-61

(Sheet 1 of 2)

Elev., TOC (ft.msl) : 6963.57
Elev., PAD (ft. msl) : 6960.91
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1633887.74
E : 2546702.36

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	Completion Results
							DESCRIPTION	
-2								OW-61
-1								
0							Hydroexcavated Location - Borehole open to 10' - no water	Steel Protective Casing
1								Concrete Pad 4' x 4' x 4'
2								Grout
3					0			4" Sch 40 PVC w/Threaded Joints
4								Bentonite Pellets
5								
6								
7								
8								
9								
10								
11	1563			ML	90		SANDY SILT, very fine, loose, moist, gravel present, brown, strong chemical odor,	10/20 Sieve Sand Filter Pack
12								
13	869			SM	80		GRAVELLY SILTY SAND, fine, loose, moist, 20 mm gravel present, brown, strong odor,	4" Sch 40 PVC Slotted 0.01" Screen w/Threaded Joints
14								
15	1081			SM	70		GRAVELLY SILTY SAND, SIMILAR TO ABOVE (STA), very moist, tan and brown, strong odor,	
16								
17	1115			SM	60		GRAVELLY SILTY SAND, STA, increase in gravel, large sandstone gravel in core, moist to very moist,very light tan, strong odor,	
18		▼						

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Augers
Sampling Method : Split Spoon 2'
Comments :
Total Depth : 32'
Ground Water : 18' BGL
Start Date : 3-13-2018
Finish Date : 3-13-2018

WELL NO. OW-61

(Sheet 2 of 2)

Elev., TOC (ft.msl) : 6963.57
Elev., PAD (ft. msl) : 6960.91
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1633887.74
E : 2546702.36

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	DESCRIPTION	Completion Results OW-61
18								GRAVELLY CLAYEY SAND, fine to coarse grain sand with brown clay, soft, very damp gravel (10-20 mm), saturated at base,	
19	1702			SC	20				
20								SILTY SAND, medium, loose, trace clay and gravel, saturated, dark brown, strong odor,	
21	1269			SM	60				
22				SM	60			SILTY SAND, STA, saturated,	
23	1638			CL	60			GRAVELLY SANDY CLAY, low, soft, gravel throughout, damp to saturated in seams, brown, strong odor,	
24								GRAVELLY CLAY, low, firm, damp, dark blueish grey, strong odor,	
25	1538			CL	50				
26								GRAVELLY CLAY, STA, trace very fine grain sand, damp, very stiff, odor,	
27	377			CL	40				
28								SILTY CLAY, low, very stiff, trace sand and very small gravel, damp, grey to light grey, odor,	
29	298			CL	60				
30								SILTY CLAY, STA, damp, light grey and pink.	
31	60.9			CL	70				
32									
33									
34									
35									
36									
37									
38									

4" Sch 40 PVC Slotted 0.01" Screen w/Threaded Joints

10/20 Sieve Sand Filter Pack

4" Flush Threaded Sch 40 PVC Cap

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190




Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Augers
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 40'
Ground Water : Not Encountered
Start Date : 03/15/2018
Finish Date : 03/15/2018

WELL NO. OW-62

(Sheet 1 of 3)

Elev., TOC (ft.msl) : 6937.36
Elev., PAD (ft. msl) : 6934.73
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634866.14
E : 2545914.00



1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Augers
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 40'
Ground Water : Not Encountered
Start Date : 03/15/2018
Finish Date : 03/15/2018

WELL NO. OW-62

(Sheet 2 of 3)

Elev., TOC (ft.msl) : 6937.36
Elev., PAD (ft. msl) : 6934.73
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634866.14
E : 2545914.00

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	DESCRIPTION	Completion Results OW-62
18								CLAYEY SANDY GRAVEL, STA except clay present, very moist, hydrocarbon (HC) odor, ,	
19	3380			GC	80				
20								CLAYEY SANDY GRAVEL, STA, damp to moist, HC odor,	
21	82.9			GC	70				
22								SILTY CLAY, low, soft, trace sand, calcareous, damp to moist, reddish brown, HC odor,	
23	33			CL	60				
24								SILTY CLAY, low, stiff, damp, reddish brown, HC odor,	
25	800			CL	70				
26								SILTY CLAY, STA, calcareous, odor,	
27	555			CL	80				
28								CLAY, high, very stiff, damp, reddish brown, faint odor,	
29	56			CH	90				
30								SILTY CLAY, low, firm/crumbly, damp, reddish brown, trace grey, no odor,	
31	351			CL	90				
32								SILTY CLAY, STA,	
33	125			CL	90				
34								SILTY CLAY, STA,	
35	159			CL	90				
36								SILTY CLAY, STA,	
37	91			CL	90				
38									

4" Sch 40 PVC Slotted 0.01" Screen w/Threaded Joints

10/20 Sieve Sand Filter Pack

4" Flush Threaded Sch 40 PVC Cap

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012


Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Augers
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 40'
Ground Water : Not Encountered
Start Date : 03/15/2018
Finish Date : 03/15/2018

WELL NO. OW-62

(Sheet 3 of 3)

Elev., TOC (ft.msl) : 6937.36
Elev., PAD (ft. msl) : 6934.73
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634866.14
E : 2545914.00

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Rec overy (%)	Sample	Saturation ▼ Saturation	Completion Results OW-62
							DESCRIPTION	
38							SILTY CLAY, STA.	
39	44			CL	90			
40								
41								
42								
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								
57								
58								



10/20 Sieve Sand Filter Pack

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190




Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Auger
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 32
Ground Water : 16'/25'
Start Date : 03/14/2018
Finish Date : 03/14/2018

WELL NO. OW-63

(Sheet 1 of 2)

Elev., TOC (ft.msl) : 6935.06
Elev., PAD (ft. msl) : 6932.34
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634859.73
E : 2546756.41



1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012


Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Auger
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 32
Ground Water : 16'/25'
Start Date : 03/14/2018
Finish Date : 03/14/2018

WELL NO. OW-63

(Sheet 2 of 2)

Elev., TOC (ft.msl) : 6935.06
Elev., PAD (ft. msl) : 6932.34
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634859.73
E : 2546756.41

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	DESCRIPTION	Completion Results OW-63
18								SANDY SILTY CLAY, low, firm, damp, occasional gravel, brown, odor,	
19	428			CL	80				
20								SILTY SANDY CLAY, STA, moist in sand seams at base, odor,	
21	652			CL	80				
22								SILTY SANDY CLAY, STA, odor,	
23	275			CL	70				
24				CH	70			CLAY, high, soft to firm,damp,brown, odor,	
25	39			CH	90			CLAY, STA, odor,	
26	28			GC	90			CLAYEY GRAVEL, sandstone gravel in pink/brown/olive green clay and silt, coarse sand present, saturated, odor,	
27	150			GC	90			CLAYEY GRAVEL, STA, saturated, odor,	
28								WEATHERED SANDSTONE, very dense, dry, grey to light purple, faint odor,	
29	40				90				
30								WEATHERED SANDSTONE, STA, grey and light purple.	
31	10.9				50				
32									
33									
34									
35									
36									
37									
38									



1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Pilot Hole 7 1/4 HSA
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 44' BGL
Ground Water : Not Encountered
Start Date : 03/05/2018
Finish Date : 03/05/2018

WELL NO. OW-64

(Sheet 1 of 3)

Elev., TOC (ft.msl) : 6947.40
Elev., PAD (ft. msl) : 6945.07
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634301.36
E : 2546150.80

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	Completion Results
							DESCRIPTION	
-2								OW-64
-1								
0							Hydroexcavated to 10' BGL, sloughed to 8' BGL, water in hole at 5.20' BGL, no separate phase hydrocarbon (SPH) detected,	Steel Protective Casing
1								Concrete Pad 4' x 4' x 4'
2								Grout
3								Bentonite Pellets
4								4" Sch 40 PVC w/Threaded Joints
5								
6								
7								
8								
9								
10								10/20 Sieve Sand Filter Pack
11	280			CL	50		SILTY CLAY, low, firm, damp, brown and grey, faint hydrocarbon (HC) odor,	4" Sch 40 PVC Slotted 0.01" Screen w/Threaded Joints
12								
13	267			CL	70		SILTY CLAY, SIMILAR TO ABOVE (STA), faint HC odor,	
14								
15	308			CL	80		SILTY CLAY, low to moderate, stiff, calcareous near and at base, damp,brown, grey to greyish white, faint HC odor,	
16								
17	137			CL	50		SILTY CLAY, STA, increase in plasticity, mostly grey-trace brown,faint HC ordor,	
18								

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Pilot Hole 7 1/4 HSA
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 44' BGL
Ground Water : Not Encountered
Start Date : 03/05/2018
Finish Date : 03/05/2018

WELL NO. OW-64

(Sheet 2 of 3)

Elev., TOC (ft.msl) : 6947.40
Elev., PAD (ft. msl) : 6945.07
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634301.36
E : 2546150.80

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	DESCRIPTION	Completion Results OW-64
18								SILTY CLAY, moderate, firm, damp, brown-trace grey, faint odor,	
19	47			CL	70				
20								SILTY CLAY, STA, reddish brown to grey at 20.5', faint odor,	
21	133			CL	70				
22								SILTY CLAY, moderate, firm to stiff, damp, grey, faint odor,	
23	20			CL	60				
24								SILTY CLAY, STA, stiff,	
25	17			CL	80				
26								SILTY CLAY, STA, stiff, calcareous at base, reddish brown and grey, greenish grey,	
27	75			CL	70				
28								SILTY CLAY, low, stiff/crumbly, damp, dark reddish brown and grey, no odor,	
29	74			CL	60				
30								SILTY CLAY, STA, very stiff, no odor,	
31	35			CL	60				
32								SILTY CLAY, low, very stiff, damp, dark reddish brown, black shale at base, no odor,	
33	20			CL	40				
34								CLAYEY SILT, sandstone gravel (cobble) at top of interval, low, firm/crumbly, dry/damp, brown, no odor,	
35	30			ML	40				
36								SILTY CLAY, low, very stiff, dry/damp, brown, no odor,	
37	8			ML	50				
38									

4" Sch 40 PVC Slotted 0.01" Screen w/Threaded Joints

4" Flush Threaded Sch 40 PVC Cap

10/20 Sieve Sand Filter Pack

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Pilot Hole 7 1/4 HSA
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 44' BGL
Ground Water : Not Encountered
Start Date : 03/05/2018
Finish Date : 03/05/2018

WELL NO. OW-64

(Sheet 3 of 3)

Elev., TOC (ft.msl) : 6947.40
Elev., PAD (ft. msl) : 6945.07
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634301.36
E : 2546150.80

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	Completion Results OW-64
							DESCRIPTION	
38	12			ML	70		SILTY CLAY, STA,	 10/20 Sieve Sand Filter Pack
39								
40	8			ML	60		SILTY CLAY, STA,	
41								
42	6			ML	60		SILTY CLAY, STA.	
43								
44								
45								
46								
47								
48								
49								
50								
51								
52								
53								
54								
55								
56								
57								
58								

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Auger
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 40' BGL
Ground Water : 20' BGL
Start Date : 03/09/2018
Finish Date : 03/09/2018

WELL NO. OW-65

(Sheet 1 of 3)

Elev., TOC (ft.msl) : 6954.05
Elev., PAD (ft. msl) : 6951.62
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634238.38
E : 2546692.01

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	DESCRIPTION	Completion Results	
									OW-65	
-2										
-1										
0								Cleared borehole to 5', 1" asphalt and base, SILTY CLAY, low, stiff, damp, mixed with gravelly sand, brown, no order,		Steel Protective Casing
1										
2										
3				CL	100					
4										
5										
5	17.4			SW	100			GRAVELLY SAND, fine to coarse, loose, damp, gravel <10 mm, brown, no odor,		Grout
6										
7	23			SW	80			GRAVELLY SAND, SIMILAR TO ABOVE (STA), clayey sand at base, very damp, brown, odor,		4" Sch 40 PVC w/Threaded Joints
8										
9	12			SM	90			SILTY SAND, medium to coarse, loose, very damp, brown, odor,		
10										
11	16			SM	80			CLAYEY GRAVELLY SAND, fine to coarse, compact, gravelly clay lense 2" thick at 11', brown, odor,		
12										Bentonite Pellets
13	66			SM	70			SILTY SAND, medium, loose, very damp, brown, odor,		
14										
15	822			GC	60			CLAYEY GRAVEL, <10 mm gravel in brown clay, coarse sand throughout, very damp, odor,		4" Sch 40 PVC Slotted 0.01" Screen w/Threaded Joints
16										
17	885			SM	60			SILTY SAND, fine, loose, very damp to moist, hydrocarbon (HC) odor,		10/20 Sieve Sand Filter Pack
18										

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190



Andeavor
Gallup Refinery - French Drain Release
WEST18012

Geologist : Tracy Payne
Driller : Enviro-Drill, Inc./Cohagan
Drilling Rig : CME75
Drilling Method : Hollow-Stem Auger
Sampling Method : 2' Split Spoon
Comments :
Total Depth : 40' BGL
Ground Water : 20' BGL
Start Date : 03/09/2018
Finish Date : 03/09/2018

WELL NO. OW-65

(Sheet 2 of 3)





Elev., TOC (ft.msl) : 6954.05
Elev., PAD (ft. msl) : 6951.62
Elev., GL (ft. msl) : NS
Site Coordinates :
N : 1634238.38
E : 2546692.01

Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation ▼ Saturation	DESCRIPTION	Completion Results OW-65
18	1195			GC	50			CLAYEY GRAVEL, 40 mm sandstone cobbles (tan and green) in brown clay, coarse sand throughout, damp, odor,	
19				GC	60			CLAYEY GRAVEL, STA, moist to saturated in sand, water in split spoon,	
20				GC	90			CLAYEY GRAVELLY SAND, coarse sand with 10 mm gravel, loose/soft, saturated, brown, HC odor,	
21				SC	80			CLAYEY SAND, coarse, loose, very soft, trace gravel, saturated, brown, odor,	
22				SC	80			CLAYEY SAND, fine to medium, compact, moist, dark brown, HC odor,	
23				CL	80			SILTY CLAY, low, very soft, damp, dark brown, strong HC odor,	
24				SC	80			CLAYEY SAND, fine, compact, saturated/oily, dark brown, saturated/oily,	
25				SC	60			CLAYEY SAND, STA, HC odor,	
26				SC	80			CLAYEY SAND, STA, increase in clay at base, becomes moist,	
27				SM	90			SILTY SAND, medium to coarse, loose, gravelly (<5 mm) at base, saturated, dark brown, HC odor,	
28				SW	80			GRAVELLY SAND, coarse, loose, trace clay-gravel (10 mm), saturated, dark brown, HC odor,	
29				CL	80			SANDY CLAY, low, firm, trace gravel, damp, dark brown, HC odor,	

1001 Louisiana Street, Suite 3250
Houston, Texas 77002
713-955-1230

DiSorbo Consulting, LLC

8501 N. MoPac Expy, Suite 300
Austin, Texas 78759
512-693-4190

							Geologist : Tracy Payne Driller : Enviro-Drill, Inc./Cohagan Drilling Rig : CME75 Drilling Method : Hollow-Stem Auger Sampling Method : 2' Split Spoon Comments : Total Depth : 40' BGL Ground Water : 20' BGL Start Date : 03/09/2018 Finish Date : 03/09/2018		WELL NO. OW-65 (Sheet 3 of 3)	
Andeavor Gallup Refinery - French Drain Release WEST18012									Elev., TOC (ft.msl) : 6954.05 Elev., PAD (ft. msl) : 6951.62 Elev., GL (ft. msl) : NS Site Coordinates : N : 1634238.38 E : 2546692.01	
Depth (ft.)	PID (ppm)	Saturation	Lithology	USCS	Recovery (%)	Sample	Saturation  Saturation		Completion Results OW-65	
							DESCRIPTION			
38				CL	40		SANDY CLAY, STA.		 10/20 Sieve Sand Filter Pack	
39										
40										
41										
42										
43										
44										
45										
46										
47										
48										
49										
50										
51										
52										
53										
54										
55										
56										
57										
58										
1001 Louisiana Street, Suite 3250 Houston, Texas 77002 713-955-1230							DiSorbo Consulting, LLC		8501 N. MoPac Expy, Suite 300 Austin, Texas 78759 512-693-4190	

Appendix B

Standard Operating Procedure – Soil Sampling



memorandum

To: Sampling Team Members
From: Project Manager
Date: November 30, 2020
Re: Standard Operating Procedure – Soil Sampling

1.0 INTRODUCTION

Soil sampling related to site characterization and site clean-up is expected to involve source sampling of potentially contaminated Soils for characterization and profiling. Soil sampling is expected to occur in and around the STP-1 French drain.

All personnel involved in Soil sampling projects are required to review this Standard Operating Procedure (SOP) before sampling to ensure the continued generation of reliable data. This SOP is based on experience gained from collecting Soil samples and the latest information available in guidance manuals. This SOP may be updated as additional experience and information are acquired.

2.0 PRE-FIELD ACTIVITIES

Several activities will be conducted prior to departure for the project site. A project team will be assigned and the members will begin coordinating the sample collection event with Marathon Petroleum Company. Field equipment will be checked and organized. Access to the areas to be sampled will be checked, and provisions made to pack the necessary equipment for delivery to the project site.

3.0 PREPARATION

The Project Manager will review the current sampling and analysis plans and work plans to determine if any documents need to be brought to the site during monitoring. The Project Manager will also evaluate whether any changes have been made in the sampling and analytical procedures, and notify the appropriate personnel.

The Sampling Team Members will review available surface water level data before leaving for the sampling site. This preparation ensures that the proper equipment and personnel are available at the site. All field screening equipment will be inspected prior to departure, ensuring that it is in proper working order. For Soil sampling, the only field monitoring equipment used will be the Photoionization detection (PID) meter and it should be calibrated and operated according to manufacturer's recommendations.



Sampling Team Members
November 30, 2020
Page 2

4.0 EQUIPMENT

The following equipment is recommended for Soil sampling:

- Required personal protective equipment (PPE), listed in the site-specific health and safety plan (HASP) (generally nitrile gloves, waders, life preserver, rope and safety glasses)
- Soil sampling devices (i.e., hand auger)
- Sampling beaker, bottles, labels, and preservatives
- Gloves
- Chain-of-custody/sample-analysis-request forms
- Flame Ionization detection meter (FID)
- Opaque Cooler(s) and bagged ice or frozen Blue Ice
- Detergent or solvent for cleaning monitoring equipment
- Brushes dedicated for decontamination
- Decontamination containers dedicated for wash, rinse 1, and rinse 2
- Paper towels
- Trash bags
- Field logbook
- Wrist watch (with digital display)

5.0 SAMPLE COLLECTION

A critical aspect of any sampling program is selection and implementation of an appropriate sampling technique. Selection of equipment and technique should be appropriate for the volume of material required and the type of analysis to be performed. In general, the sampling equipment and technique will be chosen to minimize, to the extent possible, the amount of handling a sample will undergo prior to analysis. In many cases, the material to be sampled will be easy to access, and simple "grab" samples collected using a shovel, trowel, or drive sampler are appropriate. In other cases, such as underwater or heavily saturated samples, the Soils may be difficult to access, and sampling will involve the use of specialized Soil sampling equipment. Specific analytical requirements and sampling frequencies are specified in the work plan.

Soil samples located in dry areas will be collected from representative locations using a decontaminated drive sampler equipped with clean brass or stainless steel sampling rings, a thin-walled tube sampler or a shovel or hand trowel. The sampling device will be driven completely into the material manually or using



Sampling Team Members
November 30, 2020
Page 2

a manually operated auger, drive hammer, or mallet. The sampling device will then be extracted from the material using a shovel or trowel as needed. If used, filled sampling rings or the thin walled tube will then be removed from the sampling device and immediately sealed on both ends with teflon sheeting and plastic caps. Otherwise, the material will be placed directly from the trowel or other appropriate sampling device into a clean glass jar. The jar will be filled completely to minimize headspace (by tamping during filling), and immediately sealed with a teflon-lined lid.

In accordance with the work plan saturated and underwater Soil samples will be collected using a hand auger, geoprobe, Soil sampler or a similar device. Samples will be collected from the shore or boat at each preselected sampling location. Underwater samples will be capped prior to breaking the surface of the water to prevent agitation of the sample and to assist in core characterization. In addition, care will be taken to prevent mixing when collecting saturated and underwater samples. Soil will be placed in sample containers provided by the laboratory and filled to the top to minimize headspace. If necessary, several cores may be collected from each location to provide adequate sample volume for the laboratory. The sample containers will be labeled with endurable ink. Filled sample containers should be wiped dry and placed in a cooler with ice (or equivalent) for storage at the time of collection. Enough ice and protective packing material should be used to cool the samples to 4° C and ensure that the container remains intact prior to final packing and shipment.

Field screening may involve the use of a FID probe; which will be inserted into the bag and the reading taken. All samples shall be screened at as close to the same temperature as possible to obtain consistent results.

Sampling devices will be decontaminated between sampling locations using a four-stage decontamination system consisting of a two detergent/water washes and two deionized water rinses. Sample locations will be recorded with a GPS in order to accurately map the sampling locations.

Field logbooks, Soil Sampling Field Log, and photograph logs will provide a written record of field data gathered, field observations, field equipment calibrations, the samples collected for analysis, and sample custody. Color photographs will be used to substantiate and augment the field notes, if necessary.

697-078-001

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

COMMENTS

Action 19486

COMMENTS

Operator:			OGRID:	Action Number:	Action Type:
WESTERN REFINING SOUTHWEST, IN	6700 Jefferson NE, Suite A-1	Albuquerque,	705791	19486	DISCHARGE
NM87109					PERMIT

Created By	Comment	Comment Date
cchavez	Permittee French Drain WP 12-15-2020.	03/02/2021

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 19486

CONDITIONS OF APPROVAL

Operator: WESTERN REFINING SOUTHWEST, IN NM87109	6700 Jefferson NE, Suite A-1 Albuquerque,	OGRID: 705791	Action Number: 19486	Action Type: DISCHARGE PERMIT
OCD Reviewer cchavez	Condition None			