

March 31, 2022

Mr. Oakley Hayes **Environmental Specialist** Harvest Four Corners 1755 Arroyo Drive Bloomfield, New Mexico 87413

Subject: 2021 Annual Groundwater Report

RP Number 3RP-317-0

Incident Number nAUTOfAB000185 San Juan County, New Mexico

Florance 47X

REVIEWED

By Mike Buchanan at 2:53 pm, May 10, 2024

Review of the 2021 Annual Groundwater Report: Content Satisfactory

- 1. Continue to remove PSH in MW-3 with skimmer pump to reduce LNAPL plume
- 2. Continue to conduct quarterly groundwater sampling events
- 3. Conduct O&M as prescribed in report.
- 4. Submit the 2022 & 2023 Annual Report (if they haven't already been submitted).
- 5. Submit the 2024 Annual Groundwater Monitoring Report for the site by April 1, 2025.

Dear Mr. Hayes,

WSP USA Inc. (WSP), on behalf of Harvest Four Corners, LLC (Harvest) has prepared this report detailing annual groundwater monitoring activities completed between January 2021 and December 2021 at the Florance #47X (Site), Remediation Permit (RP) Number 3RP-317-0 and Incident Number nAUTOfAB000185. The purpose of this project was to continue phase-separated hydrocarbon (PSH) recovery and monitoring of petroleum hydrocarbon impacts to groundwater resulting from a release involving a former earthen dehydrator pit.

LOCATION

The Site is located at latitude 36.843195 and longitude -107.800839 in Unit G, Section 5, Township 30 North, Range 9 West (Figure 1). The Site is located in Crow Canyon, a tributary to Pump Canyon, in the San Juan Basin in San Juan County, New Mexico.

SITE HISTORY

Groundwater at the Site is impacted by petroleum hydrocarbons due to a release from a former earthen dehydrator pit. In June 1996, source material was excavated to approximately 19 feet below ground surface (bgs). A subsequent borehole drilled in the excavation to approximately 115 feet bgs identified groundwater at approximately 97 feet bgs. Laboratory analytical results of groundwater collected from the borehole identified concentrations of benzene, toluene, ethylbenzene, and total xylenes (BTEX) exceeding New Mexico Water Quality Control Commission (NMWQCC) standards. As a result, five groundwater monitoring wells (MW-1 through MW-5) were installed.

Since installation of the five monitoring wells, groundwater elevations and groundwater quality have been monitored at the Site, with monitoring wells MW-2, MW-3, and MW-5 containing PSH during at least one sampling event. Historical records documenting monitoring activities and results can be found in previous annual reports submitted to the New Mexico Oil Conservation Division (NMOCD).

In October 2019, WSP conducted drilling activities which included the installation of two new monitoring wells, MW-6 and MW-7, located downgradient of monitoring wells MW-3 and MW-5, for use as point of compliance (POC) monitoring wells. On December 17, 2019, United Field Services in Farmington, New Mexico was contracted to survey top-of-casing elevations to accurately determine groundwater elevations above mean sea level (amsl).

WSP USA 848 EAST 2ND AVENUE **DURANGO CO 81301**

Tel.: 970-385-1096



METHODOLOGY

Groundwater monitoring activities were conducted at the Site from January through December 2021. WSP conducted quarterly site visits to monitor groundwater elevations in all monitoring wells and collected groundwater samples from monitoring wells MW-2, MW-5, MW-6, and MW-7 in May 2021.

GROUNDWATER AND PSH ELEVATIONS

Groundwater levels were monitored quarterly by recording depth to groundwater and depth to PSH measurements in the existing monitoring wells with an oil/water interface probe. The interface probe was decontaminated with AlconoxTM soap and rinsed with distilled water prior to each measurement. Top-of-casing elevations from the survey were used to calculate groundwater potentiometric elevations, draft groundwater contours, and determine groundwater flow direction.

GROUNDWATER SAMPLING

On May 24, 2021, monitoring wells MW-2, MW-5, MW-6, and MW-7 were purged using disposable polyvinyl chloride (PVC) bailers. As groundwater was purged from each monitoring well, pH, electrical conductance (EC), and temperature, were recorded for determining stabilization conditions prior to sampling. Monitoring wells were purged until a total of three casing volumes were removed or the well was purged dry, indicating that groundwater would be representative of aquifer conditions. Purged groundwater was containerized and disposed of at a nearby Harvest compressor station.

Groundwater samples were collected by filling three 40-milliliter (mL) glass vials from each well. The laboratory-supplied vials were filled and capped with zero headspace to prevent degradation of the sample. Samples were labeled with the date and time of collection, well designation, project name, sample collector's name, and parameters to be analyzed. They were immediately sealed, packed on ice, and submitted to Hall Environmental Analysis Laboratory (HEAL) in Albuquerque, New Mexico for analysis of BTEX following United States Environmental Protection Agency (EPA) Method 8021. Proper chain-of-custody (COC) procedures were followed documenting the date and time sampled, sample number, type of sample, sample collector's name, preservative used, analyses required, and sample collector's signature.

Monitoring wells MW-1 and MW-4 were not sampled in 2021. Monitoring well MW-3 was also not sampled due to the presence of PSH. The following NMWQCC standards apply to groundwater: 5 micrograms per liter (μ g/L) benzene, 1,000 μ g/L toluene, 700 μ g/L ethylbenzene, and 620 μ g/L total xylenes.

PSH RECOVERY

In November 2019, WSP installed a solar powered pneumatic pumping PSH recovery system in monitoring MW-3. The pump utilizes a hydrophobic and oleophilic skimmer that floats on the water column to remove PSH from the water PSH interface. The system cycles between vacuum and pressure to move PSH to the surface, where it is containerized. A delay between pumping cycles allows for recharge of fluids in the monitoring well and prevents over-pumping to efficiently use the power generated from the solar panels. Bi-weekly to monthly site visits were conducted in 2021 to monitor system performance, PSH recovery, and conduct system operations and maintenance (O&M). Between May 24, 2021, and October 27, 2021, the liquid recovery intake switch alarm and compressor solenoids required troubleshooting and service. Replacement parts were installed, but delivery delays due supply chain issues resulted in a longer than anticipated system downtime. The system was running efficiently after the cable was replaced.

WSP USA 848 EAST 2ND AVENUE DURANGO CO 81301

Tel.: 970-385-1096 wsp.com



RESULTS

Depth to groundwater information and analytical results are provided in Tables 1 and 2, respectively. Groundwater collection forms and analytical laboratory reports for the analyzed samples are included in Enclosure A and Enclosure B, respectively.

Depth to groundwater was collected on March 31, 2021, May 24, 2021, August 23, 2021, and November 23, 2021. Depth to groundwater data collected on May 23, 2021, during the annual groundwater sampling event, indicated groundwater was present at elevations between 6,146.15 feet (MW-7) and 6,150.74 feet (MW-1) amsl. Based on data collected during the four quarterly events, the interpreted groundwater-flow direction is to the southeast (contours shown on Figures 2 through 5). Contours were inferred based on groundwater elevations and physical characteristics at the Site (topography, proximity to irrigation ditches, etc.). PSH levels in MW-3 ranged in thickness from 0.52 feet in March 2021 to 2.03 feet in August 2021. PSH thickness and approximate plume extent are depicted on Figures 2 through 5.

The on-site wells, except for MW-1, MW-3, and MW-4, were sampled on May 24, 2021. BTEX constituents in groundwater were detected in monitoring wells MW-2 and MW-5. Groundwater from wells MW-2 and MW-5 contained benzene concentrations of 28 μ g/L and 58 μ g/L, respectively, which exceed the NMWQCC standard. Monitoring wells MW-6 and MW-7 did not contain detectable concentrations of BTEX compounds in groundwater and were all compliant with the NMWQCC standards. BTEX results and approximate plume extent are presented on Figure 4 and summarized in Table 2.

Approximately 34.3 gallons of PSH have been recovered from monitoring well MW-3 through pneumatic pumping since PSH recovery installation on November 18, 2019, through December 17, 2021. A total of 12.0 gallons of PSH were recovered in 2021. At the time of the installation of the PSH recovery system in November 2019, the PSH thickness was 1.93 feet; in 2021, PSH ranged in thickness from 0.52 feet in March 2021 to 2.03 feet in August 2021. Operation data and system maintenance data are summarized in Table 3.

CONCLUSION

Impacted groundwater at the Site has been successfully delineated with downgradient monitoring wells MW-6 and MW-7 in compliance with NMWQCC standards for BTEX in groundwater and the absence of PSH in each well. Additionally, groundwater data collected during this year, as well as historical groundwater data, indicate contaminant concentrations have declined over time. Despite the decline in contaminant concentrations in most wells, PSH remains in well MW-3.

To address residual PSH at the Site, WSP installed a mechanical PSH pumping system in monitoring well MW-3 in November 2019. Approximately 34.3 gallons of PSH have been recovered from monitoring well MW-3 through pneumatic pumping since PSH recovery installation on November 18, 2019.

With the installation of the PSH recovery system, WSP recommends monthly site visits for O&M purposes. Additional O&M visits may be necessary depending on product recovery rates and system maintenance requirements. In addition, WSP recommends groundwater monitoring through quarterly well gauging (depth-to-groundwater and depth-to-PSH measurements) and annual groundwater sampling for laboratory analysis of BTEX compounds.

Kind regards,

Eric Carroll Associate Geologist

Exic Canall

848 EAST 2ND AVENUE DURANGO CO 81301

Tel.: 970-385-1096

Brooke Herb Sr. Consultant, Geologist

Page 3



Encl.

Figure 1: Site Location Map

Figure 2: Groundwater Elevations and Analytical Results (March 2021)

Figure 3: Groundwater Elevations and Analytical Results (June 2021)

Figure 4: Groundwater Elevations and Analytical Results (September 2021)

Figure 5: Groundwater Elevations and Analytical Results (December 2021)

Table 1: Groundwater Elevation Summary

Table 2: Groundwater Laboratory Analytical Results


Table 3: Pneumatic Product Recovery System Data


Enclosure A: Groundwater Collection Forms Enclosure B: Laboratory Analytical Results


WSP USA 848 EAST 2ND AVENUE DURANGO CO 81301


Tel.: 970-385-1096 wsp.com


FIGURES











TABLES

TABLE 1

Well Name	Date	Top of Casing Elevation (feet AMSL)	Depth to Groundwater (feet BTOC)	Depth to Product (feet BTOC)	Product Thickness (feet)	Groundwater Elevation (feet AMSL)
MW-1	4/2/2012	6,229.61	UNK	UNK	UNK	UNK
MW-1	6/13/2012	6,229.61	UNK	UNK	UNK	UNK
MW-1	10/2/2012	6,229.61	UNK	UNK	UNK	UNK
MW-1	12/6/2012	6,229.61	UNK	UNK	UNK	UNK
MW-1	3/1/2013	6,229.61	99.52	NP	NP	6,130.09
MW-1*	6/24/2013	6,250.21	99.41	9.41 NP NP		6,150.80
MW-1	9/12/2013	6,250.21	98.90	NP	NP	6,151.31
MW-1	12/4/2013	6,250.21	98.79	9 NP N		6,151.42
MW-1	3/19/2014	6,250.21	99.08	NP	NP	6,151.13
MW-1	6/13/2014	6,250.21	99.02	NP	NP	6,151.19
MW-1	9/11/2014	6,250.21	99.01	NP	NP	6,151.20
MW-1	12/4/2014	6,250.21	99.18	NP	NP	6,151.03
MW-1	3/17/2015	6,250.21	99.14	NP	NP	6,151.07
MW-1	4/28/2016	6,250.21	99.17	NP	NP	6,151.04
MW-1	8/11/2016	6,250.21	99.28	NP	NP	6,150.93
MW-1	10/17/2016	6,250.21	99.20	NP	NP	6,151.01
MW-1	1/31/2017	6,250.21	99.24	NP	NP	6,150.97
MW-1	4/28/2017	6,250.21	99.24	NP	NP	6,150.97
MW-1	7/28/2017	6,250.21	99.31	NP	NP	6,150.90
MW-1**	10/7/2019	6,250.35	99.54	NP	NP	6,150.81
MW-1	3/19/2020	6,250.35	99.52	NP	NP	6,150.83
MW-1	6/23/2020	6,250.35	99.57	NP	NP	6,150.78
MW-1	9/8/2020	6,250.35	99.31	NP	NP	6,151.04
MW-1	12/4/2020	6,250.35	99.59	NP	NP	6,150.76
MW-1	3/31/2021	6,250.35	99.81	NP	NP	6,150.54
MW-1	5/24/2021	6,250.35	99.61	NP	NP	6,150.74
MW-1	8/23/2021	6,250.35	100.09	NP	NP	6,150.26
MW-1	11/23/2021	6,250.35	100.02	NP	NP	6,150.33
MW-2	4/2/2012	6,226.30	UNK	UNK	UNK	UNK
MW-2	6/13/2012	6,226.30	UNK	UNK	UNK	UNK
MW-2	10/2/2012	6,226.30	UNK	UNK	UNK	UNK
MW-2	12/6/2012	6,226.30	UNK			UNK
MW-2	3/1/2013	6,226.30	98.47			6,127.83
MW-2*	6/24/2013	6,247.15	98.45	8.45 NP NP		6,148.70
MW-2	9/12/2013	6,247.15	98.60			6,148.55
MW-2	12/4/2013	6,247.15	98.41	NP	NP	6,148.74

TABLE 1

Well Name	Date	Top of Casing Elevation (feet AMSL)	Depth to Groundwater (feet BTOC)	Depth to Product (feet BTOC)	Product Thickness (feet)	Groundwater Elevation (feet AMSL)
MW-2	3/19/2014	6,247.15	98.54	NP	NP	6,148.61
MW-2	6/13/2014	6,247.15	98.53	NP	NP	6,148.62
MW-2	9/11/2014	6,247.15	98.60	NP	NP	6,148.55
MW-2	12/4/2014	6,247.15	98.56	NP NP		6,148.59
MW-2	3/17/2015	6,247.15	98.63	NP	NP	6,148.52
MW-2	4/28/2016	6,247.15	98.73	NP	NP	6,148.42
MW-2	8/11/2016	6,247.15	98.76	NP	NP	6,148.39
MW-2	10/17/2016	6,247.15	98.73	NP	NP	6,148.42
MW-2	1/31/2017	6,247.15	98.77	NP	NP	6,148.38
MW-2	4/28/2017	6,247.15	98.76	NP	NP	6,148.39
MW-2	7/28/2017	6,247.15	98.82	NP	NP	6,148.33
MW-2**	10/7/2019	6,247.28	99.03	NP	NP	6,148.25
MW-2	3/19/2020	6,247.28	99.03	NP	NP	6,148.25
MW-2	6/23/2020	6,247.28	99.07	NP	NP	6,148.21
MW-2	9/8/2020	6,247.28	98.96	NP	NP	6,148.32
MW-2	12/4/2020	6,247.28	99.10	NP	NP	6,148.18
MW-2	3/31/2021	6,247.28	99.22	NP	NP	6,148.06
MW-2	5/24/2021	6,247.28	99.14	NP	NP	6,148.14
MW-2	8/23/2021	6,247.28	99.11	NP	NP	6,148.17
MW-2	11/23/2021	6,247.28	99.15	NP	NP	6,148.13
MW-3	4/2/2012	6,217.53	UNK	UNK	UNK	UNK
MW-3	6/13/2012	6,217.53	UNK	UNK	UNK	UNK
MW-3	10/2/2012	6,217.53	UNK	UNK	UNK	UNK
MW-3	12/6/2012	6,217.53	UNK	UNK	UNK	UNK
MW-3	3/1/2013	6,217.53	92.48	91.51	0.97	6,125.83
MW-3*	6/24/2013	6,238.51	91.71	90.86	0.85	6,147.48
MW-3	9/12/2013	6,238.51	91.69	90.89	0.80	6,147.46
MW-3	12/4/2013	6,238.51	91.23	90.83	0.40	6,147.60
MW-3	3/19/2014	6,238.51	91.59	91.03	0.56	6,147.37
MW-3	6/13/2014	6,238.51	91.38	91.08	0.30	6,147.37
MW-3	9/11/2014	6,238.51	91.47			6,147.26
MW-3	12/4/2014	6,238.51	91.15	91.15† <0.01		6,147.36
MW-3	3/17/2015	6,238.51	91.53	91.22 0.31		6,147.23
MW-3	4/28/2016	6,238.51	92.00 91.20 0.80		0.80	6,147.15
MW-3	8/11/2016	6,238.51	92.54	91.18	1.36	6,147.06

TABLE 1

Well Name	Date	Top of Casing Elevation (feet AMSL)	Depth to Groundwater (feet BTOC)	Depth to Product (feet BTOC)	Product Thickness (feet)	Groundwater Elevation (feet AMSL)	
MW-3	10/17/2016	6,238.51	92.54	91.56	0.98	6,146.75	
MW-3	1/31/2017	6,238.51	92.59	91.09	1.50	6,147.12	
MW-3	4/28/2017	6,238.51	92.10	91.21	0.89	6,147.12	
MW-3	7/28/2017	6,238.51	92.28	91.26 1.02		6,147.05	
MW-3**	10/7/2019	6,238.66	93.46	91.31	2.15	6,146.92	
MW-3	3/19/2020	6,238.66	92.85	91.62	1.23	6,146.79	
MW-3	6/23/2020	6,238.66	92.41	91.83	0.58	6,146.71	
MW-3	9/8/2020	6,238.66	91.71	91.66	0.05	6,146.99	
MW-3	12/4/2020	6,238.66	92.90	91.72	1.18	6,146.70	
MW-3	3/31/2021	6,238.66	92.60	92.08	0.52	6,146.48	
MW-3	5/24/2021	6,238.66	92.91	91.68	1.23	6,146.73	
MW-3	8/23/2021	6,238.66	93.62	91.59	2.03	6,146.66	
MW-3	11/23/2021	6,238.66	92.94	91.81	1.13	6,146.62	
				•			
MW-4	4/2/2012	6,219.93	UNK	UNK	UNK	UNK	
MW-4	6/13/2012	6,219.93	UNK	UNK	UNK	UNK	
MW-4	10/2/2012	6,219.93	UNK	UNK	UNK	UNK	
MW-4	12/6/2012	6,219.93	UNK	UNK	UNK	UNK	
MW-4	3/1/2013	6,219.93	92.02	NP	NP	6,127.91	
MW-4*	6/24/2013	6,240.67	91.98	NP	NP	6,148.69	
MW-4	9/12/2013	6,240.67	92.00	NP	NP	6,148.67	
MW-4	12/4/2013	6,240.67	91.96	NP	NP	6,148.71	
MW-4	3/19/2014	6,240.67	92.09	NP	NP	6,148.58	
MW-4	6/13/2014	6,240.67	92.06	NP	NP	6,148.61	
MW-4	9/11/2014	6,240.67	92.13	NP	NP	6,148.54	
MW-4	12/4/2014	6,240.67	92.10	NP	NP	6,148.57	
MW-4	3/17/2015	6,240.67	92.17	NP	NP	6,148.50	
MW-4	4/28/2016	6,240.67	92.25	NP	NP	6,148.42	
MW-4	8/11/2016	6,240.67	92.32	NP	NP	6,148.35	
MW-4	10/17/2016	6,240.67	92.29	NP	NP	6,148.38	
MW-4	1/31/2017	6,240.67	92.31	NP NP		6,148.36	
MW-4	4/28/2017	6,240.67	92.31	NP NP		6,148.36	
MW-4	7/28/2017	6,240.67	92.36	NP NP		6,148.31	
MW-4**	10/7/2019	6,240.80	92.60	NP NP		6148.20	
MW-4	3/19/2020	6,240.80	92.58	92.58 NP NP		6148.22	
MW-4	6/23/2020	6,240.80	92.63	NP	NP	6148.17	

TABLE 1

Well Name	Date	Top of Casing Elevation (feet AMSL)	Depth to Groundwater (feet BTOC)	Depth to Product (feet BTOC)	Product Thickness (feet)	Groundwater Elevation (feet AMSL)
MW-4	9/8/2020	6,240.80	92.53	NP	NP	6148.27
MW-4	12/4/2020	6,240.80	92.65	NP	NP	6148.15
MW-4	3/31/2021	6,240.80	92.86	NP	NP	6147.94
MW-4	5/24/2021	6,240.80	92.66	NP	NP	6148.14
MW-4	8/23/2021	6,240.80	92.67	NP	NP	6148.13
MW-4	11/23/2021	6,240.80	92.70	NP	NP	6148.10
MW-5	4/2/2012	6,216.97	UNK	UNK	UNK	UNK
MW-5	6/13/2012	6,216.97	UNK	UNK	UNK	UNK
MW-5	10/2/2012	6,216.97	UNK	UNK	UNK	UNK
MW-5	12/6/2012	6,216.97	UNK	UNK	UNK	UNK
MW-5	3/1/2013	6,216.97	90.48	90.46	0.02	6,126.51
MW-5*	6/24/2013	6,238.33	89.78	NP	NP	6,148.55
MW-5	9/12/2013	6,238.33	89.98	NP	NP	6,148.35
MW-5	12/4/2013	6,238.33	89.86	NP	NP	6,148.47
MW-5	3/19/2014	6,238.33	89.91	NP	NP	6,148.42
MW-5	6/13/2014	6,238.33	89.95	NP	NP	6,148.38
MW-5	9/11/2014	6,238.33	90.02	NP	NP	6,148.31
MW-5	12/4/2014	6,238.33	90.02	NP	NP	6,148.31
MW-5	3/17/2015	6,238.33	89.98	NP	NP	6,148.35
MW-5	4/28/2016	6,238.33	90.11	NP	NP	6,148.22
MW-5	8/11/2016	6,238.33	90.20	NP	NP	6,148.13
MW-5	10/17/2016	6,238.33	90.18	NP	NP	6,148.15
MW-5	1/31/2017	6,238.33	90.11	NP	NP	6,148.22
MW-5	4/28/2017	6,238.33	90.13	NP	NP	6,148.20
MW-5	7/28/2017	6,238.33	90.17	90.16	0.01	6,148.16
MW-5**	10/14/2019	6,236.47	88.3	NP	NP	6,148.17
MW-5	3/19/2020	6,236.47	88.37	NP	NP	6,148.10
MW-5	6/23/2020	6,236.47	88.41	NP	NP	6,148.06
MW-5	9/8/2020	6,236.47	88.35	NP	NP	6,148.12
MW-5	12/4/2020	6,236.47	88.42	NP	NP	6,148.05
MW-5	3/31/2021	6,236.47	88.55	NP	NP	6,147.92
MW-5	5/24/2021	6,236.47	88.43	NP	NP	6,148.04
MW-5	8/23/2021	6,236.47	88.46	NP	NP	6,148.01
MW-5	11/23/2021	6,236.47	88.51	NP	NP	6,147.96

TABLE 1

Well Name	Date	Top of Casing Elevation (feet AMSL)	Depth to Groundwater (feet BTOC)	Depth to Product (feet BTOC)	Product Thickness (feet)	Groundwater Elevation (feet AMSL)
MW-6**	10/14/2019	6,235.26	88.42	NP	NP	6,146.84
MW-6	3/19/2020	6,235.26	88.51 NP		NP	6,146.75
MW-6	6/23/2020	6,235.26	88.52 NP NP		NP	6,146.74
MW-6	9/8/2020	6,235.26	88.30	NP	NP	6,146.96
MW-6	12/4/2020	6,235.26	88.53	NP	NP	6,146.73
MW-6	3/31/2021	6,235.26	88.74	NP	NP	6,146.52
MW-6	5/24/2021	6,235.26	88.60	NP	NP	6,146.66
MW-6	8/23/2021	6,235.26	88.58	NP	NP	6,146.68
MW-6	11/23/2021	6,235.26	88.49	NP	NP	6,146.77
MW-7**	10/14/2019	6,237.28	90.94	NP	NP	6,146.34
MW-7	3/19/2020	6,237.28	90.98	NP	NP	6,146.30
MW-7	6/23/2020	6,237.28	91.06	NP	NP	6,146.22
MW-7	9/8/2020	6,237.28	90.91	NP	NP	6,146.37
MW-7	12/4/2020	6,237.28	91.08	NP	NP	6,146.20
MW-7	3/31/2021	6,237.28	91.22	NP	NP	6,146.06
MW-7	5/24/2021	6,237.28	91.13	91.13 NP		6,146.15
MW-7	8/23/2021	6,237.28	91.1	91.1 NP N		6,146.18
MW-7	11/23/2021	6,237.28	91.07	NP	NP	6,146.21

< - less than

Groundwater elevation calculation in wells with product: (Top of Casing Elevation - Depth to Water) + (Product Thickness * 0.8)

AMSL - above mean sea level

BTOC - below top of casing

NP - no free phase hydrocarbons are present the well

UNK - data is not known

^{* -} Top of casing elevation was resurveyed on 6/20/13

^{** -} Top of casing elevation was resurveyed on 12/17/2019

^{† -} Oil-water interface probe did not detect phase separated hydrocarbons. PSH observed visually using a bailer.

TABLE 2

GROUNDWATER LABORATORY ANALYTICAL RESULTS FLORACE #47X SAN JUAN COUNTY, NEW MEXICO

Well Name	Sample Date	Benzene (μg/L)	Toluene (μg/L)	Ethylbenzene (μg/L)	Total Xylenes (μg/L)
NMWQCC S	tandard (µg/L)	5	1,000	700	620
MW-1	1/8/1997	3,380	7,150	917	7,200
MW-1	7/13/1997	367	241	35	191
MW-1	10/1/1997	171	54	27	65
MW-1	1/6/1998	147	70	20	73.6
MW-1	3/9/1998	140	1.4	17	36
MW-1	6/11/1998	94	19	11	16.3
MW-1	8/12/1998	49	4.7	8.8	5.7
MW-1	12/15/1998	46	11	5.8	4.7
MW-1	2/9/1999	33	6.6	5.6	4.7
MW-1	4/21/1999	40	15	6.4	10.4
MW-1	7/28/1999	34	7.8	3	3.0
MW-1	11/3/1933	2.9	< 0.5	< 0.5	<1.5
MW-1	3/23/2000	10	1.1	< 0.5	<1.5
MW-1	6/14/2000	4.1	1.4	0.6	<1.5
MW-1	11/17/2000	4.64	<1.0	<1.0	<1.0
MW-1	1/31/2001	3.67	1.44	<1.0	<1.0
MW-1	4/30/2001	5.44	1.90	<1.0	1.78
MW-1	10/10/2001	1.1	<2.0	<2.0	<2.0
MW-1	12/2/2003	<2.0	<2.0	<2.0	<5.0
MW-1	9/20/2004	3.4	<2.0	<2.0	<5.0
MW-1	12/3/2004	<2.0	<2.0	<2.0	<5.0
MW-1	3/10/2005	<2.0	<2.0	<2.0	<5.0
MW-1	6/18/2005	<2.0	<2.0	<2.0	<5.0
MW-1	7/13/2006	2.2	<1.0	<1.0	<3.0
MW-1	9/21/2006	4.9	<1.0	<1.0	<3.0
MW-1	3/29/2010 6/18/2010	<1.0 <1.0	<1.0 <1.0	<1.0 <1.0	<3.0 <3.0
MW-1		1.2		<1.0	<3.0
MW-1	9/10/2010 12/4/2010	<1.0	<1.0 <1.0	<1.0	<3.0
MW-1 MW-1	3/2/2011	<1.0	<1.0	<1.0	<3.0
MW-1	6/14/2011	3.6	<1.0	<1.0	<3.0
MW-1	9/12/2011	<1.0	<1.0	<1.0	<3.0
MW-1	1/3/2012	<1.0	<1.0	<1.0	<3.0
MW-1	4/2/2012	<1.0	<1.0	<1.0	<3.0
MW-1	6/13/2012	<1.0	<1.0	<1.0	<3.0
MW-1	10/2/2012	1.1	<1.0	<1.0	<3.0
MW-1	12/6/2012	<1.0	<1.0	<1.0	<3.0
MW-1	3/1/2013	<1.0	<1.0	<1.0	<2.0
MW-1	11/1/2019	1.4	<1.0	<1.0	<1.5
MW-1	6/23/2020	NS	NS	NS NS	NS NS
MW-1	5/24/2021	NS	NS	NS	NS
112 () E		~			
MW-2	8/12/1998	9,800	14,000	920	9,200
MW-2	12/15/1998	12,000	17,000	870	8,700

TABLE 2

GROUNDWATER LABORATORY ANALYTICAL RESULTS FLORACE #47X SAN JUAN COUNTY, NEW MEXICO

Well Name	Sample Date	Benzene (µg/L)	Toluene (μg/L)	Ethylbenzene (μg/L)	Total Xylenes (μg/L)
NMWQCC St	tandard (μg/L)	5	1,000	700	620
MW-2	2/9/1999	11,000	16,000	720	7,300
MW-2	4/21/1999	14,000	20,000	850	8,500
MW-2	7/28/1999	11,000	15,000	740	6,800
MW-2	11/3/1999	11,000	14,000	770	8,100
MW-2	3/23/2000	12,000	15,000	810	8,200
MW-2	6/14/2000	6,400	7,000	570	5,800
MW-2	11/17/2000	5,980	3,240	600	4,780
MW-2	1/31/2001	6,300	2,790	458	5,490
MW-2	4/30/2001	7,160	2,200	404	7,060
MW-2	10/10/2001	4,500	1,000	390	3,800
MW-2	12/2/2003	11,000	<100	540	6,400
MW-2	9/20/2004	11,000	<200	600	5,800
MW-2	12/3/2004	11,000	<200	630	6,300
MW-2	3/10/2005	10,000	38	490	5,700
MW-2	6/18/2005	9,700	<100	640	6,000
MW-2	9/16/2005	8,900	31	370	4,800
MW-2	11/30/2005	<2.0	2.9	<2.0	12.2
MW-2	7/18/2006	16,900	<10.0	753	4,370
MW-2	3/29/2010	9,460	67	521	6,210
MW-2	6/18/2010	3,270	<1.0	260	3,530
MW-2	12/4/2010	1,470	26.3	599	2,720
MW-2	3/2/2011	2,530	1.4	764	3,700
MW-2	6/14/2011	8,500	<20.0	537	4,490
MW-2	1/3/2012	9,400	<50.0	710	6,340
MW-2	4/2/2012	10,000	710	<100	6,390
MW-2	6/13/2012	11,200	716	<50.0	6,790
MW-2	10/2/2012	10,200	765	<100	7,260
MW-2	12/6/2012	8,280	722	<50.0	5,610
MW-2	3/4/2013	8,600	<10	<10	6,500
MW-2	6/24/2013	6,300	<10	600	5,800
MW-2	9/12/2013	NSO	NSO	NSO	NSO
MW-2	12/4/2013	39	72	<5.0	150
MW-2	3/19/2014	9,700	<10	760	7,000
MW-2	6/13/2014	8,600	<10	290	5,800
MW-2	9/11/2014	9,700	<10	490	7,200
MW-2	12/8/2014	9,400	<10	360	6,900
MW-2	3/17/2015	5,000	<20	340	3,000
MW-2	4/28/2017	5,100	<5	410	3,600
MW-2	11/1/2019	4,600	<1.0	270	190
MW-2	6/23/2020	8,200	<20	410	150
MW-2	5/24/2021	28	<1.0	5.1	6.7
MANY 2	4/2/2012	NC	NG	NG	NO
MW-3	4/2/2012	NS NC	NS NG	NS	NS NG
MW-3	6/13/2012	NS	NS	NS	NS

TABLE 2

GROUNDWATER LABORATORY ANALYTICAL RESULTS FLORACE #47X SAN JUAN COUNTY, NEW MEXICO

Well Name	Sample Date	Benzene (µg/L)	Toluene (μg/L)	Ethylbenzene (µg/L)	Total Xylenes (μg/L)	
NMWQCC S	tandard (µg/L)	5	1,000	700	620	
MW-3	10/2/2012	NS	NS	NS	NS	
MW-3	12/6/2012	NS	NS	NS	NS	
MW-3	3/1/2013	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	6/24/2013	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	9/12/2013	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	12/4/2013	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	3/19/2014	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	6/13/2014	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	9/11/2014	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	12/4/2014	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	3/17/2015	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	11/1/2019	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	6/23/2020	NS-FP	NS-FP	NS-FP	NS-FP	
MW-3	5/24/2021	NS-FP	NS-FP	NS-FP	NS-FP	
NASS/ 4	12/15/1000	4.4	11	5.8	4.8	
MW-4	12/15/1998	44	11	_		
MW-4	2/9/1999 4/21/1999	11,000	16,000 25	730 9.3	7,300	
MW-4		68 25 11,000 14,000		700		
MW-4	7/2/1999 3/23/2000		/	770	6,700	
MW-4 MW-4	6/14/2000	11,000 28	13,000 42	770	7,800 135	
MW-4	11/17/2000	59.9	104	2.94	98.3	
MW-4	1/31/2001	30.3	81.0	5.20	156	
MW-4	4/30/2001	36.1	56.1	1.32	73	
MW-4	10/10/2001	24	28	<2.0	47	
MW-4	12/2/2003	2.3	2.7	<2.0	6.5	
MW-4	9/20/2004	3.6	3.2	<2.0	9.8	
MW-4	12/3/2004	2.5	2.3	<2.0	8	
MW-4	3/10/2005	3.0	3.5	<2.0	11	
MW-4	6/18/2005	<2.0	3	<2.0	8.6	
MW-4	9/16/2005	<2.0	2.3	<2.0	9.4	
MW-4	11/30/2005	<2.0	<2.0	<2.0	10.4	
MW-4	7/13/2006	2.9	<1.0	1.0	9.9	
MW-4	9/21/2006	1.2	<1.0	<1.0	9.6	
MW-4	3/29/2010	1.3	<1.0	<1.0	8.7	
MW-4	6/18/2010	<1.0	<1.0	<1.0	6.8	
MW-4	9/10/2010	<1.0	<1.0	<1.0	3.9	
MW-4	12/4/2010	<1.0	<1.0	<1.0	5.6	
MW-4	3/2/2011	<1.0	<1.0	<1.0	3	
MW-4	6/14/2011	<1.0	<1.0	<1.0	6	
MW-4	9/12/2011	<1.0	<1.0	<1.0	4.7	
MW-4	1/3/2012	<1.0	<1.0	<1.0	5.4	
MW-4	4/2/2012	<1.0 <1.0	<1.0	<1.0	6.1	
	MW-4 4/2/2012 MW-4 6/13/2012		<1.0	<1.0	3.7	

TABLE 2

GROUNDWATER LABORATORY ANALYTICAL RESULTS FLORACE #47X SAN JUAN COUNTY, NEW MEXICO

Well Name	Sample Date	Benzene (μg/L)	Toluene (μg/L)	Ethylbenzene (μg/L)	Total Xylenes (μg/L)
NMWQCC S	tandard (µg/L)	5	1,000	700	620
MW-4	10/2/2012	<1.0	<1.0	<1.0	4.5
MW-4	12/6/2012	<1.0	<1.0	<1.0	6
MW-4	3/1/2013	<1.0	<1.0	<1.0	<2.0
MW-4	11/1/2019	<1.0	<1.0	<1.0	<1.5
MW-4	6/23/2020	NS	NS	NS	NS
MW-4	5/24/2021	NS	NS	NS	NS
MW-5	6/14/2000	1,100	710	100	1,100
MW-5	6/14/2000	890	570	80	900
MW-5	11/17/2000	161	110	8.09	60.8
MW-5	4/30/2001	15.7	21.6	2.01	17.9
MW-5	10/10/2001	380	120	19	220
MW-5	12/2/2003	41	7.9	3.1	10
MW-5	9/20/2004	17	3.7	<2.0	9.9
MW-5	12/9/2004	13	3.3	<2.0	14
MW-5	3/10/2005	5.5	<2.0	<2.0	6.3
MW-5	7/13/2006	920	74	34.7	1,980
MW-5	9/21/2006	135	19.2	17.0	409
MW-5	4/2/2012	NS	NS	NS	NS
MW-5	6/13/2012	NS	NS	NS	NS
MW-5	10/2/2012	NS	NS	NS	NS
MW-5	12/6/2012	NS	NS	NS	NS
MW-5	3/1/2013	NS-FP	NS-FP	NS-FP	NS-FP
MW-5	6/24/2013	930	< 50	98	1,100
MW-5	9/12/2013	2,400	40	250	3,800
MW-5	12/4/2013	410	46	51	1,000
MW-5	3/19/2014	920	3.1	100	660
MW-5	6/13/2014	4,000	<20	480	1,700
MW-5	9/11/2014	3,000	33	370	2,800
MW-5	12/4/2014	3,000	14	390	2,900
MW-5	3/17/2015	570	<10	52	660
MW-5	4/28/2016	270	<10	30	400
MW-5	4/28/2017	380	<2.0	55	560
MW-5	11/1/2019	2,200	<1.0	150	210
MW-5	6/23/2020	360	<2.0	2.4	210
MW-5	5/24/2021	58	<5.0	<5.0	21
MW-6	11/1/2019	<1.0	<1.0	<1.0	<1.5
MW-6	6/23/2020	<1.0	<1.0	<1.0	<1.5
MW-6	5/4/2021	<1.0	<1.0	<1.0	<2.0

TABLE 2

GROUNDWATER LABORATORY ANALYTICAL RESULTS FLORACE #47X SAN JUAN COUNTY, NEW MEXICO

Well Name	Sample Date	Benzene (μg/L)	Toluene (μg/L)	Ethylbenzene (μg/L)	Total Xylenes (μg/L)	
NMWQCC St	tandard (µg/L)	5	1,000	700	620	
MW-7	11/1/2019	<1.0	<1.0	<1.0	<1.5	
MW-7	6/23/2020	<1.0	<1.0	<1.0	<1.5	
MW-7	5/4/2021	<1.0	<1.0	<1.0	<2.0	

Notes:

< - indicates result is less than laboratory reporting detection limit

 $\mu g/L$ - micrograms per liter

NMWQCC - New Mexico Water Quality Control Commission

NS - not sampled

NS-FP - not sampled due to the presence of free phase hydrocarbons in the well

NSO - not sampled due to obstruction

Bold - indicates sample exceeds NMWQCC standard

TABLE 3

PNUEMATIC PRODUCT RECOVERY SYSTEM DATA FLORANCE #47X SAN JUAN COUNTY, NEW MEXICO

Date	Well ID	Cycles	Run Time (hours)	Cycles (Lifetime)	Lifetime (hours)	Estimated Product Recovered (gallons)	Depth to Product (feet)	Depth to Water (feet)	PSH Thickness (feet)	Battery Voltage	System ON/OFF	Any Faults	Notes/Maintenance Completed
11/18/2019	MW-3	0	0:00:00	1,809	160:07:11	0.0	91.26	93.19	1.93	12.7	ON	NO	Installed sipper at MW-3 vac: 18s, press: 40s, delay: 8 hours
12/3/2019	MW-3	47	13:23:00	1,856	6:16:10	0.9	91.55	93.49	1.94	12.7	ON	NO	2.5 ounces per cycle
1/9/2020	MW-3	158	2:23:03	1,967	19:06:13	2.7	91.5	93.01	1.51	12.7	ON	NO	2 oz. per cycle, 5 inches of product in barrel
1/30/2020	MW-3	221	71:23:46	2,030	232:06:56	4.1	91.59	93.12	1.53	12.8	ON	NO	3 oz. product per cycle delay set to 6 hours.
2/26/2020	MW-3	303	99:04:18	2,112	0003:11:28	5.4	91.8	93.1	1.3	12.8	ON	NO	2 oz per cycle, changed delay to 6 hours.
3/19/2020	MW-3	390	120:22:41	2,199	0025:05:52	6.8	91.62	92.85	1.23	12.8	ON	NO	2 oz per cycle, ~4.5 inches of product in barrel
4/1/2020	MW-3	391	120:23:13	2,200	0025:06:23	6.8	91.46	92.95	1.49	12.7	ON	NO	~ 1 oz per cycle, changed solar panel to 26 degrees from 0.
4/20/2020	MW-3	467	139:23:28	2,276	0044:06:38	7.4	91.7	92.49	0.79	12.7	ON	NO	Cleaned panel/pump,~ 5" inches of product in barrel
5/4/2020	MW-3	523	154:00:04	2,332	0058:04:15	7.8	91.83	92.4	0.57	12.7	ON	NO	Cleaned panel/pump, 6" inches of product in barrel. 1 oz recovered in cycle.
6/23/2020	MW-3	727	204:01:16	2,536	108:08:27	12.6	91.83	92.41	0.58	12.9	ON	NO	Clean pump, 9" of product in barrel 3 oz. recovered per cycle.

TABLE 3

PNUEMATIC PRODUCT RECOVERY SYSTEM DATA FLORANCE #47X SAN JUAN COUNTY, NEW MEXICO

Date	Well ID	Cycles	Run Time (hours)	Cycles (Lifetime)	Lifetime (hours)	Estimated Product Recovered (gallons)	Depth to Product (feet)	Depth to Water (feet)	PSH Thickness (feet)	Battery Voltage	System ON/OFF	Any Faults	Notes/Maintenance Completed
7/24/2020	MW-3	861	235:00:56	2,670	139:08:07	17.8	91.84	92.44	0.6	12.9	ON	NO	Clean pump/solar panel, 9" of product in barrel, bailed 5 oz of product from well
8/6/2020	MW-3	918	248:02:02	2,727	152:09:12	18.3	91.84	91.87	0.03	12.9	ON	NO	Clean pump/solar panel, 9" of product in barrel
9/8/2020	MW-3	1,061	25:00:01	2,870	185:07:11	20.5	91.66	91.71	0.05	12.9	ON	NO	Change vacuum to 10 seconds and delay to 10 hours
9/25/2020	MW-3	1,070	28:08:15	2,879	188:15:26	20.6	91.72	92.69	0.97	13.3	ON	ntake Overloa	Clean pump/solar panel, 16" of product in barrel, Repair cracked intake lines
10/14/2020	MW-3	1,098	40:00:58	2,907	200:08:08	21.1	91.87	92.5	0.63	12.7	ON	ntake Overloa	Clean pump/solar panel, 20" of product in barrel, Repair cracked intake lines. Polytube needs to be replaced with vinyl.
10/26/2020	MW-3	1,110	44:05:25	2,912	204:12:36	21.3	91.72	92.69	0.97	12.6	ON	ntake Overloa	21" of product in barrel, replace intake lines. Clean snow of solar Panel.
11/4/2020	MW-3	1,118	44:05:25	2,927	204:12:36	21.4	91.7	92.66	0.96	12.6	ON	ntake Overloa	22" of product in barrel.
11/24/2020	MW-3	1,121	48:19:28	2,930	209:02:39	21.4	91.59	92.71	1.12	13	ON	ntake Overloa	21" of product in barrel. Clean solar Panel.
12/4/2020	MW-3	1,140	58:17:47	2,949	219:00:57	21.7	91.72	92.90	1.18	12.6	ON	NO	Increase pressure cycle to 2:15 to clear intake. Delay set to 10 hours
12/18/2020	MW-3	1,173	72:16:37	2,982	232:23:47	22.2	91.69	92.90	1.21	12.7	ON	NO	\sim 6" in barrel, 1 oz recovered in cycle

TABLE 3

PNUEMATIC PRODUCT RECOVERY SYSTEM DATA FLORANCE #47X SAN JUAN COUNTY, NEW MEXICO

Date	Well ID	Cycles	Run Time (hours)	Cycles (Lifetime)	Lifetime (hours)	Estimated Product Recovered (gallons)	Depth to Product (feet)	Depth to Water (feet)	PSH Thickness (feet)	Battery Voltage	System ON/OFF	Any Faults	Notes/Maintenance Completed
12/30/2020	MW-3	1,180	75:05:06	2,989	235:12:16	22.3	91.7	93.02	1.32	12.7	ON	ntake Overload	Cleaned pump, attached white tubing from pump back to solar sipper control box, changed solar panel angle to 51 degrees for winter, 1 oz PSH recovered in cycle, ~6 " in barrel.
1/13/2021	MW-3	1,214	89:05:49	3,023	249:13:00	22.8	91.78	92.48	0.7	12.7	ON	NO	~6.5" PSH in bbl. Cleaned solar panel. 2 oz yellow/brown PSH recovered in cycle.
2/1/2021	MW-3	1,256	106:19:27	3,065	11:02:37	23.5	92.07	92.64	0.57	12.8	ON	ntake Overloa	~18" PSH in bbl. Cleaned solar panel. 3 oz yellow/brown PSH recovered in cycle. Intake line cracked, repair and system returned to normal operation
2/16/2021	MW-3	1,295	121:18:34	3,104	26:01:44	24.1	91.64	92.69	1.05	13.6	ON	ntake Overload	~19" PSH in bbl. Air line frozen at well head, Warmed with hand and ran 2 cycles to clear condensation in line.
3/12/2021	MW-3	1,330	135:06:54	3,139	39:14:04	24.6	91.54	92.89	1.35	12.7	ON	ntake Overloa	Cleaned out air lines
3/31/2021	MW-3	1,402	152:16:33	3,211	56:23:43	25.8	92.08	92.6	0.52	12.8	ON	ntake Overload	~19" PSH in bbl. Replaced Discharge line.
4/15/2021	MW-3	1,437	163:09:42	3,246	67:16:52	26.0	92.00	92.70	0.70	14.3	ON	No	Angle solar panel to 54 degrees for summer sun.
5/24/2021	MW-3	1,448	166:23:46	3,257	71:06:56	26.1	91.68	92.91	1.23	12.8	ON	ntake Overload	Attached air supply line back to panel side.
6/21/2021	MW-3	1,461	170:06:08	3,270	74:13:18	26.2	91.64	93.11	1.47	13.4	ON	NO	Adjust pump depth
7/27/2021	MW-3	1,464	170:20:14	3,273	75:03:24	26.2	NP	92.61	NP	12.8	ON	intake Overrido	Clear fault and air lines reset pump

TABLE 3

PNUEMATIC PRODUCT RECOVERY SYSTEM DATA FLORANCE #47X SAN JUAN COUNTY, NEW MEXICO

Date	Well ID	Cycles	Run Time (hours)	Cycles (Lifetime)	Lifetime (hours)	Estimated Product Recovered (gallons)	Depth to Product (feet)	Depth to Water (feet)	PSH Thickness (feet)	Battery Voltage	System ON/OFF	Any Faults	Notes/Maintenance Completed
8/23/2021	MW-3	1,464	170:20:14	3,274	75:03:24	26.2	NP	93.61	NP	13.8	ON	intake Overrid	Clear fault and air lines reset pump. Need to replace cable for Intake alarm.
8/27/2021	MW-3	1,464	170:20:14	3,273	75:03:24	26.2	91.58	93.52	1.94	12.7	Off	Off	Panel off in setup mode. Directional solenoid broken.
10/27/2021	MW-3	1,479	170:21:39	3,288	75:04:49	26.4	91.57	93.55	1.98	12.8	ON	ntake Overloa	Replace cable at intake float.
11/10/2021	MW-3	1,562	184:22:51	3,371	89:06:01	28.3	ı	ı	ı	12.7	ON	NO	
11/23/2021	MW-3	1,641	197:23:12	3,450	102:06:22	30.2	91.81	92.94	1.13	12.8	ON	NO	Clean and reset pump.
12/17/2021	MW-3	1,816	220:05:20	3,625	124:01:30	34.3	l	91.47	ı	12.7	ON	ntake Overloa	~17" PSH in bbl. Reset pump. Ran 2 cycles, ice in discharge line, ~ 2 oz water and oily product recovered on 2nd cycle.

Notes:

PSH - phase separated hydrocarbons

NP - No product observed

ENCLOSURE A – GROUNDWATER COLLECTION FORMS

—
1
Name of
0
P4
-
90
õ
٠.
00
200
0
_
0
* 4
7.4
0
~
2.1
1
-
\sim
100
3
٠.
()
_
\sim
_
-
9
-
್ಲಾ
-
* 100
0
- 63
Ö
~~

			Wate	er Sample	Collection I	Form_
Sample Loc	ation	Florance	e 47x			Harvest Four Corners, LLC
Sample Dat		5.24.2				
Sample Tim		1438				
Sample ID		mw-a)	e		
1		BTEX 8021				
Analyses						11.11.5
Matrix		Groundwat	er			Hall Environmental
Turn Aroun		Standard				Hand delivery
Depth to W	ater	99.14				TD: 109.20
Time						
Vol. of H2O	to purge	4.9 ga	Uons			well or 0.6524 for 4" well) * 3 well vols
		(he	eight of wate	er column *	0.1631 for 2"	well or 0.6524 for 4" well) * 3 well vols
Method of	Purging	PVC ba	iler			
Method of	Sampling	PVCb	ailer			
	l val	Total Vol				
Time	Vol. Removed	H2O	pН	Temp.	Conductivity	Comments
"""	(gal.)	removed	(std. units)	(F or (())	(us or ms)	Comments
1111	(80)	(gal.)	2 -01	21,	10-7	0) 15 1 5
1417			7.08	21.5	1574	Black No sheen. Strong odbir
1423		2	7.09	19.0	1387	"" Sheen, ""
1428		3	7. DG	18.4	1646	(('1)
1438		4.9	7.09	17.7	2.1245	Et 15
		3				
		V				
Comments						
Comments	•					
						Nd
_			-2-2115	,		39
Describe De	eviations fro	om SOP:				
						20
<u> </u>	0 11	-1				
Signature	leith	mes	<u> </u>		- 2	5.24.21
						Released to Imagine: 5/10/2024 3:00:36
						9
						pas

- 8		
	2	ú
	5	
- 6	4	
		٠
- 6	×	
-	2	
- 0	3	١,
		۰
	٠	١
	٧	Ľ
•	Y	
-		ċ
•	Ė	3
	۰	ī
		1
. 7	•	
- 1		۵
	_	Ì
- 2		
- 0	3	۹
	•	
- 1	-	١
- 6		٦
	`	٠
-		į
,	ú	
5	٧	
9	7	
	7	
	7/7	
07.0	٧	
07.0	7/7	
0,0	`	1
07.0	•	
200	`	1
47.0	•	1
200	•	1
200	•	1
CO CELO	•	
200	•	
000	•	
200	•	
200	Y . (1) / (1)	
000	7 . () () ()	
2000	7 . () () ()	
2000 1	Y . (1) / (1)	
2000 11	A . () () () ()	
20 000 11	A . () () () ()	
22 000 21	7	1000
2000 11	7	1000
22 000 11	2	
22 000 11	2	
C C C C L L .	2	
C C C C L L .	2	
00 COO 11 .	2	
00 abo 11 .	2	
00 abo 11 .	2	
200 11 .	2	
200 11 .	2	

			vvate	er Sample	Collection	rorm
Sample Loc	ation	Floran	ce 47K			Harvest Four Corners, LLC
Sample Dat		5.24.8				
Sample Tim	ne	1324				
Sample ID		mw-5				
Analyses		BTEX 8021				
Matrix		Groundwat	er			Hall Environmental
Turn Aroun	d Time	Standard		•		Hand delivery
Depth to W		88.43		•		nv: 98.53
Time		00,13		e e		10.10.00
	to nurgo	Ца	diam.	ē.		
Vol. of H2O	to purge	4.9 ga	Pight of wate	er column *	0.1631 for 2"	well or 0.6524 for 4" well) * 3 well vols
Method of	Purging	Puc ba			0.1031 joi 2	wen or o.oszajor a weny swen vois
Method of		PVC ba				
- Iviction of			1UV		1	
Time	Vol. Removed (gal.)	Total Vol H2O removed (gal.)	pH (std. units)	Temp.	Conductivity (us)or ms)	Comments
1311		1	6.99	19.8	1335	Gray, No Sheen. Strong odor
1326		2.75	7.01	17.9	1855	" " "
		8			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
		Я.				
		4.5				
				.,		
			210			
Comments	Well 1	ouited a	ly c	2.75	gallons	
			3		,	
						× 2
						39
					-50.00	8
Describe De	eviations fro	om SOP:	Did n	et ba	1 4.9	adlinos
			710	1 1/2(1)		3
						5 0.1
Signature	Caitle	- me				5.24.21
						gallons 5.94.21
						19
						Pos
						and the second s
						2

1	
_	
2	
P	
-	
-	
80	
0	
~~	
00	
0	
-	
-	
-	
_	
C	
0	
7.4	
0	
0	
5.4	
-	
-	
00	
20	
8	
a	
٠.	
3	
Ö	
Ö	
CD:	
CD:	
OCD:	
0	
v 0CD:	
v 0C	
,00	
1 by OC	
d by OC	
ived by OC	
eived by OC	
ceived by OC	
ived by OC	

### Part				Wate	er Sample	Collection I	Form
ample Date ample Time ample ID nalyses BTEX 8021 Groundwater Standard Groundwater Standard Groundwater Standard Groundwater Ime ol. of H2O to purge letchod of Purging fetchod of Sampling Time Vol. Removed (gal.) PVC bailor Time Removed (gal.) PVC bailor Total Vol. Removed (gal.) PVC bailor Tot	Sample Loc	ation	Floran	a 47K			Harvest Four Corners, LLC
ample ID nalyses BTEX 8021 Standard Groundwater Standard	Sample Dat	te	5 24	.21			
nalyses latrix Groundwater Standard Fine oil. of H2O to purge lethod of Purging lethod of Sampling Time Removed (gal.) 70. 100 100 100 100 100 100 100 10	•	ne					
Hatrix Standard Standard Standard Standard Standard Standard Hand delivery TD '10D'. 2] Method of Purging Method of Sampling PVC bailey Time Vol. Removed (gal.) PVC bailey Time (gal.) PVC bailey Total Vol. Removed (gal.) PVC bailey Total Vol. Removed (gal.) PVC bailey Time Vol. Removed (gal.) PVC bailey Total Vol. PVC bailey Comments Local Vol. PVC bailey Local Vol. PVC bailey Comments Local Vol. PVC bailey Local Vol.	Sample ID			<u> </u>			
Time Vol. Removed (gal.) -25 7 .0 19 .1 2.0 3 (Loudy No Shein I address) -32 1.245 2.1 2.1 2.1 2.1 2.1 3	Analyses						
repth to Water time ol. of H2O to purge ol. of H2O to purge St. gall.ms	Matrix			er			
S U gallons					•		
Solidar Soli		/ater	88.U				LD (100.7]
Checked of Purging PVC bailey Comments PVC bailey Conductivity Comments PVC bailey Conductivity Comments PVC bailey PVC bail							
rethod of Purging PVC bailer PVC bailer Time Removed (gal.) PWC bailer Total Vol. H20 pH (std. units) PWC bailer Conductivity (us or fis) Comments PWC bailer Comments Comments PWC bailer Conductivity (us or fis) Comments PWC bailer Comments PWC bailer Conductivity (us or fis) Comments PWC bailer Conductivity (us or fis) Conductivity (us or fis) PWC bailer Conductivity (us or fis) Comments (1778) (1778) (1778) PWC bailer Conductivity (us or fis) Conductivity (us or fis) Comments (1778) (1778) (1779) PWC bailer Conductivity (us or fis) Conductivit	Vol. of H2O	to purge	50 gal	lons	*	0.1621 6 2"	
PVC	N 4 - 4 £	Di		-	er column *	U.1631 for 2"	well or 0.6524 for 4 well) * 3 well vols
Time Removed Removed (gal.) PH Temp. (For C) (us or ms) Comments (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.) (gal.)							
Time Removed (gal.)	vietnoa or :	Sampling	PVC bo	ulev			
Time Removed (gal.) r		Vol.	1		Tomp	Conductivity	
(gal.) (gal.) 19.1 2.03 (Loudy No sheen lodor 23.2 50 1.98 18.9 18.0 2 1.00 1.	Time		1			· ·	Comments
232 50 98 189 180215		(gal.)	(gal.)	(0001 01110)	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	(3.0)	
1934 .75 498 17.2 1795	1226		.22	7.01	19.1		Goudy No sheen lodor
omments: well bailed dry @ 2.25 gallons Describe Deviations from SOP: Did not parge 5 to gallons				6.98	18.9		J 11 W
1348 2 16.94 17.8 1798 11.5 1348 3) \$56.98 16.8 1778 61.5 156 156 156 156 156 156 156 156 156 15	1234		.75	4.98	17.2	1	
omments: well bailed dry @ 2.25 gallons escribe Deviations from SOP: Did not page 5 to gallons.					-		
omments: well bailed dry @ 2.25 gallons Tescribe Deviations from SOP: Did not page 5 to gallons							
omments: well bailed dry @ 2.25 gallons escribe Deviations from SOP: Did not page 5 to gallons	1248		3) 25	6.98	16.8	1778	a v
omments: well bailed dry @ 2.25 gallons escribe Deviations from SOP: Did not page 5 to gallons			X				
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>			5/4				
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>							
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>							
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>							
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>							
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>							
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>							
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>							
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>					222 223		1
rescribe Deviations from SOP: <u>Did not punge 5 to gallons</u>	Comments	well	baile	ddry	@ 2.2:	Sallon	5
The process of grades.				,		<u> </u>	
The process of grades.					1		
The process of grades.				.,,			
The process of grades.							
	Describe D	eviations fro	om SOP:	Rid N	t pur	ge 5.6	gallons
ignature: Carle Mac 5-24-21			•				7
	Signature	Carle	M co	9 -			5-74-11
	Signature	- Mila	MINE			-	0 64.61

٩		_	
		×	
		4	
F	٦		
		7	
¢	×	5	
1	•	٥	
	٠	٠	
•		5	
¢	Ė		
	7	٦.	
	Ĺ		
•	1	٦	
ı		L	
3		ч	
(Ì	
¢	3	ĸ	
i	7	٦	
3	C	А	
ı	_	`	
7	7	۹	
•	٧	5	
1	\	Č	
•	٧	۹	
		•	
	۰	٠	
t	8	٩	
ç	•	۳	
C		١	
2	2	•	
C	7	١	
1	•	-	
	•		
	Ė	•	١
۲	ζ	٥	
'n	_		
	0	۵	
	ŝ	Ξ	
٠	'n	á	
	0	۵	
		₹	
	0		
	B		

Comments:

			Wate	er Sample	Collection F	<u>form</u>
Sample Loca	ation	Florance	47X			Harvest Four Corners, LLC
Sample Date		5.24.2			*	
Sample Time	e	1203				· · · · · · · · · · · · · · · · · · ·
Sample ID		mw-7	1			14.5
Analyses		BTEX 8021				:
Matrix		Groundwat	er			Hall Environmental
Turn Around	d Time	Standard				Hand delivery
Depth to Wa	ater	91.13				TD: 102.13
Time						
Vol. of H2O	to purge	5.3 acu	lons			· ·
		(he	ight of wate	r column * (0.1631 for 2"	well or 0.6524 for 4" well) * 3 well vols
Method of F	Purging	PVC ba	ile/		-7	
Method of S	Sampling	PVCba	ilev			
Time	Vol. Removed (gal.)	Total Vol H2O removed	pH (std. units)	Temp.	Conductivity (us or ms)	Comments
1107	(80)	(gal.)	In Clin	17.7	11.211	(1) 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
1127		. 25	6.96		1634	Cloudy, no sheen lodor
1130		.75	4.93	16.7	1587	<i>h</i> 15

Time	Vol. Removed (gal.)	Total Vol H2O removed (gal.)	pH (std. units)	Temp.	Conductivity (us or ms)	Comments
1127		. 25	6.96	17.7	1634	Cloudy no sheen lodor
1130		-90	6.93	16.7	1587	J) (())
1133		.75	6.90	16.8	1609	ħ N
1135		1	6-91	16.6	1592	/1 //
1141		2	6.87	17.2	1625	(1)
1147		3	6.89	17.2	1407	(())
1153		4	6.91	14.9	1628	(c. N
1203		5.3	6.93	17.7	1639	(CN)
			15.1			
1						

Describe Deviations from SOP:		
Signature: (M)	5-24-21	

ENCLOSURE B - LABORATORY ANALYTICAL RESULTS



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109 TEL: 505-345-3975 FAX: 505-345-4107 Website: clients.hallenvironmental.com

May 28, 2021

Brooke Herb

Harvest

1755 Arroyo Dr.

Bloomfield, NM 87413

TEL: (505) 632-4475

FAX

RE: Florance 47X OrderNo.: 2105A45

Dear Brooke Herb:

Hall Environmental Analysis Laboratory received 4 sample(s) on 5/25/2021 for the analyses presented in the following report.

These were analyzed according to EPA procedures or equivalent. To access our accredited tests please go to www.hallenvironmental.com or the state specific web sites. In order to properly interpret your results, it is imperative that you review this report in its entirety. See the sample checklist and/or the Chain of Custody for information regarding the sample receipt temperature and preservation. Data qualifiers or a narrative will be provided if the sample analysis or analytical quality control parameters require a flag. When necessary, data qualifiers are provided on both the sample analysis report and the QC summary report, both sections should be reviewed. All samples are reported, as received, unless otherwise indicated. Lab measurement of analytes considered field parameters that require analysis within 15 minutes of sampling such as pH and residual chlorine are qualified as being analyzed outside of the recommended holding time.

Please don't hesitate to contact HEAL for any additional information or clarifications.

ADHS Cert #AZ0682 -- NMED-DWB Cert #NM9425 -- NMED-Micro Cert #NM0901

Sincerely,

Andy Freeman

Laboratory Manager

Indes

4901 Hawkins NE

Albuquerque, NM 87109

CLIENT:

Analytical Report

Lab Order: **2105A45**Date Reported: **5/28/2021**

Hall Environmental Analysis Laboratory, Inc.

Harvest Lab Order: 2105A45

Project: Florance 47X

Lab ID: 2105A45-001 **Collection Date:** 5/24/2021 2:38:00 PM

Client Sample ID: MW-2 Matrix: AQUEOUS

Analyses Result RL Qual Units DF Date Analyzed **Batch ID EPA METHOD 8021B: VOLATILES** Analyst: CCM Benzene 28 1.0 5/25/2021 3:05:00 PM R77656 μg/L 1 Toluene ND 1.0 μg/L 5/25/2021 3:05:00 PM R77656 Ethylbenzene 5 1 1.0 μg/L 1 5/25/2021 3:05:00 PM R77656 Xylenes, Total 2.0 5/25/2021 3:05:00 PM R77656 6.7 μg/L Surr: 4-Bromofluorobenzene 104 70-130 %Rec 5/25/2021 3:05:00 PM R77656

Lab ID: 2105A45-002 **Collection Date:** 5/24/2021 1:26:00 PM

Client Sample ID: MW-5 Matrix: AQUEOUS

Analyses Result RL Qual Units DF Date Analyzed **Batch ID EPA METHOD 8021B: VOLATILES** Analyst: CCM Benzene 58 5.0 μg/L 5 5/25/2021 3:25:00 PM R77656 Toluene ND 5.0 μg/L 5 5/25/2021 3:25:00 PM R77656 ND Ethylbenzene 5.0 5 μg/L 5/25/2021 3:25:00 PM R77656 Xylenes, Total 21 10 μg/L 5 5/25/2021 3:25:00 PM R77656 Surr: 4-Bromofluorobenzene 92.1 70-130 %Rec 5/25/2021 3:25:00 PM R77656

Lab ID: 2105A45-003 **Collection Date:** 5/24/2021 12:48:00 PM

Client Sample ID: MW-6 Matrix: AQUEOUS

RL Qual Units DF Date Analyzed Analyses Result **Batch ID EPA METHOD 8021B: VOLATILES** Analyst: CCM 5/25/2021 3:45:00 PM Benzene ND 1 0 μg/L R77656 1 Toluene ND 1.0 μg/L 5/25/2021 3:45:00 PM R77656 Ethylbenzene ND 1.0 μg/L 1 5/25/2021 3:45:00 PM R77656 Xylenes, Total ND 5/25/2021 3:45:00 PM 2.0 µg/L 1 R77656 Surr: 4-Bromofluorobenzene 86.6 70-130 %Rec 5/25/2021 3:45:00 PM R77656

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix

- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Limit

Page 1 of 3

Analytical Report

Lab Order: **2105A45**

Hall Environmental Analysis Laboratory, Inc.

Date Reported: 5/28/2021

CLIENT: Harvest Lab Order: 2105A45

Project: Florance 47X

Lab ID: 2105A45-004 **Collection Date:** 5/24/2021 12:03:00 PM

Client Sample ID: MW-7 Matrix: AQUEOUS

RL Qual Units DF Date Analyzed **Analyses** Result **Batch ID EPA METHOD 8021B: VOLATILES** Analyst: CCM Benzene ND 1.0 5/25/2021 4:05:00 PM R77656 μg/L 1 Toluene ND 1.0 μg/L 5/25/2021 4:05:00 PM R77656 Ethylbenzene ND 1.0 μg/L 1 5/25/2021 4:05:00 PM R77656 Xylenes, Total ND 2.0 μg/L 1 5/25/2021 4:05:00 PM R77656 Surr: 4-Bromofluorobenzene 87.0 70-130 %Rec 5/25/2021 4:05:00 PM R77656

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix

- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Limit

Page 2 of 3

QC SUMMARY REPORT

Hall Environmental Analysis Laboratory, Inc.

WO#: **2105A45**

28-May-21

Client: Harvest
Project: Florance 47X

Sample ID: 100ng btex Ics	SampType: LCS			Tes						
Client ID: LCSW	Batcl	n ID: R7	7656	R						
Prep Date:	Analysis Date: 5/25/2021			S	SeqNo: 2	757073	Units: µg/L			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	19	1.0	20.00	0	94.7	80	120			
Toluene	19	1.0	20.00	0	95.1	80	120			
Ethylbenzene	20	1.0	20.00	0	98.3	80	120			
Xylenes, Total	58	2.0	60.00	0	96.7	80	120			
Surr: 4-Bromofluorobenzene	18		20.00		92.3	70	130			

Sample ID: mb	SampType: MBLK			Tes						
Client ID: PBW	Batch ID: R77656			F	RunNo: 7	7656				
Prep Date:	Analysis Date: 5/25/2021			SeqNo: 2757074 U			Units: µg/L			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	ND	1.0								
Toluene	ND	1.0								
Ethylbenzene	ND	1.0								
Xylenes, Total	ND	2.0								
Surr: 4-Bromofluorobenzene	19		20.00		92.6	70	130			

Sample ID: 2105A45-004ams	s Samp1	SampType: MS TestCode: EPA Meth				PA Method	8021B: Volat	iles		
Client ID: MW-7	Batcl	h ID: R7	7656	F	RunNo: 7					
Prep Date:	Analysis D	nalysis Date: 5/25/2021 SeqNo: 2757118					Units: µg/L			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	18	1.0	20.00	0	90.8	80	120			
Toluene	18	1.0	20.00	0	92.4	80	120			
Ethylbenzene	19	1.0	20.00	0	96.0	80	120			
Xylenes, Total	56	2.0	60.00	0	94.1	80	120			
Surr: 4-Bromofluorobenzene	17		20.00		83.9	70	130			


Sample ID: 2105A45-004ams	d SampT	ype: MS	SD	TestCode: EPA Method 8021B: Volatiles						
Client ID: MW-7	Batch	ID: R7	7656	F	RunNo: 7	7656				
Prep Date:	Analysis D	ate: 5/	25/2021	SeqNo: 2757119			Units: µg/L			
Analyte	Result	PQL	SPK value	SPK Ref Val	%REC	LowLimit	HighLimit	%RPD	RPDLimit	Qual
Benzene	17	1.0	20.00	0	84.2	80	120	7.52	20	
Toluene	17	1.0	20.00	0	87.1	80	120	5.92	20	
Ethylbenzene	18	1.0	20.00	0	90.2	80	120	6.23	20	
Xylenes, Total	53	2.0	60.00	0	88.6	80	120	6.03	20	
Surr: 4-Bromofluorobenzene	16		20.00		80.4	70	130	0	0	

Qualifiers:

- Value exceeds Maximum Contaminant Level.
- D Sample Diluted Due to Matrix
- H Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix

- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Limit

Page 3 of 3



Hall Environmental Analysis Laboratory 4901 Hawkins NE Albuquerque, NM 87109

TEL: 505-345-3975 FAX: 505-345-4107 Website: clients.hallenvironmental.com

Sample Log-In Check List

Client Name: Harvest	Work Order Number	: 210	5A45		Rcptl	No: 1
Received By: Juan Rojas	5/25/2021 7:22:00 AM	1		Hearing)		
Completed By: Cheyenne Cason	5/25/2021 8:27:06 AM	ı		General		
Reviewed By: SPA 5.25.2				Common and the second		
Chain of Custody						
1. Is Chain of Custody complete?		Yes	V	No 🗌	Not Present]
2. How was the sample delivered?		Cour	ier			
<u>Log In</u>						
3. Was an attempt made to cool the samples	?	Yes	✓	No 🗌	NA 🗆]
4. Were all samples received at a temperatur	e of >0° C to 6.0°C	Yes	V	No 🗌	NA 🗆	
5. Sample(s) in proper container(s)?		Yes	V	No 🗌		
6. Sufficient sample volume for indicated test	(s)?	Yes	V	No 🗌		
7. Are samples (except VOA and ONG) proper	erly preserved?	Yes	V	No 🗌		
8. Was preservative added to bottles?		Yes		No 🗸	NA 🗌	
9. Received at least 1 vial with headspace <1.	/4" for AQ VOA?	Yes		No 🗌	NA 🗸	
10. Were any sample containers received brok	ten?	Yes		No 🗸		
					# of preserved bottles checked	
11. Does paperwork match bottle labels? (Note discrepancies on chain of custody)		Yes	V	No	for pH:	or >12 unless noted)
12. Are matrices correctly identified on Chain of	f Custody?	Yes	V	No 🗌	Adjusted?	of >12 unless noted)
13. Is it clear what analyses were requested?	. Successive	Yes		No 🗌		
14. Were all holding times able to be met? (If no, notify customer for authorization.)			✓	No 🗌	Checked by:	KRG 6/24/2
Special Handling (if applicable)						
15. Was client notified of all discrepancies with	this order?	Yes		No 🗌	NA 🗸	
Person Notified:	Date:	transminga es	th. in physician re	CONTRACTOR DE LA PARTICIONA PARTICIO.		
By Whom:	Via:	eMa	il [Phone Fax	In Person	
Regarding:			ASSESSED			
Client Instructions:		THE SAME PARTY AND ADDRESS OF	NEW PLANTS SANS		NOTE - COMMENT OF THE BOX OF THE PARTY	
16. Additional remarks:						
17. Cooler Information						
- I was a second of the second	Seal Intact Seal No S	eal Da	te	Signed By	1	
1 0.6 Good Ye						

Chain-of-Custody Record Turn-Around Time: HALL ENVIRONMENTAL Client: Harvest Midstream □ Rush **ANALYSIS LABORATORY** Project Name: www.hallenvironmental.com Mailing Address: Florance 47X 4901 Hawkins NE - Albuquerque, NM 87109 Project #: Tel. 505-345-3975 Fax 505-345-4107 TE 090321003 Phone #: **Analysis Request** email or Fax#: Project Manager: SO4 TPH:8015D(GRO / DRO / MRO) Coliform (Present/Absent) BTEX MTBE / TMB's (8021) QA/QC Package: 8081 Pesticides/8082 PCB's PAHs by 8310 or 8270SIMS PO₄, Brooke Herb Standard ☐ Level 4 (Full Validation) Accreditation: □ Az Compliance Sampler: C. McGinn EDB (Method 504.1) □ NELAC □ Other 8270 (Semi-VOA) On Ice: Yes □ No Br, NO₃, RCRA 8 Metals EDD (Type) PDF # of Coolers: 8260 (VOA) Cooler Temp(including CF): 6.8=0.2=0. CI, F, Total Container Preservative HEAL No. Sample Name Date Matrix Time Type and # Type 2105 A45 19.45 1438 3VOA mW-2 HC 0001 mw-5 (302 mw-6 0903 1702 mw-7 COU Date: Time: Relinquished by: Received by: Date Time Remarks: cc: Brooke.herbowsp.com eric.carrollowsp.com

If necessary, samples submitted to Hall Environmental may be subcontracted to other accredited laboratories. This serves as notice of this possibility. Any sub-contracted data will be clearly notated on the analytical report. 125/15/21

Date

Received by:

Date:

Time:

1810

Relinquished by

District III

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 94526

CONDITIONS

Operator:	OGRID:
Harvest Four Corners, LLC	373888
1755 Arroyo Dr	Action Number:
Bloomfield, NM 87413	94526
	Action Type:
	[UF-GWA] Ground Water Abatement (GROUND WATER ABATEMENT)

CONDITIONS

Created By	Condition	Condition Date
michael.buchanan	Review of the 2021 Annual Groundwater Report: Content Satisfactory 1. Continue to remove PSH in MW-3 with skimmer pump to reduce LNAPL plume 2. Continue to conduct quarterly groundwater sampling events 3. Conduct O&M as prescribed in report. 4. Submit the 2022 & 2023 Annual Report (if they haven't already been submitted). 5. Submit the 2024 Annual Groundwater Monitoring Report for the site by April 1, 2025.	5/10/2024