

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101
August 1, 2011
Permit 147395

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address COG OPERATING LLC 550 W TEXAS MIDLAND, TX 79701		2. OGRID Number 229137
		3. API Number 30-015-40366
4. Property Code 39257	5. Property Name MINA STATE	6. Well No. 004

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	27	17S	28E	M	200	S	990	W	EDDY

8. Pool Information

EMPIRE; GLORIETA-YESO	96210
-----------------------	-------

Additional Well Information

9. Work Type New Well	10. Well Type OIL	11. Cable/Rotary	12. Lease Type State	13. Ground Level Elevation 3681
14. Multiple N	15. Proposed Depth 5600	16. Formation Yeso Formation	17. Contractor	18. Spud Date 7/30/2012
Depth to Ground water 110		Distance from nearest fresh water well > 1000		Distance to nearest surface water > 1000

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	300	400	0
Int1	11	8.625	24	850	500	0
Prod	7.875	5.5	17	5600	900	0

Casing/Cement Program: Additional Comments

COG proposes to drill a 17-1/2" hole to 300' w/fr water mud system, wt 8.5, vis 28, set 13-3/8" casing & cement to surface. Drill a 11" hole to 850' w/fr mud system, wt 10, vis 30, set 8-5/8" casing & cement to surface. Drill a 7-7/8" hole to 5600' w/cut brine mud system, wt 9.1, vis 29-32. Test Yeso formation. Run 5-1/2" casing & cement to surface. Note: On production string, a caliper will be run, COG will attempt to circulate.

Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	2000	2000	

I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify that the drilling pit will be constructed according to NMOC guidelines ☒ , a general permit ☐ , or an (attached) alternative OCD-approved plan ☐ . Printed Name: Electronically filed by Diane Kuykendall Title: Production Reporting Mgr Email Address: dkuykendall@conchoresources.com Date: 6/1/2012	OIL CONSERVATION DIVISION	
	Approved By: Randy Dade	
	Title: District Supervisor	
	Approved Date: 6/5/2012	Expiration Date: 6/5/2014
	Phone: 432-683-7443	

Conditions of Approval Attached

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Diane Kuykendall
 Title: Production Reporting Mgr
 Date: 6/1/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Ronald Eidson
 Date of Survey: 4/21/2012
 Certificate Number: 3239

Permit Comments

Operator: COG OPERATING LLC , 229137

Well: MINA STATE #004

API: 30-015-40366

Created By	Comment	Comment Date
konnally	H2S concentrations of wells in this area from surface to TD are low enough that a contingency plan is not required.	4/17/2012
CSHAPARD	Land s/S	6/1/2012

Permit Conditions of Approval

Operator: COG OPERATING LLC , 229137

Well: MINA STATE #004

API: 30-015-40366

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string