<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

August 1, 2011

Form C-101

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT TO DRILL.	RE-ENTER.	DEEPEN	PLUGBACK.	OR ADD A ZONE

100.00 to 100.00	or Name and Address	2. OGRID Number		
DEVON ENERGY PE	6137			
333 W. Sheridan Avenue Oklahoma City, OK 73102		3. API Number		
- CRAMOI	a only, one rotal	30-015-41239		
4. Property Code 5. Property Name		6. Well No.		
39791	NERMAL 4 STATE	001H		

7. Surface Location

y:	7. Surface Location										
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
C	4	25S	28E	3	207	N	1980	W	EDDY		

8. Proposed Bottom Hole Location

- 6				٠.	Troposed	Dottom II	ore Docution			
	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	N	4	25S	28E	N	330	S	1980	W	Eddy

9. Pool Information

WILLOW LAKE;BONE SPRING	64450
-------------------------	-------

Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lesse Type State	15. Ground Level Elevation 3007	
16. Multiple N	17. Proposed D 12600	pth 18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date	
Depth to Ground water		Distance from nearest fresh water	well	Distance to nearest surface water	

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	170	180	0
Int1	12.25	9.625	40	2500	740	0
Prod	8.75	5.5	17	12600	1685	2000
Prod	8.75	5.5	17	7000	690	0

Casing/Cement Program: Additional Comments

Surf: Tail:180 sx C1 C Cmt + 2% bwoc Calc Chlor + 0.125 lbs/sk Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sk, TOC @ surface Intermed: Lead:380 sx(65:35) Cl C Cmt:Poz (Fly Ash): + 5% bwow Sodium Chlor + 0.125 lbs/sk Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sk, TOC @ surface Tail: 360 sx Cl C Cmt + 0.125 lbs/sk Poly-E-Flake + 63.5% Wtr, 14.8 ppg, Yld: 1.33 cf/sk Prod: Lead: 690 sx(65:35)Cl H Cmt:Poz (Fly Ash) + 6% bwoc Bent + 0.125 lbs/sk Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg Yld: 1.95 cf/sk, Tail: 1685 sx (50:50) Cl H Cmt:Poz (Fly Ash) + 1 lb/sk Sodium Chlor + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sk TOC @ 2000'

22. Proposed Blowout Prevention Program

22. I Toposcu Dionout I Tevention I Togram										
Type	Working Pressure	Test Pressure	Manufacturer							
Annular	3000	3000								
DoublePam	3000	3000								

best of my knowledge and belief.	tion given above is true and complete to the	OIL CONSERVATION DIVISION				
I further certify I have complied 19.15.14.9 (B) NMAC , if appl	with 19.15.14.9 (A) NMAC 🛮 and/or icable.	Approved By: Randy Dade				
Signature:		170000000000000000000000000000000000000				
Printed Name: Electronically	filed by Randy Bolles	Title: District Supervisor				
Title: Manager, Regulatory A	Affairs	Approved Date: 4/3/2013	Expiration Date: 4/3/2015			
Email Address: randy.bolles(Ødvn.com					
Date: 4/3/2013	Phone: 405-228-8588	Conditions of Approval Attached				

<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>
811 S. First St., Artesia, NM 88210

S11 S. First St., Artesia, NM 88210

Phone:(\$75) 748-1283 Fax:(\$75) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

August 1, 2011 Permit 164895

Form C-102

1220 S. St Francis Dr. Santa Fe, NM 87505

WELL	LOCATION	AND ACREAGE	DEDICATION	DIAT
WELL	LUCATION	AND ACKEAGE	DEDICATION	PLAI

	TELE LOCATION AND ACK	LAGE DEDICATION IL	11		
1. API Number	2. Pool Code	3. Pool Name			
30-015-41239	64450	WILLOW LAKE	;BONE SPRING		
4. Property Code	5. Property	Name	6. Well No.		
39791	NERMAL 4	STATE	001H		
7. OGRID No.	8. Operator	Name	9. Elevation		
6137	DEVON ENERGY PRODUC	CTION COMPANY, LP	3007		


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
C	4	25S	28E	3	207	N	1980	W	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	4	25S	28E	N	330	S	1980	W	EDDY
12. Dedicated Acres 160.50		13. Joint or Infill		14	14. Consolidation Code		de 15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 4/3/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Frank Jaramillo Date of Survey: 3/13/2013 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: NERMAL 4 STATE #001H

API: 30-015-41239

Created By	Comment	Comment Date	
priechers	The BOP system used to drill the intermediate hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2, a 3M system will be installed and tested prior to drilling out the surface casing shoe.	4/2/2013	
priechers	The BOP system used to drill the production hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 a 3M system will be installed prior to drilling out the intermediate casing shoe.		
priechers	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke is line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.		
CSHAPARD	Land s/S	4/3/2013	

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: NERMAL 4 STATE #001H

API: 30-015-41239

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string