<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

August 1, 2011

Form C-101

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT T	O DRILL, RE-	ENTER, DEEPEN, PL	UGBACK, OR ADD	A ZONE

1. Open	stor Name and Address	OGRID Number	
	PRODUCTION COMPANY, LP	6137	
A Property of	333 W. Sheridan Avenue Oklahoma City, OK 73102	3. API Number	
Oklano	ma City, OK 75102	30-015-41295	
4. Property Code	5. Property Name	6. Well No.	
39861	TRANQUIL 13 STATE COM	003H	

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
C	13	25S	27E	С	330	N	2080	W	EDDY

8. Proposed Bottom Hole Location

	Of a topolog Dottom and Dottom									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
N	13	25S	27E	N	330	S	1980	W	Eddy	

9. Pool Information

HAY HOLLOW:BONE SPRING, NORTH	30216

Additional Well Information

11. Work Type	12. Well Type	13. Cable/Rotary	14. Lease Type	15. Ground Level Elevation 3078
New Well 16. Multiple N	17. Proposed De 12307	pth 18. Formation Bone Spring	State 19. Contractor	20. Spud Date
Depth to Ground		Distance from nearest fresh wat	er well	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	650	670	0
Int1	12.25	9.625	36	2335	700	0
Prod	8.75	5.5	17	12303	1300	0
Prod	8.75	5.5	17	7152	885	1835

Casing/Cement Program: Additional Comments

13-3/8" Surf: 670 sx C1 C Cmt + 2% bwoc CaCl2 + 0.125 lbs/sk Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sk, TOC @ 0'. 9 5/8" Inter: Lead:340 sx(65:35)Cl C Cmt:Poz(Fly Ash): + 5% bwow NaCl + 0.125 lbs/sk Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sk, Tail: 360 sx Cl C Cmt + 0.125 lbs/sk Poly-E-Flake + 63.5% Wtr, 14.8 ppg, Yld: 1.33 cf/sk, TOC @ 0.5-1/2" Prod: Lead: 885 sx(65:35)Cl H Cmt:Poz(Fly Ash)+6% bwoc bent + 0.125 lbs/sk Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sk, Tail: 1300 sx(50:50)Cl H Cmt:Poz(Fly Ash)+ 1 lb/sk NaCl + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sk, TOC @ 1835'.

22. Proposed Blowout Prevention Program

Γ	Type	Working Pressure	Test Pressure	Manufacturer
	Annular	3000	3000	
Г	DoubleRam	3000	3000	

best of my knowledge and belief.	ation given above is true and complete to the	OIL CONSERVATION DIVISION Approved By: Randy Dade				
I further certify I have complied 19.15.14.9 (B) NMAC ⊠, if app	l with 19.15.14.9 (A) NMAC 🛮 and/or olicable.					
Signature:						
Printed Name: Electronically	y filed by Randy Bolles	Title: District Supervisor				
Title: Manager, Regulatory	Affairs	Approved Date: 4/30/2013	Expiration Date: 4/30/2015			
Email Address: randy.bolles	@dvn.com		7 - 17.			
Date: 4/25/2013	Phone: 405-228-8588					

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

,	VELL LOCATION AND AC	REAGE DEDICATION FL	AI
1. API Number	2. Pool Code	3. Po	ol Name
30-015-41295	30216	HAY HOLLOW;BONE SPRING, NO	
4. Property Code	5. Prope	rty Name	6. Well No.
39861	TRANQUIL 13	S STATE COM	003H
7. OGRID No.	8. Opera	tor Name	9. Elevation
6137	DEVON ENERGY PROD	UCTION COMPANY, LP	3078

WELL LOCATION AND ACREAGE DEDICATION PLAT


10 Surface Location

	Tot Datable Doubles									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
C	13	25S	27E		330	N	2080	W	EDDY	

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
N	13	25S	27E	N	330	S	1980	W	EDDY		
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 4/25/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 3/26/2013 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: TRANQUIL 13 STATE COM #003H API: 30-015-41295

Created By	Comment	Comment Date
priechers	The BOP system used to drill the intermediate hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order 2. A 3M system will be installed and tested prior to drilling out the surface casing shoe.	4/24/2013
priechers	The BOP system used to drill the production hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order 2. A 3M system will be installed prior to drilling out the intermediate casing shoe.	4/24/2013
priechers	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	4/24/2013
priechers	Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line); The line will be kept as straight as possible with minimal turns.	4/24/2013