<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

## State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

Form C-101 August 1, 2011

1220 S. St Francis Dr. Santa Fe, NM 87505

DEVON ENERGY P	tor Name and Address RODUCTION COMPANY, LP	OGRID Number    6137	
	Sheridan Avenue na City, OK 73102	3. API Number 30-015-41499	
4. Property Code	5. Property Name	6. Well No.	
300635	COTTON DRAW UNIT	218H	

#### 7. Surface Location

22	100	1	150	7.0	diluce Loc	utivn	90%	0 (0)		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
M	2	25S	31E	M	200	S	1120	W	EDDY	

#### 8. Proposed Bottom Hole Location

				Troposed	Dottom II	ore motures.	-		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	2	25S	31E	4	330	N	660	W	Eddy

#### 9. Pool Information

PADUCA: BONE SPRING (O)	96641

#### Additional Well Information

11. Work Type New Well	12. Well Typ OIL	13. Cable/Rotary	14. Lesse Type State	15. Ground Level Elevation 3420	
16. Multiple 17. Proposed Depth N 14948		epth 18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date	
Depth to Ground	water	Distance from nearest fresh water	well	Distance to nearest surface water	

#### 21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	800	800	0
Int1	12.25	9.625	40	4350	1340	0
Prod	8.75	5.5	17	14948	620	0
Prod	8.75	5.5	17	9700	1385	3850

### Casing/Cement Program: Additional Comments

13-3/8" Surf: Tail: 800 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 lbs/sk Poly-E-Flake + 63.1% FW, 14.8 ppg, yld: 1.35 cf/sk, TOC @ surface 9-5/8" Inter: Lead: 965 sx(65:35)Cl C Cmt:Poz(Fly Ash): + 5% bwow NACl + 0.125 lbs/sk Poly-E-Flake + 6% bwoc Bentonite + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sk, TOC @ surf, Tail: 375 sx Cl C Cmt + 0.125 lbs/sk Poly-E-Flake + 63.5% Wtr, 14.8 ppg, Yld: 1.33 cf/sk 5-1/2" Prod: 1st Lead: 230 sx (50:50) Cl H Cmt:Poz(Fty Ash) + 10% bwoc Bentonite + 8 lb/sk NACl + 0.125 lbs/sk Poly-E-Flake + 0.3% bwoc HR-601 + 0.3% bwoc Econolite + 77.2% FW, 11.8 ppg, Yld: 2.52 cf/sk, 2nd Lead: 390 sx(65:35)Cl H Cmt:Poz(Fty Ash) + 6% bwoc Bentonite+0.125 lbs/sk Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sk, Tail: 1385 sx (50:50) Cl H Cmt:Poz (Fly Ash) + 1 lb/sk NACl + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bentonite + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sk, TOC @ 3850°.

#### 22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

best of my knowledge and belief.		OIL CONSERVATION DIVISION				
I further certify I have compli 19.15.14.9 (B) NMAC ⊠, if ap	ed with 19.15.14.9 (A) NMAC 🛮 and/or plicable.	Approved By: Randy Dade				
Signature:						
Printed Name: Electronical	ly filed by Randy Bolles	Title: District Supervisor				
Title: Manager, Regulatory	Affairs	Approved Date: 6/27/2013	Expiration Date: 6/27/2015			
Email Address: randy.bolle	s@dvn.com	732	956 95			
Date: 6/27/2013	Phone: 405-228-8588	Conditions of Approval Attached				

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>
811 S. First St., Artesia, NM 88210

<u>District II</u> 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

# State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Form C-102 August 1, 2011

Doomit 160250

1220 S. St Francis Dr. Santa Fe, NM 87505

#### WELL LOCATION AND ACREAGE DEDICATION PLAT

SANCES CONTRACTOR SECURI	The state of the s	and the second s	On Assessed		
API Number     2. Pool Code		3. Poo	3. Pool Name		
30-015-41499	96641	ONE SPRING (O)			
4. Property Code	5. Property Name		6. Well No.		
300635	COTTON DRA	W UNIT	218H		
7. OGRID No.	8. Operator 1	9. Elevation			
6137	DEVON ENERGY PRODUC	3420			


#### 10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	2	25S	31E		200	S	1120	W	EDDY

#### 11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County			
D	2	25S	31E	4	330	N	660	W	EDDY			
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.				

## NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



#### OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 6/27/2013

#### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Frank Jaramillo Date of Survey: 5/8/2013 Certificate Number: 12797

## **Permit Comments**

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: COTTON DRAW UNIT #218H API: 30-015-41499

Created By	Comment	Comment Date
priechers	The BOP system used to drill the production hole will consist of a 13-5/8" Double Ram and Annular preventer. A 3M system will be installed prior to drilling out the intermediate casing shoe. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2.	6/26/2013
priechers	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	6/26/2013
priechers	Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line); if an H&P rig drills this well. Otherwise no flex line is needed. The line will be kept as straight as possible with minimal turns.	6/26/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: COTTON DRAW UNIT #218H

API: 30-015-41499

OCD Reviewer	Condition	
RDADE	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	
RDADE	DE Pit construction and closure must satisfy all requirements of your approved plan, O.C.D. Rule 19.15.2.5 and the Pit and Below-Grade Tank Guidelines	