<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>
811 S. First St., Artesia, NM 88210

<u>District II</u> 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410

Phone;(505) 334-6178 Fax:(505) 334-6170

<u>District IV</u>

1220 S. St Francis Dr., Santa Fe, NM 87505

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division

Form C-101

August 1, 2011

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT TO DRILL RE-ENTER DEEPEN PLUGBACK OR ADD A ZONE

1. Operator	Name and Address	2. OGRID Number 6137	
	DEVON ENERGY PRODUCTION COMPANY, LP 333 W. Sheridan Avenue		
	City, OK 73102	3. API Number	
Oklanonia	City, OK 13102	30-025-41252	
4. Property Code	5. Property Name	6. Well No.	
30884 THISTLE UNIT		047H	

7. Surface Location

	7. Surface Location									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
N	34	238	33E	N	280	S	2511	W	LEA	

8. Proposed Bottom Hole Location

5	C. I Toposcu Bottom Hole Eccution								
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	34	238	33E	D	330	N	660	W	Lea

9. Pool Information

TRIPLE X;BONE SPRING	59900

Additional Well Information

11. Work Type New Well				15. Ground Level Elevation 3641
16. Multiple N	17. Proposed Dep 16096	oth 18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date
Depth to Ground	water	Distance from nearest fresh water	well	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1325	1180	0
Int1	12.25	9.625	40	5250	1465	0
Prod	8.75	5.5	17	16096	1305	
Prod	8.75	5.5	17	10500	810	4750

Casing/Cement Program: Additional Comments

13 3/8" Surface: Lead w/740 sx C1 C Cmt: + 4% bwoc Bent + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake 80.9% FW, 13.5 ppg, Yld: 1.75 cf/sx. Tail w/440 sx C1 C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sx; TOC @ surface. 9 5/8" Intermediate: Lead w/1035 sx(65:35) C1 C Cmt: Poz (Fly Ash): + 5% bwow CaCL + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 49.2% FW, 12.5 ppg, Yld: 2.04 cf/sx. Tail w/430 sx C1 C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% Water, 14.8 ppg, Yld: 1.33 cf/sx; TOC @ surface. 5 ½ "* Production: 1st Lead w/485 sx(50:50) C1H: Poz (Fly.Ash) + 10% bwoc Bent + 8 #/sx CaCL + 0.15 #/sx FWCA, 0.125 #/sx Poly-E-Flake, 0.3% bwoc HR-601, 0.25 #/sx D-AIR 5000 + 64.9% FW, 11.8 ppg, Yld: 2.54 cf/sx. See Comments section for continuation of 5 1/2" production cement.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

best of my knowledge and belief.	given above is true and complete to the	OIL CONSERVATION DIVISION			
I further certify I have complied wit 19.15.14.9 (B) NMAC ⊠, if applical	h 19.15.14.9 (A) NMAC 🛮 and/or ple.	Approved By: Paul Kautz			
Signature:		100000000000000000000000000000000000000			
Printed Name: Electronically file	d by Randy Bolles	Title: Geologist			
Title: Manager, Regulatory Affa	irs	Approved Date: 7/9/2013	Expiration Date: 7/9/2015		
Email Address: randy.bolles@d	vn.com				
Date: 7/3/2013	Phone: 405-228-8588	Conditions of Approval Attached			

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

	VLLE LOCATION AND ACIA	AGE DEDICATION TEA	
1. API Number	2. Pool Code	3. Pool 1	Name
30-025-41252	59900	TRIPLE X;BO	NE SPRING
4. Property Code	5. Property 1	Vame	6. Well No.
30884	THISTLE U	JNIT	047H
7. OGRID No.	8. Operator 1	√ame	9. Elevation
6137	DEVON ENERGY PRODUC	TION COMPANY, LP	3641


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	34	238	33E		280	S	2511	W	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	34	238	33E	D	330	N	660	W	LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

Form C-102

August 1, 2011

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 7/3/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 6/7/2013 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: THISTLE UNIT #047H API: 30-025-41252

Created By	Comment	Comment Date
doook	2nd Lead w/325 sx(65:35) CI H Cmt + 6% bwow Bent + 0.25% bwoc HR-601+ 0.125 #/sx Poly-E-Flake + 49.1% FW, 12.5 ppg, Yld: 1.96 cf/sx.	7/3/2013
doook	Tail w/1305 sx(50:50) CI H Cmt + 2% bwow Bent + 0.5% bwoc Halad-344 + 0.3% bwoc CRF-3 + 1 #/sx Salt + 0.2% bwoc HR-601+ 33.6% FW, 14.5 ppg, Yld: 1.23cf/sx; TOC @ 4750°.	7/3/2013
pkautz	Land s/S	7/9/2013
DMULL	OCD Hobbs office has received C-144clez. OCD Permit Number P-06480.	7/9/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: THISTLE UNIT #047H

API: 30-025-41252

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	In order to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite.