

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101
August 1, 2011
Permit 181509

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address YATES PETROLEUM CORPORATION 105 S 4TH ST ARTESIA, NM 88210		2. OGRID Number 25575
		3. API Number 30-025-41656
		6. Well No. 002H
4. Property Code 39273	5. Property Name BELFAST BSL STATE COM	

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
Q	6	21S	34E	I	2475	S	990	E	Lea

8. Proposed Bottom Hole Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	6	21S	34E	1	330	N	660	E	Lea

9. Pool Information

BERRY;BONE SPRING, NORTH	5535
--------------------------	------

Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3726
16. Multiple N	17. Proposed Depth 15707	18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☐ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1800	1315	0
Int1	12.25	9.625	36	5950	2005	0
Prod	8.5	5.5	17	15707	990	10000
Prod	8.75	5.5	17	10000	845	5450

Casing/Cement Program: Additional Comments

--

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Double Ram	3000	3000	
Double Ram	5000	5000	

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify I have complied with 19.15.14.9 (A) NMAC ☒ and/or 19.15.14.9 (B) NMAC ☒ if applicable. Signature: _____ Printed Name: Electronically filed by LORI FLORES Title: Land Regulatory Technician Email Address: lorif@yatespetroleum.com Date: 2/13/2014	OIL CONSERVATION DIVISION Approved By: Paul Kautz Title: Geologist Approved Date: 2/14/2014 Expiration Date: 2/14/2016 Conditions of Approval Attached
Phone: 575-748-4448	

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-8181 Fax:(575) 393-0720

District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-102
August 1, 2011
Permit 181509

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-025-41656	2. Pool Code 5535	3. Pool Name BERRY;BONE SPRING, NORTH
4. Property Code 39273	5. Property Name BELFAST BSL STATE COM	6. Well No. 002H
7. OGRID No. 25575	8. Operator Name YATES PETROLEUM CORPORATION	9. Elevation 3726

10. Surface Location

UL - Lot Q	Section 6	Township 21S	Range 34E	Lot Idn I	Feet From 2475	N/S Line S	Feet From 990	E/W Line E	County Lea
---------------	--------------	-----------------	--------------	--------------	-------------------	---------------	------------------	---------------	---------------

11. Bottom Hole Location If Different From Surface

UL - Lot A	Section 6	Township 21S	Range 34E	Lot Idn 1	Feet From 330	N/S Line N	Feet From 660	E/W Line E	County Lea
12. Dedicated Acres 159.54	13. Joint or Infill			14. Consolidation Code			15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	OPERATOR CERTIFICATION <i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</i> E-Signed By: LORI FLORES Title: Land Regulatory Technician Date: 2/13/2014
	SURVEYOR CERTIFICATION <i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</i> Surveyed By: Gary Jones Date of Survey: 12/12/2013 Certificate Number: 7977

District I

1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-8161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

Form APD Comments

Permit 181509

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

PERMIT COMMENTS

Operator Name and Address: YATES PETROLEUM CORPORATION [25575] 105 S 4TH ST ARTESIA, NM 88210	API Number: 30-025-41656
	Well: BELFAST BSL STATE COM #002H

Created By	Comment	Comment Date
THAHN	Samples: 30' Sample to 5950'. 10' Samples 5950'-TD	2/13/2014
THAHN	MAXIMUM ANTICIPATED BHP: DEPTHS ARE TVD 0'-1800' is 861 PSI 1800'-5950' is 3156 PSI 5950'-10864' is 5198 PSI	2/13/2014
THAHN	Well will be drilled vertically to 10318' then be kicked off and directionally drilled at 12 degrees per 100' with a 8.75" hole to 11061' MD (10796' TVD). Hole size will then be reduced to 8.5" and drilled to 15707' MD (10864' TVD) where 5.5" casing will be set and cemented 500' into previous casing string. Production string will be cemented in two stages with a DV/packer stage tool at approximately 10000' (cement volumes will be adjusted per tool placement). Penetration point of producing zone to be stimulated will be encountered at 2970' FSL and 962' FEL, 6-21S-34E. Deepest TVD is 10864' in	2/13/2014
THAHN	H2S is not anticipated, but equipment will be on location. C-102 will follow by mail.	2/13/2014

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-8161 Fax:(575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720
District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form APD Conditions

Permit 181509

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address: YATES PETROLEUM CORPORATION [25575] 105 S 4TH ST ARTESIA, NM 88210	API Number: 30-025-41656
	Well: BELFAST BSL STATE COM #002H

OCD Reviewer	Condition
pkautz	Will require a directional survey with the C-104
pkautz	Will require administrative order for non-standard location
pkautz	Pit construction and closure must satisfy all requirements of your approved plan, O.C.D. Rule 19.15.2.50, and the Pit and Below-Grade Tank Guidelines
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	1) SURFACE & INTERMEDIATE CASING - Cement must circulate to surface -- 2) PRODUCTION CASING - Cement must tie back into intermediate casing --
pkautz	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water