

Submit within 45 days of well completion	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505	Revised November 6, 2013							
		1. WELL API NO: 30-015-41105							
		2. Well Name: ANTARES 23 FEDERAL COM #001H							
		3. Well Number: 001H							
HYDRAULIC FRACTURING FLUID DISCLOSURE ☒ Original ☐ Amendment		4. Surface Hole Location: Unit:D Lot:D Section:23 Township:19S Range:31E Feet from:1030 N/S Line:N Feet from:225 E/W Line:W							
		5. Bottom Hole Location: Unit:D Lot:D Section:23 Township:19S Range:31E Feet from:1030 N/S Line:N Feet from:225 E/W Line:W							
		6. Latitude: 32.6504057633598 Longitude: - 103.847828530183							
		7. County: Eddy							
8. Operator Name and Address: DEVON ENERGY PRODUCTION COMPANY, LP 333 W. Sheridan Avenue Oklahoma City 73102		9. OGRID: 6137	10. Phone Number: 405-228-8588						
11. Last Fracture Date: 11/16/2013 Frac Performed by: BHI		12. Production Type: O							
13. Pool Code(s): 41480		14. Gross Fractured Interval: Confidential							
15. True Vertical Depth (TVD): 9,218 ft		16. Total Volume of Fluid Pumped: 1,865,556 gals							
17. Total Volume of Re-Use Water Pumped: N/A		18. Percent of Re-Use Water in Fluid Pumped: Not Disclosed							
19. HYDRAULIC FLUID COMPOSITION AND CONCENTRATION:									
Trade Name	Supplier	Purpose	Ingredients	(CAS #) Chemical Abstract Service #	Maximum Ingredient Concentration in Additive (% by mass)	Maximum Ingredient Concentration in HF Fluid (% by mass)			
Water	Operator	Carrier	Water	7732-18-5	100%	89.10354%			
HCl, 10.1 - 15%	Baker Hughes	Acidizing	Hydrochloric Acid	7647-01-0	15%	0.41534%			
Superset-W, 55 gal drum	Baker Hughes	Activator	Water	7732-18-5	85%	2.35362%			
			Methanol	67-56-1	50%	0.01004%			
			Poly (Oxyethylene) Nonylphenol Ether	9016-45-9	50%	0.01004%			
Alpha 125	Baker Hughes	Biocide	Water	7732-18-5	75%	0.02357%			
GBW-5	Baker Hughes	Breaker	Ammonium persulphate	7727-54-0	100%	0.03741%			
ClayCare, tote	Baker Hughes	Clay Control	Choline Chloride	67-48-1	75%	0.07699%			
Clay Master-5C CI-27	Baker Hughes	Clay Control	Water	7732-18-5	30%	0.0308%			
			Oxyakylated Amine Quat	138879-94-4	60%	0.00098%			
			Fatty Acids	Trade Secret	30%	0.00134%			
			Methanol	67-56-1	60%	0.00268%			
			Olefin	Trade Secret	5%	0.00022%			
			Polyoxyalkylenes	Trade Secret	30%	0.00134%			
			Propargyl Alcohol	107-19-7	10%	0.00045%			
			Thiourea Polymer	68527-49-1	30%	0.00134%			
			MaxPerm-20A, 265 gallon tote	Baker Hughes	Friction Reducer	Oxyakylated Alcohol	Trade Secret	5%	0.01791%
			Petroleum Distillates	64742-47-8	30%	0.10746%			
Polyacrylate	Trade Secret	60%	0.21491%						
Sodium Chloride	7647-14-5	3%	0.01075%						
AG-12	Baker Hughes	Gelling Agent	Acrylic Polymers	26006-22-4	50%	0.00121%			
Ferrotrol 280L	Baker Hughes	Iron Control	Distillates, Petroleum, Hydrotreated Middle	64742-47-8	21.1%	0.00051%			
			2-Mercaptoethanol	60-24-2	100%	0.00868%			
			Ammonium Hydroxide	1336-21-6	5%	0.00043%			
NE-35, 330 gl tote	Baker Hughes	Non-emulsifier	Cupric Chloride	7447-39-4	5%	0.00043%			
Sand, White, 40/70 Sand, White, 100 mesh Super LC, 40/70	Baker Hughes	Proppant	Mixture of Surfactants	Trade Secret	50%	0.02616%			
			Propylene Glycol	57-55-6	30%	0.01569%			
			Crystalline Silica (Quartz)	14808-60-7	100%	4.98988%			
			Crystalline Silica (Quartz)	14808-60-7	100%	0.23964%			
			Hexamethylenetetramine	100-97-0	0.01%	0.00018%			
Flo-Back Prime (tote)	Baker Hughes	Surfactant	Phenol-formaldehyde Resin	9003-35-4	5%	0.08878%			
			Silicon Dioxide (Silica Sand)	14808-60-7	97%	1.72234%			
			Essential Oils	Trade Secret	60%	0.0612%			
			Isopropanol	67-63-0	30%	0.0306%			
			Citrus Terpenes	94266-47-4	0%	0.0612008%			
			Fatty Acid Esters	67701-32-0	0%	4.61E-05%			
			Fatty Acid Oxyalkylate	70142-34-6	0%	4.9E-06%			
			Formaldehyde	50-00-0	0%	2.2E-06%			
			Glutaraldehyde	111-30-8	0%	0.0094296%			
			Methanol	67-56-1	0%	7.86E-05%			
Oleate Ester	1338-43-8	0%	0.0107456%						
Organic Polyol	112-27-6	0%	0.0102001%						
Oxyalkylated Alkylphenol	9016-45-9	0%	4.37E-05%						
Polysorbate	9005-65-6	0%	0.0107456%						
Sodium Chloride	7647-14-5	0%	0.0153225%						
Surfactants	Trade Secret	0%	0.0714009%						
Water	7732-18-5	0%	0.2043034%						
Xylene	1330-20-7	0%	1.46E-05%						
diester of sulfosuccinic acid sodium salt	2673-22-5	0%	1.21E-05%						
20. I, as Operator, hereby certify that the information shown on this disclosure form is true and complete to the best of my knowledge and belief.									
Signature: Signed Electronically Printed Name: Derek Berg Title: Engineering Technician									
Date: 4/22/2014									
E-mail Address: derek.berg@dm.com									

NMOCD does not require the reporting of information beyond MSDS data as described in 29 CFR 1910.1200. NMOCD does not require the reporting or disclosure of proprietary, trade secret or confidential business information.