<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District III

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District III

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 232829

State of New Mexico **Energy, Minerals and Natural Resources**

		APPLICATIO	N FOR PERM	IT TO DRILL	., RE-E	ENTER, DEEPE	N, PLUGBAC	K, OR ADI	DAZO	NE		
BLA	me and Address ACK MOUNTAIN O) Main Street					•	-	-		ID Number 371127		
	t Worth, TX 76102								U. A. 11	30-025-43666		
4. Property Coo 317	de 7504	5. Pro	perty Name FLOWMAS	TER					6. Well I	No. 001H		
					7. Surfa	ice Location						
UL - Lot D	Section 15	Township 24S	Range 34E	Lot Idn	D	Feet From 311	N/S Line N	Feet From	1225	E/W Line W	County	Lea
				8. Propo	sed Bo	ottom Hole Locatio	on					
UL - Lot M	Section 15	Township 24S	Range 34l	Lot Idn	M	Feet From 330	N/S Line S	Feet From	654	E/W Line W	County	Lea
					9. Pool	Information						
ANTELOPE	RIDGE;WOLFCAN	P			1.1					2220		
				Add	itional \	Well Information						
11. Work Type Nev	w Well	12. Well Type OIL		13. Cable/Rotary		14. Le	ease Type Private	15.		evel Elevation 521		
16. Multiple N		17. Proposed Depti 17300	1	18. Formation Wolfc	amp	19. Co	ontractor	20.	Spud Date 6/	1/2017		
Depth to Groun	nd water		1	Distance from nea	rest fresh	water well		Dis	tance to ne	earest surface water		
We will be	using a closed-lo	op system in lieu of	lined pits									
				21. Propose	d Casir	ng and Cement Pro	ogram					
Type	Hole Size	Casing Size	2 N	Casing Weight/ft		Setting De		Sacks of			Estimated T	OC
Surf	17.5	13.375		54.5		1750		18			0	
Int1	12.25	9.65	- 1	40		7300		17			0	
Prod	8.75	5.5		20		17300)	18:	20		6800	

Casing/Cement Program: Additional Comments

22. Proposed Blowout Prevention Program						
Type	Working Pressure	Test Pressure	Manufacturer			
Annular	3500	3500				
Double Ram	5000	5000				

knowledge and be	elief. have complied with 19.15.14.9 (A	s true and complete to the best of my		OIL CONSEI	RVATION DIVISION	
Printed Name:	Electronically filed by Michael M	cCracken	Approved By:	Paul Kautz		
Title:	COO		Title:	Geologist	100	
Email Address:	michael.mccracken@blackmtn.e	com	Approved Date:	3/7/2017	Expiration Date: 3/7/2019	
Date:	3/7/2017 Phone: 817-698-9901			onditions of Approval Attached		

	1416		100							
-						WORKER			* Ballington	
Transport			Fragon, Nato							
			TORONES.							
	77	E-	-1		I				*********	

- M	1	- OPERATOR CONTENA
- server		Annual Control of the
1 migroon	1 4	Annual Contraction
B Marie Brise	1 1 1	Lenial cheta -
1.0	Ph. 645	Care III
(8)	-	Arms whighware our
1 1 1		
1 1 1	10000000	SARVEYOR CERTIFICA
11 1	A THEORY STREET	our or photo from feet was of some
	The same of the sa	and a transfer over Arbeit & a
	0 Normal	227-7
	Ga. 1220	Samuel Sandar

Form APD Comments

Permit 232829

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>:
311 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u>:
1000 Rio Brazos Rd., Azteo, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>:
1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

PERMIT COMMENTS

Operator Name and Address:	API Number:
BLACK MOUNTAIN OPERATING LLC [371127]	30-025-43666
	Well:
Fort Worth, TX 76102	FLOWMASTER #001H

Created By Comment Comment Date

Form APD Conditions

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Frencis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 478-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 232829

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:		
BLACK MOUNTAIN OPERATING LLC [371127]	30-025-43666		
500 Main Street	Well:		
Fort Worth, TX 76102	FLOWMASTER #001H		

OCD Reviewer	Condition
pkautz	Will require a directional survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	If using a pit for drilling and completion operations, must have an approved pit from prior to spudding the well.
pkautz	1) SURFACE & INTERMEDIATE CASING - Cement must circulate to surface 2) PRODUCTION CASING - Cement must tie back into intermediate casing
pkautz	If cement does not circulate to surface, must run temperature survey or other log to determine top of cement
pkautz	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water
pkautz	Only Fresh Water and Air are Valid Drilling Fluids for Surface Casing
pkautz	Operator shall notify appropriate District office when setting conductor pipe.
pkautz	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of spudding a well.
pkautz	It is the operator's responsibility to monitor cancellation dates of approved APDs. APD's are good for 2 years and may be extended for one year. Only one 1 year extension will be granted if submitted by C-103 before expiration date. After expiration date or after a 1 year extension must submit new APD.
pkautz	If an APD expires and if site construction has occurred, site remediation is required.
pkautz	Stage Tool 1) Must notify OCD Hobbs Office prior to running Stage Tool at 575-370-3186 2) If using Stage Tool on Surface casing, Stage Tool must be set greater than 350' from surface and a minimum of 200 feet above surface shoe. 3) When using a Stage Tool on Intermediate or Production Casing Stage must be a minimum of 50 feet below previous casing shoe.