<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Form C-101 August 1, 2011

Permit 239086

	and Address								2. OGR	ID Number	
EOG RESOURCES INC P.O. Box 2267									7377		
									3. API N	Number 30-025-4389	7
Midland, TX 79702 4. Property Code 5. Property Name						6. Well No.				· · · · · · · · · · · · · · · · · · ·	
4. Property Code 5. Property Name 40402 THOR 21									0. 110	709H	
					7. Surfa	ce Location					
L - Lot	Section	Township	Range)	Lot Idn	Feet From	N/S Line	Feet From	m	E/W Line	County
Р	21	26S		33E		175		S	439	Е	Le
					8. Proposed Bo	ttom Hole Location	on				
	Section	Township	Range		Lot Idn	Feet From	N/S Line	Feet From		E/W Line	County
Α	21	26S		33E	Α	230	N	1	1270	E	Le
					9. Pool l	Information					
/C-025 G-09 S2	263327G;UPPER	WOLFCAMP								98	8097
					Additional V	Well Information					
1. Work Type		12. Well Type		13. Cable/Ro			14. Lease Typ	е		d Level Elevation	
New W		OIL						vate		3253	
6. Multiple N		Proposed Dept 17209	h	18. Formation	on Jpper Wolfcamp		19. Contractor		20. Spud [Date 10/1/2017	
	vater .	17209			<u> </u>						vater
Depth to Ground water Di			Diotarioc iroi	Distance from nearest fresh water well			Distance to nearest surface water				
We will be usir	ng a closed-loop	system in lieu o	of lined pits								
We will be usir	ng a closed-loop	system in lieu o	of lined pits	21 5	Proposed Casin	og and Cement Pr	ogram				
We will be usin	ng a closed-loop	system in lieu o			Proposed Casin Weight/ft	g and Cement Pr		Sacks o	of Cement		Estimated TOC
	Hole Size 14.75	Casing Siz 10.75		Casing 4(Weight/ft 0.5	Setting D 800	epth	7	00		0
Type Surf Int1	Hole Size 14.75 8.75	Casing Siz 10.75 7.625		Casing 40 29	Weight/ft 0.5 9.7	Setting D 800 11300	epth 0	7 28	00 800		0
Type Surf	Hole Size 14.75	Casing Siz 10.75		Casing 40 29	Weight/ft 0.5	Setting D 800	epth 0	7 28	00		0
Type Surf Int1	Hole Size 14.75 8.75	Casing Siz 10.75 7.625		Casing 40 29	Weight/ft 0.5 9.7 17	Setting D 800 11300	epth 0 9	7 28	00 800		0
Type Surf Int1	Hole Size 14.75 8.75	Casing Siz 10.75 7.625		Casing 40 29	Weight/ft 0.5 9.7 17	Setting D 800 11300 1720	epth 0 9	7 28	00 800		0
Type Surf Int1	Hole Size 14.75 8.75	Casing Siz 10.75 7.625		Casing 40 29 1 Casing	Weight/ft 0.5 9.7 17 g/Cement Progra	Setting D 800 11300 1720	omments	7 28	00 800		0
Type Surf Int1	Hole Size 14.75 8.75	Casing Siz 10.75 7.625		Casing 40 29 1 Casing 22. F	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowc Pressure	Setting D 800 11300 1720: am: Additional Co	ogram	7 28	00 800	Man	0
Type Surf Int1	Hole Size 14.75 8.75 6.75	Casing Siz 10.75 7.625		Casing 40 29 1 Casing 22. F	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowc Pressure	Setting D 800 11300 1720: am: Additional Co	ogram Test P	7 29 8	00 800	Man	0 0 10800
Type Surf Int1 Prod	Hole Size 14.75 8.75 6.75 Type Double Ram	Casing Siz 10.75 7.625 5.5	re .	Casing 40 20 1 Casing 22. If Working I	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowd Pressure 00	Setting D 800 11300 1720: am: Additional Co	ogram Test P	7 28 8 8	000 800 000		0 0 10800
Type Surf Int1 Prod 3. I hereby certi	Hole Size 14.75 8.75 6.75 Type Double Ram	Casing Siz 10.75 7.625 5.5	re .	Casing 40 20 1 Casing 22. If Working I	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowd Pressure 00	Setting D 800 11300 1720: am: Additional Co	ogram Test P	7 20 8 8	000 800 000		0 0 10800
Type Surf Int1 Prod 3. I hereby certinowledge and I	Hole Size 14.75 8.75 6.75 Type Double Ram	Casing Siz 10.75 7.625 5.5	e is true and	Casing 40 20 1 Casing 22. If Working I	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowc Pressure 00 the best of my	Setting D 800 11300 17200 am: Additional Co	ogram Test P	7 28 8 8	000 800 000		0 0 10800
Type Surf Int1 Prod 23. I hereby certifications and I	Hole Size 14.75 8.75 6.75 Type Double Ram ify that the inform belief. I have complied	Casing Siz 10.75 7.625 5.5	e is true and	Casing 40 20 1 Casing 22. If Working I	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowc Pressure 00 the best of my	Setting D 800 11300 17200 am: Additional Co	ogram Test P	7 28 8 8	000 800 000		0 0 10800
Type Surf Int1 Prod 3. I hereby certinowledge and Iffurther certify It I applicable.	Hole Size 14.75 8.75 6.75 Type Double Ram ify that the inform belief. I have complied	Casing Siz 10.75 7.625 5.5	e is true and	Casing 40 20 1 Casing 22. If Working I	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowc Pressure 00 the best of my	Setting D 800 11300 17200 am: Additional Co	ogram Test P	7 28 8 8	000 800 000		0 0 10800
Type Surf Int1 Prod 3. I hereby certinowledge and I further certify I d., if applicable.	Hole Size 14.75 8.75 6.75 Type Double Ram ify that the inform belief. I have complied	Casing Siz 10.75 7.625 5.5 ation given abov	e is true and	Casing 40 20 1 Casing 22. If Working I	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowc Pressure 00 the best of my	Setting D 800 11300 17200 am: Additional Co	ogram Test P 30	7 28 8 8 rressure	000 800 000		0 0 10800
Type Surf Int1 Prod 3. I hereby certinowledge and I further certify I d, if applicable. Signature: rinted Name:	Hole Size 14.75 8.75 6.75 Type Double Ram ify that the inform belief. I have complied	Casing Siz 10.75 7.625 5.5 ation given abov with 19.15.14.9 (e is true and	Casing 40 20 1 Casing 22. If Working I	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowc Pressure 00 the best of my	Setting D 800 11300 17200 am: Additional Co	ogram Test P 30	7 20 8 8 7 ressure 000 OIL CONSER	000 800 000		0 0 10800
Type Surf Int1 Prod 3. I hereby certinowledge and ifurther certify id, if applicable.	Hole Size 14.75 8.75 6.75 Type Double Ram ify that the inform belief. I have complied Electronically Regulatory A	Casing Siz 10.75 7.625 5.5 ation given abov with 19.15.14.9 (e is true and	Casing 40 20 1 Casing 22. If Working I	Weight/ft 0.5 9.7 17 g/Cement Progra Proposed Blowc Pressure 00 the best of my	Setting D 800 11300 17200 am: Additional Co	ogram Test P 30	7 20 8 8 7 ressure 000 OIL CONSER	000 800 000		0 0 10800

District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 **District IV** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 239086

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name
30-025-43897	98097	WC-025 G-09 S263327G;UPPER WOLFCAMP
4. Property Code	5. Property Name	6. Well No.
40402	THOR 21	709H
7. OGRID No.	8. Operator Name	9. Elevation
7377	EOG RESOURCES INC	3253


10 Surface Location

				iv. Suite	CE LOCATION				
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
Р	21	268	33F		175	S	439	F	Lea

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn		N/S Line	Feet From	E/W Line	County
A	21	26S	33E	A	230	N	1270	E	Lea
12. Dedicated Acres		13. Joint or Infill		14. Consolidation Cod	de		15. Order No.		
160.00									

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Stan Wagner
Title: Regulatory Analyst
Date: 7/18/2017

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Michael Brown
Date of Survey: 5/25/2017
Certificate Number: 18329

Form APD Comments

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone: (505) 334-6178 Fax: (505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Permit 239086

PERMIT COMMENTS

Operator Name and Address:	API Number:
EOG RESOURCES INC [7377]	30-025-43897
P.O. Box 2267	Well:
Midland, TX 79702	THOR 21 #709H

Created By Comment Comment Date

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone: (505) 334-6178 Fax: (505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Permit 239086

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
EOG RESOURCES INC [7377]	30-025-43897
P.O. Box 2267	Well:
Midland, TX 79702	THOR 21 #709H

OCD	Condition
Reviewer	
pkautz	Will require a directional survey with the C-104
pkautz	Will require a administrative order for non-standard location prior to placing the well on production.
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	If using a pit for drilling and completion operations, must have an approved pit from prior to spudding the well.
pkautz	1) SURFACE & INTERMEDIATE CASING - Cement must circulate to surface 2) PRODUCTION CASING - Cement must tie back into intermediate casing
pkautz	If cement does not circulate to surface, must run temperature survey or other log to determine top of cement
pkautz	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water
pkautz	Only Fresh Water and Air are Valid Drilling Fluids for Surface Casing
pkautz	Operator shall notify appropriate District office when setting conductor pipe.
pkautz	1)- The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud 2)- Drilling Sundries Form C-103 (Casing and Cement test are to be submitted within 10 days 3)- Completion Reports & Logs are to be submitted within 20 days 4)- Deviation / Directional Drill Survey are to be filed with or prior to C-104
pkautz	It is the operator's responsibility to monitor cancellation dates of approved APDs. APD's are good for 2 years and may be extended for one year. Only one 1 year extension will be granted if submitted by C-103 before expiration date. After expiration date or after a 1 year extension must submit new APD.
pkautz	If an APD expires and if site construction has occurred, site remediation is required.
pkautz	Lost Circulation - Must notify OCD Hobbs Office if lost circulation is encountered at 575-370-3186
pkautz	Water flows - Must notify OCD Hobbs Office of any water flows in the Castile Formation at 575-370-3186. Report depth and flow rate
pkautz	Stage Tool - 1) Must notify OCD Hobbs Office prior to running Stage Tool at 575-370-3186 2) If using Stage Tool on Surface casing, Stage Tool must be set greater than 350' from surface and a minimum of 200 feet above surface shoe. 3) When using a Stage Tool on Intermediate or Production Casing Stage must be a minimum of 50 feet below previous casing shoe.
pkautz	Operator to Submit Gas Capture Plan form prior spud