District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

<u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 **District IV**

11. Work Type

16. Multiple

Depth to Ground water

New Well

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 245247

	Operator Name and Address COG OPERATING LLC									2. OGRID Number 229137			
		Concho Center and, TX 79701								3. API N	umber 30-025-44231		
4. Property	y Cod 3962		5	. Property Name GETTYSE	BURG STATE	СОМ				6. Well N	lo. 014H		
						7. Sur	face Location						
UL - Lot		Section	Township	Range	Lot I	dn	Feet From	N/S Line	Feet From		E/W Line	County	
	С	16	238	3.	4E	С	244	N	15	40	W		Lea
					8. Pi	roposed E	Bottom Hole Location	on					
JL - Lot		Section	Township	Range	Lot Id	n	Feet From	N/S Line	Feet From		E/W Line	County	
	F	21	238	34	4E	F	2440	N	13	25	W		Lea
						9. Po	ol Information						
ANTELO	PF R	IDGE;BONE SPRIN	IG WEST								2	209	

13. Cable/Rotary

18. Formation

5000

Bone Spring
Distance from nearest fresh water well

Type

Double Ram

12. Well Type

OII

18862

17. Proposed Depth

			21. Proposed Casing	g and Cement Program		
Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	13.5	10.75	45.5	1425	900	0
Int1	9.875	7.625	29.7	10800	1300	0
Prod	6.75	5	18	18862	1600	10250

14. Lease Type

19. Contractor

State

Test Pressure

5000

15. Ground Level Elevation

3425

12/13/2017

Manufacturer

Cameron

Distance to nearest surface water

20. Spud Date

Casing/Cement Program: Additional Comments

Drill 13-1/2" hole to ~1425' w/ fresh water spud mud. Run 10-3/4" 45.5# HCN80 BTC casing to TD and cement to surface in one stage. Drill 9-7/8" hole to ~10,800' with brine diesel emulsion WBM. Run 7-5/8" 29.7# HCP110 BTC casing to TD and cement to surface in one stage. Drill 6-3/4" vertical hole, curve & lateral to 18,862' with OBM. Run 5-1/2" 23# P110 BTC casing from 0' – 10,250' and 5" 18# HCP110 BTC from 10,250' to TD and cement to 10,250' in one stage.

22. Proposed Blowout Prevention Program
Working Pressure

,	<u>.</u>				
knowledge and b		true and complete to the best of my		OIL CONSERVATION	ON DIVISION
Printed Name:	Printed Name: Electronically filed by Diane Kuykendall			Paul Kautz	
Title:	e: Production Reporting Mgr			Geologist	
Email Address: production@concho.com			Approved Date:	11/30/2017	Expiration Date: 11/30/2019
Date:	11/30/2017 Phone: 432-683-7443			oval Attached	

District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 **District IV** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Form C-102 August 1, 2011 Permit 245247

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name
30-025-44231	2209	ANTELOPE RIDGE;BONE SPRING, WEST
4. Property Code	5. Property Name	6. Well No.
39622	GETTYSBURG STATE COM	014H
7. OGRID No.	8. Operator Name	9. Elevation
229137	COG OPERATING LLC	3425

				iv. Suri	ace Location				
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
С	16	238	34E	С	244	N	1540	W	Lea

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
F	21	23S	34E	F	2440	N	1325	W	Lea
12. Dedicated Acres		13. Joint or Infill		14. Consolidation Code			15. Order No.		
240.00									

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION **OPERATOR CERTIFICATION** I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. Diane Kuykendall E-Signed By: Production Reporting Mgr Title: 11/30/2017 Date SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. Chad Harcrow Surveyed By: 10/17/2017 Date of Survey: 17777 Certificate Number:

Form APD Comments

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Permit 245247

PERMIT COMMENTS

Operator Name and Address:	API Number:
COG OPERATING LLC [229137]	30-025-44231
One Concho Center	Well:
Midland, TX 79701	GETTYSBURG STATE COM #014H

Created By	Comment	Comment Date
mreye	3 OIL: COG Operating has conducted a review to determine if an H2S contingency plan is required for the above referenced well. We were able to conclude that	11/30/2017
	any potential hazardous volume would be minimal. H2S concentrations of wells in this area from surface to TD are low enough; therefore we do not believe that	
	an H2S Contingency Plan would be necessary.	

Form APD Conditions

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Permit 245247

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
COG OPERATING LLC [229137]	30-025-44231
One Concho Center	Well:
Midland, TX 79701	GETTYSBURG STATE COM #014H

OCD Reviewer	Condition
pkautz	Will require a directional survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Pit construction and closure must satisfy all requirements of your approved plan.
pkautz	If using a pit for drilling and completion operations, must have an approved pit from prior to spudding the well.
pkautz	1) SURFACE & INTERMEDIATE CASING - Cement must circulate to surface 2) PRODUCTION CASING - Cement must tie back into intermediate casing
pkautz	If cement does not circulate to surface, must run temperature survey or other log to determine top of cement
pkautz	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water
pkautz	1)- The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud 2)- Drilling Sundries Form C-103 (Casing and Cement test are to be submitted within 10 days 3)- Completion Reports & Logs are to be submitted within 45 days 4)- Deviation / Directional Drill Survey are to be filed with or prior to C-104
pkautz	Stage Tool - 1) Must notify OCD Hobbs Office prior to running Stage Tool at 575-370-3186 2) If using Stage Tool on Surface casing, Stage Tool must be set greater than 350' from surface and a minimum of 200 feet above surface shoe. 3) When using a Stage Tool on Intermediate or Production Casing Stage must be a minimum of 50 feet below previous casing shoe.
pkautz	Will require a directional survey with the C-104
pkautz	Will require a administrative order for non-standard location prior to placing the well on production.