

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101

August 1, 2011

Permit 292497

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address COLGATE OPERATING, LLC 300 North Marienfeld Street Midland, TX 79701		2. OGRID Number 371449
		3. API Number 30-015-48067
4. Property Code 330186	5. Property Name KLONDIKE 9 STATE COM	6. Well No. 133H

7. Surface Location

UL - Lot I	Section 9	Township 19S	Range 28E	Lot Idn I	Feet From 1342	N/S Line S	Feet From 300	E/W Line E	County Eddy
---------------	--------------	-----------------	--------------	--------------	-------------------	---------------	------------------	---------------	----------------

8. Proposed Bottom Hole Location

UL - Lot L	Section 8	Township 19S	Range 28E	Lot Idn L	Feet From 1793	N/S Line S	Feet From 10	E/W Line W	County Eddy
---------------	--------------	-----------------	--------------	--------------	-------------------	---------------	-----------------	---------------	----------------

9. Pool Information

WINCHESTER; BONE SPRING, WEST	97569
-------------------------------	-------

Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3541
16. Multiple N	17. Proposed Depth 8400	18. Formation 3rd Bone Spring Sand	19. Contractor	20. Spud Date 4/1/2021
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☒ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	170	156	0
Int1	12.25	9.625	36	2760	644	0
Prod	8.75	5.5	20	18559	2993	2050

Casing/Cement Program: Additional Comments

--

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Double Ram	10000	5000	Cameron

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify I have complied with 19.15.14.9 (A) NMAC ☒ and/or 19.15.14.9 (B) NMAC ☒ if applicable. Signature:	OIL CONSERVATION DIVISION	
Printed Name: Electronically filed by Mikah Thomas	Approved By: Kurt Simmons	
Title: Operations Tech	Title: Petroleum Specialist - A	
Email Address: mthomas@colgateenergy.com	Approved Date: 2/18/2021	Expiration Date: 2/18/2023
Date: 2/18/2021	Phone: 432-695-4272	Conditions of Approval Attached

DISTRICT I

1625 N. French Dr., Hobbs, N.M. 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

DISTRICT II

811 S. First St., Artesia, N.M. 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

DISTRICT III

1000 Rio Brazos Rd., Aztec, N.M. 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV

1220 S. St. Francis Dr., Santa Fe, N.M. 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, N.M. 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate
District Office

☐ AMENDED REPORT**WELL LOCATION AND ACREAGE DEDICATION PLAT**

¹ API Number 30-015-	² Pool Code 97569	³ Pool Name Winchester; Bone Spring
⁴ Property Code	⁵ Property Name Klondike 9 State Com	⁶ Well Number 133H
⁷ OGRID No. 371449	⁸ Operator Name Colgate Operating, LLC	⁹ Elevation 3541

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
I	9	19 S	28 E		1342	South	300	East	Eddy

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L	8	19 S	28 E		1793	South	10	West	Eddy

¹² Dedicated Acres 320	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
---	-------------------------------	----------------------------------	-------------------------

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

16

Legend:

- = Surface Location
- = Bottom Hole Location
- △ = First Take Point (FTP)
- = Last Take Point (LTP)
- = Found 1941 USGLO Brass Cap

SURFACE LOCATION
NAD 83 NMSPC ZONE 3001
Y= 608096.30 N
X= 590504.94 E
LAT.= 32.6716003° N
LONG.= 104.1735470° W

FIRST TAKE POINT
NAD 83 NMSPC ZONE 3001
1793' FSL, 100' FEL
SEC. 9, T19S, R28E
Y= 608549.23 N
X= 590704.46 E
LAT.= 32.6728445° N
LONG.= 104.1728964° W

BOTTOM HOLE LOCATION
NAD 83 NMSPC ZONE 3001
Y= 608434.76 N
X= 580426.71 E
LAT.= 32.6725681° N
LONG.= 104.2062982° W

LAST TAKE POINT
NAD 83 NMSPC ZONE 3001
1793' FSL, 100' FWL
SEC. 8, T19S, R28E
Y= 608435.68 N
X= 580516.72 E
LAT.= 32.6725703° N
LONG.= 104.2060057° W

17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

[Signature] **1/4/2021**
Signature Date
Mikah Thomas
Printed Name
mthomas@colgateenergy.com
E-mail Address

18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

6/24/20
Date of Survey
Signature and Seal of Professional Surveyor
[Signature]
17078
Certificate Number

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

GAS CAPTURE PLAN

Date: 2/18/2021

☒ Original

Operator & OGRID No.: [371449] COLGATE OPERATING, LLC

☐ Amended - Reason for
Amendment: _____

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
KLONDIKE 9 STATE COM #133H	30-015-48067	I-9-19S-28E	1342S 0300E	500	None	

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to LM Touchdown LLC and will be connected to LM Touchdown LLC High/Low Pressure gathering system located in Eddy County, New Mexico. It will require 1800' of pipeline to connect the facility to High/Low Pressure gathering system. COLGATE OPERATING, LLC provides (periodically) to LM Touchdown LLC a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, COLGATE OPERATING, LLC and LM Touchdown LLC have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at LM Touchdown LLC Processing Plant located in Sec. 22, Twn. 19S, Rng. 28E, Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on LM Touchdown LLC system at that time. Based on current information, it is COLGATE OPERATING, LLC's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form APD Comments

Permit 292497

PERMIT COMMENTS

Operator Name and Address: COLGATE OPERATING, LLC [371449] 300 North Marienfeld Street Midland, TX 79701		API Number: 30-015-48067
		Well: KLONDIKE 9 STATE COM #133H
Created By	Comment	Comment Date

District I

1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form APD Conditions

Permit 292497

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address: COLGATE OPERATING, LLC [371449] 300 North Marienfeld Street Midland, TX 79701	API Number: 30-015-48067
	Well: KLONDIKE 9 STATE COM #133H

OCD Reviewer	Condition
ksimmons	Notify OCD 24 hours prior to casing & cement
ksimmons	Will require a File As Drilled C-102 and a Directional Survey with the C-104
ksimmons	Cement is required to circulate on both surface and intermediate1 strings of casing
kpickford	Surface casing must be set 25' below top of Rustler Anhydrite or salt in order to seal off protectable water
kpickford	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud
kpickford	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud 2)- Drilling Sundries Form C-103 (Casing and Cement test are to be submitted within 10 days 3)- Completion Reports & Logs are to be submitted within 45 days 4)- Deviation / Directional Drill Survey are to be filed with or prior to C-104
kpickford	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system



Colgate Energy

Eddy County, NM (N83-NME)

Klondike 9 State Com

Klondike 9 State Com #133H

Permit

Plan: APD-Rev0

Standard Planning Report

10 December, 2020



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Klondike 9 State Com #133H
Company:	Colgate Energy	TVD Reference:	3541+30 @ 3571.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3541+30 @ 3571.00usft
Site:	Klondike 9 State Com	North Reference:	Grid
Well:	Klondike 9 State Com #133H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	APD-Rev0		

Project	Eddy County, NM (N83-NME)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Klondike 9 State Com				
Site Position:		Northing:	608,141.22 usft	Latitude:	32.67172382
From:	Map	Easting:	590,504.85 usft	Longitude:	-104.17354708
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.09

Well	Klondike 9 State Com #133H					
Well Position	+N/-S	-44.92 usft	Northing:	608,096.30 usft	Latitude:	32.67160035
	+E/-W	0.09 usft	Easting:	590,504.94 usft	Longitude:	-104.17354700
Position Uncertainty		0.00 usft	Wellhead Elevation:		Ground Level:	3,541.00 usft

Wellbore	Permit				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2020	12/28/2020	6.91	60.23	47,742.96556813

Design	APD-Rev0				
Audit Notes:					
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.00	
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00	269.36	

Plan Survey Tool Program	Date	12/10/2020			
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks	
1	0.00	18,559.39	APD-Rev0 (Permit)	MWD+IFR1+SAG+FDIR (SQC OWSG MWD + IFR1 + Sag + F	



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Klondike 9 State Com #133H
Company:	Colgate Energy	TVD Reference:	3541+30 @ 3571.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3541+30 @ 3571.00usft
Site:	Klondike 9 State Com	North Reference:	Grid
Well:	Klondike 9 State Com #133H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	APD-Rev0		

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00	0.00	0.00	
2,264.56	6.97	28.82	2,263.41	24.72	13.60	1.50	1.50	0.00	28.82	
6,065.81	6.97	28.82	6,036.59	428.77	235.92	0.00	0.00	0.00	0.00	
6,530.37	0.00	0.00	6,500.00	453.49	249.52	1.50	-1.50	0.00	180.00	00-EON(K9SC-133H)
7,900.77	0.00	0.00	7,870.40	453.49	249.52	0.00	0.00	0.00	0.00	
8,814.56	91.38	269.36	8,443.19	446.95	-337.19	10.00	10.00	-9.92	269.36	
10,983.01	91.38	269.36	8,391.00	422.81	-2,504.88	0.00	0.00	0.00	0.00	03-2500VS(K9SC-133H)
10,994.27	91.60	269.36	8,390.71	422.68	-2,516.14	2.00	2.00	0.00	0.03	
13,483.99	91.60	269.36	8,321.00	394.97	-5,004.72	0.00	0.00	0.00	0.00	04-5000VS(K9SC-133H)
18,469.75	91.60	269.36	8,181.41	339.47	-9,988.22	0.00	0.00	0.00	0.00	05-LTP(K9SC-133H)
18,559.80	91.60	269.36	8,178.89	338.47	-10,078.23	0.00	0.00	0.00	0.00	06-PBHL(K9SC-133H)



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Klondike 9 State Com #133H
Company:	Colgate Energy	TVD Reference:	3541+30 @ 3571.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3541+30 @ 3571.00usft
Site:	Klondike 9 State Com	North Reference:	Grid
Well:	Klondike 9 State Com #133H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	APD-Rev0		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
59.00	0.00	0.00	59.00	0.00	0.00	0.00	0.00	0.00	0.00
Rustler									
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
216.00	0.00	0.00	216.00	0.00	0.00	0.00	0.00	0.00	0.00
Top of Salt									
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
379.00	0.00	0.00	379.00	0.00	0.00	0.00	0.00	0.00	0.00
Base of Salt									
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	0.00	0.00
687.00	0.00	0.00	687.00	0.00	0.00	0.00	0.00	0.00	0.00
Yates									
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	0.00	0.00
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00	0.00	0.00
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00	0.00	0.00
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00	0.00	0.00
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00	0.00	0.00
1,900.00	1.50	28.82	1,899.99	1.15	0.63	-0.64	1.50	1.50	0.00
2,000.00	3.00	28.82	1,999.91	4.59	2.52	-2.57	1.50	1.50	0.00
2,100.00	4.50	28.82	2,099.69	10.32	5.68	-5.79	1.50	1.50	0.00
2,200.00	6.00	28.82	2,199.27	18.33	10.09	-10.29	1.50	1.50	0.00
2,264.56	6.97	28.82	2,263.41	24.72	13.60	-13.88	1.50	1.50	0.00
2,300.00	6.97	28.82	2,298.59	28.49	15.67	-15.99	0.00	0.00	0.00
2,400.00	6.97	28.82	2,397.86	39.12	21.52	-21.96	0.00	0.00	0.00
2,500.00	6.97	28.82	2,497.12	49.75	27.37	-27.93	0.00	0.00	0.00
2,600.00	6.97	28.82	2,596.38	60.38	33.22	-33.89	0.00	0.00	0.00
2,700.00	6.97	28.82	2,695.64	71.01	39.07	-39.86	0.00	0.00	0.00
2,800.00	6.97	28.82	2,794.90	81.63	44.92	-45.83	0.00	0.00	0.00
2,846.44	6.97	28.82	2,841.00	86.57	47.63	-48.60	0.00	0.00	0.00
DLWR Mnt. Group									
2,900.00	6.97	28.82	2,894.16	92.26	50.77	-51.79	0.00	0.00	0.00
3,000.00	6.97	28.82	2,993.42	102.89	56.61	-57.76	0.00	0.00	0.00
3,078.15	6.97	28.82	3,071.00	111.20	61.18	-62.42	0.00	0.00	0.00
Lower Brushy Canyon									
3,100.00	6.97	28.82	3,092.68	113.52	62.46	-63.73	0.00	0.00	0.00
3,200.00	6.97	28.82	3,191.95	124.15	68.31	-69.69	0.00	0.00	0.00
3,300.00	6.97	28.82	3,291.21	134.78	74.16	-75.66	0.00	0.00	0.00
3,350.16	6.97	28.82	3,341.00	140.11	77.09	-78.65	0.00	0.00	0.00
Bone Spring Lime									
3,400.00	6.97	28.82	3,390.47	145.41	80.01	-81.63	0.00	0.00	0.00
3,500.00	6.97	28.82	3,489.73	156.04	85.86	-87.59	0.00	0.00	0.00
3,600.00	6.97	28.82	3,588.99	166.67	91.71	-93.56	0.00	0.00	0.00
3,700.00	6.97	28.82	3,688.25	177.30	97.55	-99.53	0.00	0.00	0.00



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Klondike 9 State Com #133H
Company:	Colgate Energy	TVD Reference:	3541+30 @ 3571.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3541+30 @ 3571.00usft
Site:	Klondike 9 State Com	North Reference:	Grid
Well:	Klondike 9 State Com #133H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	APD-Rev0		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
3,800.00	6.97	28.82	3,787.51	187.93	103.40	-105.49	0.00	0.00	0.00
3,900.00	6.97	28.82	3,886.78	198.56	109.25	-111.46	0.00	0.00	0.00
4,000.00	6.97	28.82	3,986.04	209.19	115.10	-117.43	0.00	0.00	0.00
4,100.00	6.97	28.82	4,085.30	219.82	120.95	-123.40	0.00	0.00	0.00
4,200.00	6.97	28.82	4,184.56	230.45	126.80	-129.36	0.00	0.00	0.00
4,300.00	6.97	28.82	4,283.82	241.08	132.64	-135.33	0.00	0.00	0.00
4,400.00	6.97	28.82	4,383.08	251.70	138.49	-141.30	0.00	0.00	0.00
4,500.00	6.97	28.82	4,482.34	262.33	144.34	-147.26	0.00	0.00	0.00
4,600.00	6.97	28.82	4,581.60	272.96	150.19	-153.23	0.00	0.00	0.00
4,700.00	6.97	28.82	4,680.87	283.59	156.04	-159.20	0.00	0.00	0.00
4,800.00	6.97	28.82	4,780.13	294.22	161.89	-165.16	0.00	0.00	0.00
4,900.00	6.97	28.82	4,879.39	304.85	167.74	-171.13	0.00	0.00	0.00
5,000.00	6.97	28.82	4,978.65	315.48	173.58	-177.10	0.00	0.00	0.00
5,100.00	6.97	28.82	5,077.91	326.11	179.43	-183.06	0.00	0.00	0.00
5,200.00	6.97	28.82	5,177.17	336.74	185.28	-189.03	0.00	0.00	0.00
5,300.00	6.97	28.82	5,276.43	347.37	191.13	-195.00	0.00	0.00	0.00
5,400.00	6.97	28.82	5,375.70	358.00	196.98	-200.96	0.00	0.00	0.00
5,500.00	6.97	28.82	5,474.96	368.63	202.83	-206.93	0.00	0.00	0.00
5,600.00	6.97	28.82	5,574.22	379.26	208.68	-212.90	0.00	0.00	0.00
5,700.00	6.97	28.82	5,673.48	389.89	214.52	-218.87	0.00	0.00	0.00
5,800.00	6.97	28.82	5,772.74	400.52	220.37	-224.83	0.00	0.00	0.00
5,900.00	6.97	28.82	5,872.00	411.15	226.22	-230.80	0.00	0.00	0.00
6,000.00	6.97	28.82	5,971.26	421.77	232.07	-236.77	0.00	0.00	0.00
6,065.81	6.97	28.82	6,036.59	428.77	235.92	-240.69	0.00	0.00	0.00
6,100.00	6.46	28.82	6,070.54	432.27	237.84	-242.66	1.50	-1.50	0.00
6,200.00	4.96	28.82	6,170.04	440.98	242.64	-247.55	1.50	-1.50	0.00
6,200.96	4.94	28.82	6,171.00	441.05	242.68	-247.59	1.50	-1.50	0.00
1st Bone Spring SD									
6,236.08	4.41	28.82	6,206.00	443.56	244.06	-249.00	1.50	-1.50	0.00
2nd Bone Spring LM									
6,300.00	3.46	28.82	6,269.77	447.41	246.17	-251.15	1.50	-1.50	0.00
6,400.00	1.96	28.82	6,369.66	451.54	248.45	-253.48	1.50	-1.50	0.00
6,500.00	0.46	28.82	6,469.63	453.38	249.46	-254.51	1.50	-1.50	0.00
6,530.37	0.00	0.00	6,500.00	453.49	249.52	-254.57	1.50	-1.50	0.00
00-EON(K9SC-133H)									
6,600.00	0.00	0.00	6,569.63	453.49	249.52	-254.57	0.00	0.00	0.00
6,700.00	0.00	0.00	6,669.63	453.49	249.52	-254.57	0.00	0.00	0.00
6,800.00	0.00	0.00	6,769.63	453.49	249.52	-254.57	0.00	0.00	0.00
6,900.00	0.00	0.00	6,869.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,000.00	0.00	0.00	6,969.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,100.00	0.00	0.00	7,069.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,151.37	0.00	0.00	7,121.00	453.49	249.52	-254.57	0.00	0.00	0.00
2nd Bone Spring SD									
7,200.00	0.00	0.00	7,169.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,300.00	0.00	0.00	7,269.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,400.00	0.00	0.00	7,369.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,500.00	0.00	0.00	7,469.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,600.00	0.00	0.00	7,569.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,651.37	0.00	0.00	7,621.00	453.49	249.52	-254.57	0.00	0.00	0.00
3rd Bone Spring LM									
7,700.00	0.00	0.00	7,669.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,800.00	0.00	0.00	7,769.63	453.49	249.52	-254.57	0.00	0.00	0.00
7,900.77	0.00	0.00	7,870.40	453.49	249.52	-254.57	0.00	0.00	0.00



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Klondike 9 State Com #133H
Company:	Colgate Energy	TVD Reference:	3541+30 @ 3571.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3541+30 @ 3571.00usft
Site:	Klondike 9 State Com	North Reference:	Grid
Well:	Klondike 9 State Com #133H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	APD-Rev0		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
KOP: 7900.77' MD, -254.57' VS, 7870.40' TVD									
7,950.00	4.92	269.36	7,919.57	453.47	247.41	-252.46	10.00	10.00	0.00
8,000.00	9.92	269.36	7,969.14	453.39	240.95	-246.00	10.00	10.00	0.00
8,050.00	14.92	269.36	8,017.95	453.27	230.20	-235.24	10.00	10.00	0.00
8,100.00	19.92	269.36	8,065.64	453.11	215.23	-220.28	10.00	10.00	0.00
8,150.00	24.92	269.36	8,111.85	452.90	196.17	-201.21	10.00	10.00	0.00
8,200.00	29.92	269.36	8,156.21	452.64	173.15	-178.19	10.00	10.00	0.00
8,250.00	34.92	269.36	8,198.41	452.34	146.35	-151.39	10.00	10.00	0.00
8,300.00	39.92	269.36	8,238.10	452.00	115.97	-121.02	10.00	10.00	0.00
8,330.55	42.98	269.36	8,261.00	451.78	95.75	-100.79	10.00	10.00	0.00
3rd Bone Spring SD									
8,350.00	44.92	269.36	8,275.00	451.63	82.26	-87.30	10.00	10.00	0.00
8,382.73	48.20	269.36	8,297.50	451.36	58.49	-63.53	10.00	10.00	0.00
01-FTP(K9SC-133H)									
8,400.00	49.92	269.36	8,308.82	451.22	45.45	-50.49	10.00	10.00	0.00
8,450.00	54.92	269.36	8,339.30	450.78	5.84	-10.88	10.00	10.00	0.00
8,500.00	59.92	269.36	8,366.21	450.31	-36.28	31.24	10.00	10.00	0.00
8,511.56	61.08	269.36	8,371.90	450.19	-46.33	41.30	10.00	10.00	0.00
02-0VS(K9SC-133H)									
8,550.00	64.92	269.36	8,389.35	449.81	-80.58	75.55	10.00	10.00	0.00
8,600.00	69.92	269.36	8,408.54	449.30	-126.73	121.70	10.00	10.00	0.00
8,650.00	74.92	269.36	8,423.64	448.77	-174.38	169.35	10.00	10.00	0.00
8,700.00	79.92	269.36	8,434.52	448.23	-223.16	218.14	10.00	10.00	0.00
8,750.00	84.92	269.36	8,441.11	447.67	-272.70	267.69	10.00	10.00	0.00
8,800.00	89.92	269.36	8,443.36	447.12	-322.63	317.62	10.00	10.00	0.00
8,814.56	91.38	269.36	8,443.19	446.95	-337.19	332.18	10.00	10.00	0.00
EOC: 8814.56' MD, 332.18' VS, 8443.19' TVD									
8,900.00	91.38	269.36	8,441.14	446.00	-422.60	417.59	0.00	0.00	0.00
9,000.00	91.38	269.36	8,438.73	444.89	-522.57	517.57	0.00	0.00	0.00
9,100.00	91.38	269.36	8,436.32	443.78	-622.53	617.54	0.00	0.00	0.00
9,200.00	91.38	269.36	8,433.91	442.66	-722.50	717.51	0.00	0.00	0.00
9,300.00	91.38	269.36	8,431.51	441.55	-822.46	817.48	0.00	0.00	0.00
9,400.00	91.38	269.36	8,429.10	440.44	-922.43	917.45	0.00	0.00	0.00
9,500.00	91.38	269.36	8,426.69	439.32	-1,022.39	1,017.42	0.00	0.00	0.00
9,600.00	91.38	269.36	8,424.29	438.21	-1,122.36	1,117.39	0.00	0.00	0.00
9,700.00	91.38	269.36	8,421.88	437.10	-1,222.32	1,217.36	0.00	0.00	0.00
9,800.00	91.38	269.36	8,419.47	435.98	-1,322.29	1,317.33	0.00	0.00	0.00
9,900.00	91.38	269.36	8,417.07	434.87	-1,422.25	1,417.30	0.00	0.00	0.00
10,000.00	91.38	269.36	8,414.66	433.76	-1,522.22	1,517.28	0.00	0.00	0.00
10,100.00	91.38	269.36	8,412.25	432.64	-1,622.18	1,617.25	0.00	0.00	0.00
10,200.00	91.38	269.36	8,409.85	431.53	-1,722.15	1,717.22	0.00	0.00	0.00
10,300.00	91.38	269.36	8,407.44	430.42	-1,822.11	1,817.19	0.00	0.00	0.00
10,400.00	91.38	269.36	8,405.03	429.30	-1,922.07	1,917.16	0.00	0.00	0.00
10,500.00	91.38	269.36	8,402.63	428.19	-2,022.04	2,017.13	0.00	0.00	0.00
10,600.00	91.38	269.36	8,400.22	427.07	-2,122.00	2,117.10	0.00	0.00	0.00
10,700.00	91.38	269.36	8,397.81	425.96	-2,221.97	2,217.07	0.00	0.00	0.00
10,800.00	91.38	269.36	8,395.41	424.85	-2,321.93	2,317.04	0.00	0.00	0.00
10,900.00	91.38	269.36	8,393.00	423.73	-2,421.90	2,417.01	0.00	0.00	0.00
10,983.01	91.38	269.36	8,391.00	422.81	-2,504.88	2,500.00	0.00	0.00	0.00
03-2500VS(K9SC-133H)									
10,994.27	91.60	269.36	8,390.71	422.68	-2,516.14	2,511.26	2.00	2.00	0.00
11,000.00	91.60	269.36	8,390.55	422.62	-2,521.86	2,516.98	0.00	0.00	0.00
11,100.00	91.60	269.36	8,387.75	421.51	-2,621.82	2,616.95	0.00	0.00	0.00



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Klondike 9 State Com #133H
Company:	Colgate Energy	TVD Reference:	3541+30 @ 3571.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3541+30 @ 3571.00usft
Site:	Klondike 9 State Com	North Reference:	Grid
Well:	Klondike 9 State Com #133H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	APD-Rev0		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
11,200.00	91.60	269.36	8,384.95	420.39	-2,721.77	2,716.91	0.00	0.00	0.00
11,300.00	91.60	269.36	8,382.15	419.28	-2,821.73	2,816.87	0.00	0.00	0.00
11,400.00	91.60	269.36	8,379.35	418.17	-2,921.68	2,916.83	0.00	0.00	0.00
11,500.00	91.60	269.36	8,376.55	417.06	-3,021.64	3,016.79	0.00	0.00	0.00
11,600.00	91.60	269.36	8,373.75	415.94	-3,121.59	3,116.75	0.00	0.00	0.00
11,700.00	91.60	269.36	8,370.95	414.83	-3,221.54	3,216.71	0.00	0.00	0.00
11,800.00	91.60	269.36	8,368.15	413.72	-3,321.50	3,316.67	0.00	0.00	0.00
11,900.00	91.60	269.36	8,365.35	412.60	-3,421.45	3,416.63	0.00	0.00	0.00
12,000.00	91.60	269.36	8,362.55	411.49	-3,521.41	3,516.59	0.00	0.00	0.00
12,100.00	91.60	269.36	8,359.75	410.38	-3,621.36	3,616.55	0.00	0.00	0.00
12,200.00	91.60	269.36	8,356.95	409.26	-3,721.32	3,716.51	0.00	0.00	0.00
12,300.00	91.60	269.36	8,354.15	408.15	-3,821.27	3,816.48	0.00	0.00	0.00
12,400.00	91.60	269.36	8,351.35	407.04	-3,921.23	3,916.44	0.00	0.00	0.00
12,500.00	91.60	269.36	8,348.55	405.92	-4,021.18	4,016.40	0.00	0.00	0.00
12,600.00	91.60	269.36	8,345.75	404.81	-4,121.14	4,116.36	0.00	0.00	0.00
12,700.00	91.60	269.36	8,342.95	403.70	-4,221.09	4,216.32	0.00	0.00	0.00
12,800.00	91.60	269.36	8,340.15	402.58	-4,321.05	4,316.28	0.00	0.00	0.00
12,900.00	91.60	269.36	8,337.35	401.47	-4,421.00	4,416.24	0.00	0.00	0.00
13,000.00	91.60	269.36	8,334.55	400.36	-4,520.95	4,516.20	0.00	0.00	0.00
13,100.00	91.60	269.36	8,331.75	399.24	-4,620.91	4,616.16	0.00	0.00	0.00
13,200.00	91.60	269.36	8,328.95	398.13	-4,720.86	4,716.12	0.00	0.00	0.00
13,300.00	91.60	269.36	8,326.15	397.02	-4,820.82	4,816.08	0.00	0.00	0.00
13,400.00	91.60	269.36	8,323.35	395.90	-4,920.77	4,916.04	0.00	0.00	0.00
13,483.99	91.60	269.36	8,321.00	394.97	-5,004.72	5,000.00	0.00	0.00	0.00
04-5000VS(K9SC-133H)									
13,500.00	91.60	269.36	8,320.55	394.79	-5,020.73	5,016.00	0.00	0.00	0.00
13,600.00	91.60	269.36	8,317.75	393.68	-5,120.68	5,115.97	0.00	0.00	0.00
13,700.00	91.60	269.36	8,314.95	392.57	-5,220.64	5,215.93	0.00	0.00	0.00
13,800.00	91.60	269.36	8,312.15	391.45	-5,320.59	5,315.89	0.00	0.00	0.00
13,900.00	91.60	269.36	8,309.35	390.34	-5,420.55	5,415.85	0.00	0.00	0.00
14,000.00	91.60	269.36	8,306.55	389.23	-5,520.50	5,515.81	0.00	0.00	0.00
14,100.00	91.60	269.36	8,303.75	388.11	-5,620.46	5,615.77	0.00	0.00	0.00
14,200.00	91.60	269.36	8,300.95	387.00	-5,720.41	5,715.73	0.00	0.00	0.00
14,300.00	91.60	269.36	8,298.15	385.89	-5,820.36	5,815.69	0.00	0.00	0.00
14,400.00	91.60	269.36	8,295.35	384.77	-5,920.32	5,915.65	0.00	0.00	0.00
14,500.00	91.60	269.36	8,292.55	383.66	-6,020.27	6,015.61	0.00	0.00	0.00
14,600.00	91.60	269.36	8,289.75	382.55	-6,120.23	6,115.57	0.00	0.00	0.00
14,700.00	91.60	269.36	8,286.95	381.43	-6,220.18	6,215.53	0.00	0.00	0.00
14,800.00	91.60	269.36	8,284.15	380.32	-6,320.14	6,315.50	0.00	0.00	0.00
14,900.00	91.60	269.36	8,281.35	379.21	-6,420.09	6,415.46	0.00	0.00	0.00
15,000.00	91.60	269.36	8,278.55	378.09	-6,520.05	6,515.42	0.00	0.00	0.00
15,100.00	91.60	269.36	8,275.76	376.98	-6,620.00	6,615.38	0.00	0.00	0.00
15,200.00	91.60	269.36	8,272.96	375.87	-6,719.96	6,715.34	0.00	0.00	0.00
15,300.00	91.60	269.36	8,270.16	374.75	-6,819.91	6,815.30	0.00	0.00	0.00
15,400.00	91.60	269.36	8,267.36	373.64	-6,919.87	6,915.26	0.00	0.00	0.00
15,500.00	91.60	269.36	8,264.56	372.53	-7,019.82	7,015.22	0.00	0.00	0.00
15,600.00	91.60	269.36	8,261.76	371.42	-7,119.77	7,115.18	0.00	0.00	0.00
15,700.00	91.60	269.36	8,258.96	370.30	-7,219.73	7,215.14	0.00	0.00	0.00
15,800.00	91.60	269.36	8,256.16	369.19	-7,319.68	7,315.10	0.00	0.00	0.00
15,900.00	91.60	269.36	8,253.36	368.08	-7,419.64	7,415.06	0.00	0.00	0.00
16,000.00	91.60	269.36	8,250.56	366.96	-7,519.59	7,515.02	0.00	0.00	0.00
16,100.00	91.60	269.36	8,247.76	365.85	-7,619.55	7,614.99	0.00	0.00	0.00
16,200.00	91.60	269.36	8,244.96	364.74	-7,719.50	7,714.95	0.00	0.00	0.00
16,300.00	91.60	269.36	8,242.16	363.62	-7,819.46	7,814.91	0.00	0.00	0.00



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Klondike 9 State Com #133H
Company:	Colgate Energy	TVD Reference:	3541+30 @ 3571.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3541+30 @ 3571.00usft
Site:	Klondike 9 State Com	North Reference:	Grid
Well:	Klondike 9 State Com #133H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	APD-Rev0		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
16,400.00	91.60	269.36	8,239.36	362.51	-7,919.41	7,914.87	0.00	0.00	0.00
16,500.00	91.60	269.36	8,236.56	361.40	-8,019.37	8,014.83	0.00	0.00	0.00
16,600.00	91.60	269.36	8,233.76	360.28	-8,119.32	8,114.79	0.00	0.00	0.00
16,700.00	91.60	269.36	8,230.96	359.17	-8,219.27	8,214.75	0.00	0.00	0.00
16,800.00	91.60	269.36	8,228.16	358.06	-8,319.23	8,314.71	0.00	0.00	0.00
16,900.00	91.60	269.36	8,225.36	356.94	-8,419.18	8,414.67	0.00	0.00	0.00
17,000.00	91.60	269.36	8,222.56	355.83	-8,519.14	8,514.63	0.00	0.00	0.00
17,100.00	91.60	269.36	8,219.76	354.72	-8,619.09	8,614.59	0.00	0.00	0.00
17,200.00	91.60	269.36	8,216.96	353.60	-8,719.05	8,714.55	0.00	0.00	0.00
17,300.00	91.60	269.36	8,214.16	352.49	-8,819.00	8,814.52	0.00	0.00	0.00
17,400.00	91.60	269.36	8,211.36	351.38	-8,918.96	8,914.48	0.00	0.00	0.00
17,500.00	91.60	269.36	8,208.56	350.27	-9,018.91	9,014.44	0.00	0.00	0.00
17,600.00	91.60	269.36	8,205.76	349.15	-9,118.87	9,114.40	0.00	0.00	0.00
17,700.00	91.60	269.36	8,202.96	348.04	-9,218.82	9,214.36	0.00	0.00	0.00
17,800.00	91.60	269.36	8,200.16	346.93	-9,318.78	9,314.32	0.00	0.00	0.00
17,900.00	91.60	269.36	8,197.36	345.81	-9,418.73	9,414.28	0.00	0.00	0.00
18,000.00	91.60	269.36	8,194.56	344.70	-9,518.68	9,514.24	0.00	0.00	0.00
18,100.00	91.60	269.36	8,191.76	343.59	-9,618.64	9,614.20	0.00	0.00	0.00
18,200.00	91.60	269.36	8,188.96	342.47	-9,718.59	9,714.16	0.00	0.00	0.00
18,300.00	91.60	269.36	8,186.16	341.36	-9,818.55	9,814.12	0.00	0.00	0.00
18,400.00	91.60	269.36	8,183.36	340.25	-9,918.50	9,914.08	0.00	0.00	0.00
18,469.75	91.60	269.36	8,181.41	339.47	-9,988.22	9,983.81	0.00	0.00	0.00
05-LTP(K9SC-133H)									
18,500.00	91.60	269.36	8,180.56	339.13	-10,018.46	10,014.04	0.00	0.00	0.00
18,559.80	91.60	269.36	8,178.89	338.47	-10,078.23	10,073.82	0.00	0.00	0.00
TD: 18559.80' MD, 10073.82' VS, 8178.89' TVD - 06-PBHL(K9SC-133H)									



Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Klondike 9 State Com #133H
Company:	Colgate Energy	TVD Reference:	3541+30 @ 3571.00usft
Project:	Eddy County, NM (N83-NME)	MD Reference:	3541+30 @ 3571.00usft
Site:	Klondike 9 State Com	North Reference:	Grid
Well:	Klondike 9 State Com #133H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Permit		
Design:	APD-Rev0		

Design Targets									
Target Name									
- hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- Shape	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
00-EON(K9SC-133H)	0.00	0.00	6,500.00	453.49	249.52	608,549.79	590,754.46	32.67284582	-104.17273388
- plan hits target center									
- Point									
06-PBHL(K9SC-133H)	0.00	0.00	8,178.89	338.46	-10,078.23	608,434.76	580,426.71	32.67256811	-104.20629825
- plan misses target center by 0.01usft at 18559.80usft MD (8178.89 TVD, 338.47 N, -10078.23 E)									
- Point									
05-LTP(K9SC-133H)	0.00	0.00	8,181.41	339.38	-9,988.22	608,435.68	580,516.72	32.67257034	-104.20600572
- plan misses target center by 0.09usft at 18469.75usft MD (8181.41 TVD, 339.47 N, -9988.22 E)									
- Point									
04-5000VS(K9SC-133H)	0.00	0.00	8,321.00	394.97	-5,004.72	608,491.27	585,500.22	32.67270566	-104.18980976
- plan hits target center									
- Point									
03-2500VS(K9SC-133H)	0.00	0.00	8,391.00	422.81	-2,504.88	608,519.11	588,000.06	32.67277263	-104.18168548
- plan hits target center									
- Point									
01-FTP(K9SC-133H)	0.00	269.36	8,451.00	452.93	199.52	608,549.23	590,704.46	32.67284449	-104.17289637
- plan misses target center by 208.45usft at 8382.73usft MD (8297.50 TVD, 451.36 N, 58.49 E)									
- Point									
02-0VS(K9SC-133H)	0.00	0.00	8,451.00	450.65	-5.03	608,546.95	590,499.91	32.67283907	-104.17356115
- plan misses target center by 89.23usft at 8511.56usft MD (8371.90 TVD, 450.19 N, -46.33 E)									
- Point									


Formations					
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
59.00	59.00	Rustler			
216.00	216.00	Top of Salt			
379.00	379.00	Base of Salt			
687.00	687.00	Yates			
2,846.44	2,841.00	DLWR Mnt. Group			
3,078.15	3,071.00	Lower Brushy Canyon			
3,350.16	3,341.00	Bone Spring Lime			
6,200.96	6,171.00	1st Bone Spring SD			
6,236.08	6,206.00	2nd Bone Spring LM			
7,151.37	7,121.00	2nd Bone Spring SD			
7,651.37	7,621.00	3rd Bone Spring LM			
8,330.55	8,261.00	3rd Bone Spring SD			

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Comment
7,900.77	7,870.40	453.49	249.52	KOP: 7900.77' MD, -254.57' VS, 7870.40' TVD
8,814.56	8,443.19	446.95	-337.19	EOC: 8814.56' MD, 332.18' VS, 8443.19' TVD
18,559.80	8,178.89	338.47	-10,078.23	TD: 18559.80' MD, 10073.82' VS, 8178.89' TVD



WELL DETAILS: Klondike 9 State Com #133H

Northing 608096.30
Easting 590504.94
Latitude 32.67160035
Longitude -104.17354700



Azimuths to Grid North
True North: -0.09°
Magnetic North: 6.83°

Magnetic Field
Strength: 47743.0snT
Dip Angle: 60.23°
Date: 12/28/2020
Model: IGRF2020

PROJECT DETAILS: Eddy County, NM (N83-NME)
Well Name: Klondike 9 State Com #133H
Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: New Mexico Eastern Zone
System Datum: Mean Sea Level
Local North: Grid
KB Elevation: 3541+30 @ 3571.00usft
Elevation: 3541.00

Site: Klondike 9 State Com
Well: Klondike 9 State Com #133H
Wellbore: Permit
Plan: APD-Rev0

Section Details										
Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	1800.00	0.00	0.00	1800.00	0.00	0.00	0.00	0.00	0.00	
3	2264.56	6.97	28.82	2263.41	24.72	13.60	1.50	28.82	-13.88	
4	6065.81	6.97	28.82	6036.59	428.77	235.92	0.00	0.00	-240.69	
5	6530.37	0.00	0.00	6500.00	453.49	249.52	1.50	180.00	-254.57	
6	7900.77	0.00	0.00	7870.40	453.49	249.52	0.00	0.00	-254.57	
7	8814.56	91.38	269.36	8443.19	446.95	-337.19	10.00	269.36	332.18	
8	10983.01	91.38	269.36	8391.00	422.81	-2504.88	0.00	0.00	2500.00	
9	10994.27	91.60	269.36	8390.71	422.68	-2516.14	2.00	0.03	2511.26	
10	13483.99	91.60	269.36	8321.00	394.97	-5004.72	0.00	0.00	5000.00	
11	18469.75	91.60	269.36	8181.41	339.47	-9988.22	0.00	0.00	9983.81	
12	18559.80	91.60	269.36	8178.89	338.47	-10078.23	0.00	0.00	10073.82	

DESIGN TARGET DETAILS							
Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
00-EON(K9SC-133H)	6500.00	453.49	249.52	608549.79	590754.46	32.67284582	-104.17273387
01-FTP(K9SC-133H)	8451.00	452.93	199.52	608549.23	590704.46	32.67284449	-104.17289637
02-0VS(K9SC-133H)	8451.00	450.65	-5.03	608546.95	590499.91	32.67283907	-104.17356114
03-2500VS(K9SC-133H)	8391.00	422.81	-2504.88	608519.11	588000.06	32.67277263	-104.18168547
04-5000VS(K9SC-133H)	8321.00	394.97	-5004.72	608491.27	585500.22	32.67270566	-104.18980976
05-LTP(K9SC-133H)	8181.41	339.38	-9988.22	608435.68	580516.72	32.67257034	-104.20600572
06-PBHL(K9SC-133H)	8178.89	338.46	-10078.23	608434.76	580426.71	32.67256811	-104.20629824

