B SUNDRY Do not use the abandoned we SUBMIT IN 1. Type of Well ⊠ Oil Well □ Gas Well □ Ott 2. Name of Operator DJR OPERATING LLC 3a. Address 1 ROAD 3263 AZTEC, NM 87410 4. Location of Well (Footage, Sec., 7) Sec 31 T23N R7W NWSW 19 36.181496 N Lat, 107.622065	OMB Expires: 5. Lease Serial No. NMNM6681 6. If Indian, Allottee EASTERN NA 7. If Unit or CA/Ag NMNM135229 8. Well Name and N NORTH ALAMI 9. API Well No. 30-043-21338 10. Field and Pool of BASIN MANC 11. County or Parisi SANDOVAL C	NMNM6681 6. If Indian, Allottee or Tribe Name EASTERN NAVAJO 7. If Unit or CA/Agreement, Name and/or No. NMNM135229A 8. Well Name and No. NORTH ALAMITO UNIT 334H					
12. CHECK THE A	PPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION						
Attach the Bond under which the wo following completion of the involved	ally or recomplete horizontally, ork will be performed or provide d operations. If the operation re bandonment Notices must be fil	Deepen Hydraulic Fracturing New Construction Plug and Abandon Plug Back the Bond No. on file with BLM/BIA subsurface locations and measu the Bond No. on file with BLM/BIA sults in a multiple completion or recc led only after all requirements, include	red and true vertical depths of all per A. Required subsequent reports must completion in a new interval, a Form 3	tinent markers and zones. be filed within 30 days 160-4 must be filed once			
Surface Casing & Cement (Co 3/5/20: MIRU. Drill 12.25 inch Float collar at 332 ft. Cement Type I-II cement with 20% Fly	hole to 359 ft. Run 11 jts with 50% excess, pump 1 Ash at 14.5 ppg, 1.61 yie	g set depth) 9.625 inch 36# J55 STC casi 10 bbls FW spacer, 31 bbls (10 eld. Drop plug, displace with 2 Check floats. Floats held. RD	09 sx) 5 bbls FW.				
Surface Casing & Cement (Cd 3/5/20: MIRU. Drill 12.25 inch Float collar at 332 ft. Cement Type I-II cement with 20% Fly Bump plug at 250 psi, 10 bbls 14. I hereby certify that the foregoing is	hole to 359 ft. Run 11 jts with 50% excess, pump 1 / Ash at 14.5 ppg, 1.61 yie good cement to surface. s good cement to surface.	9.625 inch 36# J55 STC casin 10 bbls FW spacer, 31 bbls (10 ald. Drop plug, displace with 2 Check floats. Floats held. RD 506928 verified by the BLM Wel PERATING LLC, sent to the Farr cessing by JOHN HOFFMAN on	09 sx) 5 bbls FW. MO Il Information System mington				
Surface Casing & Cement (Cd 3/5/20: MIRU. Drill 12.25 inch Float collar at 332 ft. Cement Type I-II cement with 20% Fly Bump plug at 250 psi, 10 bbls 14. I hereby certify that the foregoing is Name(Printed/Typed) SHAW-M.	s true and correct. Electronic Submission # For DJR OF Electronic Submission # For DJR OF	9.625 inch 36# J55 STC casin 10 bbls FW spacer, 31 bbls (10 ald. Drop plug, displace with 2 Check floats. Floats held. RD 506928 verified by the BLM Wel PERATING LLC, sent to the Farr cessing by JOHN HOFFMAN on	09 sx) 5 bbls FW. MO Il Information System mington 103/12/2020 (20JH0151SE) ATORY SPECIALIST				
Surface Casing & Cement (Cd 3/5/20: MIRU. Drill 12.25 inch Float collar at 332 ft. Cement Type I-II cement with 20% Fly Bump plug at 250 psi, 10 bbls 14. I hereby certify that the foregoing is Name(Printed/Typed) SHAW-M.	s true and correct. Electronic Submission # For DJR OF ARIE FORD Submission)	9.625 inch 36# J55 STC casin 10 bbls FW spacer, 31 bbls (10 ald. Drop plug, displace with 2 Check floats. Floats held. RD ERATING LLC, sent to the Farr cessing by JOHN HOFFMAN on Title REGUL	09 sx) 5 bbls FW. MO Il Information System mington 03/12/2020 (20JH0151SE) ATORY SPECIALIST				
Surface Casing & Cement (Cd 3/5/20: MIRU. Drill 12.25 inch Float collar at 332 ft. Cement Type I-II cement with 20% Fly Bump plug at 250 psi, 10 bbls 14. I hereby certify that the foregoing is Name(Printed/Typed) SHAW-M.	s true and correct. Electronic Submission # For DJR OF Mail FORD Submission) THIS SPACE FO ELED Electronic fits notice does uitable title to those rights in the	9.625 inch 36# J55 STC casis 10 bbls FW spacer, 31 bbls (11 ald. Drop plug, displace with 2: Check floats. Floats held. RD 506928 verified by the BLM Well 506928 verified by the BLM Well 50692	09 sx) 5 bbls FW. MO Il Information System mington 03/12/2020 (20JH0151SE) ATORY SPECIALIST 020 OFFICE USE FFMAN UM ENGINEER	Date 03/12/202			

District I 1625 N. French Dr., Hobbs, NM 88240

District II

District IV

Phone:(575) 393-6161 Fax:(575) 393-0720

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

District III 1000 Rio Brazos Rd., Aztec, NM 87410 CONDITIONS

Action 16966

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS OF APPROVAL

Operator: DJR OPERATING, LLC	1 Road 3263	Aztec, NM87410		OGRID: 371838	Action Number: 16966	Action Type: C-103N
OCD Reviewer			Co	ondition		
ksimmons			No	one		