

Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM
 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30 025 40178
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator Primero Operating, Inc.		6. State Oil & Gas Lease No.
3. Address of Operator PO Box 1433, Roswell, NM 88202-1433		7. Lease Name or Unit Agreement Name Collins Heirs
4. Well Location Unit Letter <u>K</u> : <u>1650</u> feet from the <u>S</u> line and <u>1700</u> feet from the <u>W</u> line Section <u>4</u> Township <u>20S</u> Range <u>38E</u> NMPM <u>Lea</u> County		8. Well Number <u>1</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4258 GL		9. OGRID Number 018100
		10. Pool name or Wildcat Drinkard Tubb Paddock-Binebry

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

This well was plugged as follows:

12/7 to 18/20: Wash and ream scale and sand to old CIBP

12/21/20: RU Wireline and dump 35' of class C cement on top of CIPP @ 7190' and perforate 1618' Load casing and attempt to squeeze into perforations, pump 500 psi and held steady. Perforate 90' RD Wireline

12/23/20: Set CIBP @ 5923' and dump 35' class H cement on top.

12/28/20: RIH and tag @ 5885'. Circulate hole with 25 sx/100 bbls plug mud. Pull up to 5088' and pump 35 sx class C cement. Pull up and pump 35 sx class C @ 2871'. Pull up and pump 35 sx class C @ 1633'. WOC 4 hrs and tag @ 1405'. POH. Pump 21 sx cement in and out of 5 1/2" casing.

12/30/20: ND BOP, RDMO Pulling Unit.

1/15/21: Dug out cellar and hauled off contaminated soil. Cut off casing and welded plate and installed D.H. Marker.

Spud Date:

11/4/2011


Rig Release Date:

11/29/2011

See attached wellbore diagram and pictures. The location will be cleaned and remediated to NMOCD standards.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE

President

DATE

1/15/2021

Type or print name

Phelps White

E-mail address:


pwiv@zianet.com

PHONE:

575 626 7660

For State Use Only

APPROVED BY:



TITLE Compliance Officer A

DATE 3/16/21

Conditions of Approval (if any):



WELL BORE DIAGRAM

Plugs

21 sx Class C Down 5 1/2
and around 8 5/8"
Surface to 90'
Squeeze Perfs 90'

35 sx Class C @ 1633'
Tag 1405' to 1633'
Squeeze Perfs @ 1618'
Attempt to Squeeze perfs
500 psi, no squeeze

35 sx Class C @ 2871'
2518-2871'

35 sx Class C @ 5088'
4735-5088

CIBP @ 5923 + 35' Class H Cement
Tag @ 5885-5923

35' of cement on top of CIBP

Collins Heirs #1 11/17/2020
42-025-40141

8 5/8" 24# J-55 @ 1568'

Lead 533 sx 35:65:4%gel,5%Salt,.13#cf,5#sms,5%mpa-5
Tail 200 sx C+2%CaCl
Circulate 200 sx (77 bbls) to pit, Plug down 3:17, 11/6/11

LOG TOPS	Depth
Rustler	1572
Yates	2821
Seven Riv.	3080
Queen	3631
Grayburg	4050
SanAndres	4194
Glorieta	4734
Blaine	5950
Tubb	6488
Drinkard	6638
Abo	7077

DV Tool @ 5011'

Second Stage

Lead: 900 sx 35:65:6 POZ:C:Gel+5%salt+.13lb/SX CF+.45%FL52

Tail: 300 sx 50:50:2 POZ:C:Gel+5%salt+.13lb/sx CF+.45% FL

Plug Down 1:21 am 11/28/11, Circulate 107 sx

Perforate: Blaine; 5976 to 6180'

Perforate: Tubb; 6347 to 6720'

Perforate: Drinkard; 6960-7008

CIBP @ 7190' 4/2012

Perforations Abo: 7238 to 7342

Perforations Abo: 7422-7586

PBTD @ 7644

5 1/2" 17# L80 set @ 7689'

900 sx 35:65:6 POZ:C:Gel+5%salt+.13lb/SX CF+.45%FL52

Tail: 300 sx 50:50:2 POZ:C:Gel+5%salt+.13lb/sx CF+.45% FL

Plug Down 8:46 11/28/11, Circulate 55 sx cement

TD 7700', 12/26/11

PRIMERO OPERATING, INC.

PO Box 1433, Roswell, NM 88202-1433
575 622 1001

Attachement to C-103 Subsequent Report of Plugging
Collins Heirs #1 API#30-025-40178



Wellhead Cut off, cement to Surface both strings



Dry Hole Marker Installed



WELL BORE DIAGRAM

Plugs

21 sx Class C Down 5 1/2
and around 8 5/8"
Surface to 90'
Squeeze Perfs 90'

35 sx Class C @ 1633'
Tag 1405' to 1633'
Squeeze Perfs @ 1618'
Attempt to Squeeze perfs
500 psi, no squeeze

35 sx Class C @ 2871'
2518-2871'

35 sx Class C @ 5088'
4735-5088

CIBP @ 5923 + 35' Class H Cement
Tag @ 5885-5923

35' of cement on top of CIBP

Collins Heirs #1 11/17/2020
42-025-40141

8 5/8" 24# J-55 @ 1568'

Lead 533 sx 35:65:4%gel,5%Salt,.13#cf,5#sms,5%mpa-5
Tail 200 sx C+2%CaCl
Circulate 200 sx (77 bbls) to pit, Plug down 3:17, 11/6/11

LOG TOPS	Depth
Rustler	1572
Yates	2821
Seven Riv.	3080
Queen	3631
Grayburg	4050
SanAndres	4194
Glorieta	4734
Blaine	5950
Tubb	6488
Drinkard	6638
Abo	7077

DV Tool @ 5011'

Second Stage

Lead: 900 sx 35:65:6 POZ:C:Gel+5%salt+.13lb/SX CF+.45%FL52

Tail: 300 sx 50:50:2 POZ:C:Gel+5%salt+.13lb/sx CF+.45% FL

Plug Down 1:21 am 11/28/11, Circulate 107 sx

Perforate: Blaine; 5976 to 6180'

Perforate: Tubb; 6347 to 6720'

Perforate: Drinkard; 6960-7008

CIBP @ 7190' 4/2012

Perforations Abo: 7238 to 7342

Perforations Abo: 7422-7586

PBTD @ 7644

5 1/2" 17# L80 set @ 7689'

900 sx 35:65:6 POZ:C:Gel+5%salt+.13lb/SX CF+.45%FL52

Tail: 300 sx 50:50:2 POZ:C:Gel+5%salt+.13lb/sx CF+.45% FL

Plug Down 8:46 11/28/11, Circulate 55 sx cement

TD 7700', 12/26/11



WELL BORE DIAGRAM

Plugs

21 sx Class C Down 5 1/2
and around 8 5/8"
Surface to 90'
Squeeze Perfs 90'

35 sx Class C @ 1633'
Tag 1405' to 1633'
Squeeze Perfs @ 1618'
Attempt to Squeeze perfs
500 psi, no squeeze

35 sx Class C @ 2871'
2518-2871'

35 sx Class C @ 5088'
4735-5088

CIBP @ 5923 + 35' Class H Cement
Tag @ 5885-5923

35' of cement on top of CIBP

Collins Heirs #1 11/17/2020
42-025-40141

8 5/8" 24# J-55 @ 1568'

Lead 533 sx 35:65:4%gel,5%Salt,.13#cf,5#sms,5%mpa-5
Tail 200 sx C+2%CaCl
Circulate 200 sx (77 bbls) to pit, Plug down 3:17, 11/6/11

LOG TOPS	Depth
Rustler	1572
Yates	2821
Seven Riv.	3080
Queen	3631
Grayburg	4050
SanAndres	4194
Glorieta	4734
Blaine	5950
Tubb	6488
Drinkard	6638
Abo	7077

DV Tool @ 5011'

Second Stage

Lead: 900 sx 35:65:6 POZ:C:Gel+5%salt+.13lb/SX CF+.45%FL52

Tail: 300 sx 50:50:2 POZ:C:Gel+5%salt+.13lb/sx CF+.45% FL

Plug Down 1:21 am 11/28/11, Circulate 107 sx

Perforate: Blaine; 5976 to 6180'

Perforate: Tubb; 6347 to 6720'

Perforate: Drinkard; 6960-7008

CIBP @ 7190' 4/2012

Perforations Abo: 7238 to 7342

Perforations Abo: 7422-7586

PBTD @ 7644

5 1/2" 17# L80 set @ 7689'

900 sx 35:65:6 POZ:C:Gel+5%salt+.13lb/SX CF+.45%FL52

Tail: 300 sx 50:50:2 POZ:C:Gel+5%salt+.13lb/sx CF+.45% FL

Plug Down 8:46 11/28/11, Circulate 55 sx cement

TD 7700', 12/26/11

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

COMMENTS

Action 14843

COMMENTS

Operator: PRIMERO OPERATING INC P.O. Box 1433 Roswell, NM88201			OGRID: 18100	Action Number: 14843	Action Type: C-103P
Created By	Comment		Comment Date		
plmartinez	DATA ENTRY PM		03/17/2021		

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 14843

CONDITIONS OF APPROVAL

Operator:	PRIMERO OPERATING INC	P.O. Box 1433	Roswell, NM88201	OGRID:	18100	Action Number:	14843	Action Type:	C-103P
OCD Reviewer	Condition								
kfortner	None								