

Submit 1 Copy To Appropriate District Office  
 District I – (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II – (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III – (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV – (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

Form C-103  
 Revised July 18, 2013

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		WELL API NO. 30-041-10411
2. Name of Operator Ridgeway Arizona Operating Company		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input type="checkbox"/>
3. Address of Operator 575 N Dairy Ashford Rd, EC II Suite 210, Houston, TX 77079		6. State Oil & Gas Lease No.
4. Well Location Unit Letter <u>  </u> P <u>  </u> : <u>  </u> 660 <u>  </u> feet from the <u>  </u> South <u>  </u> line and <u>  </u> 660 <u>  </u> feet from the <u>  </u> East <u>  </u> line Section <u>  </u> 28 <u>  </u> Township <u>  </u> 07S <u>  </u> Range <u>  </u> 33E <u>  </u> NMPM <u>  </u> County <u>  </u> Roosevelt		7. Lease Name or Unit Agreement Name Farrell Federal
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		8. Well Number <u>  </u> 6
9. OGRID Number <u>  </u> 164557		10. Pool name or Wildcat

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ **PLUG AND ABANDON** ☒  
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
 DOWNHOLE COMMINGLE ☐  
 CLOSED-LOOP SYSTEM ☐  
 OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
 COMMENCE DRILLING OPNS. ☐ P AND A ☐  
 CASING/CEMENT JOB ☐  
 OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Approved BLM sundry attached including procedure and WBS

**SUBJECT TO LIKE  
 APPROVAL BY BLM**

**See Attached  
 Conditions of Approval**

*K 7*

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William Boyd TITLE Land & Regulatory Mgr DATE 3/30/2021

Type or print name William Boyd E-mail address: wboyd@pedevco.com PHONE: 713-574-7912

**For State Use Only**

APPROVED BY: Kerry Fortner TITLE Compliance Officer A DATE 5/6/21

Conditions of Approval (if any)

Well Name: FARRELL FEDERAL	Well Location: T7S / R33E / SEC 28 / SESE /	County or Parish/State: ROOSEVELT / NM
Well Number: 6	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM83197	Unit or CA Name:	Unit or CA Number:
US Well Number: 300411041100S1	Well Status: Oil Well Shut In	Operator: RIDGEWAY ARIZONA OIL CORPORATION

Notice of Intent

Type of Submission: Notice of Intent	Type of Action Plug and Abandonment
Date Sundry Submitted: 03/16/2021	Time Sundry Submitted: 02:10
Date proposed operation will begin: 05/04/2021	

**Procedure Description:** 1) SET 4-1/2" CIBP @ 4,220'; CIRC. WELL W/ M.L.F.; PRES. TEST 4-1/2" CSG. X CIBP TO 500# X HOLD; PUMP 25 SXS. CMT. @ 4,220'-3,970'. 2) PERF. X ATTEMPT TO SQZ. 50 SXS. CMT. @ 3,060'-2,930' (T/QN.); WOC X TAG TOC. 3) PERF. X ATTEMPT TO SQZ. 45 SXS. CMT. @ 2,364'-2,244' (T/YATES, B/SALT); WOC X TAG TOC. 4) PERF. X ATTEMPT TO SQZ. 60 SXS. CMT. @ 1,950'-1,800' (T/SALT); WOC X TAG TOC. 5) PERF. X CIRC. TO SURF., FILLING ALL ANNULI, 140 SXS. CMT. @ 442'-3' (8-5/8" CSG.SHOE). 6) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; VERIFY CMT. TO SURF. ON ALL ANNULI; WELD ON STEEL PLATE TO CSGS. X INSTALL BELOW GROUND DRY HOLE MARKER. DURING THIS PROCEDURE WE PLAN TO USE A CLOSED-LOOP SYSTEM W/ A STEEL TANK AND HAUL THE CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RULE 19.15.17.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Ridgeway\_Arizona\_Ferrell\_Fed\_006\_20210316141028.pdf

<b>Well Name:</b> FARRELL FEDERAL	<b>Well Location:</b> T7S / R33E / SEC 28 / SESE /	<b>County or Parish/State:</b> ROOSEVELT / NM
<b>Well Number:</b> 6	<b>Type of Well:</b> OIL WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM83197	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b>
<b>US Well Number:</b> 300411041100S1	<b>Well Status:</b> Oil Well Shut In	<b>Operator:</b> RIDGEWAY ARIZONA OIL CORPORATION

Conditions of Approval

Specialist Review

Conditions\_of\_Approval\_20210317085902.pdf  
General\_Conditions\_of\_Approval\_20210317085903.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

**Operator Electronic Signature:** EYLER  
**Signed on:** MAR 16, 2021 02:10 PM  
**Name:** RIDGEWAY ARIZONA OIL CORPORATION  
**Title:** Agent  
**Street Address:** 575 N. DAIRY ASHFORD, SUITE 210  
**City:** Houston **State:** TX  
**Phone:** (713) 321-1768  
**Email address:**

Field Representative

**Representative Name:**  
**Street Address:**  
**City:** **State:** **Zip:**  
**Phone:**  
**Email address:**

BLM Point of Contact

**BLM POC Name:** JENNIFER SANCHEZ  
**BLM POC Phone:** 5756270237  
**Disposition:** Approved  
**Signature:** Jennifer Sanchez  
**BLM POC Title:** Petroleum Engineer  
**BLM POC Email Address:** j1sanchez@blm.gov  
**Disposition Date:** 03/17/2021

**Farrell Federal 6  
30-041-10411  
Ridgeway Arizona Oil Corp  
March 17, 2021  
Conditions of Approval**

- 1. Operator shall place CIBP at 4,220' (50'-100' above top most perf) and place 25 sx of Class C cement on top as proposed. WOC and TAG.**
- 2. Operator shall perf and squeeze at 3,060' as proposed. Operator shall place a balanced Class C cement plug from 3,060'-2,930' as proposed. WOC and TAG.**
- 3. Operator shall perf and squeeze at 2,364'. Operator shall place a balanced Class C cement plug from 2,364'-2,244' to seal the Yates Formation and the bottom of the Salt. WOC and TAG.**
- 4. Operator shall perf and squeeze at 1,950'. Operator shall place a balanced Class C cement plug from 1,950'-1,800' to seal the top of the Salt. WOC and TAG as proposed.**
- 5. Operator shall perf and squeeze at 442' as proposed. Operator shall place a balanced Class C cement plug from 442' to surface to seal the 8-5/8" casing shoe.**
- 6. See Attached for general plugging stipulations.**

**JAM 03172021**

Released to Imaging: 5/7/2021 10:21:37 AM



Well Name: Farrell Federal 06

Well API #: 30-041-10411

County, State: Roosevelt County, NM

Date:

## Final Installation

Installation	Surface Casing
	OD: 8-5/8"
	Weight: 24
	Grade:
	Top: 0
	Bottom: 392
	Intermediate Csg.
	OD:
	Weight:
	Grade:
	Top:
	Bottom:
	Production Casing
	OD: 4.5
	Weight: 9.5
	Grade:
	Top: 0
M.H.F.	Bottom: 4462
	TOC
	800 sacks
	DV Tool
M.H.F.	
M.H.F.	Liner Top
	N/A
	KOP
	N/A
	Top Perf
M.H.F.	4271
	Bottom Perf
	4406
	TD
	4462
M.H.F.	PBTD
	4428
	TVD
	4428

T/SALT ~ 1,875'  
T/YATES ~ 2,304'  
T/QN. ~ 2,995'  
T/S.A. ~ 3,463'

PERF. X CIRC. 140 SXS. @ 442'-3'

PERF. X SQZ. 60 SXS. @ 1,950'-1,800'-TAG

PERF. X SQZ. 45 SXS. @ 2,364'-2,244'-TAG

PERF. X SQZ. 50 SXS. @ 3,060'-2,930'-TAG

Pump 25 SXS. @ 4,220'-3,970'

SET 4-1/2" CIBP @ 4,220'

DAE 03/09/21

**BUREAU OF LAND MANAGEMENT**  
**Roswell Field Office**  
**2909 W. Second Street**  
**Roswell, New Mexico 88201**  
**575-627-0272**

**General Requirements for Plug Backs**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from this approval.

**If you are unable to plug back the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged back. Failure to do so will result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plug back operations. Call 575-627-0205.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement.

**Before pumping cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either **Neat Class "C"**, for up to 7,500 feet of depth or **Neat Class "H"**, for deeper than 7,500 feet plugs.

6. **Subsequent Plug back Reporting:** Within 30 days after plug back work is completed, file one original and three copies of the Subsequent Report, Form 3160-5 to BLM. The report should give in detail the manner in which the plug back work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date work was completed.**

7. **Trash:** All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

**CONDITIONS OF APPROVAL  
FOR PLUGGING AND ABANDONMENT  
OCD - Southern District**

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office I (Hobbs) at (575)-263-6633 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down.

**Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal - commercial or private- shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water will not be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.
16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).



19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
- A) Fusselman
  - B) Devonian
  - C) Morrow
  - D) Wolfcamp
  - E) Bone Springs
  - F) Delaware
  - G) Any salt sections
  - H) Abo
  - I) Glorieta
  - J) Yates.
  - K) Potash---(In the R-111-P Area (Potash Mine Area),

A solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, woe 4 hours and tag, this plug will be SO' below the bottom and 50' above the top of the Formation.

21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, woe and tagged. These plugs will be set SO' below formation bottom to 50' above formation top inside the casing.

### **DRY HOLE MARKER REQ.UIRMENTS**

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least 1/4" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name
2. Lease and Well Number
3. API Number
4. Unit letter
5. Quarter Section (feet from the North, South, East or West)
6. Section, Township and Range
7. Plugging Date
8. County

### **SPECIAL CASES -----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS**

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

### **SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION**

Released to Imaging: 5/7/2021 10:21:37 AM

Well Name: Farrell Federal 06

Well API #: 30-041-10411

County, State: Roosevelt County, NM

Date:

## Final Installation

Installation	Surface Casing
	OD: 8-5/8"
	Weight: 24
	Grade:
	Top: 0
	Bottom: 392
	Intermediate Csg.
	OD:
	Weight:
	Grade:
	Top:
	Bottom:
	Production Casing
	OD: 4.5
	Weight: 9.5
	Grade:
	Top: 0
M.H.F.	Bottom: 4462
	TOC
	800 sacks
	DV Tool
M.H.F.	
M.H.F.	Liner Top
	N/A
	KOP
	N/A
	Top Perf
	4271
	Bottom Perf
	4406
	TD
	4462
M.H.F.	PBTD
	4428
	TVD
	4428

T/SALT ~ 1,875'  
 T/YATES ~ 2,304'  
 T/QN. ~ 2,995'  
 T/S.A. ~ 3,463'

PERF. X CIRC. 140 SXS. @ 442'-3'

PERF. X SQZ. 60 SXS. @ 1,950'-1,800'-TAG

PERF. X SQZ. 45 SXS. @ 2,364'-2,244'-TAG

PERF. X SQZ. 50 SXS. @ 3,060'-2,930'-TAG

Pump 25 SXS. @ 4,220'-3,970'

SET 4-1/2" CIBP @ 4,220'

DAE 03/09/21

**BUREAU OF LAND MANAGEMENT**  
**Roswell Field Office**  
**2909 W. Second Street**  
**Roswell, New Mexico 88201**  
**575-627-0272**

**General Requirements for Plug Backs**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from this approval.

**If you are unable to plug back the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged back. Failure to do so will result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plug back operations. Call 575-627-0205.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement.

**Before pumping cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either **Neat Class "C"**, for up to 7,500 feet of depth or **Neat Class "H"**, for deeper than 7,500 feet plugs.

6. **Subsequent Plug back Reporting:** Within 30 days after plug back work is completed, file one original and three copies of the Subsequent Report, Form 3160-5 to BLM. The report should give in detail the manner in which the plug back work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date work was completed.**

7. **Trash:** All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

**Farrell Federal 6  
30-041-10411  
Ridgeway Arizona Oil Corp  
March 17, 2021  
Conditions of Approval**

- 1. Operator shall place CIBP at 4,220' (50'-100' above top most perf) and place 25 sx of Class C cement on top as proposed. WOC and TAG.**
- 2. Operator shall perf and squeeze at 3,060' as proposed. Operator shall place a balanced Class C cement plug from 3,060'-2,930' as proposed. WOC and TAG.**
- 3. Operator shall perf and squeeze at 2,364'. Operator shall place a balanced Class C cement plug from 2,364'-2,244' to seal the Yates Formation and the bottom of the Salt. WOC and TAG.**
- 4. Operator shall perf and squeeze at 1,950'. Operator shall place a balanced Class C cement plug from 1,950'-1,800' to seal the top of the Salt. WOC and TAG as proposed.**
- 5. Operator shall perf and squeeze at 442' as proposed. Operator shall place a balanced Class C cement plug from 442' to surface to seal the 8-5/8" casing shoe.**
- 6. See Attached for general plugging stipulations.**

**JAM 03172021**



**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

COMMENTS

Action 22361

**COMMENTS**

Operator:	OGRID:	Action Number:	Action Type:
RIDGEWAY ARIZONA OIL CORP. Suite 210 Houston, TX77079	164557	22361	C-103F
575 N. Dairy Ashford			

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM	05/07/2021

**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 22361

**CONDITIONS OF APPROVAL**

Operator:		OGRID:	Action Number:	Action Type:
RIDGEWAY ARIZONA OIL CORP.	575 N. Dairy Ashford	164557	22361	C-103F
Suite 210	Houston, TX77079			

OCD Reviewer	Condition
kfortner	See attached conditions of approval