BGT 2

District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 *Page 1 of 17* Form C-144

Form C-144 Revised April 3, 2017

For temporary pits, below-grade tanks, and multi-well fluid management pits, submit to the appropriate NMOCD District Office. For permanent pits submit to the Santa Fe Environmental Bureau office and provide a copy to the appropriate NMOCD District Office.

<u>Pit, Below-Grade Tank, or</u> Proposed Alternative Method Permit or Closure Plan Application

Type of action: Below grade tank registration

Permit of a pit or proposed alternative method

Closure of a pit, below-grade tank, or proposed alternative method

] Modification to an existing permit/or registration

Closure plan only submitted for an existing permitted or non-permitted pit, below-grade tank,

or proposed alternative method

Instructions: Please submit one application (Form C-144) per individual pit, below-grade tank or alternative request

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.

Operator: Hilcorp Energy Company OGRID #: 372171		
Address: 382 Road 3100 Aztec, NM 87410		
Facility or well name: Fullerton Federal Com 12 – Pipeline Pit #2		
API Number: 16524		
U/L or Qtr/Qtr Section11 Township Range11W County: San Juan		
Center of Proposed Design: Latitude 36.594035 Longitude -107.979160 NAD83		
Surface Owner: 🛛 Federal 🗌 State 🗌 Private 🗋 Tribal Trust or Indian Allotment		
2.		
<u>Pit</u> : Subsection F, G or J of 19.15.17.11 NMAC		
Temporary: Drilling Workover		
Permanent Emergency Cavitation P&A Multi-Well Fluid Management Low Chloride Drilling Fluid yes no		
Lined Unlined Liner type: Thicknessmil LLDPE HDPE PVC Other		
String-Reinforced		
Liner Seams: 🗌 Welded 🗋 Factory 🗋 Other Volume:bbl Dimensions: L x W x D		
3		
Below-grade tank: Subsection I of 19.15.17.11 NMAC		
Volume:bbl Type of fluid:Produced Water		
Tank Construction material:Metal		
Secondary containment with leak detection 🛛 Visible sidewalls, liner, 6-inch lift and automatic overflow shut-off		
□ Visible sidewalls and liner □ Visible sidewalls only □ Other		
Liner type: Thickness45mil		
4		
Alternative Method:		
Submittal of an exception request is required. Exceptions must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.		
5.		
Fencing: Subsection D of 19.15.17.11 NMAC (Applies to permanent pits, temporary pits, and below-grade tanks)		
Chain link, six feet in height, two strands of barbed wire at top (<i>Required if located within 1000 feet of a permanent residence, school, hospital, institution or church</i>)		
Four foot height, four strands of barbed wire evenly spaced between one and four feet		
Alternate. Please specify		

Netting:	Subsection E of 19.15.17.1	1 NMAC (Applies to	permanent pits and	permanent open to	p tanks)

Screen Netting Other_

Monthly inspections (If netting or screening is not physically feasible)

Signs: Subsection C of 19.15.17.11 NMAC

12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers

Signed in compliance with 19.15.16.8 NMAC

Variances and Exceptions:

Justifications and/or demonstrations of equivalency are required. Please refer to 19.15.17 NMAC for guidance.

Please check a box if one or more of the following is requested, if not leave blank:

Variance(s): Requests must be submitted to the appropriate division district for consideration of approval.

Exception(s): Requests must be submitted to the Santa Fe Environmental Bureau office for consideration of approval.

9. Siting Criteria (regarding permitting): 19.15.17.10 NMAC Instructions: The applicant must demonstrate compliance for each siting criteria below in the application. Recommendations of acceptable source material are provided below. Siting criteria does not apply to drying pads or above-grade tanks.		
General siting		
Ground water is less than 25 feet below the bottom of a low chloride temporary pit or below-grade tank	☐ Yes ☐ No ⊠ NA	
Ground water is less than 50 feet below the bottom of a Temporary pit, permanent pit, or Multi-Well Fluid Management pit. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ⊠ NA	
 Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance adopted pursuant to NMSA 1978, Section 3-27-3, as amended. (Does not apply to below grade tanks) Written confirmation or verification from the municipality; Written approval obtained from the municipality 	🗌 Yes 🗌 No	
 Within the area overlying a subsurface mine. (Does not apply to below grade tanks) Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No	
 Within an unstable area. (Does not apply to below grade tanks) Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No	
 Within a 100-year floodplain. (Does not apply to below grade tanks) FEMA map 	🗌 Yes 🗌 No	
Below Grade Tanks		
 Within 100 feet of a continuously flowing watercourse, significant watercourse, lake bed, sinkhole, wetland or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🛛 No	
 Within 200 horizontal feet of a spring or a fresh water well used for public or livestock consumption;. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🛛 No	
Temporary Pit using Low Chloride Drilling Fluid (maximum chloride content 15,000 mg/liter)		
 Within 100 feet of a continuously flowing watercourse, or any other significant watercourse or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). (Applies to low chloride temporary pits.) Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
Within 300 feet from a occupied permanent residence, school, hospital, institution, or church in existence at the time of initial application Visual inspection (certification) of the proposed site; Aerial photo; Satellite image	🗌 Yes 🗌 No	

Within 200 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 300feet of any other fresh water well or spring, in existence at the time of the initial application. NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site

Received by OCD: 4/15/2021 1:44:37 PM	Page 3 of 1	
 Within 100 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
Temporary Pit Non-low chloride drilling fluid		
 Within 300 feet of a continuously flowing watercourse, or any other significant watercourse, or within 200 feet of any lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No	
 Within 500 horizontal feet of a spring or a private, domestic fresh water well used by less than five households for domestic or stock watering purposes, or 1000 feet of any other fresh water well or spring, in the existence at the time of the initial application; NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
 Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
Permanent Pit or Multi-Well Fluid Management Pit		
Within 300 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, or lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark).		
- Topographic map; Visual inspection (certification) of the proposed site	Yes No	
 Within 1000 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No	
Within 500 horizontal feet of a spring or a fresh water well used for domestic or stock watering purposes, in existence at the time of initial application.		
- NM Office of the State Engineer - iWATERS database search; Visual inspection (certification) of the proposed site	Yes No	
 Within 500 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No	
10. Temporary Pits, Emergency Pits, and Below-grade Tanks Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. Hydrogeologic Report (Below-grade Tanks) - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.9 NMAC Hydrogeologic Data (Temporary and Emergency Pits) - based upon the requirements of Paragraph (2) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Design Plan - based upon the appropriate requirements of 19.15.17.10 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC Previously Approved Design (attach copy of design) API Number: or Permit Number: 		
11. Multi Wall Fluid Management Pit Checklist: Subjection R of 10 15 17 0 NMAC		
Multi-Well Fluid Management Pit Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the doc attached. Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC A List of wells with approved application for permit to drill associated with the pit. Closure Plan (Please complete Boxes 14 through 18, if applicable) - based upon the appropriate requirements of Subsection C of 19. and 19.15.17.13 NMAC Hydrogeologic Data - based upon the requirements of Paragraph (4) of Subsection B of 19.15.17.10 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC 		
Previously Approved Design (attach copy of design) API Number: or Permit Number:		

•

^{12.} <u>Permanent Pits Permit Application Checklist</u> : Subsection B of 19.15.17.9 NMAC <i>Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the of</i>	documents are		
 attached. Hydrogeologic Report - based upon the requirements of Paragraph (1) of Subsection B of 19.15.17.9 NMAC Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Climatological Factors Assessment 			
 Certified Engineering Design Plans - based upon the appropriate requirements of 19.15.17.11 NMAC Dike Protection and Structural Integrity Design - based upon the appropriate requirements of 19.15.17.11 NMAC Leak Detection Design - based upon the appropriate requirements of 19.15.17.11 NMAC Liner Specifications and Compatibility Assessment - based upon the appropriate requirements of 19.15.17.11 NMAC Quality Control/Quality Assurance Construction and Installation Plan Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC 			
 Freeboard and Overtopping Prevention Plan - based upon the appropriate requirements of 19.15.17.11 NMAC Nuisance or Hazardous Odors, including H₂S, Prevention Plan Emergency Response Plan Oil Field Waste Stream Characterization 			
 Monitoring and Inspection Plan Erosion Control Plan 			
Closure Plan - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC			
^{13.} <u>Proposed Closure</u> : 19.15.17.13 NMAC Instructions: Please complete the applicable boxes, Boxes 14 through 18, in regards to the proposed closure plan.			
Type: Drilling Workover Emergency Cavitation P&A Permanent Pit Below-grade Tank Multi-well F	luid Management Pit		
Proposed Closure Method: Waste Excavation and Removal Waste Removal (Closed-loop systems only) On-site Closure Method (Only for temporary pits and closed-loop systems) In-place Burial On-site Trench Burial			
Alternative Closure Method			
Waste Excavation and Removal Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure plan. Please indicate, by a check mark in the box, that the documents are attached.			
15. <u>Siting Criteria (regarding on-site closure methods only)</u> : 19.15.17.10 NMAC Instructions: Each siting criteria requires a demonstration of compliance in the closure plan. Recommendations of acceptable sour provided below. Requests regarding changes to certain siting criteria require justifications and/or demonstrations of equivalency. P 19.15.17.10 NMAC for guidance.	rce material are llease refer to		
 Ground water is less than 25 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA		
Ground water is between 25-50 feet below the bottom of the buried waste - NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells	☐ Yes ☐ No ☐ NA		
 Ground water is more than 100 feet below the bottom of the buried waste. NM Office of the State Engineer - iWATERS database search; USGS; Data obtained from nearby wells 	☐ Yes ☐ No ☐ NA		
 Within 100 feet of a continuously flowing watercourse, or 200 feet of any other significant watercourse, lakebed, sinkhole, or playa lake (measured from the ordinary high-water mark). Topographic map; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
 Within 300 feet from a permanent residence, school, hospital, institution, or church in existence at the time of initial application. Visual inspection (certification) of the proposed site; Aerial photo; Satellite image 	🗌 Yes 🗌 No		
 Within 300 horizontal feet of a private, domestic fresh water well or spring used for domestic or stock watering purposes, in existence at the time of initial application. NM Office of the State Engineer - iWATERS database; Visual inspection (certification) of the proposed site 	🗌 Yes 🗌 No		
Written confirmation or verification from the municipality; Written approval obtained from the municipality	Yes No		
Within 300 feet of a wetland. US Fish and Wildlife Wetland Identification map; Topographic map; Visual inspection (certification) of the proposed site	🗌 Yes 🗌 No		
Within incorporated municipal boundaries or within a defined municipal fresh water well field covered under a municipal ordinance			
Form C 144 Oil Conservation Division Page 4 o	f 6		

Received l	by C	CD:	4/15/2	021 1:4	44:37 PM

Received by OCD: 4/15/2021 1:44:37 PM	Page 5 of 1
adopted pursuant to NMSA 1978, Section 3-27-3, as amended. - Written confirmation or verification from the municipality; Written approval obtained from the municipality	🗌 Yes 🗌 No
 Within the area overlying a subsurface mine. Written confirmation or verification or map from the NM EMNRD-Mining and Mineral Division 	🗌 Yes 🗌 No
 Within an unstable area. Engineering measures incorporated into the design; NM Bureau of Geology & Mineral Resources; USGS; NM Geological Society; Topographic map 	🗌 Yes 🗌 No
Within a 100-year floodplain. - FEMA map	Yes No
16. On-Site Closure Plan Checklist: (19.15.17.13 NMAC) Instructions: Each of the following items must be attached to the closure play a check mark in the box, that the documents are attached. Siting Criteria Compliance Demonstrations - based upon the appropriate requirements of 19.15.17.10 NMAC Proof of Surface Owner Notice - based upon the appropriate requirements of Subsection E of 19.15.17.13 NMAC Construction/Design Plan of Burial Trench (if applicable) based upon the appropriate requirements of Subsection K of 19.15.17. Construction/Design Plan of Temporary Pit (for in-place burial of a drying pad) - based upon the appropriate requirements of 19.15.17.13 NMAC Protocols and Procedures - based upon the appropriate requirements of 19.15.17.13 NMAC Confirmation Sampling Plan (if applicable) - based upon the appropriate requirements of 19.15.17.13 NMAC Waste Material Sampling Plan - based upon the appropriate requirements of 19.15.17.13 NMAC Disposal Facility Name and Permit Number (for liquids, drilling fluids and drill cuttings or in case on-site closure standards cann Soil Cover Design - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Re-vegetation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC Site Reclamation Plan - based upon the appropriate requirements of Subsection H of 19.15.17.13 NMAC	11 NMAC 15.17.11 NMAC
 17. Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and beli 	
Name (Print): Title:	
Signature: Date:	
e-mail address: Telephone:	
18. OCD Approval: Permit Application (including closure plan) \bigcirc Closure Plan (only) \bigcirc OCD Conditions (see attachment)	
OCD Representative Signature: Approval Date: July 2	28, 2021
Title: Environmental Specialist OCD Permit Number: BGT 2	
 19. <u>Closure Report (required within 60 days of closure completion)</u>: 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not section of the form until an approved closure plan has been obtained and the closure activities have been completed. 	
20. Closure Method: ⊠ Waste Excavation and Removal □ On-Site Closure Method □ Alternative Closure Method □ Waste Removal (Closed-lo □ If different from approved plan, please explain.	oop systems only)
21. Closure Report Attachment Checklist: Instructions: Each of the following items must be attached to the closure report. Please in mark in the box, that the documents are attached.	

Operator Closure Certification: I hereby certify that the information and attachments submitted with the belief. I also certify that the closure complies with all applicable closure complex with all applicabl			
Name (Print): Kandis Roland	Title:	Operations/Regulatory T	
Signature:Kandís Roland		I	Date: <u>4/15/2021</u>
e-mail address: kroland@hilcorp.com	Telephone:	(505) 324-5149	

Hilcorp Energy Company San Juan Basin: New Mexico Assets Below Grade Tank Closure Report

Lease Name: Fullerton Federal Com 12 – Pipeline Pit #2 **Permit No.:** 16524

In accordance with Rule 19.15.17.13 NMAC, the following information describes the closure of the below-grade tank referenced above. All proper documentation regarding closure activities is being included with the C-144.

General Plan Requirements:

1. Prior to initiating any BGT closure, except in the case of an emergency, HILCORP will notify the surface owner of the intent to close the BGT by certified mail no later than 72 hours or one week before closure and a copy of this notification will be included in the closure report. In the case of an emergency, the surface owner will be notified as soon as practical.

The surface owner was notified by email of the closure process and the notification is attached.

- 2. Notice of closure will be given to the District Division office between 72 hours and one week of the scheduled closure via email or phone. The notification of closure will include the following:
 - a. Operators Name
 - b. Well Name and API Number
 - c. Location

Notification is attached.

3. All liquids will be removed from the BGT following cessation of operation. Produced water will be disposed of at one of HILCORP's approved Salt Water Disposal facilities or at a District Division approved facility.

All recovered liquids were disposed of at an approved SWD facility or an approved District Division facility within 60 days of cessation of operation.

 Solids and sludge's will be shoveled and/or vacuumed out for disposal at one of the District Division approved facilities, depending on the proximity of the BGT site: Envirotech Land Farm (Permit #NM-01-011), JFJ Land Farm % Industrial Ecosystems Inc. (Permit #NM-01-0010B), and Basin Disposal (Permit #NM-01-005).

Any sludge or soil required to be removed to facilitate closure was transported to Envirotech Land Farm (Permit # NM-01-011) and/or JFJ Landfarm % IEI (Permit# NM-01-0010B).

Revised 10/14/2015

5. HILCORP will obtain prior approval from District Division to dispose, recycle, reuse, or reclaim the BGT and provide documentation of the disposition of the BGT in the closure report. Steel materials will be recycled or reused as approved by the District Division. Fiberglass tanks will be empty, cut up or shredded, and EPA cleaned for disposal as solid waste. Liner materials will be cleaned without soils or contaminated material for disposal as solid waste. Fiberglass tanks and liner materials will meet the conditions of 19.15.35 NMAC. Disposal will be at a licensed disposal facility, presently San Juan County Landfill operated by Waste Management under NMED Permit SWM-052426.

The below-grade tank was disposed of in a division-approved manner. The liner was cleaned per 19.15.35.8.C(1)(m) NMAC and disposed of at the San Juan County Regional Landfill located on CR 3100.

6. Any equipment associated with the BGT that is no longer required for some other purpose, following the closure, will be removed.

All on-site equipment associated with the below-grade tank was removed.

- 7. Following removal of the tank and any liner material, HILCORP will test the soils beneath the BGT as follows:
 - a. At a minimum, a five-point composite sample will be taken to include any obvious stained or wet soils or any other evidence of contamination.
 - b. The laboratory sample shall be analyzed for the constituents listed in Table I of 19.15.17.13.

A five point composite sample was taken of the below-grade tank using sampling tools and all samples tested per Table I of 19.15.17.13 and the results are attached.

8. If the District Division and/or HILCORP determine there is a release, HILCORP will comply with 19.15.17.13.C.3b.

A release was not determined for the above referenced well.

9. Upon completion of the tank removal, pursuant to 19.15.17.13.C.3c, if all contaminant concentrations are less than or equal to the parameters listed in Table I of 19.15.17.13 NMAC, the excavation will be backfilled with non-waste earthen material compacted and covered with a minimum of one foot top soil or background thickness whichever is greater and to existing grade. The surface will be re-contoured to match the native grade and to prevent ponding.

The tank removal area passed all requirements of Table I of 19.15.17.13 NMAC and was backfilled with compacted, non-waste containing, earthen material which included at least one foot of suitable material to establish vegetation at the site.

Revised 10/14/2015

10. For those portions of the former BGT area no longer required for production activities, HILCORP will seed the disturbed area the first favorable growing season after the BGT is covered. Seeding will be accomplished via drilling on the contour whenever practical, or by other District Division-approved methods. HILCORP will notify the District Division when reclamation and re-vegetation is complete.

Reclamation of the BGT shall be considered complete when:

- Vegetative cover reflects a life form ratio of +/- 50% of pre disturbance levels.
- Total percent plant cover of at least 70% of pre-disturbance levels (Excluding noxious weeds) OR
- Pursuant to 19.15.17.13.H.5d HILCORP will comply with obligations imposed by other applicable federal or tribal agencies in which there re-vegetation and reclamation requirements provide equal or better protection of fresh water, human health and the environment.

Provision 10 will be accomplished pursuant to 19.15.17.H.5d and notification will be submitted upon completion.

11. For those portions of the former BGT area required for production activities, reseeding will be done at well abandonment, and following the procedure noted above.

The former BGT area is required for production activities and reseeding will be completed upon plug and abandonment, per the procedure noted above.

Closure Report:

All closure activities will include proper documentation and will be submitted to OCD within 60 days of the BGT closure on a Closure Report using District Division Form C-144. The Report will include the following:

- Proof of Closure Notice (surface owner and District Division) (Attached)
- Backfilling & cover installation (See Report)
- Confirmation Sampling Analytical Results (Attached)
- Application Rate & Seeding techniques (See Report)
- Photo Documentation of Reclamation (Attached)

Revised 10/14/2015

Kandis Roland

From:	Kandis Roland
Sent:	Monday, March 15, 2021 9:25 AM
То:	Smith, Cory, EMNRD; 'rjoyner@blm.gov'; Kelly, Jonathan, EMNRD
Cc:	Kandis Roland; Mandi Walker; Roman Lucero; Clara Cardoza; Kurt Hoekstra; Keri Hutchins
Subject:	Fullerton Federal Com 12 (3004524584) Pipeline BGTs - 72 Hour BGT Closure Notification
Attachments:	Fullerton Federal Com 12-Pipeline Pit 1_BGT Registration.pdf; Fullerton Federal Com 12-
	Pipeline Pit 2_BGT Registration.pdf

Subject: 72 Hour BGT Closure Notification

Anticipated Start Date: Wednesday, March 17, 2021 at approximately 9:00 AM.

The subject well has 2 pipeline below-grade tanks that will be permanently removed. The BGT permits are attached. Please contact me at any time if you have any questions or concerns.

Well Name:	Fullerton Federal Com 12 – Pipeline BGT #1 & #2	
API#:	30-045-24584	
Location:	Unit D Section 11, T27N, R11W	
Footages:	990' FNL & 990' FWL	
Operator:	Hilcorp Energy	Surface Owner: BLM
Reason:	INC – Permanently close both BGTs.	

Please forward to anyone that I may have missed.

Thank you,

Kandis Roland HILCORP ENERGY San Juan South Regulatory 505.324.5149 kroland@hilcorp.com District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 State of New Mexico Energy Minerals and Natural Resources Department

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-141 Revised August 24, 2018 Submit to appropriate OCD District office

)

Page 11 of 17

Incident ID	
District RP	
Facility ID	
Application ID	

Release Notification

Responsible Party

Responsible Party Hilcorp Energy Company	OGRID 372171
Contact Name Kandis Roland	Contact Telephone (505) 324-5149
Contact email kroland@hilcorp.com	Incident # (assigned by OCD)
Contact mailing address 382 Road 3100 Aztec NM 87410	

Location of Release Source

Latitude	36.5940	35	Longitude	-107.979160	
			(NAD 83 in decimal a	legrees to 5 decimal places)	
Site Name F	ullerton Fede	eral Com 12 – Pipe	eline Pit #2	Site Type Pipeline	
Date Release Discovered N/A		API# (if applicable)			
Unit Letter	Section	Township	Range	County]
D	11	27N	11W	San Juan	
D	11	27N	11W	San Juan	

Surface Owner: State Federal Tribal Private (Name: _____

Nature and Volume of Release

Materia	l(s) Released (Select all that apply and attach calculations or specific	justification for the volumes provided below)
Crude Oil	Volume Released (bbls)	Volume Recovered (bbls)
Produced Water	Volume Released (bbls)	Volume Recovered (bbls)
	Is the concentration of dissolved chloride in the produced water >10,000 mg/l?	Yes No
Condensate	Volume Released (bbls)	Volume Recovered (bbls)
Natural Gas	Volume Released (Mcf)	Volume Recovered (Mcf)
Other (describe)	Volume/Weight Released (provide units)	Volume/Weight Recovered (provide units)
Cause of Release		

No release was encountered during the BGT Closure.

Received by	OCD: 4/15/2021	1:44:37 PM State	of New Mexico

Page 2

Incident ID	
District RP	
Facility ID	
Application ID	

Was this a major release as defined by 19.15.29.7(A) NMAC?	If YES, for what reason(s) does the responsible party consider this a major release?
🗌 Yes 🖾 No	N/A
If YES, was immediate ne	otice given to the OCD? By whom? To whom? When and by what means (phone, email, etc)?
Not Required	

Initial Response

The responsible party must undertake the following actions immediately unless they could create a safety hazard that would result in injury

The impacted area has been secured to protect human health and the environment.

Released materials have been contained via the use of berms or dikes, absorbent pads, or other containment devices.

All free liquids and recoverable materials have been removed and managed appropriately.

If all the actions described above have not been undertaken, explain why:

The source of the release has been stopped.

Per 19.15.29.8 B. (4) NMAC the responsible party may commence remediation immediately after discovery of a release. If remediation has begun, please attach a narrative of actions to date. If remedial efforts have been successfully completed or if the release occurred within a lined containment area (see 19.15.29.11(A)(5)(a) NMAC), please attach all information needed for closure evaluation.

I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to OCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the OCD does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to groundwater, surface water, human health or the environment. In addition, OCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.

Printed Name: Kandis Ro	bland	Title:	Operations/Regul	atory Technician – Sr.	
Signature:Kandís F	Roland		Da	te:4/15/2021	
email:	kroland@hilcorp.com		Telephone:	(505) 324-5149	
OCD Only					
Received by:		Date:			

Analytical Report Lab Order 2103911

Date Reported:

Hall Environmental Analysis Laboratory, Inc.

	· · · · · · · · · · · · · · · · · · ·					Date Reported.	
CLIENT:	Hilcorp Energy		Cl	ient Sample II	D: BC	T Pipeline S	
Project:	Fullerton Federal Com 12		(Collection Dat	e: 3/1	7/2021 9:05:00 AM	
Lab ID:	2103911-001	Matrix: SOIL		Received Dat	e: 3/1	8/2021 8:00:00 AM	
Analyses		Result	RL	Qual Units	DF	Date Analyzed	Batch
EPA MET	THOD 300.0: ANIONS					Analyst:	ЈМТ
Chloride		ND	60	mg/Kg	20	3/26/2021 10:31:00 AM	58988
EPA MET	THOD 8015M/D: DIESEL RANG	E ORGANICS				Analyst	mb
Diesel R	ange Organics (DRO)	16	9.9	mg/Kg	1	3/21/2021 6:09:41 AM	58838
Motor Oi	I Range Organics (MRO)	170	49	mg/Kg	1	3/21/2021 6:09:41 AM	58838
Surr: I	DNOP	102	70-130	%Rec	1	3/21/2021 6:09:41 AM	58838
EPA MET	THOD 8015D: GASOLINE RANG	GE				Analyst	NSB
Gasoline	e Range Organics (GRO)	ND	4.9	mg/Kg	1	3/23/2021 7:07:22 PM	58833
Surr: I	BFB	94.9	75.3-105	%Rec	1	3/23/2021 7:07:22 PM	58833
EPA MET	THOD 8021B: VOLATILES					Analyst	NSB
Benzene	9	ND	0.025	mg/Kg	1	3/23/2021 7:07:22 PM	58833
Toluene		ND	0.049	mg/Kg	1	3/23/2021 7:07:22 PM	58833
Ethylben	izene	ND	0.049	mg/Kg	1	3/23/2021 7:07:22 PM	58833
Xylenes,	Total	ND	0.098	mg/Kg	1	3/23/2021 7:07:22 PM	58833
Surr: 4	4-Bromofluorobenzene	96.7	80-120	%Rec	1	3/23/2021 7:07:22 PM	58833

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.D Sample Diluted Due to Matrix
- D Sample Diluted Due to MatrixH Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix

- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Limit

Page 1 of 0

Analytical Report Lab Order 2103911

Date Reported:

Hall Environmental Analysis Laboratory, Inc.

		,				Date Reported.	
CLIENT: H	Hilcorp Energy		Cl	ient Sample II	D: BC	GT Pipeline N	
Project: F	Fullerton Federal Com 12		(Collection Dat	e: 3/1	7/2021 9:25:00 AM	
Lab ID: 2	2103911-002	Matrix: SOIL		Received Dat	e: 3/1	8/2021 8:00:00 AM	
Analyses		Result	RL	Qual Units	DF	Date Analyzed	Batch
EPA METH	OD 300.0: ANIONS					Analyst:	ЈМТ
Chloride		ND	60	mg/Kg	20	3/26/2021 10:43:00 AM	58988
EPA METH	OD 8015M/D: DIESEL RANGE	ORGANICS				Analyst	mb
Diesel Ran	ge Organics (DRO)	ND	9.7	mg/Kg	1	3/22/2021 8:56:20 AM	58838
Motor Oil R	Range Organics (MRO)	ND	49	mg/Kg	1	3/22/2021 8:56:20 AM	58838
Surr: DN	IOP	95.4	70-130	%Rec	1	3/22/2021 8:56:20 AM	58838
EPA METH	OD 8015D: GASOLINE RANG	E				Analyst	NSB
Gasoline R	ange Organics (GRO)	ND	5.0	mg/Kg	1	3/23/2021 7:30:58 PM	58833
Surr: BF	В	94.3	75.3-105	%Rec	1	3/23/2021 7:30:58 PM	58833
EPA METH	OD 8021B: VOLATILES					Analyst	NSB
Benzene		ND	0.025	mg/Kg	1	3/23/2021 7:30:58 PM	58833
Toluene		ND	0.050	mg/Kg	1	3/23/2021 7:30:58 PM	58833
Ethylbenze	ne	ND	0.050	mg/Kg	1	3/23/2021 7:30:58 PM	58833
Xylenes, To	otal	ND	0.099	mg/Kg	1	3/23/2021 7:30:58 PM	58833
Surr: 4-E	Bromofluorobenzene	96.6	80-120	%Rec	1	3/23/2021 7:30:58 PM	58833

Refer to the QC Summary report and sample login checklist for flagged QC data and preservation information.

Qualifiers:

- * Value exceeds Maximum Contaminant Level.D Sample Diluted Due to Matrix
- D Sample Diluted Due to MatrixH Holding times for preparation or analysis exceeded
- ND Not Detected at the Reporting Limit
- PQL Practical Quanitative Limit
- S % Recovery outside of range due to dilution or matrix

- B Analyte detected in the associated Method Blank
- E Value above quantitation range
- J Analyte detected below quantitation limits
- P Sample pH Not In Range
- RL Reporting Limit

Page 2 of 0

Received by OCD: 4/15/2021 1:44:37 PM

Fullerton Federal Com 12 – Pipeline Pit # 2







District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:
HILCORP ENERGY COMPANY	372171
1111 Travis Street	Action Number:
Houston, TX 77002	24207
	Action Type:
	[C-144] Below Grade Tank Plan (C-144B)

CONDITIONS

Created By	Condition	Condition Date
cwhitehead	None	7/28/2021

CONDITIONS

Page 17 of 17

Action 24207