

Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM
 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-27376
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Caffall FD
8. Well Number 2
9. OGRID Number 7377
10. Pool name or Wildcat Kennedy Farms; Morrow

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other	
2. Name of Operator EOG Resources, Inc.	
3. Address of Operator 104 South Fourth Street, Artesia, NM 88210	
4. Well Location Unit Letter <u>I</u> : <u>1980</u> feet from the <u>South</u> line and <u>660</u> feet from the <u>East</u> line Section <u>15</u> Township <u>17S</u> Range <u>26E</u> NMPM Eddy County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3330'GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/> CLOSED-LOOP SYSTEM <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>
---	---

Notify OCD 24 hrs. prior to any work done

13. Describe proposed or completed operations. (Clearly state all pertinent details, including proposed completion or recompletion date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

EOG Resources, Inc. plans to plug and abandon this well as follows:

1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
2. Set a CIBP at 8317' with 25 sx Class "H" cement on top to 8097'. WOC and tag. This will cover Morrow perfs and top and Atoka top.
3. Spot a 25 sx Class "H" cement plug from 7850'-7630'. This will cover Strawn top.
4. Spot a 25 sx Class "C" cement plug from 7420'-7173'. This will cover Canyon top.
5. Spot a 25 sx Class "C" cement plug from 6534'-6287'. This will cover Penn top.
6. Perforate at 5640'. Spot a 33 sx Class "C" cement plug from 5640'-5481'. WOC and tag. This will cover TOC and Wolfcamp top.
7. Perforate at 4420'. Spot a 36 sx Class "C" cement plug from 4420'-4275'. WOC and tag. This will cover Abo top.
8. Perforate at 2417'. Spot a 32 sx Class "C" cement plug from 2417'-2288'. WOC and tag. This will cover Glorieta top.
9. Perforate at 1467'. Spot a 26 sx Class "C" cement plug from 1467'-1362'. WOC and tag. This will cover casing shoe.
10. Perforate at 1005'. Spot a 26 sx Class "C" cement plug from 1005'-900'. WOC and tag. This will cover San Andres top.
11. Perforate at 50'. Spot a 13 sx Class "C" cement plug from 50' up to surface. Back fill as needed.
12. Cut off wellhead and install dry hole marker. Clean location as per regulated.

Wellbore schematics attached.

Spud Date:

Rig Release Date:

****SEE ATTACHED COA's****

Must be plugged by 8/20/2022

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Specialist DATE August 12, 2021

Type or print name Tina Huerta E-mail address: tina.huerta@eogresources.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 8/20/2021

Conditions of Approval (if any):

Perf A

Caffall FD 2 Proposed			Sec-TWN-RNG: Sec. 15-17S-26E FOOTAGES: 1980' FSL & 660' FEL		API: 30-015-27376 GL: 3330 KB:																																																																																																																																																																																																																																																																																																																																																																																																																			
<div>Plug 10: Casing shoe + Surface plug</div> <div>Plug 9: San Andres</div> <div>Plug 8: Casing shoe</div> <div> </div> <div>Plug 7: Glorieta top</div> <div> </div> <div>Plug 6: Abo top</div> <div> </div> <div>Plug 5: TOC plug + Wolfcamp top</div> <div> </div> <div>Plug 4: Penn top</div> <div> </div> <div>Plug 3: Canyon top</div> <div> </div> <div>Plug 2: Strawn top</div> <div> </div> <div>Plug 1: CIBP + Morrow perms + Morrow top + Atoka top</div>	<div>A</div> <div>B</div> <div>C</div>		<table><tr><th colspan="10">CASING DETAIL</th></tr><tr><th>#</th><th>HOLE SIZE</th><th>SIZE</th><th>WGHT</th><th>GRADE</th><th>Top</th><th>Bottom</th><th>Sx Cmt</th><th>Circ/TOC</th><th>TOC Method</th></tr><tr><td>A</td><td>17 1/2</td><td>13 3/8</td><td>54.5</td><td>J-55</td><td>0</td><td>480</td><td>525</td><td>Circ</td><td></td></tr><tr><td>B</td><td>12 1/4</td><td>8 5/8</td><td>24</td><td>J-55</td><td>0</td><td>1,417</td><td>770</td><td>Circ</td><td></td></tr><tr><td>C</td><td>7 7/8</td><td>5 1/2</td><td>15.5/17</td><td>J-55/K-55</td><td>0</td><td>8,655</td><td>450</td><td>TOC 5590</td><td>Calculated</td></tr><tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><th colspan="10">FORMATION TOPS</th></tr><tr><td> </td><td> </td><th>Formation</th><th>Top</th><td> </td><td> </td><th>Formation</th><th>Top</th><td> </td><td> </td></tr><tr><td> </td><td> </td><td>San Andres</td><td>955</td><td> </td><td> </td><td>Atoka</td><td>8152</td><td> </td><td> </td></tr><tr><td> </td><td> </td><td>Glorieta</td><td>2367</td><td> </td><td> </td><td>Morrow</td><td>8315</td><td> </td><td> </td></tr><tr><td> </td><td> </td><td>Abo</td><td>4370</td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td>Wolfcamp</td><td>5560</td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td>Penn</td><td>6484</td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td>Canyon</td><td>7370</td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td>Strawn</td><td>7800</td><td> </td><td> </td><td> </td><td> </td><td> </td><td> </td></tr><tr><th colspan="10">TUBING DETAIL</th></tr><tr><th>#</th><th>Joints</th><th>Description</th><th>Length</th><th>OD</th><th>ID</th><th>Grade</th><th>Wt (lb/ft):</th><th>Top (ftKB):</th><th>Btm (ftKB):</th></tr><tr><td> </td><td> </td><td>2-7/8" Tubing</td><td> </td><td> </td><td> </td><td> </td><td> </td><td>8,179</td><td> </td></tr><tr><td colspan="10">Packer @ 8174</td></tr><tr><td colspan="10"> </td></tr><tr><td colspan="10"> </td></tr><tr><th colspan="10">Perforation Detail</th></tr><tr><td> </td><th>Formation</th><th>Top</th><th>Bottom</th><th colspan="3">Treatment</th><td> </td><td> </td><td> </td></tr><tr><td>A</td><td>Morrow</td><td>8,367</td><td>8,491</td><td colspan="3">All: Acidized w/1500 gals 15% NEFE acid w/1000 sscf/bbl N2. w/30,000 gals 35# crosslink gel & 32,000# 20-40 resin coated super DC sand. 8367-8421</td><td> </td><td> </td><td> </td></tr><tr><td>B</td><td> </td><td> </td><td> </td><td colspan="3"> </td><td> </td><td> </td><td> </td></tr><tr><th colspan="10">Plugs</th></tr><tr><th>#</th><th>SX</th><th>Class</th><th>Top</th><th>Bottom</th><th>Δ</th><th>Notes</th><th colspan="2">Tag</th></tr><tr><td>1</td><td>25</td><td>H</td><td>8,097</td><td>8,317</td><td>220</td><td>CIBP + Morrow perms + Morrow top + Atoka top</td><td colspan="2">Y</td></tr><tr><td>2</td><td>25</td><td>H</td><td>7630</td><td>7850</td><td>220</td><td>Strawn top</td><td colspan="2">N</td></tr><tr><td>3</td><td>25</td><td>C</td><td>7173</td><td>7420</td><td>247</td><td>Canyon top</td><td colspan="2">N</td></tr><tr><td>4</td><td>25</td><td>C</td><td>6287</td><td>6534</td><td>247</td><td>Penn top</td><td colspan="2">N</td></tr><tr><td>5</td><td>33</td><td>C</td><td>5481</td><td>5640</td><td>159</td><td>TOC plug + Wolfcamp top</td><td colspan="2">Y</td></tr><tr><td>6</td><td>36</td><td>C</td><td>4275</td><td>4420</td><td>145</td><td>Abo top</td><td colspan="2">Y</td></tr><tr><td>7</td><td>32</td><td>C</td><td>2,288</td><td>2,417</td><td>129</td><td>Glorieta top</td><td colspan="2">Y</td></tr><tr><td>8</td><td>26</td><td>C</td><td>1,362</td><td>1,467</td><td>105</td><td>Casing shoe</td><td colspan="2">Y</td></tr><tr><td>9</td><td>26</td><td>C</td><td>900</td><td>1,005</td><td>105</td><td>San Andres top</td><td colspan="2">Y</td></tr><tr><td>10</td><td>13</td><td>C</td><td>0</td><td>50</td><td>50</td><td>Surface plug</td><td colspan="2">Y</td></tr><tr><td colspan="10">PBTD: 8,620 MD</td></tr><tr><td colspan="10">TD: 8,660 MD</td></tr><tr><td colspan="5">Prepared by: Naomi F 5/5/21</td><td colspan="5"> </td></tr></table>							CASING DETAIL										#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt	Circ/TOC	TOC Method	A	17 1/2	13 3/8	54.5	J-55	0	480	525	Circ		B	12 1/4	8 5/8	24	J-55	0	1,417	770	Circ		C	7 7/8	5 1/2	15.5/17	J-55/K-55	0	8,655	450	TOC 5590	Calculated																					FORMATION TOPS												Formation	Top			Formation	Top					San Andres	955			Atoka	8152					Glorieta	2367			Morrow	8315					Abo	4370									Wolfcamp	5560									Penn	6484									Canyon	7370									Strawn	7800							TUBING DETAIL										#	Joints	Description	Length	OD	ID	Grade	Wt (lb/ft):	Top (ftKB):	Btm (ftKB):			2-7/8" Tubing						8,179		Packer @ 8174																														Perforation Detail											Formation	Top	Bottom	Treatment						A	Morrow	8,367	8,491	All: Acidized w/1500 gals 15% NEFE acid w/1000 sscf/bbl N2. w/30,000 gals 35# crosslink gel & 32,000# 20-40 resin coated super DC sand. 8367-8421						B										Plugs										#	SX	Class	Top	Bottom	Δ	Notes	Tag		1	25	H	8,097	8,317	220	CIBP + Morrow perms + Morrow top + Atoka top	Y		2	25	H	7630	7850	220	Strawn top	N		3	25	C	7173	7420	247	Canyon top	N		4	25	C	6287	6534	247	Penn top	N		5	33	C	5481	5640	159	TOC plug + Wolfcamp top	Y		6	36	C	4275	4420	145	Abo top	Y		7	32	C	2,288	2,417	129	Glorieta top	Y		8	26	C	1,362	1,467	105	Casing shoe	Y		9	26	C	900	1,005	105	San Andres top	Y		10	13	C	0	50	50	Surface plug	Y		PBTD: 8,620 MD										TD: 8,660 MD										Prepared by: Naomi F 5/5/21									
		CASING DETAIL																																																																																																																																																																																																																																																																																																																																																																																																																						
		#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt	Circ/TOC	TOC Method																																																																																																																																																																																																																																																																																																																																																																																																													
		A	17 1/2	13 3/8	54.5	J-55	0	480	525	Circ																																																																																																																																																																																																																																																																																																																																																																																																														
		B	12 1/4	8 5/8	24	J-55	0	1,417	770	Circ																																																																																																																																																																																																																																																																																																																																																																																																														
		C	7 7/8	5 1/2	15.5/17	J-55/K-55	0	8,655	450	TOC 5590	Calculated																																																																																																																																																																																																																																																																																																																																																																																																													
		FORMATION TOPS																																																																																																																																																																																																																																																																																																																																																																																																																						
				Formation	Top			Formation	Top																																																																																																																																																																																																																																																																																																																																																																																																															
		San Andres	955			Atoka	8152																																																																																																																																																																																																																																																																																																																																																																																																																	
		Glorieta	2367			Morrow	8315																																																																																																																																																																																																																																																																																																																																																																																																																	
		Abo	4370																																																																																																																																																																																																																																																																																																																																																																																																																					
		Wolfcamp	5560																																																																																																																																																																																																																																																																																																																																																																																																																					
		Penn	6484																																																																																																																																																																																																																																																																																																																																																																																																																					
		Canyon	7370																																																																																																																																																																																																																																																																																																																																																																																																																					
		Strawn	7800																																																																																																																																																																																																																																																																																																																																																																																																																					
TUBING DETAIL																																																																																																																																																																																																																																																																																																																																																																																																																								
#	Joints	Description	Length	OD	ID	Grade	Wt (lb/ft):	Top (ftKB):	Btm (ftKB):																																																																																																																																																																																																																																																																																																																																																																																																															
		2-7/8" Tubing						8,179																																																																																																																																																																																																																																																																																																																																																																																																																
Packer @ 8174																																																																																																																																																																																																																																																																																																																																																																																																																								
Perforation Detail																																																																																																																																																																																																																																																																																																																																																																																																																								
	Formation	Top	Bottom	Treatment																																																																																																																																																																																																																																																																																																																																																																																																																				
A	Morrow	8,367	8,491	All: Acidized w/1500 gals 15% NEFE acid w/1000 sscf/bbl N2. w/30,000 gals 35# crosslink gel & 32,000# 20-40 resin coated super DC sand. 8367-8421																																																																																																																																																																																																																																																																																																																																																																																																																				
B																																																																																																																																																																																																																																																																																																																																																																																																																								
Plugs																																																																																																																																																																																																																																																																																																																																																																																																																								
#	SX	Class	Top	Bottom	Δ	Notes	Tag																																																																																																																																																																																																																																																																																																																																																																																																																	
1	25	H	8,097	8,317	220	CIBP + Morrow perms + Morrow top + Atoka top	Y																																																																																																																																																																																																																																																																																																																																																																																																																	
2	25	H	7630	7850	220	Strawn top	N																																																																																																																																																																																																																																																																																																																																																																																																																	
3	25	C	7173	7420	247	Canyon top	N																																																																																																																																																																																																																																																																																																																																																																																																																	
4	25	C	6287	6534	247	Penn top	N																																																																																																																																																																																																																																																																																																																																																																																																																	
5	33	C	5481	5640	159	TOC plug + Wolfcamp top	Y																																																																																																																																																																																																																																																																																																																																																																																																																	
6	36	C	4275	4420	145	Abo top	Y																																																																																																																																																																																																																																																																																																																																																																																																																	
7	32	C	2,288	2,417	129	Glorieta top	Y																																																																																																																																																																																																																																																																																																																																																																																																																	
8	26	C	1,362	1,467	105	Casing shoe	Y																																																																																																																																																																																																																																																																																																																																																																																																																	
9	26	C	900	1,005	105	San Andres top	Y																																																																																																																																																																																																																																																																																																																																																																																																																	
10	13	C	0	50	50	Surface plug	Y																																																																																																																																																																																																																																																																																																																																																																																																																	
PBTD: 8,620 MD																																																																																																																																																																																																																																																																																																																																																																																																																								
TD: 8,660 MD																																																																																																																																																																																																																																																																																																																																																																																																																								
Prepared by: Naomi F 5/5/21																																																																																																																																																																																																																																																																																																																																																																																																																								

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water **will not** be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Potash---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3. API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S – R 30E

Sec 1 – Sec 36

T 21S – R 31E

Sec 1 – Sec 36

T 22S – R 28E

Sec 36 Unit A,H,I,P.

T 22S – R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S – R 30E

Sec 1 – Sec 36

T 22S – R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

T 23S – R 28E

Sec 1 Unit A

T 23S – R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S – R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S – R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S – R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S – R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S – R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 41583

CONDITIONS

Operator: EOG RESOURCES INC P.O. Box 2267 Midland, TX 79702	OGRID: 7377
	Action Number: 41583
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	8/20/2021