

<b>Well Name:</b> Easy Company 36 35 W01J Fed Co	<b>Well Location:</b> T20S / R28E / SEC 36 / NESE / 32.5264172 / -104.1235192	<b>County or Parish/State:</b> EDDY / NM
<b>Well Number:</b> 1H	<b>Type of Well:</b> CONVENTIONAL GAS WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM103877	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b>
<b>US Well Number:</b> 3001548551	<b>Well Status:</b> Drilling Well	<b>Operator:</b> MEWBOURNE OIL COMPANY

Subsequent Report

<b>Type of Submission:</b> Subsequent Report	<b>Type of Action:</b> Drilling Operations
<b>Date Sundry Submitted:</b> 08/11/2021	<b>Time Sundry Submitted:</b> 09:31
<b>Date Operation Actually Began:</b> 07/13/2021	

**Actual Procedure:** TD'ed 17 ½" hole @ 1380'. Ran 1365' of 13 3/8" 54.5# J55 ST&C csg. cmt w/1100 sks Class C w/4% Gel, 0.4#/sk Defoamer, #/sk Cellophane, 2% CaCl2 (yd @ 1.74 cuft/sk @ 13.5 PPG). Displaced w/205 bbls of FW. Plug down @ 4:30 A.M. 07/14/21. Circ 306 sks of cmt to the pit. Tested BOPE to 5000# high/250# low & Annular to 3500#. At 6:15 P.M. 07/14/21, tested csg to 1500# for 30 mins, held OK. Set wear bushing. PU dir tools & test. TIH. Drlg plug, floats & cmt. Drlg from 1380' to 1390'. FIT to 9.5 PPG EMW. Drilled out at 12 ¼". 07/15/21 TD'ed 12 ¼" hole @ 3050'. Ran 3035' of 9 5/8" 40# HCL80 LT&C csg. cmt 1st stage w/500 sks 35/65 Poz C w/5% Salt, 4% Gel, 5% Strength Enhancer, 1% Chemical Extender, 3#/sk Kolseal, 0.4#/sk Defoamer & #/sk Cellophane (yd @ 2.17 cuft/sk @ 12.5 PPG). Tail w/200 sks Class C Neat (yd @ 1.32 cuft/sk @ 14.8 PPG). Displaced w/227 bbls of FW. Slow rate lift pressure 499 psi @ 3 BPM. Plug down @ 6:45 A.M. 07/16/21. Set ACP w/1824#. Dropped bomb & opened DV tool w/929#. Circ 20 sks cmt off DV tool. Cmt 2nd stage w/400 sks Class C Neat (yd @ 1.32 cuft/sk @ 14.8 PPG). Displaced w/111 bbls of FW. Plug down @ 8:15 A.M. 07/16/21. Closed DV tool w/2030 psi. Circ 25 sks of cmt to the pit. , At 5:45 P.M. 07/16/21, tested csg to 1500# for 30 mins, held OK. Drlg plug, floats & cmt. Drlg from 3050' to 3060'. FIT to 10 PPG EMW. Drilled out at 8 ¾". 07/20/21 TD'ed 8 ¾" hole @ 9454'. Ran 9424' of 7" 29# ICP110 LT&C csg. cmt w/550 sks PVL, 0.7% Fluid loss, 12% Potter beads, 12% Strength enhancer, 3#/sk Kolseal & 0.4#/sk defoamer (yd @ 2.86 cuft/sk @ 10.5 PPG). Tail w/400 Class H, 0.5% Fluid loss & 0.2% Retarder (yd @ 1.18 cuft/sk @ 15.6 PPG). Displaced w/349 bbls of OBM. Plug down @ 4:00 A.M. Circ 10 sks of cmt to the pit. Set Cameron mandrel hanger through BOP w/210k#. At 8:30 P.M. 07/21/21, tested csg to 1500# for 30 min, held OK. TIH. Drlg plug, floats & cmt. Drlg from 9454' to 9464'. FIT to 11.5 PPG EMW. Drilled out at 6 1/8". 07/29/21 TD'ed 6 1/8" hole @ 17425' MD. Ran 4 ½" 13.5# HCP110 BPN csg from 8606' (top of liner) to 17423'. cmt w/650 sks Poz H (35:65:6) w/0.55% Retarder, 0.5% Fluid loss, 0.2% Extender & 10#/sk Pumice (1.74 ft³/sk @ 13.5 ppg). Drop dart. Displaced w/219 bbls of sugar BW. Plug down @ 9:00 A.M. 07/30/21. Bumped plug w/3000#. Set packer w/80k#. Sting out of liner hanger w/2500# on DP. Displaced 7" csg w/300 bbls of polymer BW. Circ 129 sks cmt off liner top. At 10:15 A.M. 07/30/21, tested liner top to 2500# for 30 min, held OK. Rig released to walk @ 8:00 P.M. 07/30/21.

Received by OCD: 8/26/2021 2:45:36 PM

Page 2 of 3

Well Name: Easy Company 36 35 W0IJ Fed Co	Well Location: T20S / R28E / SEC 36 / NESE / 32.5264172 / -104.1235192	County or Parish/State: EDDY / NM
Well Number: 1H	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMNM103877	Unit or CA Name:	Unit or CA Number:
US Well Number: 3001548551	Well Status: Drilling Well	Operator: MEWBOURNE OIL COMPANY

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: BRADLEY BISHOP	Signed on: AUG 11, 2021 09:31 AM
Name: MEWBOURNE OIL COMPANY	
Title: Regulatory	
Street Address: PO Box 5270	
City: Hobbs	State: NM
Phone: (575) 393-5905	
Email address: bbishop@mewbourne.com	

Field Representative

Representative Name: Ruby Caballero		
Street Address: 4801 Business Park Boulevard, Hobbs		
City: Hobbs	State: NM	Zip: 88240
Phone: (575)393-5905		
Email address: rcaballero@mewbourne.com		

BLM Point of Contact

BLM POC Name: Jonathon W Shepard	BLM POC Title: Petroleum Engineer
BLM POC Phone: 5752345972	BLM POC Email Address: jshepard@blm.gov
Disposition: Accepted	Disposition Date: 08/25/2021
Signature: Jonathon Shepard	

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
  
Action 44724

CONDITIONS

Operator: MEWBOURNE OIL CO P.O. Box 5270 Hobbs, NM 88241	OGRID: 14744
	Action Number: 44724
	Action Type: [C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
ksimmons	None	8/30/2021