

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Sundry Print Report 002/03/2021

County or Parish/State: LEA /

Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 /

Well Status: Approved Application for

NWNE / 32.280448 / -103.403716

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Permit to Drill

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Notice of Intent

Type of Submission: Notice of Intent

Type of Action APD Change

Date Sundry Submitted: 01/24/2021

Time Sundry Submitted: 03:26

Date proposed operation will begin: 01/23/2021

Procedure Description: INTERMEDIATE CASING/CMT CHANGE - PLEASE SEE REVISED DRILL PLAN

Application

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

County or Parish/State: LEA/

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Permit to Drill

Section 1 - General

APD ID: 10400060210 Tie to previous NOS? N Submission Date: 08/12/2020

BLM Office: CARLSBAD

Surface access agreement in place?

User: Rebecca Deal

Title: Regulatory Compliance

Professional Is the first lease penetrated for production Federal or Indian? FED

Federal/Indian APD: FED

Lease Acres:

Lease number: NMNM115426

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? Y

Permitting Agent? NO

APD Operator: DEVON ENERGY PRODUCTION COMPANY LP

Operator letter of designation:

Operator Info

Operator Organization Name: DEVON ENERGY PRODUCTION COMPANY LP

Operator Address: 333 WEST SHERIDAN AVE

Zip: 73102

Operator PO Box:

Operator City: OKLAHOMA CITY State: OK

Operator Phone: (405)235-3611 **Operator Internet Address:**

Section 2 - Well Information

Well in Master Development Plan? NO **Master Development Plan name:**

Well in Master SUPO? NO **Master SUPO name:**

Well in Master Drilling Plan? NO Master Drilling Plan name:

Well Name: RED BULL 30-31 FED STATE COM Well Number: 4H Well API Number: 3002548327

Field Name: WC-025 G-08 Field/Pool or Exploratory? Field and Pool Pool Name: LOWER BONE

S233528D SPRING

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL

Is the proposed well in a Helium production area? N Use Existing Well Pad? N New surface disturbance?

Type of Well Pad: MULTIPLE WELL Multiple Well Pad Name: RED Number: 4

BULL 30 WELLPAD Well Class: HORIZONTAL Number of Legs: 1

Well Work Type: Drill Well Type: OIL WELL

Page 2 of 24

eived by OCD; 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 /

County or Parish/State: LEA/

NWNE / 32.280448 / -103.403716

Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426 **Unit or CA Name: Unit or CA Number:**

US Well Number: 3002548327 Well Status: Approved Application for Operator: DEVON ENERGY PRODUCTION COMPANY LP

Permit to Drill

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL

Describe Well Type:

Well sub-Type: INFILL

Describe sub-type:

Distance to town: Distance to nearest well: 769 FT Distance to lease line: 883 FT

Reservoir well spacing assigned acres Measurement: 320 Acres

RED_BULL_30_31_FED_STATE_COM_4H_C_102_20200812084228.pdf

Well work start Date: 04/01/2021 **Duration: 45 DAYS**

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83 Vertical Datum: NAVD88

Survey number: Reference Datum: GROUND LEVEL

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
SHL	883	FNL	171	FEL	23S	35E	30	Aliquot	32.28044	-	LEA	NEW	NEW	F	NMNM	340	0	0	Υ
Leg			1					NWNE	8	103.4037		MEXI			115426	9			
#1										16		СО	СО						
KOP	50	FNL	330	FEL	23S	35E	30	Aliquot	32.28275	-	LEA	NEW	NEW	F	NMNM	-	112	110	Υ
Leg								NENE	9	103.3992		MEXI			115426	767	48	87	
#1										24		СО	СО			8			
PPP	263	FSL	330	FEL	23S	35E	30	Aliquot	32.27499	-	LEA	NEW	NEW	F	NMNM	-	144	116	Υ
Leg	0							NESE	5	103.3992		MEXI			138884	825	00	60	
#1-1										22		СО	СО			1			
PPP	100	FNL	330	FEL	23S	35E	30	Aliquot	32.28261	-	LEA	NEW	NEW	F	NMNM	-	115	113	Υ
Leg								NENE	5	103.3992		MEXI			115426	795	34	61	
#1-2										51		CO	CO			2			

Page 3 of 24

eceived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 /

NWNE / 32.280448 / -103.403716

County or Parish/State: LEA/

Well Number: 4H Type of Well: OIL WELL **Allottee or Tribe Name:**

Lease Number: NMNM115426 **Unit or CA Name: Unit or CA Number:**

US Well Number: 3002548327 Well Status: Approved Application for **Operator:** DEVON ENERGY

Permit to Drill

PRODUCTION COMPANY LP

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
EXIT	100	FSL	330	FEL	23S	35E	31	Aliquot	32.25409	-	LEA	NEW	NEW	S	STATE	-	220	116	Υ
Leg					ĺ			SESE	4	103.3992		MEXI	MEXI			825	04	60	
#1										15		CO	CO			1			
BHL	20	FSL	330	FEL	23S	35E	31	Aliquot	32.25387	-	LEA	NEW	NEW	S	STATE	-	220	116	Υ
Leg								SESE	5	103.3992		MEXI				825	84	60	
#1										15		CO	CO			1			1

Drilling Plan

Section 1 - Geologic Formations

Formation			True Vertical				Producing
ID	Formation Name	Elevation	Depth	Depth	Lithologies	Mineral Resources	Formation
1513220		3421	0	0	OTHER : Surface	NONE	N
1513221	RUSTLER	2321	1100	1100	SANDSTONE	NONE	N
1513222	TOP SALT	2021	1400	1400	SALT	NONE	N
1513216	CAPITAN REEF	-569	3990	3990	ANHYDRITE	NONE	N
1513230	BASE OF SALT	-1828	5249	5249	ANHYDRITE	NONE	N
1513231	BELL CANYON	-1879	5300	5300	SANDSTONE	NATURAL GAS, OIL	N
1513233	CHERRY CANYON	-2984	6405	6405	SANDSTONE	NATURAL GAS, OIL	N
1513234	BRUSHY CANYON	-4141	7562	7562	SANDSTONE	NATURAL GAS, OIL	N
1513219	BONE SPRING 1ST	-5467	8888	8888	LIMESTONE	NATURAL GAS, OIL	N
1513235	BONE SPRING 1ST	-6479	9900	9900	SANDSTONE	NATURAL GAS, OIL	N
1513238	2ND BONE SPRING LIME	-6704	10125	10125	LIMESTONE	NATURAL GAS, OIL	N
1513228	BONE SPRING 2ND	-6929	10350	10350	SANDSTONE	NATURAL GAS, OIL	N
1513226	BONE SPRING 3RD	-7458	10879	10879	LIMESTONE	NATURAL GAS, OIL	N
1513236	BONE SPRING 3RD	-7929	11350	11350	SANDSTONE	NATURAL GAS, OIL	Y
1513229	WOLFCAMP	-8271	11692	11692	SHALE	NATURAL GAS, OIL	N

eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Number: 4H

Well Location: T23S / R35E / SEC 30 /

NWNE / 32.280448 / -103.403716

County or Parish/State: LEA/

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for

Permit to Drill

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Formation	Formation Name	Elevation	True Vertical	Measured Depth		Mineral Resources	Producing Formation
1513237	STRAWN	-8929	12350	12350	SHALE	NATURAL GAS, OIL	N

Section 2 - Blowout Prevention

Pressure Rating (PSI): 5M Rating Depth: 11660

Equipment: BOP/BOPE will be installed per Onshore Oil & Gas Order #2 requirements prior to drilling below surface and intermediate casing, a BOP/BOPE system with the above minimum rating will be installed on the wellhead system. BOP/BOPE will be tested by an independent service company per Onshore Oil & Gas Order #2 requirements and MASP (Maximum Anticipated Surface Pressure) calculations. If the system is upgraded, all the components installed will be functional and tested.

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP stack to the choke manifold. See attached for specs for hydrostatic test chart.

Testing Procedure: A multibowl wellhead may be used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

Choke Diagram Attachment:

5M_BOPE__CK_20200812085423.pdf

BOP Diagram Attachment:

MB_Verb_5M_20200812085446.pdf

MB_Wellhd_5M_13.375_8.625_20200812085446.pdf

Section 3 - Casing

_																							
	Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	L
	1	SURFACE	17.5	13.375	NEW	API	N	0	1125	0	1125	3409	2284	1125	H-40	48	ST&C	1.12 5	1	BUOY	1.6	BUOY	1.
		INTERMED IATE	12.2 5	9.625	NEW	API	N	0	5275	0	5275		-1866	5275	J-55	_	OTHER - BTC	1.12 5	1	BUOY	1.6	BUOY	1.
	-	PRODUCTI ON	8.75	5.5	NEW	API	N	0	22084	0	11660	3681	-8251	22084	P- 110		OTHER - BTC	1.12 5	1	BUOY	1.6	BUOY	1.

Casing Attachments

Well Name: RED BULL 30-31 FED

Well Name: RED BULL 30-31 FED

Well Location: T23S / R35E / SEC 30 / County or Parish/State: LEA / NAME (20.0001410 / 10001

STATE COM NWNE / 32.280448 / -103.403716

Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426 Unit or CA Name: Unit or CA Number:

US Well Number: 3002548327 Well Status: Approved Application for Operator: DEVON ENERGY

Permit to Drill PRODUCTION COMPANY LP

Casing Attachments

Well Number: 4H

Casing ID: 1 String Type: SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Surf_Csg_Ass_20191031065635.pdf

13.375_48lb_H40_20200611092322.pdf

Casing ID: 2 String Type: INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Int_Csg_Ass_20200812085548.pdf

 $9.625_40lb_J_55_20210124151657.pdf$

Casing ID: 3 String Type: PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Prod_Csg_Ass_20200812085635.pdf

5.5_17_P_110_BTC_20200812085635.pdf

Section 4 - Cement

eived by OCD; 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

County or Parish/State: LEA/

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Number: 4H

Well Status: Approved Application for

Permit to Drill

Operator: DEVON ENERGY

PRODUCTION COMPANY LP

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	1125	853	1.44	13.2	1227. 8	50	С	Class C + Adds

INTERMEDIATE	Lead	0	4775	584	3.27	9	1909. 7	30	С	Class C + Adds
INTERMEDIATE	Tail	4775	5275	154	1.44	13.2	221.5	30	С	Class C + Adds
PRODUCTION	Lead	3940	1124 8	625	3.27	9	2042. 6	25	TUNED	Class C + adds
PRODUCTION	Tail	1124 8	2208 4	2091	1.44	13.2	3010. 9	25		(50:50) Clas H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

Describe the mud monitoring system utilized: PVT/Pason/Visual Monitoring

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	ЬН	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	1125	WATER-BASED MUD	8.5	9				2			
1125	5275	SALT SATURATED	10	10.5				2			
5275	2208 4	WATER-BASED MUD	8.5	9				12			WBM/OBM

eived by OCD; 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

Well Location: T23S / R35E / SEC 30 /

County or Parish/State: LEA/

STATE COM NWNE / 32.280448 / -103.403716

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Number: 4H

Well Status: Approved Application for

Permit to Drill

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Will run GRMWD from TD to from KOP. Cement bond logs will be run in vertical to determine top of cement. Stated logs run will be in the Completion Report and submitted to the BLM.

List of open and cased hole logs run in the well:

CALIPER, CEMENT BOND LOG, DIRECTIONAL SURVEY, GAMMA RAY LOG, MUD LOG/GEOLOGIC LITHOLOGY LOG,

Coring operation description for the well:

N/A

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 5457 Anticipated Surface Pressure: 2891

Anticipated Bottom Hole Temperature(F): 163

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Contingency Plans geoharzards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Red Bull 30 31 Fed State Com 4H 20200812085826.pdf

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Devon_Red_Bull_30_31_Fed_State_Com_4H_Permit_Plan_1_20200812085848.pdf Devon_Red_Bull_30_31_Fed_State_Com_4H_Plot_Permit_Plan_1_20200812085848.pdf

Other proposed operations facets description:

DIRECTIONAL SURVEY DRILLING PLAN MULTI-BOWL VERBIAGE MULTI-BOWL WELLHEAD **CLOSED LOOP DESIGN PLAN CO-FLEX HOSE** SPUDDER RIG REQUEST **GCP FORM** SPEC SHEETS

Other proposed operations facets attachment:

Spudder_Rig_Info_20190124102728.pdf Clsd_Loop_20190124102727.pdf

Red_Bull_30_WP_4_GCP_Form_20200706151114.pdf

Red Bull 30 31 Fed State Com 4H Permit Plan 1 20201105152113.pdf

Other Variance attachment:

ceived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

County or Parish/State:

JM

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Number:

US Well Number: 3002548327

Unit or CA Name:

Operator: DEVON ENERGY

Permit to Drill

PRODUCTION COMPANY LP

Co_flex_20190124102748.pdf

SUPO

Well Status: Approved Application for

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

ACCESS_RDS_20200812085927.pdf

Existing Road Purpose: ACCESS,FLUID TRANSPORT

Row(s) Exist? NO

ROW ID(s)

ID:

Do the existing roads need to be improved? YES

Existing Road Improvement Description: Improve road to accommodate Drilling and Completion operations.

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

RED_BULL_30_CTB_2_ACC_P_20200706151259.pdf

RED_BULL_30_PRIMARY_ACC_P_20200706151258.pdf

RED_BULL_30_WP_4_ACC_P_20200706151300.pdf

NEW_ACCESS_RDS_20200812085952.pdf

New road type: COLLECTOR, RESOURCE

Length: 10518.65

Feet

Width (ft.): 30

Max slope (%): 6

Max grade (%): 4

Army Corp of Engineers (ACOE) permit required? N

ACOE Permit Number(s):

New road travel width: 20

New road access erosion control: Water Drainage Ditch

New road access plan or profile prepared? Y

New road access plan attachment:

ACCESS_RD_PLATS_DOC_20191030124347.pdf

Access road engineering design? Y

Access road engineering design attachment:

 ${\tt ACCESS_RD_PLATS_DOC_20191030124357.pdf}$

Turnout? N

Page 9 of 24

eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 /

NWNE / 32.280448 / -103.403716

Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426 **Unit or CA Name: Unit or CA Number:**

US Well Number: 3002548327 Well Status: Approved Application for **Operator: DEVON ENERGY**

Permit to Drill PRODUCTION COMPANY LP

County or Parish/State: LEA

Access surfacing type: OTHER Access topsoil source: ONSITE

Access surfacing type description: caliche

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: See attached Interim reclamation diagram.

Access other construction information:

Access miscellaneous information:

Number of access turnouts: Access turnout map:

Drainage Control

New road drainage crossing: CULVERT

Drainage Control comments: N/A

Road Drainage Control Structures (DCS) description: N/A

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

OneMileBuffer_WA018127909_20200812090148.pdf

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: 6 ATTACHMENTS - WELLPAD PLAT, CTB PLAT, FLOWLINE PLAT, 3 ELECTRIC PLATS. GAS, WATER, AND CRUDE HANDLED BY ROW OR THIRD PARTIES

Production Facilities map:

RED_BULL_30_CTB_2_EL_P_20200706151424.pdf

RED BULL 30 CTB 2 P 20200706151427.pdf

RED_BULL_30_PRIMARY_EL_P_20200706151423.pdf

RED_BULL_30_WP_4_EL_P_20200706151424.pdf

RED_BULL_30_WP_4_P_20200706151424.pdf

RED_BULL_30_WP_4_TO_CTB_2_FL_P_20200706151423.pdf

Section 5 - Location and Types of Water Supply

Water Source Table

Page 10 of 24

ceived by OCD; 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

County or Parish/State: LEA

NM

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for

Permit to Drill

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Water source type: RECYCLED

Water source use type:

STIMULATION

Source latitude:

Source longitude:

Source datum:

Water source permit type:

OTHER

Water source transport method:

PIPELINE

Source land ownership: FEDERAL

Source transportation land ownership: FEDERAL

Water source volume (barrels): 320000

Source volume (acre-feet): 41.24579083

Source volume (gal): 13440000

Water source and transportation map:

RED_BULL_30_31_FED_STATE_COM_3H_4H_20200706151444.pdf

Water source comments: The attached Water Transfer Map is a proposal only and the final route and documentation will be provided by a Devon contractor prior to installation. When available Devon will always follow existing disturbance.

New water well? N

New Water Well Info

Well latitude: Well Longitude: Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft): Well casing type:

Well casing outside diameter (in.): Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method: Drill material:

Grout material: Grout depth:

Casing length (ft.): Casing top depth (ft.):

Well Production type: Completion Method:

Water well additional information:

State appropriation permit:

Additional information attachment:

Page 11 of 24

County or Parish/State: LEA / Well Location: T23S / R35E / SEC 30 /

STATE COM NWNE / 32.280448 / -103.403716

Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426 **Unit or CA Name: Unit or CA Number:**

US Well Number: 3002548327 Well Status: Approved Application for **Operator: DEVON ENERGY** PRODUCTION COMPANY LP

Permit to Drill

Section 6 - Construction Materials

Using any construction materials: YES

Construction Materials description: Dirt fill and caliche will be used to construct well pad. See attached map.

Construction Materials source location attachment:

Red_Bull_30_WP_4_Caliche_Map_20200706151459.pdf

Section 7 - Methods for Handling Waste

Waste type: DRILLING

Waste content description: Water Based and Oil Based Cuttings

Amount of waste: 1918 barrels

Waste disposal frequency: Daily Safe containment description: N/A

Safe containment attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: All cuttings will disposed of at R360, Sundance, or equivalent.

Waste type: FLOWBACK

Waste content description: Average produced BWPD over the flowback period (first 30 days of production).

Amount of waste: 3000 barrels

Waste disposal frequency: Daily Safe containment description: N/A

Safe containment attachment:

Waste disposal type: OFF-LEASE INJECTION Disposal location ownership: COMMERCIAL

Disposal type description:

Disposal location description: Produced water will primarily be disposed of in commercial disposals connected via pipeline.

Waste type: PRODUCED WATER

Waste content description: Average produced BWPD over the first year of production.

Amount of waste: 1000 barrels

Waste disposal frequency: Daily Safe containment description: N/A

Safe containment attachment:

Waste disposal type: OFF-LEASE INJECTION Disposal location ownership: COMMERCIAL

Disposal type description:

Disposal location description: Produced water will primarily be disposed of in commercial disposals connected via pipeline.

Page 12 of 24

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

Well Status: Approved Application for

County or Parish/State: LEA

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Operator: DEVON ENERGY

Permit to Drill

PRODUCTION COMPANY LP

Waste type: COMPLETIONS/STIMULATION

Waste content description: Flow back water during completion operations.

Amount of waste: 3000

barrels

Waste disposal frequency: One Time Only

Safe containment description: N/A

Safe containment attachment:

Waste disposal type: HAUL TO COMMERCIAL

Disposal location ownership: COMMERCIAL

FACILITY

Disposal type description:

Disposal location description: Various disposal locations in Lea and Eddy counties.

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit? NO

Reserve pit length (ft.)

Reserve pit width (ft.)

Reserve pit depth (ft.)

Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? N

Description of cuttings location

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: N

Ancillary Facilities attachment:

Comments:

gived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

NWNE / 32.280448 / -103.403716

County or Parish/State: LEA

Well Location: T23S / R35E / SEC 30 /

Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for Permit to Drill

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Section 9 - Well Site Layout

Well Site Layout Diagram:

Well_Layout_20200812090456.pdf

Comments:

Section 10 - Plans for Surface Reclamation

Multiple Well Pad Name: RED BULL 30 WELLPAD Type of disturbance: New Surface Disturbance

Multiple Well Pad Number: 4

Recontouring attachment:

INTERIM_RECL_20200812090526.pdf

Drainage/Erosion control construction: All areas disturbed shall be reclaimed as early and as nearly as practicable to their original condition or their final land use and shall be maintained to control dust and minimize erosion to the extent practicable. Drainage/Erosion control reclamation: Topsoils and subsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns. The disturbed area then shall be reseeded in the first favorable growing season.

Well pad proposed disturbance

(acres): 5.85

Road proposed disturbance (acres):

Powerline proposed disturbance

(acres): 4.905

Pipeline proposed disturbance

(acres): 0.746

Other proposed disturbance (acres):

5.74

Total proposed disturbance: 24.485

Well pad interim reclamation (acres):

4 341

Road interim reclamation (acres): 0

Pipeline interim reclamation (acres): 0

Other interim reclamation (acres): 0

Total interim reclamation: 4.341

Well pad long term disturbance

(acres): 1.509

Road long term disturbance (acres):

7.244

Powerline interim reclamation (acres): Powerline long term disturbance

(acres): 4.905

Pipeline long term disturbance

(acres): 0.746

Other long term disturbance (acres):

5.74

Total long term disturbance:

20.1440000000000002

Disturbance Comments:

Reconstruction method: Operator will use Best Management Practices"BMP" to mechanically recontour to obtain the desired outcome.

Topsoil redistribution: Topsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns.

Soil treatment: Topsoils shall be replaced to their original relative positions and contoured so as to achieve erosion control, long-term stability and preservation of surface water flow patterns.

Existing Vegetation at the well pad: Shinnery, yucca, grasses and mesquite.

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road: Shinnery, yucca, grasses and mesquite.

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline: Shinnery, yucca, grasses and mesquite.

Page 14 of 24

eived by *OCD*; 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 /

County or Parish/State: LEA

NWNE / 32.280448 / -103.403716

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for

Permit to Drill

Operator: DEVON ENERGY

PRODUCTION COMPANY LP

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances: Shinnery, yucca, grasses and mesquite.

Existing Vegetation Community at other disturbances attachment:

Non native seed used? N

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? N

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? N

Seed harvest description:

Seed harvest description attachment:

Seed Management

Seed Table

Seed Summary

Pounds/Acre

Seed reclamation attachment:

Seed Type

Total pounds/Acre:

Operator Contact/Responsible Official Contact Info

First Name: Blake Last Name: Richardson

Phone: (405)552-6556 Email: blake.richardson@dvn.com

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? N

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Weed treatment plan description: Maintain weeds on an as need basis.

Weed treatment plan attachment:

Monitoring plan description: Monitor as needed.

Monitoring plan attachment:

eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

County or Parish/State: LEA

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for

Permit to Drill

Operator: DEVON ENERGY

PRODUCTION COMPANY LP

Success standards: N/A Pit closure description: N/A

Pit closure attachment:

Section 11 - Surface Ownership

Disturbance type: NEW ACCESS ROAD

Describe:

Surface Owner: PRIVATE OWNERSHIP

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office: Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Fee Owner: Limestone Livestock, LLC

Fee Owner Address: 76 Angell Road

Phone: (575)369-6303

Email:

Surface use plan certification: NO

Surface use plan certification document:

Surface access agreement or bond: AGREEMENT

Surface Access Agreement Need description: SUA between Limestone Livestock, LLC and Devon Energy

Production Company, L.P. Uploaded in Sec. 12 **Surface Access Bond BLM or Forest Service:**

BLM Surface Access Bond number:

USFS Surface access bond number:

Page 16 of 24

Well Name: RED BULL 30-31 FED

Well Name: RED BULL 30-31 FED

Well Location: T23S / R35E / SEC 30 / County or Parish/State: LEA

STATE COM NWNE / 32.280448 / -103.403716

Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426 Unit or CA Name: Unit or CA Number:

US Well Number: 3002548327 Well Status: Approved Application for Operator: DEVON ENERGY

Permit to Drill PRODUCTION COMPANY LP

Disturbance type: EXISTING ACCESS ROAD

Describe:

Surface Owner: PRIVATE OWNERSHIP

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland: USFS Ranger District:

Fee Owner: Limestone Livestock, LLC Fee Owner Address: 76 Angell Road

Phone: (575)369-6303 **Email:**

Surface use plan certification: NO

Surface use plan certification document:

Surface access agreement or bond: AGREEMENT

Surface Access Agreement Need description: SUA between Limestone Livestock, LLC and Devon Energy

Production Company, L.P. Uploaded in Sec. 12 Surface Access Bond BLM or Forest Service:

BLM Surface Access Bond number:

USFS Surface access bond number:

Disturbance type: PIPELINE

Describe:

Surface Owner: PRIVATE OWNERSHIP

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

County or Parish/State: Page 18 of eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED Well Location: T23S / R35E / SEC 30 / STATE COM NWNE / 32.280448 / -103.403716 Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name: Lease Number: NMNM115426 **Unit or CA Name: Unit or CA Number: US Well Number: 3002548327** Well Status: Approved Application for **Operator: DEVON ENERGY** Permit to Drill PRODUCTION COMPANY LP **DOD Local Office: NPS Local Office: State Local Office: Military Local Office: USFWS Local Office:** Other Local Office: **USFS** Region: **USFS Forest/Grassland: USFS Ranger District:** Fee Owner: Limestone Livestock, LLC Fee Owner Address: 76 Angell Road Phone: (575)369-6303 Email: Surface use plan certification: NO Surface use plan certification document: Surface access agreement or bond: AGREEMENT Surface Access Agreement Need description: SUA between Limestone Livestock, LLC and Devon Energy Production Company, L.P. Uploaded in Sec. 12 **Surface Access Bond BLM or Forest Service: BLM Surface Access Bond number: USFS Surface access bond number:** Disturbance type: WELL PAD Describe: Surface Owner: PRIVATE OWNERSHIP Other surface owner description: **BIA Local Office: BOR Local Office: COE Local Office: DOD Local Office: NPS Local Office: State Local Office: Military Local Office: USFWS Local Office: Other Local Office: USFS** Region:

eived by OCD; 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

County or Parish/State: LEA

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for

Operator: DEVON ENERGY

Permit to Drill

PRODUCTION COMPANY LP

USFS Forest/Grassland:

USFS Ranger District:

Fee Owner: Limestone Livestock, LLC

Fee Owner Address: 76 Angell Road

Phone: (575)369-6303

Email:

Surface use plan certification: NO

Surface use plan certification document:

Surface access agreement or bond: AGREEMENT

Surface Access Agreement Need description: SUA between Limestone Livestock, LLC and Devon Energy

Production Company, L.P. Uploaded in Sec. 12 **Surface Access Bond BLM or Forest Service:**

BLM Surface Access Bond number:

USFS Surface access bond number:

Section 12 - Other Information

Right of Way needed? N

Use APD as ROW?

ROW Type(s):

ROW Applications

SUPO Additional Information: See Section 4 for Facility & Infrastructure Plats. See C-102 for grading plats. Limestone

Livestock LLC SUA page attached. Use a previously conducted onsite? Y

Previous Onsite information: Red Bull 30 - 7/13/19

Other SUPO Attachment

Limestone_Livestock_LLC_SUA_1st_Pg_20200812083416.pdf

PWD

eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 /

NWNE / 32.280448 / -103.403716

County or Parish/State: LEA

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for

Permit to Drill

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 /

NWNE / 32.280448 / -103.403716

Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426 **Unit or CA Name: Unit or CA Number:**

US Well Number: 3002548327 Well Status: Approved Application for **Operator: DEVON ENERGY**

Permit to Drill

PRODUCTION COMPANY LP

County or Parish/State: LEA/

Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? N

Produced Water Disposal (PWD) Location:

PWD disturbance (acres): PWD surface owner:

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? N

Page 21 of 24

County or Parish/State: LEA/ eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED Well Location: T23S / R35E / SEC 30 /

STATE COM NWNE / 32.280448 / -103.403716

Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426 **Unit or CA Name: Unit or CA Number:**

US Well Number: 3002548327 Well Status: Approved Application for **Operator: DEVON ENERGY**

Permit to Drill PRODUCTION COMPANY LP

Produced Water Disposal (PWD) Location:

PWD surface owner: PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number: Injection well name:

Assigned injection well API number? Injection well API number:

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection attachment:

Underground Injection Control (UIC) Permit?

UIC Permit attachment:

Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner: PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 - Other

Would you like to utilize Other PWD options? N

Produced Water Disposal (PWD) Location:

PWD surface owner: PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Other PWD type description:

Other PWD type attachment:

Have other regulatory requirements been met?

Other regulatory requirements attachment:

Operator Certification

Page 22 of 24

eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

County or Parish/State: Page 23 of

Well Number: 4H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Well Status: Approved Application for

Permit to Drill

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Rebecca Deal Signed on: 01/24/2021

Title: Regulatory Compliance Professional

Street Address: 333 West Sheridan Avenue

State: OK City: Oklahoma City **Zip:** 73102

Phone: (405)228-8429

Email address: Rebecca.Deal@dvn.com

Field Representative

Representative Name: TRAVIS PHIBBS

Street Address: 333 W. Sheridan Ave

City: OKC State: OK **Zip:** 73102

Phone: (157)574-8992

Email address: TRAVIS.PHIBBS@DVN.COM

NOI Attachments

Procedure Description

Red Bull 30 31 Fed State Com 4H Permit Plan 1 20210124151448.pdf

Page 23 of 24

eived by OCD: 8/27/2021 10:05:22 AM Well Name: RED BULL 30-31 FED

STATE COM

Well Location: T23S / R35E / SEC 30 / NWNE / 32.280448 / -103.403716

Well Status: Approved Application for

County or Parish/State: LEA

Well Number: 4H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM115426

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002548327

Permit to Drill

Operator: DEVON ENERGY PRODUCTION COMPANY LP

Conditions of Approval

Additional Reviews

Red Bull 30 31 Fed State Com 3H Dr COA 20210202072443.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: DEAL

Signed on: JAN 24, 2021 03:25 PM

Title: Regulatory Compliance Professional

Name: DEVON ENERGY PRODUCTION COMPANY LP

Street Address: 333 WEST SHERIDAN AVE

City: OKLAHOMA CITY State: OK

Phone: (405) 235-3611

Email address:

Field Representative

Representative Name: TRAVIS PHIBBS

Street Address: 333 W. Sheridan Ave

City: OKC State: OK **Zip:** 73102

Phone: (157)574-8992

Email address: TRAVIS.PHIBBS@DVN.COM

BLM Point of Contact

Signature: Chris Walls

BLM POC Name: CHRISTOPHER WALLS BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752342234 BLM POC Email Address: cwalls@blm.gov

Disposition: Approved Disposition Date: 02/03/2021

Page 24 of 24

Red Bull 30-31 Fed State Com 4H

1. Geologic Formations

TVD of target	11660	Pilot hole depth	N/A
MD at TD:	22084	Deepest expected fresh water	

Basin

Dasin	Donth	Water/Mineral	
T	Depth		TT 1 4
Formation	(TVD)	Bearing/Target	Hazards*
	from KB	Zone?	
Rustler	1100		
Salt	1400		
Capitan	3990		
Base of Salt	5249		
Delaware	5300		
Bone Spring 1st	9900		
Bone Spring 2nd	10350		
Bone Spring 3rd	11350		
Wolfcamp	11692		

^{*}H2S, water flows, loss of circulation, abnormal pressures, etc.

Red Bull 30-31 Fed State Com 4H

2. Casing Program

		Wt			Casing	Interval	Casing Interval		
Hole Size	Csg. Size	(PPF)	Grade	Conn	From (MD)	To (MD)	From (TVD)	To (TVD)	
17 1/2	13 3/8	48	H40	ВТС	0	1125	0	1125	
12 1/4	9 5/8	40	J-55	ВТС	0	5275	0	5275	
8 3/4	5 1/2	17	P110	ВТС	0	22084	0	11660	

[•] All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for continengcy casing.

3. Cementing Program (3-String Primary Design)

Casing	# Sks	TOC	Wt. (lb/gal)	Yld (ft3/sack)	Slurry Description
Surface	853	Surf	13.2	1.4	Lead: Class C Cement + additives
T., 1	584	Surf	9.0	3.3	Lead: Class C Cement + additives
Int 1	154	500' above shoe	13.2	1.4	Tail: Class H / C + additives
Int 1	As Needed	Surf	9.0	3.3	Squeeze Lead: Class C Cement + additives
Intermediate	584	Surf	9.0	3.3	Lead: Class C Cement + additives
Squeeze	154	500' above shoe	13.2	1.4	Tail: Class H / C + additives
Production	625	500' tieback	9.0	3.3	Lead: Class H /C + additives
Production	2091	KOP	13.2	1.4	Tail: Class H / C + additives

Casing String	% Excess
Surface	50%
Intermediate	30%
Production	10%

4. Pressure Control Equipment (Three String Design)

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	T	ype	✓	Tested to:														
			Anı	nular	X	50% of rated working pressure														
Int 1	13-58"	5M	Blind	l Ram	X															
IIIt I	13-36	3101	Pipe	Ram		5M														
			Doub	le Ram	X	31V1														
			Other*																	
	13-5/8"		Anı	nular	X	50% of rated working pressure														
Production		13-5/8" 5M	13-5/8" 5M	13-5/8" 5M	13-5/8" 5M		13-5/8" 5M	13-5/8" 5M		12 5/9" 5M	12 5/9" 5M	12 5/9" 5M	12 5/0" 5M	12 5/0" 5M	5M	5/0" 5M	Blind	l Ram	X	
Floduction										31/1	JIVI	Pipe	Ram		5M					
													Doub	le Ram	X	31V1				
			Other*																	
			Annul	ar (5M)																
			Blind	l Ram																
				Ram]														
			Doub	le Ram																
			Other*																	

5. Mud Program (Three String Design)

Section	Туре	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	Brine	10-10.5
Production	WBM/OBM	8.5-9

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring

6. Logging and Testing Procedures

Logging, C	Logging, Coring and Testing				
	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the				
X	Completion Report and sbumitted to the BLM.				
	No logs are planned based on well control or offset log information.				
	Drill stem test? If yes, explain.				
	Coring? If yes, explain.				

Additional logs planned		Interval
	Resistivity	
	Density	
X	CBL	Production casing
X	Mud log	KOP to TD
	PEX	

7. Drilling Conditions

Condition	Specfiy what type and where?
BH pressure at deepest TVD	5457
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogren Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

encou	encountered measured values and formations will be provided to the BLW.		
N	H2S is present		
Y	H2S plan attached.		

8. Other facets of operation

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
 - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pad.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. At that time an approved BOP stack will be nippled up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments	
X	Directional Plan
	Other, describe

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME: | **Devon Energy Production Company LP**

LEASE NO.: | NMNM115426

LOCATION: | Section 30, T.23 S., R.35 E., NMPM

COUNTY: Lea County, New Mexico

WELL NAME & NO.: Red Bull 30-31 Fed State Com 3H

SURFACE HOLE FOOTAGE: 883'/N & 1741'/E BOTTOM HOLE FOOTAGE 20'/S & 1870'/E

WELL NAME & NO.: Red Bull 30-31 Fed State Com 4H

SURFACE HOLE FOOTAGE: 883'/N & 1711'/E **BOTTOM HOLE FOOTAGE** 20'/S & 330'/E

COA

H2S	Yes	□ No	
Potash	None	☐ Secretary	R -111-P
Cave/Karst Potential	⊡ Low	☐ Medium	☐ High
Cave/Karst Potential	Critical		
Variance	□ None	☑ Flex Hose	Other
Wellhead	Conventional	Multibowl	□ Both
Other	☐ 4 String Area		□WIPP
Other	Fluid Filled	✓ Cement Squeeze	☐ Pilot Hole
Special Requirements	☐ Water Disposal	™ COM	□ Unit

A. HYDROGEN SULFIDE

A Hydrogen Sulfide (H2S) Drilling Plan shall be activated 500 feet prior to drilling into the **Jamat and Antelope** formation. As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.

B. CASING

- 1. The 13-3/8 inch surface casing shall be set at approximately 1236 feet (a minimum of 25 feet (Lea County) into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature

- survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
- b. Wait on cement (WOC) time for a primary cement job will be a minimum of <u>8</u> hours or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

- 2. The minimum required fill of cement behind the 8-5/8 inch intermediate casing is:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above.
 Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, potash or capitan reef.
 Cement excess is less than 25%, more cement might be required.
 - ❖ In <u>Capitan Reef Areas</u> if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
 - ❖ Special Capitan Reef requirements. If lost circulation (50% or greater) occurs below the Base of the Salt, the operator shall do the following:
 - Switch to fresh water mud to protect the Capitan Reef and use fresh water mud until setting the intermediate casing. The appropriate BLM office is to be notified for a PET to witness the switch to fresh water.
 - Daily drilling reports from the Base of the Salt to the setting of the intermediate casing are to be submitted to the BLM CFO engineering staff via e-mail by 0800 hours each morning. Any lost circulation encountered is to be recorded on these drilling reports. The daily drilling report should show mud volume per shift/tour. Failure to submit these reports will result in an Incidence of Non-Compliance being issued for failure to comply with the Conditions of Approval. If not already planned, the operator shall run a caliper survey for the intermediate well bore and submit to the appropriate BLM office.

Operator has proposed to pump down 13-3/8" X 8-5/8" annulus. Operator must run a CBL from TD of the 8-5/8" casing to surface. Submit results to BLM.

- 3. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back at least **50 feet** on top of Capitan Reef top **or 200 feet** into the previous casing, whichever is greater. If cement does not circulate see B.1.a, c-d above.

Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, potash or capitan reef. Cement excess is less than 25%, more cement might be required.

C. PRESSURE CONTROL

- 1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
- 2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000** (**5M**) psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.

• In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)
 - Eddy County
 Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (575) 361-2822
 - Lea County
 Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
 393-3612
- 1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
- 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
- 3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

- 1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
- 2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing intergrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing intergrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
- 5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
- 6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
- 7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
- 8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.
- B. PRESSURE CONTROL

- 1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
- 2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
- 3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
- 4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- 5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not

- hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 44824

CONDITIONS

Operator:	OGRID:
DEVON ENERGY PRODUCTION COMPANY, LP	6137
333 West Sheridan Ave.	Action Number:
Oklahoma City, OK 73102	44824
	Action Type:
	[C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
pkautz	None	9/2/2021