Received by UCD: Sy22/2021 12:05:29 PM U.S. Department of the Interior BUREAU OF LAND MANAGEMENT		Sundry Print Report 02/17/2021
Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / NM
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Notice of Intent

Type of Submission: Notice of Intent

Date Sundry Submitted: 02/03/2021

Time Sundry Submitted: 07:48

Type of Action APD Change

Date proposed operation will begin: 02/28/2021

Procedure Description: EOG respectfully requests an amendment to our approved APD for this well to reflect the following changes: Change SHL to T-24-S R-34-E Sec 20 495 feet FNL 2243 feet FEL Lea Co, NM Change BHL to T-24-S R-34-E Sec 29 100 feet FSL 670 feet FEL Lea Co, NM Change surface hole size to 16 inches This well has an approved sundry changing the well to 303H, please approve the sundry with the correct well number.

Application

R	eceived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA/
	Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
	Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
	US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES

Section 1 - General		
APD ID: 10400047507	Tie to previous NOS?	Submission Date: 09/17/2019
BLM Office: CARLSBAD	User: Lisa Trascher	Title: Regulatory Specialist
Federal/Indian APD: FED	Is the first lease penetra	ted for production Federal or Indian? FED
Lease number: NMNM17241	Lease Acres:	
Surface access agreement in place?	Allotted?	Reservation:
Agreement in place? NO	Federal or Indian agreen	nent:
Agreement number:		
Agreement name:		
Keep application confidential? N		
Permitting Agent? NO	APD Operator: EOG RES	SOURCES INCORPORATED
Operator letter of designation:		

Operator Info

. . . .

Operator Organization Name: EOG RESOU	RCES INCORPORATED
Operator Address: 1111 BAGBY SKY LOBB	Y2
Operator PO Box:	
Operator City: HOUSTON State:	ГХ
Operator Phone: (713)651-7000	
Operator Internet Address:	

Section 2 - Well Information

Well in Master Development Plan? NO **Master Development Plan name:** Well in Master SUPO? NO Master SUPO name: Well in Master Drilling Plan? NO Master Drilling Plan name: Well Name: YUKON 20 FED COM Well Number: 703H Well API Number: 3002547170 Field/Pool or Exploratory? Field and Pool Field Name: BOBCAT DRAW; Pool Name: WC-025 G-09 UPR WOLFCAMP S253309P; UPPER WOLFCAMP

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL

Is the proposed well in a Helium production area? N Use Existing Well Pad? N Type of Well Pad: MULTIPLE WELL Well Class: HORIZONTAL

Well Work Type: Drill Well Type: OIL WELL Multiple Well Pad Name: YUKON 20 FED COM Number of Legs: 1


Zip: 77002

New surface disturbance?

Number: 701H/702H/703H

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA/ 3 of 38
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL



Section 3 - Well Location Table

Survey Type: RECTANGULAR Describe Survey Type:

Datum: NAD83

Survey number:

Vertical Datum: NAVD88

Reference Datum: KELLY BUSHING

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
SHL Leg	495		224 3	FEL	24S	34E	1 1		32.20895 9	- 103.4906	LEA	NEW MEXI			NMNM 017241	353 5	0	0	Y
#1		L		L	<u> </u>	<u> </u>				877		со	со						
KOP Leg #1	50	FNL	670	FEL	24S	34E	_			- 103.4856 021	LEA		NEW MEXI CO		NMNM 017241	- 814 5	117 11	116 80	Y
	100	FNL	670	FEL	24S	34E	_			- 103.4856 02	LEA		NEW MEXI CO		NMNM 017241	- 635 7	101 26	989 2	Y
EXIT Leg #1	100	FSL	670	FEL	24S	34E	-			- 103.4855 664	LEA		NEW MEXI CO		NMNM 016139	- 662 2	205 87	101 57	Y

 Page 4 of 38

 Well Name: YUKON 20 FED COM
 Well Location: T24S / R34E / SEC 20 / County or Parish/State: LEA / NWNE / 32.20845 / -103.4872401

 Well Number: 303H
 Type of Well: OIL WELL
 Allottee or Tribe Name:

Lease Number: NMNM17241

US Well Number: 300254717000X1

Unit or CA Name:

Permit to Drill

Operator: EOG RESOURCES INCORPORATED

Unit or CA Number:

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	DM	TVD	Will this well produce from this lease?
BHL	100	FSL	670	FEL	24S	34E	29	Aliquot	32.18156	-	LEA	NEW	NEW	F	NMNM	-	205	101	Y
Leg						'	1	SESE	74	103.4855			MEXI		016139	662	87	57	
#1										664		со	CO			2			

Well Status: Approved Application for

Drilling Plan

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
1540358	PERMIAN	3491	0	0	ALLUVIUM	NONE	N
1540359	RUSTLER	2653	838	838	ANHYDRITE	NONE	N
1540360	TOP SALT	2113	1378	1378	SALT	NONE	N
1540362	BASE OF SALT	-1447	4938	4938	SALT	NONE	N
1540363	LAMAR	-1708	5199	5199	LIMESTONE	NONE	N
1540364	BELL CANYON	-1734	5225	5225	SANDSTONE	NATURAL GAS, OIL	N
1540365	CHERRY CANYON	-2112	5603	5603	SANDSTONE	NATURAL GAS, OIL	N
1540366	BRUSHY CANYON	-4148	7639	7639	SANDSTONE	NATURAL GAS, OIL	N
1540361	BONE SPRING LIME	-5625	9116	9116	LIMESTONE	NONE	N
1540367	FIRST BONE SPRING SAND	-6578	10069	10069	SANDSTONE	NATURAL GAS, OIL	N
1540368	BONE SPRING 2ND	-6982	10473	10473	SANDSTONE	NATURAL GAS, OIL	N
1540369	BONE SPRING 3RD	-8170	11661	11661	SANDSTONE	NATURAL GAS, OIL	N
1540370	WOLFCAMP	-8637	12128	12128	SHALE	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES

Pressure Rating (PSI): 10M

Rating Depth: 12157

Equipment: The minimum blowout preventer equipment (BOPE) shown in Exhibit #1 will consist of a single ram, mud cross and double ram-type (10,000 psi WP) preventer and an annular preventer (10,000-psi WP). Both units will be hydraulically operated and the ram-type will be equipped with blind rams on bottom and drill pipe rams on top. A multi-bowl wellhead system will be utilized. After running the 9-5/8" surface casing, a 9-5/8" BOP/BOPE system with a minimum working pressure of 10,000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 10,000 psi pressure test. This pressure test will be repeated at least every 30 days, as per Onshore Order No. 2. The minimum working pressure of the BOP and related BOPE required for drilling below the surface casing shoe shall be 10,000 psi. The multi-bowl wellhead will be installed by vendor's representative(s). A copy of the installation instructions for the Cactus Multi-Bowl WH system has been sent to the NM BLM office in Carlsbad, NM. The wellhead will be installed by a third party welder while being monitored by WH vendor's representative. All BOP equipment will be tested utilizing a conventional test plug. Not a cup or J-packer type. A solid steel body pack-off will be utilized after running and cementing the intermediate casing. After installation the pack-off and lower flange will be pressure tested to 5000 psi. Casing strings will be tested as per Onshore Order No. 2 to at least 0.22 psi/ft or 1500 psi, whichever is greater. **Requesting Variance?** YES

Variance request: Variance is requested to use a co-flex line between the BOP and choke manifold (instead of using a 4" OD steel line). Variance is requested to use a 5,000 psi annular BOP with the 10,000 psi BOP stack. Variance is requested to waive the centralizer requirements for the 7-5/8" FJ casing in the 8-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 8-3/4" hole interval to maximize cement bond and zonal isolation. Variance is also requested to waive any centralizer requirements for the 5-1/2" FJ casing in the 6-3/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 6-3/4" hole interval to maximize cement bond and zonal isolation. Variance is also requested to waive the annular clearance requirements for the 5 1/2" casing by 7 5/8" casing annulus to the proposed top of cement. EOG requests permission to allow deviation from the 0.422" annulus clearance requirement from Onshore Order #2 under the following conditions: - Annular clearance to meet or exceed 0.422" between intermediate casing ID and production casing coupling only on the first 500' overlap between both casing strings. - Annular clearance less than 0.422" is acceptable for the curve and lateral portions of the production open hole section.

Testing Procedure: Pipe rams and blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. A hydraulically operated choke will be installed prior to drilling out of the intermediate casing shoe.

Choke Diagram Attachment:

10_M_Choke_Manifold_20190508145233.pdf

Co_Flex_Hose_Certification_20190508145234.pdf

Co_Flex_Hose_Test_Chart_20190508145234.pdf

BOP Diagram Attachment:

10_M_BOP_Diagram_9.675_in_20190508145331.pdf

EOG_BLM_10M_Annular_Variance____9.675_in_20190508145332.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type
1	SURFACE	12.2 5	9.625	NEW	API	N	0	1140	0	1140	3529	2389	1140	J-55	40	LT&C	1.12 5	1.25	BUOY	1.6	BUOY

eceived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM

Well Number: 303H

Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401

Type of Well: OIL WELL

County or Parish/State: LEA/

Allottee or Tribe Name:

Lease Number: NMNM17241

Unit or CA Name:

Unit or CA Number:

US Well Number: 300254717000X1

Well Status: Approved Application for Permit to Drill

Operator: EOG RESOURCES INCORPORATED

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	
2	PRODUCTI ON	6.75	5.5	NEW	API	N	0	10980	0	10980	3491	-7451	10980	OTH ER		OTHER - DWC/C-IS MS	1.12 5	1.25	BUOY	1.6	BUOY	1.
3	INTERMED IATE	8.75	7.625	NEW	API	Ν	0	11480	0	11480	3491	-7951		HCP -110		OTHER - FXL	1.12 5	1.25	BUOY	1.6	BUOY	1.
4	PRODUCTI ON	6.75	5.5	NEW	API	Ν	10980	11480	10980	11480	- 10451	-7951		OTH ER	-	OTHER - VAM SFC	1.12 5	1.25	BUOY	1.6	BUOY	1.
5	PRODUCTI ON	6.75	5.5	NEW	API	N	11480	22397	11480		- 10951	-8625	10917	OTH ER		OTHER - DWC/C-IS MS	1.12 5	1.25	BUOY	1.6	BUOY	1.

Casing Attachments

Casing ID: 1 String Type: SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Yukon_20_Fed_Com_704H_Permit_Info_REV2_20200225095700.pdf

Casing ID: 2 String Type: PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

5.500in_20.00_VST_P110EC_DWC_C_IS_MS_Spec_Sheet_20190917064033.pdf

See_previously_attached_Drill_Plan_20190917064033.pdf

eceived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Casing Attachments

 Casing ID: 3
 String Type: PRODUCTION

 Inspection Document:
 Spec Document:

 Tapered String Spec:
 String Spec:

Casing Design Assumptions and Worksheet(s):

Please_see_previously_attached_drill_plan_20180910200917.pdf

5.500in_20.00_VST_P110EC_VAM_SFC_20190916090418.pdf

Casing ID: 4 String Type: INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Please_see_previously_attached_drill_plan_20180913084044.pdf

7.625in_29.70_P110HC_FXL_20190916090606.pdf

Casing ID: 5 String Type: PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Please_see_previously_attached_drill_plan_20180913083920.pdf

5.500in_20.00_VST_P110EC_DWC_C_IS_MS_Spec_Sheet_20190916090459.pdf

Section 4 - Cement

eceived by OCD: 9 Well Name: YU	/22/2021 KON 20	12:05: FED C	29 <i>PM</i> COM					/ R34E 03.4872		20 /	County NM	or Parish/State: LEA
Well Number: 3	303H			ту	ype of	Well: (DIL WE	ELL			Allottee	e or Tribe Name:
Lease Number:	: NMNM	17241		Ui	nit or C	CA Nar	ne:				Unit or	CA Number:
US Well Numbe	er: 3002	54717(000X1		ell Sta ermit to		oprove	d Applic	cation	for	-	or: EOG RESOURCES PORATED
String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%		Cement type	Additives
PRODUCTION	Lead		0	0	0	0	0	0	0	0		0
PRODUCTION	Lead		0	0	0	0	0	0	0	0		0
										5		
SURFACE	Lead		0	940	1000	1.73	13.5	1730	25	Class	С	Class C + 4.0% Bentonite Gel + 0.5% CaCl2 + 0.25 lb/sk Cello-Flake (TOC @ Surface)
SURFACE	Tail		940	1140	100	1.34	14.8	134	25	Class	С	Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 940')
INTERMEDIATE	Lead		0	7600	1000	2.3	12.7	2300	25	Class	С	2nd Stage Bradenhead Squeeze Class C + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (TOC @ Surface)
INTERMEDIATE	Tail		7600	1148 0	500	1.11	14.2	555	25	Class	С	Class C + 0.6% Halad-9 + 0.45% HR-601 + 3% Microbond (TOC @ 7,600')
PRODUCTION	Lead		1098 0	2239 4	1000	1.31	14.2	1310	25	Class	Н	Class H + 0.4% Halad- 344 + 0.35% HR-601 + 3% Microbond (TOC @ 10,980')

•

Well Number: 303HType of Well: OLL WELLAllottee or Tribe Name:Lease Number: NMNM17241Unit or CA Name:Unit or CA Number:US Well Number: 300254717000X1Well Status: Approved Application for Permit to DrillOperator: EOG RESOURCES NCORPORATED	eceived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
US Well Number: 300254717000X1 Well Status: Approved Application for Operator: EOG RESOURCES	Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
	Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
	US Well Number: 300254717000X1		-

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: (A) A Kelly cock will be kept in the drill string at all times. (B) A full opening drill pipe-stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times. (C) H2S monitoring and detection equipment will be utilized from surface casing point to TD. **Describe the mud monitoring system utilized:** The highest mud weight needed to balance formation is expected to be 11.5 ppg. In order to maintain hole stability, mud weights up to 14.0 ppg may be utilized. An electronic pit volume totalizer (PVT) will be utilized on the circulating system, to monitor pit volume, flow rate, pump pressure and stroke rate. Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the wellsite at all times.

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (Ibs/gal)	Max Weight (Ibs/gal)	Density (Ibs/cu ft)	Gel Strength (lbs/100 sqft)	Н	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
1140	1148 0	SALT SATURATED	10	10.2							
1148 0	1171 2	OIL-BASED MUD	8.7	9.4							
0	1140	WATER-BASED MUD	8.6	8.8							
1171 2	1215 7	OIL-BASED MUD	10	14							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Open-hole logs are not planned for this well.

List of open and cased hole logs run in the well:

DIRECTIONAL SURVEY,

Coring operation description for the well:

None

R	eceived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / of 38 NM	3
	Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:	
	Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:	
	US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED	

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 8841

Anticipated Surface Pressure: 6271

Anticipated Bottom Hole Temperature(F): 181

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geoharzards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Yukon_20_Fed_Com_703H_H2S_Plan_Summary_20190917063936.pdf

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Yukon_20_Fed_Com_703H_Wall_Plot_20190917064127.pdf

Yukon_20_Fed_Com_703H_Planning_Report_20190917064127.pdf

Other proposed operations facets description:

EOG requests to pump a two stage cement job on the 7-5/8" intermediate casing string with the first stage being pumped conventionally with the calculated top of cement at the Brushy Canyon (7,494') and the second stage performed as a bradenhead squeeze with planned cement from the Brushy Canyon to surface. If necessary, a top out consisting of 1,000 sacks of Class C cement + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (2.30 yld, 12.91 ppg) will be executed as a contingency. The final cement top will be verified by Echo-meter.

EOG will include the Echo-meter verified fluid top and the volume of displacement fluid above the cement slurry in the annulus in all post-drill sundries on wells utilizing this cement program.

EOG will report to the BLM the volume of fluid (limited to 5 bbls) used to flush intermediate casing valves following backside cementing procedures.

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.

(A) EOG Resources requests the option to contract a Surface Rig to drill, set surface casing, and cement on the subject well. After WOC 8 hours or 500 psi compressive strength (whichever is greater), the Surface Rig will move off so the wellhead can be installed. A welder will cut the casing to the proper height and weld on the wellhead (both "A" and "B" sections). The weld will be tested to 1000 psi. All valves will be closed and a wellhead cap will be installed (diagram attached). If the timing between rigs is such that EOG Resources would not be able to preset the surface, the Primary Rig will MIRU and drill the well in its entirety per the APD.

Other proposed operations facets attachment:

Wellhead_9.675_in_20190509124528.pdf 7.625in_29.70_P110HC_FXL_20190509124527.pdf 5.500in_20.00_VST_P110EC_VAM_SFC_20190509124527.pdf 5.500in_20.00_VST_P110EC_DWC_C_IS_MS_Spec_Sheet_20190509124526.pdf Yukon_20_Fed_Com_703H_Rig_Layout_20190917064119.pdf Yukon_20_Fed_Com_704H_Permit_Info_REV2_20200225095735.pdf

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Other Variance attachment:

EOG_BLM_10M_Annular_Variance____9.675_in_20190509124742.pdf Co_Flex_Hose_Certification_20190509124741.pdf Co_Flex_Hose_Test_Chart_20190509124741.pdf 10_M_BOP_Diagram_9.675_in_20190509124740.pdf

<u>SU</u>PO

Row(s) Exist? NO

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

YUKON_20_FED_COM_703H_Vicinity_20190917064205.pdf

Existing Road Purpose: ACCESS, FLUID TRANSPORT

ROW ID(s)

ID:

Do the existing roads need to be improved? NO

Existing Road Improvement Description:

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

 YUKON_20_FED_COM_703H_Padsite_20190917064225.pdf

 YUKON_20_FED_COM_703H_Wellsite_20190917064225.pdf

 YUKON_20_FED_COM_INFRA_REV1_20190916093144.pdf

 New road type: RESOURCE

 Length: 1276
 Feet

 Width (ft.): 30

 Max slope (%): 2
 Max grade (%): 20

 Army Corp of Engineers (ACOE) permit required? N

 ACOE Permit Number(s):

New road travel width: 30

New road access erosion control: Newly constructed or reconstructed roads will be constructed as outlined in the BLM "Gold Book" and to meet the standards of the anticipated traffic flow and all anticipated weather requirements as needed. Construction will include ditching, draining, crowning and capping or sloping and dipping the roadbed as necessary to provide a well-constructed and safe road. We plan to grade and water twice a year. **New road access plan or profile prepared?** N

New road access plan attachment:

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / 38
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Access road engineering design? N

Access road engineering design attachment:

Turnout? N

Access surfacing type: OTHER

Access topsoil source: ONSITE

Access surfacing type description: 6" of Compacted Caliche

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: An adequate amount of topsoil/root zone will be stripped by dozer from the proposed well location and stockpiled along the side of the well location as depicted on the well site diagram / survey plat. **Access other construction information:**

Access miscellaneous information:

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: CULVERT

Drainage Control comments: An appropriately sized culvert will be installed where drainages cross the access road.

Road Drainage Control Structures (DCS) description: N/A

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

YUKON_20_FED_COM_703H_Radius_20190917064430.pdf

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: Yukon 20 Fed Com CTB is located in the NE/4 of Section 20.

Production Facilities map:

YUKON_20_FED_COM_WATER_SEC_20_S_20190916100840.pdf YUKON_20_FED_COM_WATER_SEC_21_S_20190916100840.pdf YUKON_20_FED_COM_701H_703H_FL_REV1_S_20190916094011.pdf YUKON_20_FED_COM_CTB_SEC_20_S_20190916094205.pdf YUKON_20_FED_COM_ELEC_SEC_20_S_20190916094204.pdf YUKON_20_FED_COM_ELEC_SEC_21_PRIVATE_S_20190916094204.pdf YUKON_20_FED_COM_ELEC_SEC_21_USA_S_20190916094205.pdf

eceived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S NWNE / 32.20845 / -1		County or Parish/State: LEA	
Well Number: 303H	Type of Well: OIL WE	ELL	Allottee or Tribe Name:	
Lease Number: NMNM17241	Unit or CA Name:		Unit or CA Number:	
US Well Number: 300254717000X1	Well Status: Approver Permit to Drill	d Application for	Operator: EOG RESOURCES INCORPORATED	
YUKON_20_FED_COM_ELEC_SEC_2 YUKON_20_FED_COM_GAS_SEC_20 YUKON_20_FED_COM_GAS_SEC_21 YUKON_20_FED_COM_INFRA_REV1 YUKON_20_FED_COM_SEC_20_RD_	0_S_20190916094204.pdf 1_S_20190916094204.pdf _20190916094204.pdf	.pdf		
Section 5 - Location ar				
Water Source Tab	le			
Water source type: RECYCLED				
Water source use type:	OTHER	Describe u	se type: NA	
Source latitude:		Source lor	ngitude:	
Source datum:			- 3	
Water source permit type:	WATER RIGHT			
Water source transport method:	TRUCKING			
	PIPELINE			
Source land ownership: FEDERAL				
Source transportation land owner	ship: FEDERAL			
Water source volume (barrels): 1		Source vo	lume (acre-feet): 0.00012889	
Source volume (gal): 42				
Water source and transportation map	p:			
Yukon_Water_and_Caliche_Map_2019	0916094812.pdf			
Water source comments:				
New water well? N				
New Water Well I	nfo			
Well latitude:	Well Longitude:	We	ell datum:	
Well target aquifer:				
Est. depth to top of aquifer(ft):	Est thickne	ss of aquifer:		
Aquifer comments:				
Aquifer documentation:				
Well depth (ft):	Well casing ty	ype:		
Well casing outside diameter (in.):	Well casing in	nside diameter (in	.):	
ew water well casing? Used casing source:				

Drill material:

•

Water well additional information: State appropriation permit:		
Well Production type:	Completion Method:	
Casing length (ft.):	Casing top depth (ft.):	
Grout material:	Grout depth:	
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
eceived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / NM

Additional information attachment:

Section 6 - Construction Materials

Using any construction materials: YES

Construction Materials description: Caliche will be supplied from pits shown on the attached caliche source map. Caliche utilized for the drilling pad will be obtained either from an existing approved mineral pit, or by benching into a hill, which will allow the pad to be level with existing caliche from the cut, or extracted by "Flipping" the well location. A mineral material permit will be obtained from BLM prior to excavating any caliche on Federal Lands. Amount will vary for each pad. The procedure for "Flipping" a well location is as follows: * -An adequate amount of topsoil/root zone (usually top 6 inches of soil) will be stripped from the proposed well location and stockpiled along the side of the well location as depicted on the well site diagram/survey plat. -An area will be used within the proposed well site dimensions to excavate caliche. Subsoil will be removed and stockpiled within the surveyed well pad dimensions. -Once caliche/surfacing mineral is found, the mineral material will be excavated and stock piled within the approved drilling pad dimensions. -Then, subsoil will be pushed back in the excavated hole and caliche will be spread accordingly across the entire well pad and road (if available). -Neither caliche, nor subsoil will be stock piled outside of the well pad dimensions. Topsoil will be stockpiled along the edge of the pad as depicted in the Well Site Layout or survey plat. * In the event that no caliche is found onsite, caliche will be hauled in from a BLM approved caliche pit or other established mineral pit. A BLM mineral material permit will be acquired prior to obtaining any mineral material permit will be acquired prior to obtaining any mineral material from BLM pits or federal land.

Construction Materials source location attachment:

Yukon_Water_and_Caliche_Map_20190916095144.pdf

Section 7 - Methods for Handling Waste

Waste type: DRILLING

Waste content description: Drill fluids and produced oil and water from the well during drilling and completion operations will be stored safely and disposed of properly in an NMOCD approved disposal facility. Garbage and trash produced during drilling and completion operations will be collected in a trash container and disposed of properly. Human waste and grey water will be properly contained of and disposed of properly. After drilling and completion operations; trash, chemicals, salts, frac sand, and other waste material will be removed and disposed of properly at a state approved disposal facility. **Amount of waste:** 0 barrels

Waste disposal frequency : Daily

Safe containment description: Steel Tanks

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL Disposal location ownership: COMMERCIAL

FACILITY Disposal type description:

Disposal location description: Trucked to NMOCD approved disposal facility

Reserve Pit

Reserve Pit being used? N

Temporary disposal of produced water into reserve pit? NO

eived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED
		•

Reserve pit length (ft.)

Reserve pit width (ft.)

Reserve pit depth (ft.)

Reserve pit volume (cu. yd.)

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? Y

Description of cuttings locationClosed Loop System. Drill cuttings will be disposed of into steel tanks and taken to anNMOCD approved disposal facility.Cuttings area length (ft.)Cuttings area length (ft.)Cuttings area width (ft.)

Cuttings area depth (ft.) Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: N Ancillary Facilities attachment:

Comments:

Section 9 - Well Site Layout

Well Site Layout Diagram:

YUKON_20_FED_COM_703H_Padsite_20190917064522.pdf YUKON_20_FED_COM_703H_Wellsite_20190917064522.pdf Yukon_20_Fed_Com_703H_Rig_Layout_20190917064541.pdf **Comments:** Exhibit 2A-Wellsite & Exhibit 2B-Padsite Rig Layout Exhibit 4

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: YUKON 20 FED COM Multiple Well Pad Number: 701H/702H/703H

Recontouring attachment:

YUKON_20_FED_COM_703H_Reclamation_20190917064608.pdf

Drainage/Erosion control construction: Proper erosion control methods will be used on the area to control erosion, runoff, and siltation of the surrounding area.

Drainage/Erosion control reclamation: The interim reclamation will be monitored periodically to ensure that vegetation has reestablished and that erosion is controlled.

Well pad proposed disturbance (acres): 0 Road proposed disturbance (acres): 0		(acres): 0 Road long term disturbance (acres): 0
Powerline proposed disturbance (acres): 0 Pipeline proposed disturbance	Powerline interim reclamation (acres): 0 Pipeline interim reclamation (acres): 0	(acres): 0
(acres): 0 Other proposed disturbance (acres): 0	Other interim reclamation (acres): 0 Total interim reclamation: 0	(acres): 0 Other long term disturbance (acres): 0
Total proposed disturbance: 0	Total Internit regiandion. 0	Total long term disturbance: 0

Disturbance Comments: All Interim and Final reclamation must be within 6 months. Interim must be within 6 months of completion and final within 6 months of abandonment plugging. Dual pad operations may alter timing.

Reconstruction method: In areas planned for interim reclamation, all the surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads. Areas planned for interim reclamation will be recontoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 ratio, unless the adjacent native topography is steeper. Note: Constructed slopes may be much steeper during drilling, but will be recontoured to the above ratios during interim reclamation.

Topsoil redistribution: Topsoil will be evenly respread and aggressively revegetated over the entire disturbed area not needed for all-weather operations including cuts and fills. To seed the area, the proper BLM seed mixture, free of noxious weeds, will be used. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites. **Soil treatment:** Re-seed according to BLM standards. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, and that erosion is controlled.

Existing Vegetation at the well pad: Grass, forbs, and small woody vegetation, such as mesquite will be excavated as the topsoil is removed. Large woody vegetation will be stripped and stored separately and respreads evenly on the site following topsoil respreading. Topsoil depth is defined as the top layer of soil that contains 80% of the roots. In areas to be heavily disturbed, the top 6 inches of soil material, will be stripped and stockpiled on the perimeter of the well location and along the perimeter of the access road to control run-on and run-off, to keep topsoil viable, and to make redistribution of topsoil more efficient during interim reclamation. Stockpiled topsoil should include vegetative material. Topsoil will be clearly segregated and stored separately from subsoils.

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation. **Existing Vegetation Community at the road attachment:**

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Existing Vegetation Community at the pipeline: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation. **Existing Vegetation Community at the pipeline attachment:**

Existing Vegetation Community at other disturbances: All disturbed areas, including roads, pipelines, pads, will be recontoured to the contour existing prior to the initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation. **Existing Vegetation Community at other disturbances attachment:**

Non native seed used? N

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? N

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? N

Seed harvest description:

Seed harvest description attachment:

Seed Management

Seed Table

Seed Summary

Total pounds/Acre:

Seed reclamation attachment:

Seed Type

Operator Contact/Responsible Official Contact Info

Pounds/Acre

First Name:

Phone:

Last Name: Email:

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? N

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / NM
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES

Weed treatment plan description: All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, erosion is controlled, and free of noxious weeds. Weeds will be treated if found. Weed treatment plan attachment:

Monitoring plan description: Reclamation will be completed within 6 months of well plugging. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, erosion is controlled, and free of noxious weeds.

Monitoring plan attachment:

Success standards: N/A

Pit closure description: NA

Pit closure attachment:

Section 11 - Surface Ownership

Disturbance type: WELL PAD

Describe:

Surface Owner: PRIVATE OWNERSHIP

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / 9 of 38
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Email:

Fee Owner: COG Operating LLC - ATTN Surface Management Dept **Phone:** (432)683-7443 Fee Owner Address: 600 West Illinois Ave.

Surface use plan certification: NO Surface use plan certification document:

Surface access agreement or bond: AGREEMENT

Surface Access Agreement Need description: surface use agreement

Surface Access Bond BLM or Forest Service:

BLM Surface Access Bond number:

USFS Surface access bond number:

Section 12 - Other Information

Use APD as ROW?

Right of Way needed? N ROW Type(s):

ROW Applications

SUPO Additional Information: An onsite meeting was conducted 5/2018. Poly lines are planned to transport water for operations. Will truck if necessary. See attached SUPO Plan. **Use a previously conducted onsite?** N

Previous Onsite information:

Other SUPO Attachment

Gas_Capture_Enterprise_Regency_Yukon20FedCom701H_711H_20190916100638.pdf YUKON_20_FED_COM_703H_Location_20190917064639.pdf SUPO_YUKON_20_FED_COM_703H_20190917064648.pdf

PWD

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / NM	
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:	
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:	
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED	

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? N Produced Water Disposal (PWD) Location: **PWD** surface owner: Lined pit PWD on or off channel: Lined pit PWD discharge volume (bbl/day): Lined pit specifications: Pit liner description: Pit liner manufacturers information: Precipitated solids disposal: Decribe precipitated solids disposal: Precipitated solids disposal permit: Lined pit precipitated solids disposal schedule: Lined pit precipitated solids disposal schedule attachment: Lined pit reclamation description: Lined pit reclamation attachment: Leak detection system description: Leak detection system attachment: Lined pit Monitor description: Lined pit Monitor attachment: Lined pit: do you have a reclamation bond for the pit? Is the reclamation bond a rider under the BLM bond? Lined pit bond number: Lined pit bond amount: Additional bond information attachment:

PWD disturbance (acres):

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? N

Produced Water Disposal (PWD) Location:

PWD disturbance (acres):

PWD surface owner:

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Decribe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? $\ensuremath{\mathsf{N}}$

eceived by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / NM	
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:	
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:	
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED	
Produced Water Disposal (PWD) Location	n:		
PWD surface owner:	PWD disturbance	(acres):	
Injection PWD discharge volume (bbl/day):		
Injection well mineral owner:			
Injection well type:			
Injection well number:	Injection well nar	ne:	
Assigned injection well API number?	Injection well AP	number:	
Injection well new surface disturbance (a	cres):		
Minerals protection information:			
Mineral protection attachment:			
Underground Injection Control (UIC) Perr	nit?		
UIC Permit attachment:			
Section 5 - Surface Discharge			
Would you like to utilize Surface Discharg	ge PWD options? N		
Produced Water Disposal (PWD) Location	1:		
PWD surface owner:	PWD disturbance	(acres):	
Surface discharge PWD discharge volum	e (bbl/day):		
Surface Discharge NPDES Permit?			
Surface Discharge NPDES Permit attachr	nent:		
Surface Discharge site facilities informat	on:		
Surface discharge site facilities map:			
Section 6 - Other			
Would you like to utilize Other PWD optic	ns? N		
Produced Water Disposal (PWD) Location	n:		
PWD surface owner:	PWD disturbance	(acres):	
Other PWD discharge volume (bbl/day):			
Other PWD type description:			
Other PWD type attachment:			
	mot?		
Have other regulatory requirements been	met :		

Operator Certification

•

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA / 3 of 38 NM
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Lisa Trascher		Signed on: 02/03/2021
Title: Regulatory Specialist		
Street Address: 5509 Champions	s Drive	
City: Midland	State: TX	Zip: 79706
Phone: (432)247-6331		
Email address: lisa_trascher@ec	ogresources.com	
Field Representative	e	
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

NOI Attachments		
Procedure Description		
Yukon_20_Fed_Com_30	3H_Wall_Plot_20210203074315.pdf	
Yukon 20 Fed Com 30	BH_Planning_Report_20210203074308.pdf	

Received by OCD: 9/22/2021 12:05:29 PM Well Name: YUKON 20 FED COM	Well Location: T24S / R34E / SEC 20 / NWNE / 32.20845 / -103.4872401	County or Parish/State: LEA
Well Number: 303H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM17241	Unit or CA Name:	Unit or CA Number:
US Well Number: 300254717000X1	Well Status: Approved Application for Permit to Drill	Operator: EOG RESOURCES INCORPORATED

Yukon_20_Fed_Com_303H_Permit_Info___Rev_casing_SHL_BHL_2.1.2021_20210203074302.pdf

YUKON_20_FED_COM_303H_C_102_20210203074253.pdf

Conditions of Approval

Additional Reviews

Yukon_20_Master_SurfaceUseCOAs___Copy_20210208153151.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: HARRELL

Name: EOG RESOURCES INCORPORATED

Title: Regulatory Specialist

Street Address: 1111 BAGBY SKY LOBBY2

City: HOUSTON State: TX

Phone: (713) 651-7000

Email address:

Field Representative

Representative Name:	
Street Address:	
City:	State
Phone:	
Email address:	

Zip:

BLM Point of Contact

BLM POC Name: CHRISTOPHER WALLS BLM POC Phone: 5752342234 Disposition: Approved Signature: Chris Walls BLM POC Title: Petroleum Engineer

BLM POC Email Address: cwalls@blm.gov Disposition Date: 02/12/2021

Signed on: FEB 03, 2021 07:47 AM

 District I

 1625 N. French Dr., Hobbs, NM 88240

 Phone: (575) 393-6161 Fax: (575) 393-0720

 District II

 811 S. First St., Artesia, NM 88210

 Phone: (575) 748-1283 Fax: (575) 748-9720

 District III

 1000 Rio Brazos Road, Aztec, NM 87410

 Phone: (505) 334-6178 Fax: (505) 334-6170

 District IV

 1220 S. St. Francis Dr., Santa Fe, NM 87505

 Phone: (505) 476-3460 Fax: (505) 476-3462


State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

FORM C-102 Revised August 1, 2011 Submit one copy to appropriate District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT ¹API Number ²Pool Code ³Pool Name 96434 RED HILLS; BONE SPRING, NORTH 30-025-⁴Property Code ⁵Property Name Well Number 327233 YUKON 20 FED COM 303H ⁸Operator Name ⁷OGRID No. ⁹Elevation 3535 7377 EOG RESOURCES, INC. ¹⁰Surface Location UL or lot no. Section Township Rang Lot Idn Feet from the North/South line Feet from the East/West line County 20 24-S 34 - E495' NORTH 2243 EAST LEA Β ¹¹Bottom Hole Location If Different From Surface UL or lot no. Section Township Lot Idn Feet from the North/South line Feet from the East/West line County Rang 100' 670' 29 SOUTH EAST Ρ 24-S 34-ELEA ²Dedicated Acres ³Joint or Infill ⁴Consolidation Code ⁵Order No. 640.00

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



Released to Imaging: 9/22/2021 1:27:51 PM

S\SURVEY\EOG_MIDLAND\YUKON_20_FED_COM\FINAL_PRODUCTS\LO_YUKON_20_FC_303H_C102_REV1.DWG 1/28/2021 12:25:12 PM bgregory

Page 25 of 38

Revised Permit Information 2/1/2021:

Yukon 20 Fed Com #303H Well Name:

Location:

SHL: 495' FNL & 2243' FEL, Section 20, T-24-S, R-34-E, Lea Co., N.M. BHL: 100' FSL & 670' FEL, Section 29, T-24-S, R-34-E, Lea Co., N.M.

Casing Program:

Hole		Csg				DFmin	DF _{min}	DF _{min}
Size	Interval	OD	Weight	Grade	Conn	Collapse	Burst	Tension
16"	0'-1,140'	13.375"	54.5#	J-55	STC	1.125	1.25	1.60
12.25"	0'-4,000'	9.625"	40#	J-55	LTC	1.125	1.25	1.60
12.25"	4,000' - 5,050'	9.625"	40#	HCK-55	LTC	1.125	1.25	1.60
8.75"	0'-10,655'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60
8.5"	10,655' –	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60
	20,587'							

Variance is requested to waive the centralizer requirements for the 9-5/8" casing in the 12-1/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 12-1/4" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive any centralizer requirements for the 5-1/2" casing in the 8-3/4" and 8-1/2" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 8-3/4" and 8-1/2" hole interval to maximize cement bond and zonal isolation.

Slurry Description

	No.		Yld				
Depth	Sacks	ppg	Ft ³ /sk				
1,140'	310	13.5	1.73	Lead: Class C + 4			
				Cello-Flake (TO			
	100	14.8	1.34	Tail: Class C + 0			

Cementing Program:

Depth	Sacks	ppg	Ft ⁻ /SK	Surry Description
1,140'	310	13.5	1.73	Lead: Class C + 4.0% Bentonite + 0.5% CaCl ₂ + 0.25 lb/sk
				Cello-Flake (TOC @ Surface)
	100	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2%
				Sodium Metasilicate (TOC @ 940')
5,050'	740	12.7	2.22	Lead: Class C + 10% NaCl + 6% Bentonite Gel + 3% MagOx
				(TOC @ Surface)
	320	14.8	1.21	Tail: Class C + 10% NaCl + 3% MagOx (TOC @ 4,040')
20,587'	540	11.0	3.21	Lead: Class C + 3% CaCl2 + 3% Microbond (TOC @ 4,550')
	2,590	14.4	1.2	Tail: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3%
				Microbond (TOC @ 9,705')

.

Additive	Purpose
Bentonite Gel	Lightweight/Lost circulation prevention
Calcium Chloride	Accelerator
Cello-flake	Lost circulation prevention
Sodium Metasilicate	Accelerator
MagOx	Expansive agent
Sodium Chloride	Accelerator
FL-62	Fluid loss control
Halad-344	Fluid loss control
Halad-9	Fluid loss control
HR-601	Retarder
Microbond	Expansive Agent

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.


Depth	Туре	Weight (ppg)	Viscosity	Water Loss
0-1,140'	Fresh - Gel	8.6-8.8	28-34	N/c
1,140' – 5,050'	Brine	8.6-8.8	28-34	N/c
5,050' - 20,587'	Oil Base	8.8-9.5	58-68	N/c - 6

495' FNL 2243' FEL Section 20 T-24-S, R-34-E

Proposed Wellbore Revised 2/1/2021

API: 30-025-47170

KB: 3,560' GL: 3,535'





EOG Resources - Midland

Lea County, NM (NAD 83 NME) Yukon 20 Fed Com #303H

OH

Plan: Plan #0.1 RT

Standard Planning Report

29 January, 2021



Planning Report

Database: Company: Project: Site: Well: Wellbore: Design:			ME)	TVD Refere MD Referer North Refe	ice:	 	Vell #303H KB = 26' @ 3561.0us KB = 26' @ 3561.0us Grid ⁄linimum Curvature	
Project	Lea County, N	IM (NAD 83 NM	IE)					
Geo Datum:	US State Plane North American New Mexico Ea	1983 Datum 1983		System Datu	m:	Me	an Sea Level	
Site	Yukon 20 Fed	Com						
Site Position: From: Position Uncertainty:	Мар	0.0 usft	Northing: Easting: Slot Radius:		07.00 usft L	.atitude: .ongitude: Grid Converge	ence:	32.2085042°N 103.4892387°W 0.45 °
Well	#303H							
Well Position	+N/-S +E/-W	162.0 usft -449.0 usft	Northing: Easting:		440,775.00 u 801,958.00 u		tude: gitude:	32.2089592°N 103.4906862°W
Position Uncertainty		0.0 usft	Wellhead Ele	vation:		Gro	und Level:	3,535.0 usft
Wellbore	OH							
Magnetics	Model Na	me	Sample Date	Declinati (°)	on	Dip A (°	-	Field Strength (nT)
	IGF	RF2020	12/8/2020		6.57		59.92	47,546.33418453
Design	Plan #0.1 RT							
Audit Notes:								
Version:			Phase:	PLAN	Tie C	On Depth:	0.0	
Vertical Section:		(u	rom (TVD) sft)	+N/-S (usft)	+E/-\ (usf	ťt)	Directio (°)	
		C	0.0	0.0	0.0)	170.52	
Plan Survey Tool Pro	gram	Date 1/29/2	2021					
Depth From (usft)	Depth To (usft)	Survey (Wellbo	ore)	Tool Name		Remarks		
1 0.0	20,587.0	Plan #0.1 RT (()	EOG MWD+IFF MWD + IFR1	1			



Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well #303H
Company:	EOG Resources - Midland	TVD Reference:	KB = 26' @ 3561.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 26' @ 3561.0usft
Site:	Yukon 20 Fed Com	North Reference:	Grid
Well:	#303H	Survey Calculation Method:	Minimum Curvature
Wellbore:	ОН		
Design:	Plan #0.1 RT		

Plan Sections

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,125.6	16.51	73.79	2,114.2	33.0	113.5	2.00	2.00	0.00	73.79	
7,042.9	16.51	73.79	6,828.8	423.0	1,455.5	0.00	0.00	0.00	0.00	
7,868.6	0.00	0.00	7,643.0	456.0	1,569.0	2.00	-2.00	0.00	180.00	
9,905.1	0.00	0.00	9,679.5	456.0	1,569.0	0.00	0.00	0.00	0.00	KOP(Yukon 20 Fed
10,125.5	26.46	180.00	9,892.2	406.0	1,569.0	12.00	12.00	81.65	180.00	FTP(Yukon 20 Fed
10,655.0	90.00	179.47	10,156.9	-21.5	1,571.8	12.00	12.00	-0.10	-0.60	
15,406.8	90.00	179.47	10,157.0	-4,773.0	1,616.0	0.00	0.00	0.00	0.00	Fed Perf 1(Yukon 2
20,587.0	90.00	179.52	10,157.0	-9,953.0	1,662.0	0.00	0.00	0.00	88.55	PBHL(Yukon 20 Fe



Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well #303H
Company:	EOG Resources - Midland	TVD Reference:	KB = 26' @ 3561.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 26' @ 3561.0usft
Site:	Yukon 20 Fed Com	North Reference:	Grid
Well:	#303H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.1 RT		

Planned Survey

Measure Depth (usft)	i Inc	clination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
	0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
10	0.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.00	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.00	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.0	0.00	0.00	500.0 600.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.00	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
	0.00	0.00	0.00	1,100.0	0.0 0.0	0.0	0.0 0.0	0.00 0.00	0.00	0.00
	0.0 0.0	0.00 0.00	0.00 0.00	1,200.0 1,300.0	0.0	0.0 0.0	0.0	0.00	0.00 0.00	0.00 0.00
	0.0	2.00	73.79	1,300.0	0.0	1.7	-0.2	2.00	2.00	0.00
1,50		4.00	73.79	1,499.8	1.9	6.7	-0.8	2.00	2.00	0.00
1,60		6.00	73.79	1,599.5	4.4	15.1	-1.8	2.00	2.00	0.00
	0.00	8.00	73.79	1,698.7	7.8	26.8	-3.3	2.00	2.00	0.00
1,80		10.00	73.79	1,797.5	12.1	41.8	-5.1	2.00	2.00	0.00
	0.00	12.00	73.79	1,895.6	17.5	60.1	-7.3	2.00	2.00	0.00
2,00		14.00	73.79	1,993.1	23.7	81.7	-10.0	2.00	2.00	0.00
	0.0	16.00	73.79	2,089.6	31.0	106.6	-13.0	2.00	2.00	0.00
	25.6	16.51	73.79	2,114.2	33.0	113.5	-13.8	2.00	2.00	0.00
	0.00	16.51	73.79	2,185.6	38.9	133.8	-16.3	0.00	0.00	0.00
2,30	0.00	16.51	73.79	2,281.4	46.8	161.0	-19.6	0.00	0.00	0.00
2,40		16.51	73.79	2,377.3	54.7	188.3	-23.0	0.00	0.00	0.00
	0.00	16.51	73.79	2,473.2	62.7	215.6	-26.3	0.00	0.00	0.00
	0.00	16.51	73.79	2,569.1	70.6	242.9	-29.6	0.00	0.00	0.00
	0.00	16.51	73.79	2,664.9	78.5	270.2	-33.0	0.00	0.00	0.00
2,80	0.00	16.51	73.79	2,760.8	86.5	297.5	-36.3	0.00	0.00	0.00
2,90	0.00	16.51	73.79	2,856.7	94.4	324.8	-39.6	0.00	0.00	0.00
3,00	0.00	16.51	73.79	2,952.6	102.3	352.1	-42.9	0.00	0.00	0.00
3,10	0.00	16.51	73.79	3,048.4	110.3	379.4	-46.3	0.00	0.00	0.00
	0.00	16.51	73.79	3,144.3	118.2	406.7	-49.6	0.00	0.00	0.00
3,30	0.00	16.51	73.79	3,240.2	126.1	434.0	-52.9	0.00	0.00	0.00
3,40	0.00	16.51	73.79	3,336.1	134.1	461.3	-56.3	0.00	0.00	0.00
	0.0	16.51	73.79	3,431.9	142.0	488.6	-59.6	0.00	0.00	0.00
	0.0	16.51	73.79	3,527.8	149.9	515.9	-62.9	0.00	0.00	0.00
	0.00	16.51	73.79	3,623.7	157.9	543.2	-66.2	0.00	0.00	0.00
3,80	0.00	16.51	73.79	3,719.6	165.8	570.4	-69.6	0.00	0.00	0.00
3.90	0.00	16.51	73.79	3,815.4	173.7	597.7	-72.9	0.00	0.00	0.00
4,00		16.51	73.79	3,911.3	181.7	625.0	-76.2	0.00	0.00	0.00
	0.0	16.51	73.79	4,007.2	189.6	652.3	-79.6	0.00	0.00	0.00
4,20		16.51	73.79	4,103.1	197.5	679.6	-82.9	0.00	0.00	0.00
4,30		16.51	73.79	4,198.9	205.5	706.9	-86.2	0.00	0.00	0.00
4,40	0.00	16.51	73.79	4,294.8	213.4	734.2	-89.5	0.00	0.00	0.00
4,40		16.51	73.79	4,390.7	213.4	761.5	-09.9	0.00	0.00	0.00
4,60		16.51	73.79	4,486.6	229.2	788.8	-96.2	0.00	0.00	0.00
4,70		16.51	73.79	4,582.4	237.2	816.1	-99.5	0.00	0.00	0.00
4,80		16.51	73.79	4,678.3	245.1	843.4	-102.9	0.00	0.00	0.00
						870.7				
4,90	0.0 0.0	16.51 16.51	73.79 73.79	4,774.2 4,870.1	253.0 261.0	870.7 898.0	-106.2 -109.5	0.00 0.00	0.00 0.00	0.00 0.00
5,00		16.51	73.79	4,870.1	261.0	925.3	-109.5	0.00	0.00	0.00
5,20		16.51	73.79	4,905.9 5,061.8	276.8	925.5	-112.0	0.00	0.00	0.00
0,20		10.01	10.10	0,001.0	210.0	502.0	110.2	0.00	0.00	0.00



Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well #303H
Company:	EOG Resources - Midland	TVD Reference:	KB = 26' @ 3561.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 26' @ 3561.0usft
Site:	Yukon 20 Fed Com	North Reference:	Grid
Well:	#303H	Survey Calculation Method:	Minimum Curvature
Wellbore:	ОН		
Design:	Plan #0.1 RT		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,300.0	16.51	73.79	5,157.7	284.8	979.8	-119.5	0.00	0.00	0.00
5,400.0	16.51	73.79	5,253.6	292.7	1,007.1	-122.8	0.00	0.00	0.00
5,500.0	16.51	73.79	5,349.5	300.6	1,034.4	-126.2	0.00	0.00	0.00
5,600.0	16.51	73.79	5,445.3	308.6	1,061.7	-120.2	0.00	0.00	0.00
5,700.0	16.51	73.79	5,541.2	316.5	1,089.0	-132.8	0.00	0.00	0.00
5,800.0	16.51	73.79	5,637.1	324.4	1,116.3	-136.1	0.00	0.00	0.00
5,900.0	16.51	73.79	5,733.0	332.4	1,143.6	-139.5	0.00	0.00	0.00
6,000.0	16.51	73.79	5,828.8	340.3	1,170.9	-142.8	0.00	0.00	0.00
6,100.0	16.51	73.79	5,924.7	348.2	1,198.2	-146.1	0.00	0.00	0.00
6,200.0	16.51	73.79	6,020.6	356.2	1,225.5	-149.5	0.00	0.00	0.00
6,300.0	16.51	73.79	6,116.5	364.1	1,252.8	-152.8	0.00	0.00	0.00
6,400.0	16.51	73.79	6,212.3	372.0	1,280.1	-156.1	0.00	0.00	0.00
6,500.0	16.51	73.79	6,308.2	380.0	1,307.4	-159.4	0.00	0.00	0.00
6,600.0	16.51	73.79	6,404.1	387.9	1,334.7	-162.8	0.00	0.00	0.00
6,700.0	16.51	73.79	6,500.0	395.8	1,361.9	-166.1	0.00	0.00	0.00
6,800.0	16.51	73.79	6,595.8	403.8	1,389.2	-169.4	0.00	0.00	0.00
	16 64				1 446 5	170.0	0.00	0.00	0.00
6,900.0	16.51	73.79	6,691.7	411.7	1,416.5	-172.8	0.00	0.00	0.00
7,000.0	16.51	73.79	6,787.6	419.6	1,443.8	-176.1	0.00	0.00	0.00
7,042.9	16.51	73.79	6,828.8	423.0	1,455.5	-177.5	0.00	0.00	0.00
7,100.0	15.37	73.79	6,883.6	427.4	1,470.6	-179.3	2.00	-2.00	0.00
7,200.0	13.37	73.79	6,980.5	434.3	1,494.4	-182.3	2.00	-2.00	0.00
7,300.0	11.37	73.79	7,078.2	440.3	1,515.0	-184.8	2.00	-2.00	0.00
7,400.0	9.37	73.79	7,176.5	445.3	1,532.3	-186.9	2.00	-2.00	0.00
7,500.0	7.37	73.79	7,275.5	449.4	1,546.3	-188.6	2.00	-2.00	0.00
7,600.0	5.37	73.79	7,374.8	452.5	1,556.9	-189.9	2.00	-2.00	0.00
7,700.0	3.37	73.79	7,474.5	454.6	1,564.2	-190.8	2.00	-2.00	0.00
7,800.0	1.37	73.79	7,574.4	455.8	1,568.2	-191.3	2.00	-2.00	0.00
7,868.6	0.00	0.00	7,643.0	456.0	1,569.0	-191.4	2.00	-2.00	0.00
7,900.0	0.00	0.00	7,674.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,000.0	0.00	0.00	7,774.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,100.0	0.00	0.00	7,874.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,200.0	0.00	0.00	7,974.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,200.0	0.00	0.00	8,074.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,400.0	0.00	0.00	8,174.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,500.0	0.00	0.00	8,274.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,600.0	0.00	0.00	8,374.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,700.0	0.00	0.00	8,474.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,800.0	0.00	0.00	8,574.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
8,900.0	0.00	0.00	8,674.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,000.0	0.00	0.00	8,774.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,100.0	0.00	0.00	8,874.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
0.000.0									
9,200.0	0.00	0.00	8,974.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,300.0	0.00	0.00	9,074.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,400.0	0.00	0.00	9,174.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,500.0	0.00	0.00	9,274.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,600.0	0.00	0.00	9,374.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,700.0	0.00	0.00	9,474.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,800.0	0.00	0.00	9,574.4	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,905.1	0.00	0.00	9,679.5	456.0	1,569.0	-191.4	0.00	0.00	0.00
9,905.1	2.39	180.00	9,679.5 9,699.4	455.6	1,569.0	-191.4	12.00	12.00	0.00
9,925.0 9,950.0	5.39	180.00	9,699.4 9,724.4	455.6 453.9	1,569.0	-190.9	12.00	12.00	0.00
9,900.0		100.00	3,124.4	400.9	1,509.0	-109.3	12.00	12.00	0.00
9,975.0	8.39	180.00	9,749.2	450.9	1,569.0	-186.3	12.00	12.00	0.00
10,000.0	11.39	180.00	9,773.8	446.6	1,569.0	-182.1	12.00	12.00	0.00
10,025.0	14.39	180.00	9,798.2	441.0	1,569.0	-176.6	12.00	12.00	0.00

1/29/2021 9:48:48AM

Page 5

COMPASS 5000.15 Build 91

.



Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well #303H
Company:	EOG Resources - Midland	TVD Reference:	KB = 26' @ 3561.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 26' @ 3561.0usft
Site:	Yukon 20 Fed Com	North Reference:	Grid
Well:	#303H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.1 RT		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,050.0	17.39	180.00	9,822.2	434.2	1,569.0	-169.8	12.00	12.00	0.0
10,075.0	20.39	180.00	9,845.9	426.1	1,569.0	-161.8	12.00	12.00	0.0
			,						
10,100.0	23.39	180.00	9,869.1	416.8	1,569.0	-152.6	12.00	12.00	0.0
10,125.5	26.46	180.00	9,892.2	406.0	1,569.0	-142.0	12.00	12.00	0.0
10,150.0	29.40	179.94	9,913.8	394.5	1,569.0	-130.7	12.00	12.00	-0.2
10,175.0	32.39	179.88	9,935.3	381.7	1,569.0	-118.1	12.00	12.00	-0.2
10,200.0	35.39	179.84	9,956.0	367.8	1,569.1	-104.3	12.00	12.00	-0.1
10,225.0	38.39	179.80	9.976.0	352.8	1,569.1	-89.5	12.00	12.00	-0.1
			- ,						
10,250.0	41.39	179.77	9,995.2	336.7	1,569.2	-73.7	12.00	12.00	-0.1
10,275.0	44.39	179.74	10,013.5	319.7	1,569.2	-56.9	12.00	12.00	-0.1
10,300.0	47.39	179.71	10,030.9	301.8	1,569.3	-39.2	12.00	12.00	-0.1
10,325.0	50.39	179.69	10,047.3	282.9	1,569.4	-20.6	12.00	12.00	-0.1
10,350.0	53.39	179.66	10,062.8	263.3	1,569.5	-1.1	12.00	12.00	-0.0
10,375.0	56.39	179.64	10,077.1	242.8	1,569.7	19.0	12.00	12.00	-0.0
10,400.0	59.39	179.62	10,090.4	221.6	1,569.8	40.0	12.00	12.00	-0.0
10,400.0	62.39	179.61	10,102.6	199.8	1,569.9	40.0 61.5	12.00	12.00	-0.0
10,425.0	65.39	179.61	10,102.6	199.8	1,569.9	83.7	12.00	12.00	-0.0 -0.0
					,				
10,475.0	68.39	179.57	10,123.4	154.4	1,570.3	106.4	12.00	12.00	-0.0
10,500.0	71.39	179.56	10,132.0	130.9	1,570.5	129.6	12.00	12.00	-0.0
10,525.0	74.39	179.54	10,139.3	107.0	1,570.6	153.2	12.00	12.00	-0.0
10,550.0	77.39	179.53	10,145.4	82.7	1,570.8	177.1	12.00	12.00	-0.0
10,575.0	80.39	179.51	10,150.3	58.2	1,571.0	201.3	12.00	12.00	-0.0
10,600.0	83.39	179.50	10,153.8	33.5	1,571.3	225.8	12.00	12.00	-0.0
				8.6		220.0			-0.0
10,625.0	86.39	179.48	10,156.0		1,571.5		12.00	12.00	
10,650.0	89.39	179.47	10,156.9	-16.4	1,571.7	275.0	12.00	12.00	-0.0
10,655.0	90.00	179.47	10,156.9	-21.5	1,571.8	280.0	12.00	12.00	-0.0
10,700.0	90.00	179.47	10,156.9	-66.4	1,572.2	324.4	0.00	0.00	0.0
10,800.0	90.00	179.47	10,156.9	-166.4	1,573.1	423.2	0.00	0.00	0.0
10,900.0	90.00	179.47	10,157.0	-266.4	1,574.0	522.0	0.00	0.00	0.0
11,000.0	90.00	179.47	10,157.0	-366.4	1,575.0	620.8	0.00	0.00	0.0
11,100.0	90.00	179.47	10,157.0	-466.4	1,575.9	719.6	0.00	0.00	0.0
11,200.0	90.00	179.47	10,157.0	-566.4	1,576.8	818.4	0.00	0.00	0.0
	90.00	179.47	10,157.0	-666.4		917.1	0.00	0.00	0.0
11,300.0			,		1,577.8				
11,400.0	90.00	179.47	10,157.0	-766.4	1,578.7	1,015.9	0.00	0.00	0.0
11,500.0	90.00	179.47	10,157.0	-866.4	1,579.6	1,114.7	0.00	0.00	0.0
11,600.0	90.00	179.47	10,157.0	-966.4	1,580.6	1,213.5	0.00	0.00	0.0
11,700.0	90.00	179.47	10,157.0	-1,066.4	1,581.5	1,312.3	0.00	0.00	0.0
11,800.0	90.00	179.47	10,157.0	-1,166.4	1,582.4	1,411.1	0.00	0.00	0.0
11,900.0	90.00	179.47	10,157.0	-1,266.4	1,583.3	1,509.8	0.00	0.00	0.0
12,000.0	90.00	179.47	10,157.0	-1,366.3	1,584.3	1,608.6	0.00	0.00	0.0
12,100.0	90.00	179.47	10,157.0	-1,466.3	1,585.2	1,707.4	0.00	0.00	0.0
12,200.0	90.00	179.47	10,157.0	-1,566.3	1,586.1	1,806.2	0.00	0.00	0.0
12,300.0	90.00	179.47	10,157.0	-1,666.3	1,587.1	1,905.0	0.00	0.00	0.0
12,400.0	90.00	179.47	10,157.0	-1,766.3	1,588.0	2,003.8	0.00	0.00	0.0
12,500.0	90.00	179.47	10,157.0	-1,866.3	1,588.9	2,102.5	0.00	0.00	0.0
12,600.0	90.00	179.47	10,157.0	-1,966.3	1,589.9	2,201.3	0.00	0.00	0.0
12,700.0	90.00	179.47	10,157.0	-2,066.3	1,590.8	2,300.1	0.00	0.00	0.0
12,800.0	90.00	179.47	10,157.0	-2,166.3	1,591.7	2,398.9	0.00	0.00	0.0
12,900.0	90.00	179.47	10,157.0	-2,266.3	1,592.7	2,497.7	0.00	0.00	0.0
13,000.0	90.00	179.47	10,157.0	-2,366.3	1,593.6	2,596.5	0.00	0.00	0.0
13,100.0	90.00	179.47	10,157.0	-2,466.3	1,594.5	2,695.2	0.00	0.00	0.0
13,200.0	90.00	179.47	10,157.0	-2,400.3	1,594.5	2,095.2	0.00	0.00	0.0
13,300.0	90.00	179.47	10,157.0	-2,666.3	1,596.4	2,892.8	0.00	0.00	0.0
13,400.0	90.00	179.47	10,157.0	-2,766.3	1,597.3	2,991.6	0.00	0.00	0.0

1/29/2021 9:48:48AM

Page 6

COMPASS 5000.15 Build 91

.



Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well #303H
Company:	EOG Resources - Midland	TVD Reference:	KB = 26' @ 3561.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 26' @ 3561.0usft
Site:	Yukon 20 Fed Com	North Reference:	Grid
Well:	#303H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #0.1 RT		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
13,500.0	90.00	179.47	10,157.0	-2,866.3	1,598.2	3,090.4	0.00	0.00	0.00
13,600.0	90.00	179.47	10,157.0	-2,966.3	1,599.2	3,189.2	0.00	0.00	0.00
13,700.0	90.00	179.47	10,157.0	-3,066.3	1,600.1	3,287.9	0.00	0.00	0.00
13,800.0	90.00	179.47	10,157.0	-3,166.3	1,601.0	3,386.7	0.00	0.00	0.00
13,900.0	90.00	179.47	10,157.0	-3,266.3	1,602.0	3,485.5	0.00	0.00	0.00
14,000.0	90.00	179.47	10,157.0	-3,366.3	1,602.9	3,584.3	0.00	0.00	0.00
14,100.0	90.00	179.47	10,157.0	-3,466.3	1,603.8	3,683.1	0.00	0.00	0.00
14,200.0	90.00	179.47	10,157.0	-3,566.3	1,604.8	3,781.9	0.00	0.00	0.00
14,300.0	90.00	179.47	10,157.0	-3,666.2	1,605.7	3,880.6	0.00	0.00	0.00
14,400.0	90.00	179.47	10,157.0	-3,766.2	1,606.6	3,979.4	0.00	0.00	0.00
14,500.0	90.00	179.47	10,157.0	-3,866.2	1,607.6	4,078.2	0.00	0.00	0.00
14,600.0	90.00	179.47	10,157.0	-3,966.2	1,608.5	4,177.0	0.00	0.00	0.00
14,700.0	90.00	179.47	10,157.0	-4,066.2	1,609.4	4,275.8	0.00	0.00	0.00
14,800.0	90.00	179.47	10,157.0	-4,166.2	1,610.3	4,374.6	0.00	0.00	0.00
14,900.0	90.00	179.47	10,157.0	-4,266.2	1,611.3	4,473.3	0.00	0.00	0.00
15,000.0	90.00	179.47	10,157.0	-4,366.2	1,612.2	4,572.1	0.00	0.00	0.00
15,100.0	90.00	179.47	10,157.0	-4,466.2	1,613.1	4,670.9	0.00	0.00	0.00
15,200.0	90.00	179.47	10,157.0	-4,566.2	1,614.1	4,769.7	0.00	0.00	0.00
15,300.0	90.00	179.47	10,157.0	-4,666.2	1,615.0	4,868.5	0.00	0.00	0.00
15,406.8	90.00	179.47	10,157.0	-4,773.0	1,616.0	4,974.0	0.00	0.00	0.00
15,500.0	90.00	179.47	10,157.0	-4,866.2	1,616.9	5,066.0	0.00	0.00	0.00
15,600.0	90.00	179.47	10,157.0	-4,966.2	1,617.8	5,164.8	0.00	0.00	0.00
15,700.0	90.00	179.47	10,157.0	-5,066.2	1,618.7	5,263.6	0.00	0.00	0.00
15,800.0	90.00	179.47	10,157.0	-5,166.2	1,619.6	5,362.4	0.00	0.00	0.00
15,900.0	90.00	179.47	10,157.0	-5,266.2	1,620.6	5,461.2	0.00	0.00	0.00
16,000.0	90.00	179.47	10,157.0	-5,366.2	1,621.5	5,560.0	0.00	0.00	0.00
16,100.0	90.00	179.47	10,157.0	-5,466.2	1,622.4	5,658.7	0.00	0.00	0.00
16,200.0	90.00	179.47	10,157.0	-5,566.2	1,623.3	5,757.5	0.00	0.00	0.00
16,300.0	90.00	179.48	10,157.0	-5,666.2	1,624.3	5,856.3	0.00	0.00	0.00
16,400.0	90.00	179.48	10,157.0	-5,766.2	1,625.2	5,955.1	0.00	0.00	0.00
16,500.0	90.00	179.48	10,157.0	-5,866.2	1,626.1	6,053.9	0.00	0.00	0.00
16,600.0	90.00	179.48	10,157.0	-5,966.1	1,627.0	6,152.6	0.00	0.00	0.00
16,700.0	90.00	179.48	10,157.0	-6,066.1	1,627.9	6,251.4	0.00	0.00	0.00
16,800.0	90.00	179.48	10,157.0	-6,166.1	1,628.8	6,350.2	0.00	0.00	0.00
16,900.0	90.00	179.48	10,157.0	-6,266.1	1,629.7	6,449.0	0.00	0.00	0.00
17,000.0	90.00	179.48	10,157.0	-6,366.1	1,630.6	6,547.8	0.00	0.00	0.00
17,100.0	90.00	179.48	10,157.0	-6,466.1	1,631.5	6,646.5	0.00	0.00	0.00
17,200.0	90.00	179.48	10,157.0	-6,566.1	1,632.4	6,745.3	0.00	0.00	0.00
17,300.0	90.00	179.48	10,157.0	-6,666.1	1,633.3	6,844.1	0.00	0.00	0.00
17,400.0	90.00	179.49	10,157.0	-6,766.1	1,634.2	6,942.9	0.00	0.00	0.00
17,500.0	90.00	179.49	10,157.0	-6,866.1	1,635.1	7,041.7	0.00	0.00	0.00
17,600.0	90.00	179.49	10,157.0	-6,966.1	1,636.0	7,140.4	0.00	0.00	0.00
17,700.0	90.00	179.49	10,157.0	-7,066.1	1,636.9	7,239.2	0.00	0.00	0.00
17,800.0	90.00	179.49	10,157.0	-7,166.1	1,637.8	7,338.0	0.00	0.00	0.00
17,900.0	90.00	179.49	10,157.0	-7,266.1	1,638.7	7,436.8	0.00	0.00	0.00
18,000.0	90.00	179.49	10,157.0	-7,366.1	1,639.6	7,535.5	0.00	0.00	0.00
18,100.0	90.00	179.49	10,157.0	-7,466.1	1,640.5	7,634.3	0.00	0.00	0.00
18,200.0	90.00	179.49	10,157.0	-7,566.1	1,641.4	7,733.1	0.00	0.00	0.00
18,300.0	90.00	179.49	10,157.0	-7,666.1	1,642.2	7,831.9	0.00	0.00	0.00
18,400.0	90.00	179.50	10,157.0	-7,766.1	1,643.1	7,930.6	0.00	0.00	0.00
18,500.0	90.00	179.50	10,157.0	-7,866.1	1,644.0	8,029.4	0.00	0.00	0.00
18,600.0	90.00	179.50	10,157.0	-7,966.1	1,644.9	8,128.2	0.00	0.00	0.00
18,700.0	90.00	179.50	10,157.0	-8,066.1	1,645.8	8,227.0	0.00	0.00	0.00
18,800.0	90.00	179.50	10,157.0	-8,166.1	1,646.6	8,325.7	0.00	0.00	0.00

Released to Imaging: 9/22/2021 1:27:51 PM

.



Planning Report

Database:	EDM	Local Co-ordinate Reference:	Well #303H
Company:	EOG Resources - Midland	TVD Reference:	KB = 26' @ 3561.0usft
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 26' @ 3561.0usft
Site:	Yukon 20 Fed Com	North Reference:	Grid
Well:	#303H	Survey Calculation Method:	Minimum Curvature
Wellbore:	ОН		
Design:	Plan #0.1 RT		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
18,900.0 19,000.0	90.00 90.00	179.50 179.50	10,157.0 10,157.0	-8,266.1 -8,366.1	1,647.5 1,648.4	8,424.5 8,523.3	0.00 0.00	0.00 0.00	0.00 0.00
19,100.0 19,200.0	90.00 90.00	179.50 179.50	10,157.0 10,157.0	-8,466.1 -8,566.0	1,649.3 1,650.1	8,622.1 8,720.8	0.00 0.00	0.00 0.00	0.00 0.00
19,300.0	90.00	179.50	10,157.0	-8,666.0	1,651.0	8,819.6	0.00	0.00	0.00
19,400.0 19,500.0	90.00 90.00	179.50 179.51	10,157.0 10.157.0	-8,766.0 -8,866.0	1,651.9 1,652.7	8,918.4 9,017.2	0.00 0.00	0.00 0.00	0.00 0.00
19,600.0	90.00	179.51	10,157.0	-8,966.0	1,653.6	9,017.2	0.00	0.00	0.00
19,700.0	90.00	179.51	10,157.0	-9,066.0	1,654.4	9,214.7	0.00	0.00	0.00
19,800.0	90.00	179.51	10,157.0	-9,166.0	1,655.3	9,313.5	0.00	0.00	0.00
19,900.0 20,000.0	90.00 90.00	179.51 179.51	10,157.0 10,157.0	-9,266.0 -9,366.0	1,656.2 1,657.0	9,412.3 9,511.0	0.00 0.00	0.00 0.00	0.00 0.00
20,000.0	90.00	179.51	10,157.0	-9,366.0 -9,466.0	1,657.0	9,511.0	0.00	0.00	0.00
20,200.0	90.00	179.51	10,157.0	-9,566.0	1,658.7	9,708.6	0.00	0.00	0.00
20,300.0	90.00	179.51	10,157.0	-9,666.0	1,659.6	9,807.3	0.00	0.00	0.00
20,400.0 20,500.0	90.00 90.00	179.51 179.52	10,157.0 10,157.0	-9,766.0 -9,866.0	1,660.4 1,661.3	9,906.1 10,004.9	0.00 0.00	0.00 0.00	0.00 0.00
20,587.0	90.00	179.52	10,157.0	-9,953.0	1,662.0	10,090.8	0.00	0.00	0.00

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
KOP(Yukon 20 Fed Com - plan hits target cer - Point		0.00	9,679.5	456.0	1,569.0	441,231.00	803,527.00	32.2101787°N	103.4856021°W
FTP(Yukon 20 Fed Com - plan hits target cer - Point		0.00	9,892.2	406.0	1,569.0	441,181.00	803,527.00	32.2100412°N	103.4856034°W
Fed Perf 1(Yukon 20 Fe - plan hits target cer - Point		0.00	10,157.0	-4,773.0	1,616.0	436,002.00	803,574.00	32.1958051°N	103.4855835°W
PBHL(Yukon 20 Fed Co - plan hits target cer - Point		0.00	10,157.0	-9,953.0	1,662.0	430,822.00	803,620.00	32.1815663°N	103.4855668°W

leogresources



To convert a Magnetic Direction to a Grid Direction, Add 6.12° To convert a Magnetic Direction to a True Direction, Add 6.57° East To convert a True Direction to a Grid Direction, Subtract 0.45°


Lea County, NM (NAD 83 NME)

Yukon 20 Fed Com #303H


Plan #0.1 RT

PROJECT DETAILS: Lea County, NM (NAD 83 NME) Geodetic System: US State Plane 1983 Datum: North American Datum 1983 Ellipsoid: GRS 1980






Page 37 of 3



vived by OCD: 9/22/2021 12:05:29 PM



4800-5100-

5400-

5700

6000-

6300-

6600-

6900-

7200-

7500-

7800-

8100-

8400-

8700-

9000-

9300

2100-

2400-

2700-

3000-

3300-

3600-

3900-


4200-

4500-


+++-

- + + + + .

_ _ _ _ _ _



West(-)/East(+)



Lea County, NM (NAD 83 NME) Yukon 20 Fed Com #303H OH Plan #0.1 RT 9:48, January 29 2021

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:
EOG RESOURCES INC	7377
P.O. Box 2267	Action Number:
Midland, TX 79702	51099
	Action Type:
	[C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
pkautz	None	9/22/2021

CONDITIONS

Page 38 of 38

Action 51099