

Well Name: CARSON UNIT 11	Well Location: T25N / R12W / SEC 11 / NWSW / 36.41206 / 108.08582	County or Parish/State: SAN JUAN / NM
Well Number: 313	Type of Well: OTHER	Allottee or Tribe Name:
Lease Number: NMSF078067	Unit or CA Name: CARSON UNIT--FRCL	Unit or CA Number: NMNM78385D
US Well Number: 300452773700S1	Well Status: Gas Well Shut In	Operator: DJR OPERATING LLC

Subsequent Report

Type of Submission: Subsequent Report	Type of Action: Plug and Abandonment
Date Sundry Submitted: 04/28/2021	Time Sundry Submitted: 09:55
Date Operation Actually Began: 04/20/2021	

Actual Procedure: The subject well was Plugged & Abandoned on 04/20/2021 per the attached detailed As Plugged Wellbore Diagram and Marker.

SR Attachments

Actual Procedure

- Carson_Unit_11_313_PXA_Marker_Template_20210428095536.pdf
- Carson_Unit_11_313_EOWR___AsPlugged_WBD_20210428095536.pdf

Well Name: CARSON UNIT 11	Well Location: T25N / R12W / SEC 11 / NWSW / 36.41206 / 108.08582	County or Parish/State: SAN JUAN / NM
Well Number: 313	Type of Well: OTHER	Allottee or Tribe Name:
Lease Number: NMSF078067	Unit or CA Name: CARSON UNIT--FRCL	Unit or CA Number: NMNM78385D
US Well Number: 300452773700S1	Well Status: Gas Well Shut In	Operator: DJR OPERATING LLC

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: DACYE SHULL	Signed on: APR 28, 2021 09:55 AM
Name: DJR OPERATING LLC	
Title: Regulatory Technician	
Street Address: 1 ROAD 3263	
City: AZTEC	State: NM
Phone: (505) 632-3476	
Email address: DSHULL@DJRLLC.COM	

Field Representative

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

BLM Point of Contact

BLM POC Name: WILLIAM F TAMBEKOU	BLM POC Title: PETROLEUM ENGINEER
BLM POC Phone: 7192698500	BLM POC Email Address: wtambekou@blm.gov
Disposition: Accepted	Disposition Date: 05/04/2021
Signature: William Max Tambekou	

DJR Operating, LLC

Carson Unit 11 313

API # 30-045-27737

NW/SW, Unit L, Sec. 11, T25N, R12W

San Juan County, NM



P&A End of Well Report
DJR Operating, LLC
Carson Unit 11 #313
API: 30-045-27737
NWSW L-11-25N-12W
San Juan County, NM

Spud Date: 04/20/1991

Plugged Date: 04/20/2021

4/19/21: Set CR at 1005'. PT casing, did not test.

4/20/21: Plug 1: Fruitland perfs: Mix and pump 12 sx class G cement + 2% CaCl₂ through CR. Plug 2: From top of CR at 1005', mix and place 88 sx class G + 2% CaCl₂ cement on top of CR, TOOH. WOC. Tagged at 122'. Plug 3: Mix and pump 10 sx class G cement to fill 4 1/2" casing. Cut off WH, TOC in annulus was 14'. Install P&A marker. Mix and pump 16 sx class G to top off cellar.

All cement used: Class G cement mixed at 15.8 ppg, 1.15 yield.

BLM Representative onsite to witness: Michael Gilbreath

**DJR Operating, LLC
P&A End of Well Report**

Carson Unit 11 313

API # 30-045-27737

NW/SW Unit L Sec.11, T25N, R12W

San Juan County, NM

GL 6225'

KB 6229'

Spud Date 4/20/1990

SURF CSG

Hole size 8.75"
Csg Size: 7"
Wt: 20#
Grade: J-55
ID: 6.456"
Depth 128'
casing cap ft³/ft: 0.2273
TOC: Circ to surf

FORMATION TOPS

Nacimiento	Surface
Ojo Alamo	162'
Kirtland	262'
Fruitland	738'
Pictured Cliffs	1114'

PROD CSG

Hole size 6.25"
Csg Size: 4.5"
Wt: 9.5#
Grade: J-55
ID: 4.090"
Depth 1197'
casing cap ft³/ft: 0.0912
Csg/Csg cap ft³/ft 0.1169
TOC: Circ to surf

Fruitland Coal perms
1065'-1108'

PBTD 1153'
TD 1195'

4-20-2021: Cut off WH, TOC in annulus was 14'. Install P&A marker. Mix and pump 16 sx class G to top off cellar

4-20-2021: Plug 3: Mix and pump 10 sx class G cement to fill 4 1/2" casing.

4-20-2021: Plug 2: From top of CR at 1005', mix and place 88 sx class G + 2% CaCl₂ cement on top of CR, TOOH.
WOC Tagged at 122'

4-20-2021: Plug 1: Fruitland perms: Mix and pump 12 sx class G cement + 2% CaCl₂ through CR.

4-19-2021: Set CR at 1005'. PT casing, did not test.

All cement used was class G mixed at 15.8 ppg, yield 1.15
Regulatory representative, Michael Gilbreath, BLM
GPS Coordinates: Lat: 36.412090519443154, Lng: -108.08659169822931

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 56507

CONDITIONS

Operator: DJR OPERATING, LLC 1 Road 3263 Aztec, NM 87410	OGRID: 371838
	Action Number: 56507
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
mkuehling	None	11/3/2021