

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Sundry Print Report

Well Name: ANGEL PEAK Well Location: T27N / R11W / SEC 20 / County or Parish/State: SAN

Well Number: 2 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

ELL

Lease Number: NMNM020496 Unit or CA Name: Unit or CA Number:

US Well Number: 300450637300S1 Well Status: Abandoned Operator: MORNINGSTAR

PARTNERS LP

### **Subsequent Report**

**Sundry ID: 2388391** 

Type of Submission: Subsequent Report

Type of Action: Plug and Abandonment

Date Sundry Submitted: 05/21/2021 Time Sundry Submitted: 08:38

**Date Operation Actually Began:** 05/04/2021

**Actual Procedure:** The permanent plug and abandonment of the Angel Peak #2 has been completed as of 5/13/2021. Attached are the Final WBD, Daily and Cementing Reports, and CBL.

### **SR Attachments**

### **Actual Procedure**

Angel\_Peak\_2\_CBL\_20210521083705.pdf

Angel\_Peak\_2\_\_P\_A\_Daily\_\_\_Cementing\_Reports\_20210521083635.pdf

Angel\_Peak\_2\_\_\_P\_A\_WBD\_Final\_20210521083621.pdf

County or Parish/State: SAN Well Location: T27N / R11W / SEC 20 /

NWSW / 36.558075 / -108.032104 JUAN / NM

Well Number: 2 Type of Well: CONVENTIONAL GAS

WELL

Allottee or Tribe Name:

Lease Number: NMNM020496 **Unit or CA Name: Unit or CA Number:** 

**US Well Number: 300450637300S1** Well Status: Abandoned **Operator: MORNINGSTAR** 

PARTNERS LP

### **Operator Certification**

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

**Operator Electronic Signature: CONNIE BLAYLOCK** Signed on: MAY 21, 2021 08:37 AM

Name: MORNINGSTAR PARTNERS LP

Title: Regulatory Technician Street Address: 400 W 7th St.

City: Forth Worth State: TX

Phone: (817) 334-7882

Email address: CBLAYLOCK@MSPARTNERS.COM

### **Field Representative**

Representative Name: Eric Kittinger

**Street Address:** 

City: State: Zip:

Phone:

Email address: ekittinger@mspartners.com

### **BLM Point of Contact**

**BLM POC Name: KENNETH G RENNICK BLM POC Title:** Petroleum Engineer

**BLM POC Phone:** 5055647742 BLM POC Email Address: krennick@blm.gov

**Disposition:** Accepted Disposition Date: 10/15/2021

Signature: Kenneth Rennick

Page 2 of 2

### AZTEC WELL-SERVICING

### AZTEC WELL SERVICING CO.

	_	-						•									
CUSTOME					ALTY COMI	PANY	DATE:		May 4, 202		API Number:	30-045-063		TYPE OF JOB:		P&A	
LEASE & V	VELL NAME	:	Angel Pe	ak #2			LOCATION	l:	Sec 20 T27	7N R11W	SERVICE SUP:		MICHEL C	RANE	_		
SERVICE (	CONTRACT	OR:	481				OPERATO	R:	AWS			COUNTY:		SAN JUAN	STATE:	NEW	MEXICO
MATERIAL	S FURNISH	IED:			TYPE OF PLU	JGS:	197 /	CSG. HARI		SQUEEZE	TOP		PL	YSICAL SLURR	-		
LINIAL	JIMIJE			<b>—</b>	OP	N/A	LIST	JOO. HARI	- MAINE.	MANIFOLD:	OF	SLURRY	SLURRY	WATER	PUMP	SLURRY:	MIX
					TTOM	0					EACH	WEIGHT:	YIELD:	REQ.:	TIME:	OLOTUT.	WATER:
					TTOW					NO	FLUID:	Lb/gal	Cuft/sk	Gals/sk	hr:mm	bbls	bbls
DDE ELUC	H - FRES	III MA TED					1			1							
PRE-FLUS	H - FRES	OH WAIER										-			<b> </b>		
															L		
																1	
															<b></b>		
												+			<del>                                     </del>	1	
AVAILABLE N	IIX WATER:	100.0	BBLS		AVAILABLE [	DISPLACEMENT	WATER:		BBLS							IIX WATER:	0.0
	HOLE			TBG	CSGD.P.			TBG	CSGD.P.					COLLAR DEPTH	IS		
SIZE	% EXCESS	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	SIZE	WEIGHT	TYPE	DEPTH			SHOE	FLOAT	STAGE		
12 1/4	100	307	9 5/8	32.30	H-40	307	2 3/8	4.70	J-55	6,311			0	0	0		
	LAST C				-CMT RET-BR		PERF DE				ONNECTION			WEL	LBORE FLUID		
SIZE	WEIGHT	TYPE	DEPTH		0 & TYPE	DEPTH	TOP	воттом	ī	SIZE	THREAD	ī		TYF		WEIGHT	
4 1/2	10.50	J-55	6,583		VA	N/A	0	0	1	2 3/8	8 ROUND	1		FRESH		8.30	
		EMENT VOLU		CAL. PSI		MAX PSI	OP. MAX		TBG. PSI		CASING PSI	<u>†                                     </u>		DISPLACEMENT F			ATER
		CASING	TOTAL	BUMP PLUG		EVERSE	SQ. PSI	RATED	OP		OP	1					URCE
TUBING	CASING	CASING	IUIAL		IOR					RATED		<del> </del>		TYPE	WEIGHT		
				0		0	500 PSI	0	0	0	0		FRE	SH WATER	8.30	CITY	WATER
		UBLE SETTING PRIOR TO CE															
		PUMP DE	TAILS:								DAILY SU	JMMARY:					
TIME	PRESSU	JRE - PSI	RATE	BBL FLUID	FLUID	SAFETY MEETIN	NG:	CREW	7	CO. REP	<b>Z</b>						
HR: MIN:	PIPE	ANNULUS	BPM:	PUMPED:	TYPE:	TEST LINES:				0	PSI	1					
						CIRCULATING V	VELL DIG:			WPS		1					
						ì				******		1					
6:00	-	-	-	-	-	Travel to loc.											
7:00	-	-	-	-	-	Service and	start rig and	d equip,	fill out JSA	, held safety	mtg.						
7:30	-	-	-	-	-	Road equip t	to new loc.										
9:00						Snot in unit :	and equin	(sandy l	nc had rig a	and several t	rucks stuck at s	ome noint)					
								(Sandy I	oc, nau ng e	and Severar	rucks stuck at a	some pomity					
11:30						RU unit and											
12:15						Check PSI or	n Well, 100 <sub>l</sub>	osi on cs	sg, 0psi on t	bg and BH.							
12:30	-	-	-	-		ND well head	d, NU BOP,	RU work	c floor.								
13:15			-			Release Pkr	and TOOH	w produ	ction tba. 5	9 stands. LD	22 its of bad tb	a down.(43	55' of tha	out of hole) enc	ountered tight	spot in th	ne
.00						csg, attempe						g ao,( .o.			vantor ou tigiti	oper t.	
16:45	-	-	-	-	-						and loaded the			50psi.			
17:00						Bleed of pres	ssure and p	ull up to	tight spot	and attempe	d to work thoug	h, unsucce	ssful.				
17:30						Secure well,	SDFN.										
18:00						Travel to AW	/S vard.										
							- <b>,</b>										
			<del>                                     </del>	1		1											
			<u> </u>	1		<b> </b>											
						1					<del></del>			<del></del>	<del></del>		
						İ											
			<del>                                     </del>			<del>                                     </del>											
			1	1		-											
						ļ											
			<u> </u>	<u> </u>		<u></u>											
						1					<del></del>			<del></del>	<del></del>		
			<b></b>														
			1	1		-											
						ļ											
		<u></u> _	<u></u>	<u>L</u>		<u> </u>											
						1									-		
						1											
			<del>                                     </del>	1		<del>                                     </del>											
			<u> </u>	1		<b> </b>											
			<u></u>	<u> </u>		<u></u>											
						1					<del></del>			<del></del>	<del></del>		
						1											
			<del>                                     </del>			<del>                                     </del>											
			1	1		<u> </u>											
						ļ											
		<u> </u>	<u></u>	<u> </u>		<u> </u>											
DUME		TO.	<del>  _</del>	-cT	TOTAL	DD: 0:	50:	Ι.	POT	A 7750	LL GEDVICES	00 000					
BUMPED		ТО		EST	TOTAL	BBL CMT.	PSI		SPOT		LL SERVICING	CO KEP.:			HEL CRANE		
PLUG:		MP		OAT	BBL.	RETURNS/			TOP	CUSTOME				JAS	SON PEACE		
		UG:		PMENT:		REVERSED:			MENT:	CUSTOME	R REP. SIGNATU	JRE:					
N/A	N.	/A	N	I/A	0.0	1.5	0		1163'					CUSTOME	R AUTHORIZING AGEN	NI.	

## AZTEC WELL-SERVICING

### AZTEC WELL SERVICING CO.

CUSTOME	R:	SOUTHLAND ROYALTY COMPANY				DATE:		May 5, 202	21	API Number:	30-045-06	373	TYPE OF JOB:		P & A		
LEASE & V	ELL NAME	i:	Angel Pe				LOCATION		Sec 20 T2		SERVICE SUP:		MICHEL C	-			
	CONTRACT		481				OPERATO		AWS			COUNTY:			STATE:		MEXICO
MATERIAL	S FURNISH	IED:			TYPE OF PLU		LIST	CSG. HARI	OWARE:	SQUEEZE	TOP			YSICAL SLURR			
					TTOM	N/A 0				MANIFOLD:	OF EACH	SLURRY WEIGHT:	SLURRY YIELD:	WATER REQ.:	PUMP TIME:	SLURRY:	MIX WATER:
					TTOW					NO	FLUID:	Lb/gal	Cuft/sk	Gals/sk	hr:mm	bbls	bbls
PRE-FLUS	H - FRES	H WATER															
																	<b></b>
																	<b></b>
																	ļ
																	-
					7	<b>~</b>											
						1 1											
AVAILABLE N	ΛΙΧ WATER·	100.0	BBI S		AVAII ABI E I	DISPLACEMENT	WATER:	300.0	BBLS			1	1	l	TOTAL M	IX WATER:	0.0
AVAILABLE	HOLE	100.0	DDEO	TBG	CSGD.P.	JIOI LAOLIIILIAI	MATER.		CSGD.P.					COLLAR DEPTH		IX WATER.	0.0
SIZE	% EXCESS	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	SIZE	WEIGHT		DEPTH			SHOE	FLOAT	STAGE	]	
12 1/4	100	307	9 5/8	32.30	H-40	307	2 3/8	4.70	J-55	6,311			0	0	0	1	
SIZE	WEIGHT	TYPE	DEPTH		-CMT RET-BR D & TYPE	DEPTH	TOP	BOTTOM	1	SIZE	ONNECTION THREAD	+		TYF	LBORE FLUID	WEIGHT	ł
4 1/2	10.50	J-55	6,583		V/A	N/A	0	0		2 3/8	8 ROUND			FRESH		8.30	l
		EMENT VOLU		CAL. PSI		MAX PSI	OP. MAX		TBG. PSI		CASING PSI			DISPLACEMENT F			ATER
TUBING	CASING	CASING	TOTAL	BUMP PLUG	TO R	EVERSE	SQ. PSI	RATED	OP	RATED	OP			TYPE	WEIGHT		URCE
				0		0	500 PSI	0	0	0	0		FRE	SH WATER	8.30	CITY	WATER
		JBLE SETTING PRIOR TO CE															
		PUMP DE	TAILS:								DAILY SU	JMMARY:					
TIME	PRESSU		RATE	BBL FLUID	FLUID	SAFETY MEETII	NG:	CREW		CO. REP							
HR: MIN:	PIPE	ANNULUS	BPM:	PUMPED:	TYPE:	TEST LINES:				0	PSI						
						CIRCULATING V	WELL RIG:			WPS							
8:00	-	-	-	-	-	Travel to loc											
9:00	-	-	-	-	-	Service and					mtg.						
9:15	-	-	-	-	-	Check PSI o					<u> </u>						
9:30										ally 21 jts fro	m float.						
11:15						RU WL, RIH		ig tag bt	m @ 6127'.								
12:45 13:45	-				_	WOO from re Make up and		mical au	ttor and au	4 4ba @6112!	PD WI						
15:00	-	-	-	-	-	LD 1 jt, RU p											
16:15				_							cut off piece.						
18:00	_	_	_	_	_						v tools, RD WL.						
19:00						Secure well,				,							
19:30						Travel to AW	/S yard.										
										BLM REP	ON LOC, CLAY Y	AZZIE					
				1													
				<u> </u>													
				1	]												
BUMPED	Dei	то	TE	EST	TOTAL	BBL CMT.	PSI		SPOT	AZTEC WE	LL SERVICING (	CO REP ·		MIC	HEL CRANE		
PLUG:	BU			OAT	BBL.	RETURNS/			TOP	CUSTOME					SON PEACE		-
		JG:		PMENT:		REVERSED:			MENT:		R REP. SIGNATU	JRE:					
N/A		/A		I/A	0.0	1.5	0		1163'	1				CUSTOME	R AUTHORIZING AGEN	IT	



### AZTEC WELL SERVICING CO.

CUSTOME	R:		SOUTHL	AND ROY	ALTY COM	PANY	DATE:		May 6, 202	21	API Number:	30-045-06	373	TYPE OF JOB:		P&A	
	ELL NAME		Angel Pe	eak #2			LOCATION		Sec 20 T2	7N R11W	SERVICE SUP:		MICHEL C				
	CONTRACT		481	1	T/05 05 01		OPERATO		AWS	Laguerae	700	_COUNTY:		SAN JUAN HYSICAL SLURE	STATE:		MEXICO
WAIERIAL	S FURNISH	HED:		-	TYPE OF PL	N/A	LIST	CSG. HAR	DWARE:	SQUEEZE MANIFOLD:	TOP OF	SLURRY	SLURRY	WATER	PUMP	SLURRY:	MIX
					TTOM	0				NO	EACH	WEIGHT:	YIELD:	REQ.:	TIME:		WATER:
											FLUID:	Lb/gal	Cuft/sk	Gals/sk	hr:mm	bbls	bbls
PRE-FLUS	H - FRES	SH WATER															
																	<u> </u>
					- J												1
AVAILABLE N	MIY WATED:	100.0	DDI C		AVAII ABI E	DISPLACEMENT	WATED:	300 (	) BBLS						TOTAL M	IX WATER:	0.0
AVAILABLE	HOLE	100.0	DDLS	TBG	iCSGD.P.	DISPLACEMENT	WAIER:		iCSGD.P.					COLLAR DEPTH		IX WATER.	0.0
SIZE	% EXCESS	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	SIZE	WEIGHT	TYPE	DEPTH			SHOE	FLOAT	STAGE	1	
12 1/4	100	307	9 5/8	32.30	H-40 -CMT RET-BR	307	2 3/8	4.70	J-55	6,311	CONNECTION	1	0	0	0		
SIZE	WEIGHT	TYPE	DEPTH		-CMT RET-BR D & TYPE	DEPTH	PERF DI TOP	BOTTON	Л	SIZE	THREAD	1		TYF	LBORE FLUID	WEIGHT	
4 1/2	10.50	J-55	6,583	ı	N/A	N/A	0	0	<u> </u>	2 3/8	8 ROUND	<u>L</u>		FRESH	WATER	8.30	
		EMENT VOLU		CAL. PSI		MAX PSI	OP. MAX		( TBG. PSI		CASING PSI			DISPLACEMENT F	ì	-	ATER
TUBING	CASING	CASING	TOTAL	BUMP PLUC	TOF	REVERSE	SQ. PSI	RATED		RATED	OP			TYPE	WEIGHT		DURCE
				0		0	500 PSI	0	0	0	0		FRE	SH WATER	8.30	CITY	WATER
		UBLE SETTING															
						1											
		PUMP DE		T	T						DAILY SU	JMMARY:					
TIME HR: MIN:	PRESSI PIPE	JRE - PSI ANNULUS	RATE BPM:	BBL FLUID PUMPED:	FLUID TYPE:	SAFETY MEETII TEST LINES:	NG:	CREW		CO. REP	PSI						
		74410200	D. 111.	1 01111 2.01		CIRCULATING V	VELL RIG:			WPS		-					
6:00	-	-	-	-	-	Travel to loc						4					
7:00		-	-	-	-	Service and	start rig an	d equip	fill out JSA	, held safety	/ mtg.						
7:15	-	-	-	-	-	Check PSI o	n Well, 0ps	i on csg	and BH, no	tbg in well.							
7:30						PU and make	e drilling Bl	HA, TIH	to 1940'.								
8:15						RU power sv	vivel, break	circula	tion w fresh	l <u>.</u>							
8:45						Mill on tight			966' +/- , PU	l 2 jts w swiv	vel to 2004'.						
9:30	-	-	-	-	-	RD power sv											
10:00 11:45	-	-	-	-	-						9' TOF, LD 1 jt. (			through 4880')			
13:15		_	_	_	_	TOOH, LD de			is and lost t	one, pump c	onventional 125	obis of fres	ol I.				
14:45						RU WL, run	•		surface, RD	WL.							
16:45						TIH open en											
17:15						Secure well,	SDFN.										
17:30						Travel to AW	/S yard.										
		<del>                                     </del>	<del>                                     </del>			<del> </del>											
										RI M REP (	ON LOC, CLAY Y	Δ77IF					
										SEM INEF C	LOO, OLAI I	,					
		1		1		1											
	-												-				
		ļ		1		1											
		-															
		1	<del>                                     </del>			1											
		-															
		<del>                                     </del>		1													
		<del>                                     </del>		<u> </u>		1											
		<u> </u>	1														
		<u> </u>															
		İ															
BUMPED		I TO		EST	TOTAL	BBL CMT.	PSI		SPOT		LL SERVICING	CO REP.:			HEL CRANE		
PLUG:		JMP		OAT	BBL.	RETURNS/			TOP	CUSTOME				JA	SON PEACE		
N/A		UG:		PMENT:	PUMPED: 0.0	REVERSED: 1.5	CSG.:		MENT: 1163'	CUSTOME	R REP. SIGNATI	JKE:		CUSTOME	ER AUTHORIZING AGEN	IT	
		naging:							. 100	1							

## AZTEC WELL-SERVICING CO

### AZTEC WELL SERVICING CO.

	_	-															
CUSTOME					ALTY COMI	PANY	DATE:		May 7, 202		API Number:	30-045-06		TYPE OF JOB:		P & A	
	VELL NAME		Angel Pe	ak #2			LOCATION		Sec 20 T27	7N R11W	SERVICE SUP:		MICHEL C		•		
SERVICE (	CONTRACT	OR:	481				OPERATO	R:	AWS			COUNTY:		SAN JUAN	STATE:	NEW	MEXICO
MATERIAL	S FURNISH	IED:			TYPE OF PLU		LIST	CSG. HARD	WARE:	SQUEEZE	TOP		PH	YSICAL SLURR	Y PROPERTIE		
					OP	N/A		· <u></u>		MANIFOLD:	OF	SLURRY	SLURRY	WATER	PUMP	SLURRY:	MIX
				BO	TTOM	0				NO	EACH	WEIGHT:	YIELD:	REQ.:	TIME:		WATER:
											FLUID:	Lb/gal	Cuft/sk	Gals/sk	hr:mm	bbls	bbls
PRE-FLUS	H - FRES	SH WATER															
Plug #1, Da	akota and F	Fish Tops: N	/I&P 16 sx	s, 15.8# cl	ass G cmt,	from 6105' to	5900' TOC,	, Disp w	22bbls.		5,900	15.80	18.40	5.00		3.3	1.9
Plug #2, G	allup Top: I	M&P 16 sxs	, 15.8# cla	ass G cmt,	from 5418'	to 5213' TOC	, Disp w 19.	.5bbls.			5,213	15.80	18.40	5.00		3.3	1.9
•			,								,						
															<del></del>		
															<b></b>		
					J	4											
					1	1.1											
AVAILABLE N	/IX WATER:	100.0	BBLS		AVAILABLE I	DISPLACEMENT V	WATER:	300.0	BBLS			•			TOTAL N	IIX WATER:	3.8
	HOLE				CSGD.P.		T		-CSGD.P.					COLLAR DEPTH		<u> </u>	
SIZE	% EXCESS	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	SIZE	WEIGHT	TYPE	DEPTH			SHOE	FLOAT	STAGE	1	
12 1/4	100	307	9 5/8	32.30	H-40	307	2 3/8	4.70	J-55	6,311			0	0	0	1	
	LAST C				-CMT RET-BR		PERF DE				ONNECTION			WEL	LBORE FLUID	•	
SIZE	WEIGHT	TYPE	DEPTH		O & TYPE	DEPTH	TOP	воттом	Ī	SIZE	THREAD	]		TYP		WEIGHT	
4 1/2	10.50	J-55	6,583		V/A	N/A	0	0	Ī	2 3/8	8 ROUND			FRESH V		8.30	
CALCULA	TED DISPLAC	EMENT VOLU	ME; BBL	CAL. PSI	CAL.	MAX PSI	OP. MAX	MAX	TBG. PSI	MAX	CASING PSI			DISPLACEMENT FI	LUID	W	ATER
TUBING	CASING	CASING	TOTAL	BUMP PLUG	TO R	EVERSE	SQ. PSI	RATED	OP	RATED	OP	1		TYPE	WEIGHT	SO	URCE
				0		0	500 PSI	0	0	0	0	1	FRES	SH WATER	8.30	CITY	WATER
EXPLAN	IATION: TRO	UBLE SETTING	TOOL.														
		PRIOR TO CE															
		PUMP DE	TAILS:								DAILY SU	JMMARY:					
TIME	PRESSI	JRE - PSI	RATE	BBL FLUID	FLUID	SAFETY MEETIN	NG:	CREW		CO. REP	-						
HR: MIN:	PIPE	ANNULUS	BPM:	PUMPED:	TYPE:	TEST LINES:	10.	ORLEN		0	PSI	1					
						CIRCULATING V	VELL RIG:			WPS		1					
6:00		-		-		Travel to loc.				0							
	<u> </u>								CII 10 A	h - 1 -1							
7:00		-	-	-	-	Service and					mtg.						
7:15	-	-	-	-	-	Check PSI or	n Well, Opsi	on tbg,	csg and BH	ł							
7:30						TIH open end	ded to 6105	', RU pur	np to tbg a	nd est circ w	2bbls of fresh.						
8:30						Plug #1, Dak	ota and Fis	h Tops:	M&P 16 sxs	s, 15.8# class	G cmt, from 61	05' to 5900	TOC, Dis	o w 22bbls.			
9:00						WOC, LD tbg	to 5802'. re	everse o	ut w 26bbls	of fresh. TC	OH to 5224'.						
13:45						TIH tag plug				,							
14:00		-	-	-		LD tbg to 54°				a w 2hhla af	frach						
		<u> </u>	<u> </u>	<u> </u>	-							. = = = = :					
14:15											m 5418' to 5213	TOC, DISP	W 19.500	S.			
14:45	-	-	-	-	-	LD tbg to 512			bbls of fre	esh.							
15:15						TOOH 52 sta	nds, EOT @	<b>2</b> 1876'.									
16:15						Secure well,	SDFN.										
16:30						Travel to AW	S yard.										
															-		
		<del>                                     </del>	<del>                                     </del>	1						DI M DEC 1	NI OC CACE	ADMITTE					
				-		-				BLINI KEP (	ON LOC, CASEY	AKNETTE					
			<u> </u>			<u> </u>											
										•							
				-		-											
		<u> </u>	-														
		1		1													
											-				-		
		t	1														
		<del>                                     </del>	<del>                                     </del>	1													
		<del>                                     </del>	<del>                                     </del>	1													
		ļ															
		l						1									
BUMPED	PSI	I TO	TE	EST	TOTAL	BBL CMT.	PSI	s	POT	AZTEC WE	LL SERVICING	CO REP.:		MIC	HEL CRANE		
PLUG:	BU	JMP	FL	OAT	BBL.	RETURNS/	LEFT ON		ТОР	CUSTOME	R REP.:			JAS	SON PEACE		
	PL	UG:		PMENT:	PUMPED:	REVERSED:	CSG.:	CE	MENT:	CUSTOME	R REP. SIGNATU	JRE:					
N/A	N	/A	N	I/A	0.0	1.5								CUSTOME	ER AUTHORIZING AGEN	NT	

### AZTEC WELL-SERVICING

### AZTEC WELL SERVICING CO.

CUSTOME						21	API Number:	30-045-063	373	TYPE OF JOB:		P&A					
	VELL NAME		Angel Pe	ak #2			LOCATION		Sec 20 T27	'N R11W	SERVICE SUP:		MICHEL C				
SERVICE (	CONTRACT	OR:	481				OPERATO	R:	AWS			COUNTY:		SAN JUAN	STATE:	NEW	MEXICO
MATERIAL	S FURNISH	IED:			TYPE OF PLU		LIST	SG. HARD	WARE:	SQUEEZE	TOP			IYSICAL SLURR			
					OP TTOM	N/A				MANIFOLD:	OF EACH	SLURRY	SLURRY	WATER	PUMP TIME:	SLURRY:	MIX
				ВО	ТТОМ	0				NO	EACH FLUID:	WEIGHT: Lb/gal	YIELD: Cuft/sk	REQ.: Gals/sk	hr:mm	bbls	WATER: bbls
PRF-FI US	H - FRES	H WATER								1							
			s. 15.8# cl	lass G cm	t. w 2% Cal	, from 4669' to	4400' TOC	. Disn w	16.5bbls.		4,400	15.80	24.15	5.00		4.3	2.5
						3431' to 3226'					3,226	15.80	18.40	5.00		3.3	1.9
		- p			,						-,	10.00		-			
					J	1											
					i	11											
AVAILABLE N	IIX WATER:	100.0	BBLS		AVAILABLE I	DISPLACEMENT	WATER:	300.0	BBLS					,	TOTAL M	IX WATER:	4.4
	HOLE			TBG	CSGD.P.			TBG	CSGD.P.					COLLAR DEPTH	is	[	
SIZE	% EXCESS	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	ł		SHOE	FLOAT	STAGE		
12 1/4	100	307	9 5/8	32.30	H-40	307	2 3/8	4.70	J-55	6,311			0	0	0		
SIZE	WEIGHT	TYPE	DEPTH		-CMT RET-BR	DEPTH	TOP	BOTTOM		SIZE	THREAD	4		TYP	LBORE FLUID	WEIGHT	
4 1/2	10.50	J-55	6,583		VA	N/A	0	0		2 3/8	8 ROUND	Ī		FRESH		8.30	
		EMENT VOLU		CAL. PSI		MAX PSI	OP. MAX		TBG. PSI		CASING PSI			DISPLACEMENT FI			ATER
TUBING	CASING	CASING	TOTAL	BUMP PLUG		EVERSE	SQ. PSI	RATED	OP	RATED	OP			TYPE	WEIGHT		URCE
				0		0	500 PSI	0	0	0	0		FRES	SH WATER	8.30		WATER
,		<u> </u>	<u> </u>														
		UBLE SETTING															
RUNNING C	ASING, ETC.,	PRIOR TO CE	MENTING:														
7045	PD 5001	PUMP DE			511115	0.5557/145571	10	005111		00 050	DAILY SU	IMMARY:					
TIME HR: MIN:	PRESSU	JRE - PSI ANNULUS	RATE BPM:	BBL FLUID PUMPED:	FLUID TYPE:	SAFETY MEETIN TEST LINES:	NG:	CREW		CO. REP	PSI	1					
TIIX. IVIIIV.	FIFE	ANNOLOS	DFIVI.	FOWIFED.	TIFE.	CIRCULATING V	VELL RIG:			WPS	FSI	-					
6:00	-					Travel to loc				WIO		<u> </u>					
7:00	-	-	-	-	-	Service and		d equip f	ill out JSA	held safety	mta						
7:15	-			_	-	Check PSI or					m.g.						
7:13		_	_	_													
8:45							tag plug #2 @ 5232', good tag. bg to 4604' and TOOH LD tagging sub.										
10:00										injection ra	to prossure up t	o 600 nei la	et 100 nei	in 50 sec. RD W	п		
11:15			_	_	-						2 bbls of fresh.		3t 100 pai	III 30 Sec. ND V	· L.		
12:15	-			_							2% Cal, from 4		' TOC Die	en w 16 5bble			
12:45				_		WOC, LD tbg						003 10 4400	100, Dis	sp w 10.5bbis.			
16:00				_		TIH tag plug				or irean, re	201110 00011						
16:15						LD tbg to 34				c w 3hhls of	fresh						
16:45											it, from 3431' to	3226' TOC	Disn w 12	hhls			
17:15						LD tbg to 31						,	2.0p <u>2</u>	20101			
17:45						Secure well,		0411111	22.0 0 0								
18:00						Travel to AW											
							· ,										
										BLM REP (	ON LOC, CLAY	/AZZIE					
											<u> </u>						
															_		
			Ĺ														
BUMPED	PSI	то	TE	ST	TOTAL	BBL CMT.	PSI	S	РОТ	AZTEC WE	LL SERVICING	CO REP.:		MIC	HEL CRANE		
PLUG:		IMP		TAC	BBL.	RETURNS/	LEFT ON		ОР	CUSTOME				JAS	SON PEACE		
		UG:		MENT:		REVERSED:	CSG.:		MENT:	CUSTOME	R REP. SIGNATU	JRE:		OLIOTE: :=	D ALITHODIZAGO ACTU		
N/A	N	/A	N	/A	0.0	1.5	0	1	163'					CUSTOME	R AUTHORIZING AGEN	ı	

## AZTEC WELL-SERVICING-

### AZTEC WELL SERVICING CO.

	_	-															
CUSTOME					ALTY COMI	PANY	DATE:		May 11, 20		API Number:	30-045-063		TYPE OF JOB:		P & A	
	VELL NAME		Angel Pe	ak #2			LOCATION		Sec 20 T27	N R11W	SERVICE SUP:		MICHEL C		•		
SERVICE (	CONTRACT	UR:	481				OPERATO	R:	AWS			COUNTY:		SAN JUAN	STATE:	NEW	MEXICO
MATERIAL	S FURNISH	IED:			TYPE OF PLU		LIST	CSG. HARD	WARE:	SQUEEZE	TOP		PH	YSICAL SLURR	Y PROPERTIE		
				T	OP	N/A				MANIFOLD:	OF	SLURRY	SLURRY	WATER	PUMP	SLURRY:	MIX
				BO	TTOM	0				NO	EACH	WEIGHT:	YIELD:	REQ.:	TIME:		WATER:
											FLUID:	Lb/gal	Cuft/sk	Gals/sk	hr:mm	bbls	bbls
PRE-FLUS	H - FRES	H WATER															
Plug #5, Cl	hacra Top:	M&P 17 sxs	s, 15.8# cl	ass G cmt,	, w 2% Cal,	from 2745' to	2527' TOC,	Disp w	9bbls.		2,527	15.80	19.55	5.00		3.5	2.0
Plug #6, P	C and (OCD	) Fruitland	Tops: M&	P 32 sxs,	15.8# class	G cmt, from 1	1845' to 143	5' TOC, I	Disp w 5bbl	s.	1,435	15.80	36.80	5.00		6.6	3.8
						-											
															<del></del>		
															<b></b>		
					J	4											
					1	H											
AVAILABLE N	IIX WATER:	100.0	BBLS		AVAILABLE [	DISPLACEMENT V	WATER:	300.0	BBLS					•	TOTAL N	IIX WATER:	5.8
	HOLE				CSGD.P.				-CSGD.P.					COLLAR DEPTH		<u> </u>	
SIZE	% EXCESS	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	SIZE	WEIGHT	TYPE	DEPTH			SHOE	FLOAT	STAGE		
12 1/4	100	307	9 5/8	32.30	H-40	307	2 3/8	4.70	J-55	6,311			0	0	0		
	LAST C				-CMT RET-BR		PERF DE				ONNECTION			WEL	LBORE FLUID		
SIZE	WEIGHT	TYPE	DEPTH	BRANI	0 & TYPE	DEPTH	TOP	BOTTOM	Ī	SIZE	THREAD	I		TYF	'E	WEIGHT	
4 1/2	10.50	J-55	6,583	N	V/A	N/A	0	0	<u></u>	2 3/8	8 ROUND	<u></u>		FRESH	WATER	8.30	
CALCULA	TED DISPLAC	EMENT VOLU	ME; BBL	CAL. PSI	CAL.	MAX PSI	OP. MAX	MAX	TBG. PSI	MAX	CASING PSI			DISPLACEMENT F	LUID	W	ATER
TUBING	CASING	CASING	TOTAL	BUMP PLUG	TO R	EVERSE	SQ. PSI	RATED	OP	RATED	OP			TYPE	WEIGHT	SO	URCE
				0		0	500 PSI	0	0	0	0		FRES	SH WATER	8.30	CITY	WATER
EXPLAN	IATION: TRO	UBLE SETTING	TOOL,														
		PRIOR TO CE															
		PUMP DE	TAILS:								DAILY SU	MMARY:					
TIME	PRESSU	JRE - PSI	RATE	BBL FLUID	FLUID	SAFETY MEETIN	IG:	CREW		CO. REP							
HR: MIN:	PIPE	ANNULUS	BPM:	PUMPED:	TYPE:	TEST LINES:				0	PSI	1					
						CIRCULATING W	/ELL RIG:			WPS		1					
6:00				-		Travel to loc.											
				_					611 a.u. 10 A	hald anfatu							
7:00	-			-		Service and					mtg.						
7:15	-	-	-	-	-	Check PSI or				1.							
7:30						TIH tag plug	#4 @3259',	good tag	g.								
7:45						LD tbg to 262	21' and TOC	DH.									
8:30						Pressure test	t csg @600	psi, no t	est lost 100	psi in 105 s	ec.						
8:45	-					RU WL, RIH a	and perf @	2675', no	injection r	ate lost 100	si in 1 min, RD	WL.(CCL s	topped wo	rking had to co	me out and re	place it)	
10:15		-		-			•				2 bbls of fresh.	•					
10:45											2% Cal, from 27		TOC Die	n w Ohble	-		
11:00		_	_									45 10 2521	100, Dis	p w Judia.			
		-	•		-	WOC, LD tbg				iresii, 100F	110 1014.						
14:00						TIH tag plug		_									
14:15						LD tbg to 184	15', RU pun	np to tbg	and est cir	c w 2bbls of	fresh.						
14:45						Pressure test	t csg @600	psi, no t	test, lost 10	0psi in 6 mir	١.						
15:00						Plug #6, PC a	and (OCD) I	Fruitland	Tops: M&F	32 sxs, 15.8	3# class G cmt,	from 1845'	to 1435' To	OC, Disp w 5bbl	s.		
15:15						LD tbg to 138	31', reverse	out w 8b	obls of fresl	n and TOOH	to 1071'.						
15:45						Secure well,	SDFN.										
16:00						Travel to AW	S vard.										
							, <i>t</i>										
			1														
			<del>                                     </del>														
			<u> </u>									/ A =====					
										BLM REP (	ON LOC, CLAY	AZŽIE					
			1														
			<del>                                     </del>														
		-	<del>                                     </del>	<u> </u>													
			<b> </b>	<del>                                     </del>													
				<del>                                     </del>													
		<u> </u>	<b>.</b>					1		T							
BUMPED		ТО		ST	TOTAL	BBL CMT.	PSI		POT		LL SERVICING	O REP.:			HEL CRANE		
PLUG:		IMP		OAT	BBL.	RETURNS/	LEFT ON		ТОР	CUSTOMER				JAS	SON PEACE		
		UG:		PMENT:		REVERSED:	CSG.:		MENT:	CUSTOMER	R REP. SIGNATU	JRE:					
N/A	N.	/A	N	I/A	0.0	1.5	0	1	163'					CUSTOME	R AUTHORIZING AGEN	NI	

## AZTEC WELL-SERVICING-

### AZTEC WELL SERVICING CO.

	_	*									J L L .						
CUSTOME	R:		SOUTHL	AND ROY	ALTY COMI	PANY	DATE:		May 12, 20		API Number:	30-045-063		TYPE OF JOB:		P & A	
	VELL NAME		Angel Pe	ak #2			LOCATION		Sec 20 T27	'N R11W	SERVICE SUP:		MICHEL C		•		
SERVICE (	CONTRACT	OR:	481				OPERATO	R:	AWS			COUNTY:		SAN JUAN	STATE:	NEW	MEXICO
	S FURNISH				TYPE OF PLU	JGS:	I IST (	CSG. HARD		SQUEEZE	TOP		PH	YSICAL SLURR	Y PROPERTIE		
MAILMAL		ild.		-	OP	N/A	LIST	JOG. HAND	WARE.	MANIFOLD:	OF	SLURRY	SLURRY	WATER	PUMP	SLURRY:	MIX
					TTOM	0					EACH	WEIGHT:	YIELD:	REQ.:	TIME:	OLOIGITI.	WATER:
					TTOW					NO	FLUID:	Lb/gal	Cuft/sk	Gals/sk	hr:mm	bbls	bbls
DDE ELLIE	H - FRES	LIMATED								•							
			45.00									15.00					
						l, from 1350' i					1,119	15.80	20.70	5.00	<del>                                     </del>	3.7	2.1
Plug #8, K	irtland and	Ojo Tops: I	M&P Insid	e/outside	plug w 93 s	xs 15.8# class	G cmt, fro	m 835' to	534' TOC,	Disp w 1.5b	534	15.80	106.95	5.00	L	19.0	11.1
																1	
															<del>                                     </del>	1	
					J	4											
					1	1.1											
AVAILABLE N	AIV WATED:	100.0	DDIC		AVAII ADI E I	DISPLACEMENT \	MATED.	300.0	DDI C						TOTAL N	IIX WATER:	13.2
AVAILABLE	HOLE	100.0	DDLO		CSGD.P.	DISPLACEMENT	VAIER.		·CSGD.P.					COLLAR DEPTH		IIA WATER.	13.2
SIZE	% EXCESS	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	SIZE	WEIGHT	TYPE	DEPTH			SHOE	FLOAT	STAGE	-	
					H-40										0	1	
12 1/4	100	307	9 5/8	32.30		307	2 3/8	4.70	J-55	6,311	ONNECTION	1	0	0		1	
0175	LAST C		DEDT!		-CMT RET-BR		TOP		}		ONNECTION	+			LBORE FLUID	WEIGHT	
SIZE	WEIGHT	TYPE	DEPTH		O & TYPE	DEPTH		воттом		SIZE	THREAD	1		TYF		WEIGHT	
4 1/2	10.50	J-55	6,583		VA	N/A	0	0		2 3/8	8 ROUND	<del>                                     </del>		FRESH		8.30	
		EMENT VOLU		CAL. PSI		MAX PSI	OP. MAX		TBG. PSI		CASING PSI	4		DISPLACEMENT F		+	ATER
TUBING	CASING	CASING	TOTAL	BUMP PLUG	TO R	EVERSE	SQ. PSI	RATED	OP	RATED	OP -	4 !		TYPE	WEIGHT		URCE
				0		0	500 PSI	0	0	0	0		FRES	SH WATER	8.30	CITY	WATER
											·			·			
		UBLE SETTING															
RUNNING C	ASING, ETC.,	PRIOR TO CE	MENTING:														
		PUMP DE	TAILS:								DAILY SU	IMMARY:					
TIME	PRESSU	JRE - PSI	RATE	BBL FLUID	FLUID	SAFETY MEETIN	IG:	CREW		CO. REP							
HR: MIN:	PIPE	ANNULUS	BPM:	PUMPED:	TYPE:	TEST LINES:				0	PSI	1					
						CIRCULATING W	/FIT RIG:			WPS							
C-00	-	-	-	-		î e	LLL IIIO.										
6:00				-		Travel to loc.											
7:00	-	-	-	-	-	Service and	start rig and	d equip, f	fill out JSA	, held safety	mtg.						
7:15	-	-	-	-	-	Check PSI or	n Well, 0 ps	i on tbg,	csg and Bl	Н.							
7:30						TIH tag plug	#6 @1475',	good tag	<b>j.</b>								
7:45						LD tbg to 125											
									d toot								
8:00						Pressure tes											
8:15	-	•	-	-	•	RU WL, RIH a	and perf @	1296', no	injection r	ate lost 100p	si in 70 sec, RE	WL.					
8:45	-	-	-	-	-	TIH open end	led to 1350	', RU pun	np to tbg ar	nd est circ w	2 bbls of fresh.						
9:15						Plug #7, Frui	tland Top:	M&P 18 s	sxs, 15.8# c	lass G cmt,	w 2% Cal, from	1350' to 111	9' TOC, D	sp w 4bbls.			
9:30	-		-			WOC, LD tbg	to 1009' re	verse ou	t w 8bbls o	f fresh. TOO	H to 696'.						
12:30						TIH tag plug											
									y								
12:45						LD tbg to 821											
13:15											n @ 350psi, RD	WL.					
14:00						TIH w 4-1/2"	CR and set	790', stir	ng out of Cl	R.							
14:30		<u> </u>	<u> </u>	<u></u>		Plug #8, Kirtl	and and Oj	jo Tops: I	M&P Inside	outside plug	g w 93 sxs 15.8	# class G cr	nt, from 83	85' to 534' TOC,	Disp w 1.5bbl	s.	
						70 sxs outsic									-		
15:30						LD tbg to 445				TOOHID	etting tool				-		
		<b> </b>	<del>                                     </del>	<del>                                     </del>		_	_	-a. W 4DL		, , , , , , , , , , , , , , , ,	y 1001.						
16:00		-	<del>                                     </del>	-		Secure well,											
16:30			<del>                                     </del>	<u> </u>		Travel to AW	১ yard.										
						<u> </u>											
		<u> </u>	<u></u>	<u> </u>		<u></u> _											
															-		
				Ì													
			1	1													
		-	1	}		1											
			1	1		ļ				BLM REP C	ON LOC, CLAY	AZZIE					
			ļ			<u> </u>											
						<u> </u>											
						1											
		-	1	1		1											
			ļ	1		-											
						ļ											
						<u> </u>											
						1											
						1											
			1	1		1											
			1					1		I							
BUMPED		то		EST	TOTAL	BBL CMT.	PSI		POT		LL SERVICING	CO REP.:			HEL CRANE		
PLUG:		MP		OAT	BBL.	RETURNS/	LEFT ON		ГОР	CUSTOMER				JAS	SON PEACE		
		UG:		PMENT:		REVERSED:	CSG.:			CUSTOMER	R REP. SIGNATU	JRE:					
N/A	N.	/A	N	I/A	0.0	1.5								CUSTOME	R AUTHORIZING AGEN	NT	



### AZTEC WELL SERVICING CO.

CUSTOME	USTOMER: SOUTHLAND ROYALTY COMPANY DATE: May 13, 2021								)21	API Number:	30-045-06	373	TYPE OF JOB:		P & A		
	VELL NAME	<u>:</u>	Angel Pe				LOCATION	<b>l</b> :	Sec 20 T2		SERVICE SUP:		MICHEL C	-			-
SERVICE (	CONTRACT	OR:	481				OPERATO	R:	AWS			COUNTY:		SAN JUAN	STATE:	NEW	MEXICO
MATERIAL	S FURNISH	IED:			TYPE OF PLU		LIST (	CSG. HARI	OWARE:	SQUEEZE	TOP			IYSICAL SLURR			
					TOP	N/A				MANIFOLD:	OF	SLURRY	SLURRY	WATER	PUMP	SLURRY:	MIX
				ВО	ТТОМ	0	_			NO	EACH FLUID:	WEIGHT: Lb/gal	YIELD: Cuft/sk	REQ.: Gals/sk	TIME: hr:mm	bbls	WATER: bbls
PRE-FLUS	H - FRES	H WATER								•		Ŭ					
			ce: M&P 1	71 sxs, 15	i.8# class G	cmt, w 2% ca	al, from 357	' to 0' Ur	ntil good cn	nt retuns up	0	15.80	196.65	5.00		35.0	20.4
					g and cellui						0	15.80	13.80	5.00		2.5	1.4
																	<b></b>
					J	4								ļ			
														<u> </u>			
AVAILABLE N	HOLE	100.0	BBLS	TRG	AVAILABLE D CSGD.P.	DISPLACEMENT	WATER:		BBLS -CSGD.P.					COLLAR DEPTH		IIX WATER:	21.8
SIZE	% EXCESS	DEPTH	SIZE	WEIGHT	TYPE	DEPTH	SIZE	WEIGHT		DEPTH			SHOE	FLOAT	STAGE	1	
12 1/4	100	307	9 5/8	32.30	H-40	307	2 3/8	4.70	J-55	6,311			0	0	0	1	
	LAST C			-	-CMT RET-BR		PERF DE				ONNECTION				LBORE FLUID		
SIZE	WEIGHT	TYPE	DEPTH		D & TYPE	DEPTH	TOP	воттом	1	SIZE	THREAD			TYP		WEIGHT	l
4 1/2	10.50	J-55 EMENT VOLU	6,583	CAL. PSI	V/A	N/A MAX PSI	OP. MAX	0	TBG. PSI	2 3/8	8 ROUND CASING PSI			FRESH V		8.30	ATER
TUBING	CASING	CASING	TOTAL	BUMP PLUG		EVERSE	SQ. PSI	RATED	OP	RATED	OP			TYPE	WEIGHT	1	URCE
10510	0/10/110	0/10/110	TOTAL	0	1011	0	500 PSI	0	0	0	0		FRES	SH WATER	8.30		WATER
							•	•									
		UBLE SETTING PRIOR TO CE															
KOMMING	ASING, LTC.,	PRIOR TO CL	WENTING.														
		PUMP DE	TAILS:								DAILY SU	MMARY:					
TIME	PRESSU	JRE - PSI	RATE	BBL FLUID	FLUID	SAFETY MEETIN	NG:	CREW		CO. REP							
HR: MIN:	PIPE	ANNULUS	BPM:	PUMPED:	TYPE:	TEST LINES:				0	PSI						
						CIRCULATING V	WELL RIG:			WPS							
6:00	-	-	-	-	-	Travel to loc											
7:00	-	-	-	-	-	Service and					mtg.						
7:15	-	-	-	-	-	Check PSI or				tbg in well.							
7:30				<del>                                     </del>	<del>                                     </del>	RU hydrovad		•									
7:45				-					t circ up cel	llur, 3bbls/mi	in @ 50psi, RD V	VL.					
8:15					<del>                                     </del>	TIH w 4-1/2"			MOD 4	74 45 0#		00/! /	0571 0				
8:30		-	-	-	-					/1 SXS, 15.8#	class G cmt, w	2% cal, fro	m 357° to U	)' Until good cmt	t retuns up cei	nur.	
9:00 9:15	-	-	-			WOC, LD all RD work floo				oquin							
12:00			_	_							@ surface, instal	II DHM					
13:15										top off csg a							
13:30						RD unit and											
14:30						Road unit an			rd.								
16:00						Spot equip @	② yard.										
										BLM REP (	ON LOC, CLAY Y	'AZZIE					
					<b></b>												
				<b> </b>	<b>—</b>												
				<del>                                     </del>													
				$\vdash$	<del></del>												
				-													
												-					
					<u> </u>												
					<b>├</b>			1									
BUMPED		ТО		EST	TOTAL	BBL CMT.	PSI		SPOT		LL SERVICING (	O REP.:			HEL CRANE		
PLUG:		MP UG:		OAT PMENT:	BBL.	RETURNS/ REVERSED:			TOP	CUSTOMER		IDE:		JAS	SON PEACE		
N/A		/A	-	I/A	0.0	1.5	/ERSED: CSG.: CEMENT: CUSTOMER RE			SIGNATO	,,,L.		CUSTOME	ER AUTHORIZING AGEN	٩T		

# MorningStar Operating, LLC

#### **Final P&A WBD**

9

8

7

6

Date 05/20/2021 KB =6,198 ft GL = 6,186 ft API# 30-045-06373

Spud Date: 04/06/1962 Completion Date: 04/25/1962

Plugged: 05/13/2021

Angel Peak 2 San Juan County, NM

TD - 6,584'

**Sfc Casing:** 10 jts 9-5/8" 32.3# csg set @ 307' Cement w/ 200 sx regular, ½ cu ft stata-crete 6/sk, 2%

A-6

Circulated to sfc.

Production Casing: 209 jts 4-½" J-55, 10.5# casing

set @ 6,583'. Baker Stage Tool @ 1,964'

Cement  $1^{st}$  stage w/ 200 sx Incor followed by 50 sx

regular.

Cemented 2<sup>nd</sup> stage w/ 120 sx Incor.

Perforations

**Dakota (1962):** 6,346' – 6,352' (4 spf)

6,388' - 6,400' (2 spf)

6,452' - 6,464' (2 spf)

Place 171 sx inside/outside
Plug to sfc
Top off w/ 12 sx
Set CICR @ 321'
Perf @ 357'

Kirtland: 782', OCD-785'
Fruitland: BLM-1,250', OCD-1,560'
Picture Cliffs: 1,792', OCD-1790'
Chacra: OCD-2,680'
MV Cliff House: 3,373', OCD-3,370'
Mancos: 4,550', OCD-4,565'
Gallup: 5,352', OCD-5350'

Ojo Alamo: 657', OCD-650'

93 sx cement from 534'-835' inside/outside (Kirtland, Ojo Alamo)

CICR @ 790' Perf @ 835'

18 sx cement from 1128' - 1350' (BLM Fruitland)

Perf @ 1296'

32 sx cement from 1475 - 1845' 1,560' (OCD Fruitland) (PC & OCD Fruitland) 1,792' BLM, 1,790' OCD (PC)

17 sx cement from 2534' - 2745' (Chacra)

Perf @ 2675'

16 sx cement from 3259' -3431' (Mesaverde)

21 sx cement from 4456' - 4669' (Mancos)

Perf @ 4615'

16 sx cement from 5,232' - 5,418' (Gallup)

16 sx balanced cmt plug from 6105' up to 5916'

Cut 2-3/8" tbg @ 6119' tbg tally

3 <u>1</u>

HowCo EZ Drill Packer @ 6,311'

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505** 

CONDITIONS

Action 57184

#### **CONDITIONS**

Operator:	OGRID:
MorningStar Operating LLC	330132
400 W 7th St	Action Number:
Fort Worth, TX 76102	57184
	Action Type:
	[C-103] Sub. Plugging (C-103P)

#### CONDITIONS

Created By	Condition	Condition Date
mkuehling	None	11/4/2021