

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Sundry Print Report of 10
11/04/2021

Well Name: POKER LAKE UNIT Well Location: T24S / R30E / SEC 7 / County or Parish/State: EDDY /

NWNE /

Well Number: 159 Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMLC068545 Unit or CA Name: POKER LAKE Unit or CA Number:

DELAWARE C NMNM71016G

US Well Number: 3001531691 **Well Status:** Producing Oil Well **Operator:** XTO PERMIAN

OPERATING LLC

NM

Accepted for record – NMOCD gc 11/12/2021

Notice of Intent

Sundry ID: 2641730

Type of Submission: Notice of Intent

Type of Action: Plug and Abandonment

Date Sundry Submitted: 10/26/2021 Time Sundry Submitted: 08:45

Date proposed operation will begin: 11/21/2021

Procedure Description: 1) MIRU plugging company. Set open top steel pits for plugging operations. 2) POOH laying down rods and pump. Unseat 5.5" x 2-7/8" TAC and POOH laying down 2-7/8" 6.5# J-55 tbg. ND WH, NU 3K manual BOP. 3) MIRU WL lubricators. RIH w/ 5.5" gauge ring & junk basket. Contact the engineer Nick Kreimeier (972-832-9601) if any tight spots exist. POOH w/ 5.5" gauge ring & junk basket. 4) RIH WL w/ 5.5" CIBP and dump bailer to 7,100'. Set CIBP and dump 35' cement over plug. WOC and Tag at least 7,065'. POOH & RDMO WL. 5) RIH 2-3/8" workstring, Load csg w/ 2% KCl with biocide and pressure test csg to 500 psi for 30 minutes. Notify BLM of result. POOH w/ 2-3/8" workstring. 6) RDMO PU, transport trucks, and pump truck. 7) Pull fluid from steel tank and haul to disposal. Release steel tank.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Poker Lake Unit 159 Proposed WBD 20211026204453.pdf

Released to Imaging: 11/12/2021 2:31:59 PM

Received by OCD: 11/5/2021 7:44:47 AM
Well Name: POKER LAKE UNIT
Well Location: T24S / R30E / SEC 7 /

NWNE /

County or Parish/State: EDDY

NM

Well Number: 159 Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMLC068545 Unit or CA Name: POKER LAKE

DELAWARE C

Unit or CA Number:

NMNM71016G

US Well Number: 3001531691 **Well Status:** Producing Oil Well **Operator:** XTO PERMIAN

OPERATING LLC

Conditions of Approval

Specialist Review

Poker_Lake_Unit_159_Sundry_ID_2641730_P_A_20211031084409.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: CASSIE EVANS Signed on: OCT 26, 2021 08:44 PM

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 Holiday Hill Road, Bldg 5

City: Midland State: TX

Phone: (432) 218-3671

Email address: CASSIE.EVANS@EXXONMOBIL.COM

Field Representative

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact


BLM POC Name: LONG VO

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972 BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved **Disposition Date:** 10/31/2021

Poker Lake Unit 159 - Current and Proposed WBD's



PLUG AND ABANDONMENT CONDITIONS OF APPROVAL

OPERATOR'S NAME: XTO PERMIAN OPERATING LLC

LEASE NO.: | NMLC068545

WELL NAME & NO.: | POKER LAKE UNIT 159

US Well Number: | 3001531691

LOCATION: Section 7, T.24 S., R.30 E., NMPM

COUNTY: Eddy County, New Mexico

1) MIRU plugging company. Set open top steel pits for plugging operations.

- 2) POOH laying down rods and pump. Unseat $5.5'' \times 2-7/8''$ TAC and POOH laying down 2-7/8'' 6.5# J-55 tbg. ND WH, NU 3K manual BOP.
- 3) MIRU WL lubricators. RIH w/ 5.5" gauge ring & junk basket. Contact the engineer Nick Kreimeier (972-832-9601) if any tight spots exist. POOH w/ 5.5" gauge ring & junk basket.
- 4) RIH WL w/ 5.5" CIBP and dump bailer to 7,100'. Set CIBP and dump 35' cement over plug. WOC and Tag at least 7,065'. POOH & RDMO WL.
- 5) RIH 2-3/8" workstring, Load csg w/ 2% KCl with biocide and pressure test csg to 500 psi for 30 minutes. Notify BLM of result. POOH w/ 2-3/8" workstring.
- RDMO PU, transport trucks, and pump truck.
- Pull fluid from steel tank and haul to disposal. Release steel tank.


Approval Subject to General Requirements and Special Stipulations Attached

- Spot 25 sx @ (3610' - 3470')

Perf & Spz @ 661'
170 Sx (661' to surface) (in/out)

Verify @ surface.

Secretary Potach, Medium Carre Poker Lake Unit 159 - Current and Proposed WBD's



BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

officer such as metes and bounds).

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

 The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized
- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged.</u>
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Received by OCD: 11/5/2021 7:44-47 AM

United States Department of the Interior

EURBAU OF LAND MANAGEMENT Carlsbad Field Office

620 E Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/mm

In Reply Refer To: 1310

Reclamation Objectives and Procedures

Recignation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent During the life of the development all disturbed areas not needed for active support of production operations should undergo "inform" reclamation in order to minimize the support of production operations support minerally minerally rectangulation in order to mineral and state of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration. including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the dismibance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives

To achieve these objectives, remove any and all contaminants, scrap/wash, equipment, pipelines and powerlines (Contact service companies, eliowing plenty of time to have the riggres and power lines and poles removed prior to reclamation, don't wait fill the last day and try to get them to remove infrared by the second poles. infrestructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, and the position of the original re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to saits of other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- I. The Application for Permit to Drill or Reenter (APD, Form 3160-3). Surface Use plan of Operations must include adequate measures for stabilization and reclamation of dishubed lands.

 Oil and Gas operators must plan for reclamation hold interim and final up from in the APD. Operations must include adequate mensures to autometion and remainded of contract and Oil and Gas operators must plan for reclamation, both interim and final, up from in the APD
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonnent, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within a months of well abandonment
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you make marked and provide you to be a special state of Operation and/or with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access row property of reclamation and access to a property of the removal of reclamation. Equipment to ensure the societies of the societies to the Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify Work was completed as per approved plans.

- The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will
- it is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved. releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell) Arthur Arias

Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist

Melissa Hom Environmental Protection Specialist

Kelsey Wade Environmental Protection Specialist

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 60387

CONDITIONS

| Operator: | OGRID: |
|----------------------------|-------------------------------------|
| XTO PERMIAN OPERATING LLC. | 373075 |
| 6401 HOLIDAY HILL ROAD | Action Number: |
| MIDLAND, TX 79707 | 60387 |
| | Action Type: |
| | [C-103] NOI Plug & Abandon (C-103F) |

CONDITIONS

| Created By | Condition | Condition Date |
|------------|-----------|----------------|
| gcordero | None | 11/12/2021 |