

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Name: GINNY CORBETT Well Location: T25N / R11W / SEC 31 / County or Parish/State: SAN

NWSE / 36.35672 / 108.04155 JUAN / NM

Well Number: 1 Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM76857 Unit or CA Name: Unit or CA Number:

US Well Number: 3004527125 Well Status: Abandoned Operator: DJR OPERATING LLC

Subsequent Report

Type of Submission: Subsequent Report

Type of Action: Plug and Abandonment

Date Sundry Submitted: 02/25/2021 Time Sundry Submitted: 01:26

Date Operation Actually Began: 01/18/2021

Actual Procedure: The subject well was plugged and abandoned per the attached detailed as plugged wellbore diagram and marker.

SR Attachments

Actual Procedure

PA_Marker_Ginny_Corbett_1_20210225132619.pdf

EOW_Ginny_Corbett_1_20210225132619.pdf

Well Location: T25N / R11W / SEC 31 /

NWSE / 36.35672 / 108.04155

County or Parish/State: SAN JUAN / NM

Zip:

Well Number: 1

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM76857

Unit or CA Name:

Unit or CA Number:

US Well Number: 3004527125

Well Status: Abandoned

Operator: DJR OPERATING LLC

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: FORD Signed on: FEB 25, 2021 01:26 PM

Name: DJR OPERATING LLC Title: Regulatory Specialist Street Address: 1 Road 3263

City: Aztec State: NM

Phone: (505) 632-3476

Email address: sford@djrllc.com

Field Representative

Representative Name:

Street Address:

City: State:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: WILLIAM F TAMBEKOU BLM POC Title: PETROLEUM ENGINEER

BLM POC Phone: 7192698500 BLM POC Email Address: wtambekou@blm.gov

Disposition: Accepted Disposition Date: 03/31/2021

Signature: William Max Tambekou

Page 2 of 2

DJR Operating, LLC Ginny Corbett # 1 API # 30-045-27125 NW/SE, Unit J, Sec. 31, T25N, R11W San Juan County, NM



P&A End of Well Report DJR Operating, LLC Ginny Corbett #001 API: 30-045-27125 NWSE J-31-25N-11W

Spud Date: 11/08/1988 Plugged Date: 01/18/2021

1-17-2021:

Plug 1: Gallup: Mix and pump balanced plug of 29 sx Class G cement from 4750'. WOC. Tagged at

4705'.

1-18-2021:

Plug 2: Mancos: Mix and pump balanced plug of 26 Class G cement from 3795'. WOC. Tagged at 3595'. Plug3: Mesa Verde and Chacra: Mix and pump balanced plug of 74 sx Class G cement + 2% CaCl2 from 1971'. WOC. Tagged at 1396'.

Plug 4: Pictured Cliffs and Fruitland: Mix and pump balanced plug of 56 sx Class G cement + 2% CaCl2 from 1173'. WOC. Tagged at 766'.

Plug 5: Kirtland, Ojo to surface. Mix and pump balanced plug of 118 sx Class G cement from 663', circulate cement to surface.

Plug 6: Top off with 34 sx Class G cement. Install P&A marker.

All cement used: Class G cement mixed at 15.8 ppg. 1.15 yield. BLM Representative onsite to witness: Darrell Priddy

P&A End of Well Report DJR Operating, LLC Ginny Corbett # 1

API # 30-045-27125 NW/SE, Unit J, Sec 31, T25N, R11W San Juan County, NM

GL 6425' KΒ 6437' **Spud Date** 11/8/1988 1-18-2021: Plug 6: Top off with 34 sx Class G cement. Install P&A marker. **SURF CSG FORMATION TOPS** Hole size 12.25" 1-18-2021: Plug 5: Kirtland, Ojo to surface. **Nacimiento** Surface Csg Size: 8.625" Mix and pump balanced plug of 118 sx Class Ojo Alamo 275' Wt: 24# G cement from 663', circulate cement to Grade: J-55 Kirtland 412' surface. ID: 8.097' Fruitland 875' **Depth** 283' **Pictured Cliffs** 1123' Csg cap ft³: 0.3576 Lewis 1311' TOC: Surf Chacra 1496' Mesa Verde 1921' Mancos 3745' 1-18-2021: Plug 4: Pictured Cliffs and Gallup 4758' Fruitland: Mix and pump balanced plug of 56 sx Class G cement + 2% CaCl2 from **PROD CSG** 1173'. WOC. Tagged at 766'. Hole size 7.875" Csg Size: 5.5" Wt: 15.5# Grade: K-55 1-18-2021: Plug3: Mesa Verde and Chacra: ID: 4.95" Mix and pump balanced plug of 74 sx Class Depth 4977' G cement + 2% CaCl2 from 1971'. WOC. Csq cap ft³: 0.1336 Tagged at 1396'. Csg/Csg 0.1926 Ann ft³: Csg/OH cap 0.1732 ft³: 1-18-2021: Plug 2: Mancos: Mix and pump Circ TOC: surf balanced plug of 26 Class G cement from 3795'. WOC. Tagged at 3595'. 1-17-2021: Plug 1: Gallup: Mix and pump ⋘ **Perfs** 4770'-4779' balanced plug of 29 sx Class G cement from 4750'. WOC. Tagged at 4705'.

> All cement was Class G cement mixed at 15.8 ppg, yield 1.15 Regulatory representative on site; Darrell Priddy, BLM GPS Coordinates: Lat; 36.356840, Long; -108.042198

PBTD

TD

4930'

4978'

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 57942

CONDITIONS

Operator:	OGRID:	
DJR OPERATING, LLC	371838	
1 Road 3263	Action Number:	
Aztec, NM 87410	57942	
	Action Type:	
	[C-103] Sub. Plugging (C-103P)	

CONDITIONS

Created By	Condition	Condition Date
mkuehling	None	11/15/2021