

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT

I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT

¹ Operator name and Address Colgate Operating, LLC 300 N Marienfeld Street, Suite 1000 Midland, Tx 79701		² OGRID Number 371449	
		³ Reason for Filing Code/ Effective Date NW	
⁴ API Number 30 – 015 – 46299	⁵ Pool Name WINCHESTER; BONE SPRING		⁶ Pool Code 65010
⁷ Property Code 326127	⁸ Property Name LADY FRANKLIN 25 STATE		⁹ Well Number 131H

II. ¹⁰ Surface Location

UL or lot no. D	Section 25	Township 19S	Range 28E	Lot Idn	Feet from the 1,045	North/South Line North	Feet from the 265	East/West line West	County Eddy
--------------------	---------------	-----------------	--------------	---------	------------------------	---------------------------	----------------------	------------------------	----------------

¹¹ Bottom Hole Location

UL or lot no. A	Section 25	Township 19S	Range 28E	Lot Idn	Feet from the 956	North/South line North	Feet from the 24	East/West line East	County Eddy
¹² Lse Code S	¹³ Producing Method Code P	¹⁴ Gas Connection Date 06/22/2020	¹⁵ C-129 Permit Number		¹⁶ C-129 Effective Date		¹⁷ C-129 Expiration Date		

III. Oil and Gas Transporters


¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
329097	LM TOUCHDOWN, LLC	O
329097	LM TOUCHDOWN, LLC	G

IV. Well Completion Data

²¹ Spud Date 03/15/2020	²² Ready Date 06/22/2020	²³ TD 13,505 MD 8,810 TVD	²⁴ PBTD 13,408 MD	²⁵ Perforations 8,944-13,317	²⁶ DHC, MC
²⁷ Hole Size		²⁸ Casing & Tubing Size	²⁹ Depth Set		³⁰ Sacks Cement
17.5		13.375	334		1,135
12.25		9.625	3,025		730
8.5		5.5	13,495		1,825

V. Well Test Data

³¹ Date New Oil 06/26/2020	³² Gas Delivery Date 06/26/2020	³³ Test Date 07/12/2020	³⁴ Test Length 24 hours	³⁵ Tbg. Pressure 176	³⁶ Csg. Pressure 776
³⁷ Choke Size 44/64	³⁸ Oil 1,709	³⁹ Water 2,269	⁴⁰ Gas 3,887		⁴¹ Test Method P

⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: 		OIL CONSERVATION DIVISION	
Printed name: Mikah Thomas		Approved by: <i>PATRICIA MARTINEZ</i>	
Title: Operations Tech		Title: <i>PETROLEUM SPECIALIST</i>	
E-mail Address: mthomas@colgateenergy.com		Approval Date: <i>12/7/2021</i>	
Date: 11/07/2021	Phone: 432-695-4272		

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office
☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-015-46299	² Pool Code 65010	³ Pool Name WINCHESTER; BONE SPRING
⁴ Property Code 326127	⁵ Property Name LADY FRANKLIN 25 STATE	
⁷ OGRID No. 371449	⁸ Operator Name COLGATE ENERGY LLC	⁶ Well Number 131H ⁹ Elevation 3358.8

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	25	19 S	28 E		1045	NORTH	265	WEST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	25	19 S	28 E		956	NORTH	24	EAST	EDDY

¹² Dedicated Acres	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
-------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

N89°25'05"E 2611.74 FT

NW CORNER SEC. 25
LAT. = 32.6391151°N
LONG. = 104.1389225°W
NMSP EAST (FT)
N = 596295.72
E = 601180.81

N4 CORNER SEC. 25
LAT. = 32.6391746°N
LONG. = 104.1304402°W
NMSP EAST (FT)
N = 596322.24
E = 603791.78

NE CORNER SEC. 25
LAT. = 32.6392359°N
LONG. = 104.1219567°W
NMSP EAST (FT)
N = 596349.64
E = 606403.13

AS-DRILLED BORE PATH (FTP TO BHL)
N89°24'26"E 5101.02 FT

LTP
(13427.38 MD) BHL

LADY FRANKLIN 25 STATE 131H
ELEV. = 3358.8'
LAT. = 32.6362493°N (NAD83)
LONG. = 104.1380578°W
NMSP EAST (FT)
N = 595253.63
E = 601448.90

AS-DRILLED KOP
955' FNL, 109' FWL
(8118 MD)
LAT. = 32.6364924°N
LONG. = 104.1385639°W
NMSP EAST (FT)
N = 595341.76
E = 601292.96

AS-DRILLED BOTTOM OF HOLE
(13505 MD)
LAT. = 32.6366078°N
LONG. = 104.1220277°W
NMSP EAST (FT)
N = 595393.50
E = 606383.18

W/4 CORNER SEC. 25
LAT. = 32.6318567°N
LONG. = 104.1389127°W
NMSP EAST (FT)
N = 593655.08
E = 601188.65

AS-DRILLED FIRST TAKE POINT
956' FNL, 100' FWL
(7990.59 MD)
LAT. = 32.6364896°N
LONG. = 104.1385940°W
NMSP EAST (FT)
N = 595340.75
E = 601283.69

E/4 CORNER SEC. 25
LAT. = 32.6319766°N
LONG. = 104.1219393°W
NMSP EAST (FT)
N = 593708.69
E = 606413.74

NOTE:
LATITUDE AND LONGITUDE COORDINATES ARE SHOWN USING THE NORTH AMERICAN DATUM OF 1983 (NAD83) LISTED NEW MEXICO STATE PLANE EAST COORDINATES ARE GRID (NAD83). BASIS OF BEARING AND DISTANCES USED ARE NEW MEXICO STATE PLANE EAST COORDINATES MODIFIED TO THE SURFACE, VERTICAL DATUM NAVD88.

SW CORNER SEC. 25
LAT. = 32.6245986°N
LONG. = 104.1388945°W
NMSP EAST (FT)
N = 591014.56
E = 601199.10

S/4 CORNER SEC. 25
LAT. = 32.6246368°N
LONG. = 104.1304029°W
NMSP EAST (FT)
N = 591033.35
E = 603813.37

SE CORNER SEC. 25
LAT. = 32.6246728°N
LONG. = 104.1219115°W
NMSP EAST (FT)
N = 591051.52
E = 606427.58

S89°35'18"W 2614.97 FT

S89°36'06"W 2614.91 FT

17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature

Mikah Thomas

Printed Name

mthomas@colgateenergy.com

E-mail Address

Date

06/12/2020

18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

MAY 5, 2020

Date of Survey

Signature and Seal of Professional Surveyor

William F. Jaramila

Certificate Number: **PL 12797**

WILLIAM F. JARAMILA
REGISTERED PROFESSIONAL SURVEYOR
NEW MEXICO
12797

SURVEY NO. 7383A

Intent ☐ As Drilled ☒

API #		
Operator Name: COLGATE ENERGY LLC	Property Name: LADY FRANKLIN 25 STATE	Well Number 131H

Kick Off Point (KOP)

UL D	Section 25	Township 19S	Range 28E	Lot	Feet 955	From N/S NORTH	Feet 109	From E/W WEST	County EDDY
Latitude 32.6364924					Longitude 104.1385639			NAD 83	

First Take Point (FTP)

UL D	Section 25	Township 19S	Range 28E	Lot	Feet 956	From N/S NORTH	Feet 100	From E/W WEST	County EDDY
Latitude 32.6364896					Longitude 104.1385940			NAD 83	

Last Take Point (LTP)

UL A	Section 25	Township 19S	Range 28E	Lot	Feet 955	From N/S NORTH	Feet 101	From E/W EAST	County EDDY
Latitude 32.6366093					Longitude 104.1222791			NAD 83	

Is this well the defining well for the Horizontal Spacing Unit?

☐ No

Is this well an infill well?

☐ No

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #		
Operator Name:	Property Name:	Well Number

KZ 06/29/2018



Colgate Energy

Eddy County, NM (N83-NME)

Lady Franklin 25

Lady Franklin 25 State 131H - Slot N02

30-015-46299

131H

Design: 131H

Standard Survey Report

04 May, 2020



Survey Report

Company:	Colgate Energy	Local Co-ordinate Reference:	Well Lady Franklin 25 State 131H - Slot N02
Project:	Eddy County, NM (N83-NME)	TVD Reference:	3358.8+26 @ 3384.80usft (HP481)
Site:	Lady Franklin 25	MD Reference:	3358.8+26 @ 3384.80usft (HP481)
Well:	Lady Franklin 25 State 131H	North Reference:	Grid
Wellbore:	131H	Survey Calculation Method:	Minimum Curvature
Design:	131H	Database:	EDM 5000.14 Single User Db

Project	Eddy County, NM (N83-NME)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site		Lady Franklin 25			
Site Position:		Northing:		596,295.72 usft	
From:		Easting:		601,180.81 usft	
Position Uncertainty:		Slot Radius:		Grid Convergence:	
Map		0.00 usft		13-3/16 "	
				32.63911509	
				-104.13892250	
				0.10 °	

Well		Lady Franklin 25 State 131H - Slot N02				
Well Position	+N-S	0.00 usft	Northing:	595,253.63 usft	Latitude:	32.63624934
	+E-W	0.00 usft	Easting:	601,448.90 usft	Longitude:	-104.13805779
Position Uncertainty		0.00 usft	Wellhead Elevation:	usft	Ground Level:	3,358.80 usft

Wellbore	131H				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	User Defined	3/15/2020	7.29	60.44	47,934.00000000

Design	131H				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00	89.41	

Survey Program	Date	5/4/2020			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
199.00	13,434.00	Survey #4 - FDIR Thru TD (131H)	MWD+IFR1+FDIR (SQC)	OWSG MWD + IFR1 + FDIR Correction	
13,434.00	13,505.00	Survey #5 - PTB (131H)	BLIND	BLIND	

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
199.00	0.23	271.21	199.00	0.01	-0.40	-0.40	0.12	0.12	0.00	
232.00	0.38	251.31	232.00	-0.03	-0.57	-0.57	0.55	0.45	-60.30	
428.00	0.61	289.40	427.99	0.11	-2.17	-2.17	0.20	0.12	19.43	
522.00	0.42	296.50	521.99	0.43	-2.95	-2.94	0.21	-0.20	7.55	
616.00	0.21	45.11	615.99	0.71	-3.14	-3.13	0.56	-0.22	115.54	
662.00	0.38	62.26	661.99	0.84	-2.94	-2.93	0.41	0.37	37.28	
756.00	0.38	63.33	755.98	1.12	-2.39	-2.37	0.01	0.00	1.14	
851.00	0.38	40.75	850.98	1.50	-1.90	-1.88	0.16	0.00	-23.77	
945.00	0.61	15.23	944.98	2.22	-1.56	-1.54	0.33	0.24	-27.15	



Survey Report

Company:	Colgate Energy	Local Co-ordinate Reference:	Well Lady Franklin 25 State 131H - Slot N02
Project:	Eddy County, NM (N83-NME)	TVD Reference:	3358.8+26 @ 3384.80usft (HP481)
Site:	Lady Franklin 25	MD Reference:	3358.8+26 @ 3384.80usft (HP481)
Well:	Lady Franklin 25 State 131H	North Reference:	Grid
Wellbore:	131H	Survey Calculation Method:	Minimum Curvature
Design:	131H	Database:	EDM 5000.14 Single User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
1,039.00	0.50	20.26	1,038.97	3.09	-1.29	-1.26	0.13	-0.12	5.35
1,133.00	0.64	34.41	1,132.97	3.91	-0.85	-0.81	0.21	0.15	15.05
1,228.00	0.65	12.91	1,227.96	4.87	-0.43	-0.38	0.25	0.01	-22.63
1,323.00	0.90	21.35	1,322.96	6.09	-0.04	0.02	0.29	0.26	8.88
1,418.00	0.94	25.70	1,417.94	7.49	0.57	0.65	0.08	0.04	4.58
1,512.00	1.07	21.36	1,511.93	9.00	1.22	1.32	0.16	0.14	-4.62
1,607.00	0.93	28.58	1,606.91	10.50	1.92	2.02	0.20	-0.15	7.60
1,702.00	1.05	25.99	1,701.90	11.96	2.67	2.79	0.13	0.13	-2.73
1,796.00	0.78	315.52	1,795.89	13.19	2.59	2.73	1.15	-0.29	-74.97
1,891.00	1.56	282.35	1,890.87	13.93	0.88	1.02	1.06	0.82	-34.92
1,986.00	1.55	281.83	1,985.84	14.47	-1.64	-1.49	0.02	-0.01	-0.55
2,081.00	1.57	283.13	2,080.80	15.03	-4.17	-4.01	0.04	0.02	1.37
2,175.00	1.70	286.04	2,174.76	15.71	-6.76	-6.60	0.16	0.14	3.10
2,270.00	1.91	278.18	2,269.72	16.32	-9.68	-9.51	0.34	0.22	-8.27
2,365.00	2.58	280.87	2,364.64	16.95	-13.35	-13.17	0.71	0.71	2.83
2,459.00	3.22	280.86	2,458.52	17.85	-18.02	-17.84	0.68	0.68	-0.01
2,554.00	3.19	280.92	2,553.37	18.85	-23.24	-23.04	0.03	-0.03	0.06
2,649.00	3.28	279.57	2,648.22	19.80	-28.51	-28.31	0.12	0.09	-1.42
2,744.00	3.58	279.44	2,743.05	20.74	-34.12	-33.90	0.32	0.32	-0.14
2,838.00	3.94	277.74	2,836.85	21.66	-40.21	-39.99	0.40	0.38	-1.81
2,933.00	4.08	275.87	2,931.62	22.44	-46.81	-46.57	0.20	0.15	-1.97
2,954.00	4.02	278.45	2,952.56	22.63	-48.28	-48.04	0.91	-0.29	12.29
3,061.00	4.86	277.62	3,059.24	23.78	-56.48	-56.23	0.79	0.79	-0.78
3,156.00	4.68	278.28	3,153.91	24.87	-64.31	-64.05	0.20	-0.19	0.69
3,251.00	4.52	279.74	3,248.61	26.06	-71.83	-71.56	0.21	-0.17	1.54
3,346.00	4.47	300.48	3,343.32	28.58	-78.71	-78.41	1.70	-0.05	21.83
3,441.00	4.40	298.86	3,438.04	32.21	-85.09	-84.76	0.15	-0.07	-1.71
3,535.00	4.14	304.64	3,531.78	35.88	-91.04	-90.67	0.53	-0.28	6.15
3,630.00	3.89	309.35	3,626.54	39.87	-96.36	-95.94	0.44	-0.26	4.96
3,725.00	3.56	304.35	3,721.34	43.58	-101.28	-100.83	0.49	-0.35	-5.26
3,819.00	4.16	299.30	3,815.13	46.90	-106.66	-106.18	0.73	0.64	-5.37
3,914.00	4.10	300.84	3,909.88	50.32	-112.59	-112.06	0.13	-0.06	1.62
4,008.00	2.81	303.36	4,003.71	53.31	-117.40	-116.84	1.38	-1.37	2.68
4,103.00	2.80	303.39	4,098.60	55.87	-121.28	-120.70	0.01	-0.01	0.03
4,197.00	2.79	304.67	4,192.48	58.44	-125.08	-124.47	0.07	-0.01	1.36
4,292.00	2.50	301.22	4,287.38	60.82	-128.75	-128.12	0.35	-0.31	-3.63
4,387.00	2.45	301.60	4,382.29	62.96	-132.25	-131.60	0.06	-0.05	0.40
4,481.00	2.19	293.81	4,476.22	64.74	-135.61	-134.93	0.43	-0.28	-8.29
4,576.00	1.97	295.43	4,571.15	66.17	-138.74	-138.05	0.24	-0.23	1.71
4,671.00	2.18	290.11	4,666.09	67.50	-141.91	-141.21	0.30	0.22	-5.60
4,765.00	2.34	288.92	4,760.02	68.73	-145.41	-144.69	0.18	0.17	-1.27
4,860.00	2.59	286.99	4,854.93	69.99	-149.29	-148.57	0.28	0.26	-2.03
4,954.00	2.74	295.65	4,948.83	71.58	-153.35	-152.61	0.46	0.16	9.21



Survey Report

Company:	Colgate Energy	Local Co-ordinate Reference:	Well Lady Franklin 25 State 131H - Slot N02
Project:	Eddy County, NM (N83-NME)	TVD Reference:	3358.8+26 @ 3384.80usft (HP481)
Site:	Lady Franklin 25	MD Reference:	3358.8+26 @ 3384.80usft (HP481)
Well:	Lady Franklin 25 State 131H	North Reference:	Grid
Wellbore:	131H	Survey Calculation Method:	Minimum Curvature
Design:	131H	Database:	EDM 5000.14 Single User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,049.00	1.96	287.27	5,043.75	73.05	-156.95	-156.19	0.90	-0.82	-8.82
5,143.00	0.89	253.39	5,137.72	73.32	-159.18	-158.42	1.40	-1.14	-36.04
5,237.00	1.42	278.74	5,231.70	73.29	-161.03	-160.27	0.77	0.56	26.97
5,332.00	1.57	282.16	5,326.67	73.74	-163.47	-162.70	0.18	0.16	3.60
5,427.00	1.85	290.61	5,421.63	74.55	-166.18	-165.40	0.40	0.29	8.89
5,505.28	2.09	298.78	5,499.86	75.68	-168.61	-167.82	0.47	0.30	10.44
00-LF25-131H-EON									
5,521.00	2.14	300.20	5,515.57	75.97	-169.11	-168.32	0.47	0.33	9.00
5,616.00	2.39	304.42	5,610.50	77.98	-172.28	-171.47	0.32	0.26	4.44
5,711.00	2.80	303.20	5,705.40	80.37	-175.86	-175.02	0.44	0.43	-1.28
5,806.00	1.08	314.65	5,800.34	82.27	-178.44	-177.58	1.85	-1.81	12.05
5,900.00	1.55	307.78	5,894.32	83.67	-180.07	-179.20	0.53	0.50	-7.31
5,995.00	1.74	300.57	5,989.28	85.19	-182.33	-181.44	0.30	0.20	-7.59
6,090.00	1.12	291.55	6,084.25	86.27	-184.43	-183.54	0.69	-0.65	-9.49
6,169.00	0.42	256.43	6,163.24	86.48	-185.43	-184.53	1.03	-0.89	-44.46
6,279.00	0.27	239.44	6,273.24	86.26	-186.05	-185.15	0.16	-0.14	-15.45
6,374.00	0.87	250.09	6,368.23	85.90	-186.92	-186.02	0.64	0.63	11.21
6,468.00	0.96	270.36	6,462.22	85.66	-188.38	-187.49	0.36	0.10	21.56
6,563.00	0.95	278.48	6,557.21	85.78	-189.95	-189.06	0.14	-0.01	8.55
6,658.00	1.64	287.10	6,652.18	86.30	-192.03	-191.13	0.75	0.73	9.07
6,753.00	1.79	289.35	6,747.14	87.19	-194.73	-193.82	0.17	0.16	2.37
6,848.00	1.81	278.69	6,842.09	87.91	-197.61	-196.70	0.35	0.02	-11.22
6,942.00	1.58	257.78	6,936.05	87.86	-200.35	-199.43	0.70	-0.24	-22.24
7,037.00	1.23	219.09	7,031.03	86.79	-202.27	-201.37	1.04	-0.37	-40.73
7,131.00	1.14	195.64	7,125.01	85.10	-203.16	-202.27	0.52	-0.10	-24.95
7,226.00	2.55	108.82	7,219.97	83.51	-201.41	-200.54	2.88	1.48	-91.39
7,321.00	3.68	79.58	7,314.83	83.38	-196.41	-195.54	2.02	1.19	-30.78
7,415.00	4.47	65.73	7,408.60	85.43	-190.11	-189.22	1.34	0.84	-14.73
7,510.00	3.05	69.97	7,503.39	87.82	-184.36	-183.44	1.52	-1.49	4.46
7,605.00	2.28	100.23	7,598.29	88.35	-180.12	-179.20	1.66	-0.81	31.85
7,699.00	2.40	104.02	7,692.21	87.54	-176.37	-175.46	0.21	0.13	4.03
7,794.00	2.19	96.15	7,787.14	86.87	-172.64	-171.73	0.40	-0.22	-8.28
7,889.00	1.64	86.91	7,882.08	86.74	-169.48	-168.57	0.66	-0.58	-9.73
7,983.00	3.03	83.59	7,976.00	87.09	-165.66	-164.76	1.49	1.48	-3.53
7,990.59	3.20	83.54	7,983.58	87.14	-165.25	-164.35	2.25	2.25	-0.72
100'FWL/956'FNL: 7990.59' MD, -164.35' VS,7983.58' TVD									
8,031.00	4.11	83.32	8,023.91	87.44	-162.69	-161.79	2.25	2.25	-0.53
8,110.00	4.66	84.11	8,102.68	88.09	-156.69	-155.78	0.70	0.70	1.00
8,118.00	5.62	85.51	8,110.64	88.16	-155.98	-155.06	12.08	11.97	17.55
KOP: 8118.00' MD, -155.06' VS,8110.64' TVD									
8,157.00	10.31	88.62	8,149.26	88.39	-150.58	-149.66	12.08	12.03	7.96
8,205.00	17.22	91.44	8,195.85	88.32	-139.17	-138.25	14.46	14.40	5.88
8,252.00	20.20	90.81	8,240.36	88.03	-124.10	-123.19	6.35	6.34	-1.34
8,299.00	24.69	92.58	8,283.79	87.47	-106.17	-105.26	9.66	9.55	3.77



Survey Report

Company:	Colgate Energy	Local Co-ordinate Reference:	Well Lady Franklin 25 State 131H - Slot N02
Project:	Eddy County, NM (N83-NME)	TVD Reference:	3358.8+26 @ 3384.80usft (HP481)
Site:	Lady Franklin 25	MD Reference:	3358.8+26 @ 3384.80usft (HP481)
Well:	Lady Franklin 25 State 131H	North Reference:	Grid
Wellbore:	131H	Survey Calculation Method:	Minimum Curvature
Design:	131H	Database:	EDM 5000.14 Single User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,346.00	30.60	93.71	8,325.41	86.25	-84.41	-83.51	12.62	12.57	2.40
8,394.00	34.20	94.20	8,365.93	84.47	-58.75	-57.88	7.52	7.50	1.02
8,441.00	36.89	93.44	8,404.17	82.66	-31.49	-30.64	5.80	5.72	-1.62
8,488.00	40.62	93.19	8,440.81	80.96	-2.13	-1.29	7.94	7.94	-0.53
8,583.00	50.37	89.11	8,507.34	79.81	65.51	66.33	10.71	10.26	-4.29
01-LF25-131H-FTP									
8,678.00	58.51	85.57	8,562.55	83.51	142.62	143.47	9.09	8.57	-3.73
8,772.00	62.89	85.21	8,608.54	90.10	224.30	225.22	4.67	4.66	-0.38
8,867.00	66.68	86.34	8,649.01	96.42	310.00	310.98	4.13	3.99	1.19
8,962.00	72.39	93.43	8,682.25	96.50	398.90	399.87	9.22	6.01	7.46
9,056.00	85.88	95.33	8,699.93	89.43	490.72	491.62	14.49	14.35	2.02
9,124.00	87.55	94.53	8,703.82	83.59	558.36	559.19	2.72	2.45	-1.18
EOC: 9124.00' MD, 559.19' VS, 8703.82' TVD									
9,151.00	88.21	94.21	8,704.82	81.54	585.26	586.07	2.72	2.45	-1.18
9,245.00	87.79	91.84	8,708.11	76.58	679.07	679.82	2.56	-0.45	-2.52
9,340.00	87.85	91.25	8,711.72	74.02	773.96	774.68	0.62	0.06	-0.62
9,435.00	87.49	91.08	8,715.58	72.09	868.86	869.56	0.42	-0.38	-0.18
9,530.00	89.53	90.79	8,718.05	70.54	963.82	964.49	2.17	2.15	-0.31
9,624.00	89.69	90.57	8,718.69	69.43	1,057.81	1,058.46	0.29	0.17	-0.23
9,719.00	89.32	90.75	8,719.51	68.33	1,152.80	1,153.44	0.43	-0.39	0.19
9,814.00	89.14	90.49	8,720.79	67.31	1,247.78	1,248.41	0.33	-0.19	-0.27
9,908.00	89.07	90.08	8,722.26	66.84	1,341.77	1,342.39	0.44	-0.07	-0.44
10,003.00	90.42	89.72	8,722.68	67.00	1,436.77	1,437.38	1.47	1.42	-0.38
10,098.00	90.80	88.83	8,721.67	68.21	1,531.75	1,532.37	1.02	0.40	-0.94
10,193.00	90.89	88.47	8,720.27	70.44	1,626.71	1,627.35	0.39	0.09	-0.38
10,287.00	90.85	88.32	8,718.84	73.08	1,720.67	1,721.33	0.17	-0.04	-0.16
10,382.00	90.55	88.42	8,717.68	75.78	1,815.62	1,816.31	0.33	-0.32	0.11
10,476.00	88.64	87.51	8,718.34	79.12	1,909.55	1,910.27	2.25	-2.03	-0.97
10,571.00	88.15	87.28	8,721.00	83.43	2,004.42	2,005.17	0.57	-0.52	-0.24
10,666.00	88.38	87.48	8,723.88	87.77	2,099.28	2,100.07	0.32	0.24	0.21
10,760.00	89.06	88.23	8,725.98	91.29	2,193.19	2,194.01	1.08	0.72	0.80
10,855.00	89.45	88.56	8,727.22	93.95	2,288.14	2,288.99	0.54	0.41	0.35
10,949.00	89.18	88.31	8,728.34	96.52	2,382.10	2,382.97	0.39	-0.29	-0.27
11,044.00	89.56	88.05	8,729.38	99.53	2,477.04	2,477.94	0.48	0.40	-0.27
11,139.00	89.17	87.80	8,730.44	102.97	2,571.98	2,572.90	0.49	-0.41	-0.26
11,233.00	89.30	87.98	8,731.69	106.43	2,665.90	2,666.86	0.24	0.14	0.19
11,328.00	88.94	88.97	8,733.15	108.96	2,760.86	2,761.83	1.11	-0.38	1.04
11,423.00	89.55	88.52	8,734.40	111.04	2,855.83	2,856.82	0.80	0.64	-0.47
11,517.00	89.58	88.46	8,735.12	113.52	2,949.79	2,950.80	0.07	0.03	-0.06
11,612.00	89.49	88.39	8,735.89	116.13	3,044.75	3,045.79	0.12	-0.09	-0.07
11,707.00	89.40	88.14	8,736.81	119.01	3,139.70	3,140.76	0.28	-0.09	-0.26
11,801.00	89.00	90.08	8,738.12	120.47	3,233.68	3,234.75	2.11	-0.43	2.06
11,896.00	89.20	89.98	8,739.61	120.42	3,328.67	3,329.73	0.24	0.21	-0.11



Survey Report

Company:	Colgate Energy	Local Co-ordinate Reference:	Well Lady Franklin 25 State 131H - Slot N02
Project:	Eddy County, NM (N83-NME)	TVD Reference:	3358.8+26 @ 3384.80usft (HP481)
Site:	Lady Franklin 25	MD Reference:	3358.8+26 @ 3384.80usft (HP481)
Well:	Lady Franklin 25 State 131H	North Reference:	Grid
Wellbore:	131H	Survey Calculation Method:	Minimum Curvature
Design:	131H	Database:	EDM 5000.14 Single User Db

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
11,990.00	89.24	89.62	8,740.89	120.75	3,422.66	3,423.72	0.39	0.04	-0.38	
12,085.00	89.71	89.50	8,741.76	121.47	3,517.65	3,518.71	0.51	0.49	-0.13	
12,179.00	90.46	89.22	8,741.62	122.52	3,611.64	3,612.71	0.85	0.80	-0.30	
12,274.00	89.10	88.96	8,741.99	124.03	3,706.63	3,707.71	1.46	-1.43	-0.27	
12,368.00	87.18	88.94	8,745.04	125.76	3,800.56	3,801.65	2.04	-2.04	-0.02	
12,416.00	86.89	88.79	8,747.52	126.70	3,848.48	3,849.58	0.68	-0.60	-0.31	
12,463.00	87.06	88.87	8,750.00	127.66	3,895.41	3,896.52	0.40	0.36	0.17	
12,558.00	86.65	88.78	8,755.21	129.61	3,990.25	3,991.37	0.44	-0.43	-0.09	
12,653.00	86.84	88.73	8,760.61	131.67	4,085.07	4,086.21	0.21	0.20	-0.05	
12,747.00	87.32	88.55	8,765.40	133.90	4,178.92	4,180.08	0.55	0.51	-0.19	
12,842.00	87.26	88.27	8,769.89	136.53	4,273.78	4,274.96	0.30	-0.06	-0.29	
12,937.00	86.89	88.04	8,774.74	139.58	4,368.60	4,369.81	0.46	-0.39	-0.24	
13,031.00	87.19	89.56	8,779.59	141.55	4,462.46	4,463.68	1.65	0.32	1.62	
13,126.00	86.77	89.29	8,784.60	142.50	4,557.32	4,558.54	0.53	-0.44	-0.28	
13,221.00	86.49	90.75	8,790.18	142.47	4,652.15	4,653.37	1.56	-0.29	1.54	
13,316.00	86.22	90.77	8,796.22	141.21	4,746.95	4,748.15	0.28	-0.28	0.02	
13,410.00	86.03	90.26	8,802.57	140.37	4,840.73	4,841.92	0.58	-0.20	-0.54	
13,427.38	85.86	90.28	8,803.80	140.29	4,858.07	4,859.26	1.01	-1.00	0.12	
100FEL: 13427.38' MD, 4859.26' VS, 8803.80' TVD										
13,427.49	85.86	90.28	8,803.81	140.29	4,858.18	4,859.37	0.00	0.00	0.00	
02-LF25-131H-PBHL										
13,434.00	85.79	90.29	8,804.28	140.25	4,864.67	4,865.86	1.03	-1.02	0.13	
Final MWD Survey: 13434.00' MD, 85.79°INC, 90.29°AZ										
13,505.00	85.79	90.29	8,809.50	139.90	4,935.48	4,936.66	0.00	0.00	0.00	
PTB: 13505.00' MD, 4936.66' VS, 8809.50' TVD										

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
00-LF25-131H-EON	0.00	0.00	5,500.00	73.28	-165.18	595,326.91	601,283.72	32.63645160	-104.13859395	
- actual wellpath misses target center by 4.19usft at 5505.28usft MD (5499.86 TVD, 75.68 N, -168.61 E)										
- Point										
01-LF25-131H-FTP	0.00	0.00	8,783.00	73.28	-165.18	595,326.91	601,283.72	32.63645160	-104.13859395	
- actual wellpath misses target center by 359.51usft at 8583.00usft MD (8507.34 TVD, 79.81 N, 65.51 E)										
- Point										
02-LF25-131H-PBHL	2.00	89.41	8,803.19	125.19	4,858.15	595,378.82	606,307.05	32.63656791	-104.12227508	
- actual wellpath misses target center by 15.11usft at 13427.49usft MD (8803.81 TVD, 140.29 N, 4858.18 E)										
- Rectangle (sides W0.00 H1,246.40 D20.00)										



Survey Report

Company:	Colgate Energy	Local Co-ordinate Reference:	Well Lady Franklin 25 State 131H - Slot N02
Project:	Eddy County, NM (N83-NME)	TVD Reference:	3358.8+26 @ 3384.80usft (HP481)
Site:	Lady Franklin 25	MD Reference:	3358.8+26 @ 3384.80usft (HP481)
Well:	Lady Franklin 25 State 131H	North Reference:	Grid
Wellbore:	131H	Survey Calculation Method:	Minimum Curvature
Design:	131H	Database:	EDM 5000.14 Single User Db

Design Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
7,990.59	7,983.58	87.14	-165.25	100'FWL/956 'FNL: 7990.59' MD, -164.35' VS,7983.58' TVD
8,118.00	8,110.64	88.16	-155.98	KOP: 8118.00' MD, -155.06' VS,8110.64' TVD
9,124.00	8,703.82	83.59	558.36	EOC: 9124.00' MD, 559.19' VS,8703.82' TVD
13,427.38	8,803.80	140.29	4,858.07	100FEL: 13427.38' MD, 4859.26' VS,8803.80' TVD
13,434.00	8,804.28	140.25	4,864.67	Final MWD Survey: 13434.00' MD, 85.79°INC, 90.29°AZ
13,505.00	8,809.50	139.90	4,935.48	PTB: 13505.00' MD, 4936.66' VS,8809.50' TVD

Checked By: _____ Approved By: _____ Date: _____

Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-46299
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Lady Franklin 25 State
8. Well Number 131H
9. OGRID Number 371449
10. Pool name or Wildcat Winchester; Bone Spring
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3359 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Colgate Operating, LLC

3. Address of Operator
300 North Marienfeld, Suite 1,000 – Midland, Tx 79701

4. Well Location

Unit Letter: D 1045 feet from the North line and 265 feet from the West line

Section: 25 Township: 19S Range: 28E NMPM County: Eddy

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: New Well Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

6/10/2020- Pressured up casing to 7,750 psi with a 30 minute test

6/14/2020- Perf and frac stages 1-26.

Perfs 8,944 - 13,317

Frac with 204,142 bbl liquid and 10,040,205 lbs of proppant

6/22/2020- Drilled out plugs

Turn over to production. Tubing 2.875 @ 8,427

TD 13,505 - PBTD 13,408

Spud Date: 03/15/2020

Rig Release Date: 03/29/2020

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Mikah Thomas

TITLE: Operations Tech

DATE: 12/06/2021

Type or print name Mikah Thomas

E-mail address: mtthomas@colgateenergy.com

PHONE: 432-695-4272

For State Use Only

APPROVED BY: _____ TITLE: _____ DATE: _____

Conditions of Approval (if any):

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505				Form C-105 Revised April 3, 2017				
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name Lady Franklin 25 State		
								6. Well Number: 131H		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER										
8. Name of Operator Colgate Operating, LLC						9. OGRID 371449				
10. Address of Operator 300 North Marcienfeld, Suite 1,000 Midland, Texas 79705						11. Pool name or Wildcat Winchester; Bone Spring				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	D	25	19S	28E		1,045	North	265	West	Eddy
BH:	A	25	19S	28E		956	North	17	East	Eddy
13. Date Spudded 03/15/2020	14. Date T.D. Reached 03/26/2020		15. Date Rig Released 03/29/2020			16. Date Completed (Ready to Produce) 06/22/2020		17. Elevations (DF and RKB, RT, GR, etc.) 3,359		
18. Total Measured Depth of Well 13,505			19. Plug Back Measured Depth 13,408			20. Was Directional Survey Made? Yes		21. Type Electric and Other Logs Run Gamma Ray		
22. Producing Interval(s), of this completion - Top, Bottom, Name 8,944-13,317 Bone Spring										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
13.375		54.5		334		17.5		Class C: 400 sx 1.35, 510 sx 1.369, 225 sx 1.332		
9.625		40		3,025		12.25		Class C: 510 sx 2.81, 220 sx 1.33		
5.5		20		13,495		8.75		Class C: 1,015 sx 1.68, 810 sx 2.33		
24. LINER RECORD										
SIZE	TOP	BOTTOM	SACKS CEMENT		SCREEN		25. TUBING RECORD			
							SIZE			
							DEPTH SET			
							PACKER SET			
26. Perforation record (interval, size, and number) 8,944-13,317 3.0 897 holes						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.				
						DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED		
						8,944-13,317		Total Proppant 10,040,205 – Total Fluid 212,557		
28. PRODUCTION										
Date First Production 06/26/2020		Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>) Gas Lift				Well Status (<i>Prod. or Shut-in</i>) Producing				
Date of Test 07.12.2020	Hours Tested 24	Choke Size 44/64	Prod'n For Test Period	Oil – Bbl 1,709	Gas – MCF 3,887	Water - Bbl. 2,269	Gas - Oil Ratio 2,274			
Flow Tubing Press. 176	Casing Pressure 776	Calculated 24- Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API - (<i>Corr.</i>) 43.3				
29. Disposition of Gas (<i>Sold, used for fuel, vented, etc.</i>) Sold								30. Test Witnessed By Colgate Operating, LLC		
31. List Attachments C-102, C-103, C-104, Directionnel Survey										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.								33. Rig Release Date:		
34. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude				Longitude				NAD83		

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature 

Printed

Name: Mikah Thomas

Title: Operations Tech

Date: 11/07/2021

E-mail Address: mthomas@colgateenergy.com

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Rustler- 117	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt- 372	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt- 619	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates- 1,051	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. DLWR Mnt. Group- 3,123	T. Devonian	T. Cliff House	T. Leadville
T. L Brushy Canyon- 3,460	T. Silurian	T. Menefee	T. Madison
T. BS Lime- 3,793	T. Montoya	T. Point Lookout	T. Elbert
T. 1 st Bone Spring SD- 6,623	T. Simpson	T. Mancos	T. McCracken
T. 2 nd Bone Spring LM- 7,036	T. McKee	T. Gallup	T. Ignacio Otzte
T. 2 nd Bone Spring SD- 7,483	T. Ellenburger	Base Greenhorn	T. Granite
T. 3 rd Bone Spring LM- 7,703	T. Gr. Wash	T. Dakota	
T. 3 rd Bone Spring SD- 8,543	T. Delaware Sand	T. Morrison	
T. Drinkard	T. Bone Springs	T. Todilto	
T. Abo	T.	T. Entrada	
T. Wolfcamp	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....

No. 3, from.....to.....

No. 2, from.....to.....

No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....

No. 2, from.....to.....feet.....

No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
------	----	----------------------	-----------	------	----	----------------------	-----------

--	--	--	--	--	--	--	--	--

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 61274

ACKNOWLEDGMENTS

Operator: COLGATE OPERATING, LLC 300 North Marienfeld Street Midland, TX 79701	OGRID: 371449
	Action Number: 61274
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 61274

CONDITIONS

Operator: COLGATE OPERATING, LLC 300 North Marienfeld Street Midland, TX 79701	OGRID: 371449
	Action Number: 61274
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
plmartinez	None	12/7/2021