

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

| |
|---|
| WELL API NO. 30-025-43592 |
| 5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 6. State Oil & Gas Lease No. |
| 7. Lease Name or Unit Agreement Name Pinkman Fee |
| 8. Well Number 4H |
| 9. OGRID Number 371682 |
| 10. Pool name or Wildcat Bronco; San Andres, South |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Steward Energy II, LLC

3. Address of Operator
**2600 North Dallas Parkway, Suite 400
Frisco, TX 75034**

4. Well Location
Unit Letter **D** : **470** feet from the **North** line and **330** feet from the **West** line
Section **23** Township **14S** Range **38E** NMPM County **Lea**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

| | |
|---|---|
| <p>NOTICE OF INTENTION TO:</p> <p>PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/></p> <p>TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/></p> <p>PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/></p> <p>DOWNHOLE COMMINGLE <input type="checkbox"/></p> <p>CLOSED-LOOP SYSTEM <input type="checkbox"/></p> <p>OTHER: <input type="checkbox"/></p> | <p>SUBSEQUENT REPORT OF:</p> <p>REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/></p> <p>COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input checked="" type="checkbox"/></p> <p>CASING/CEMENT JOB <input type="checkbox"/></p> <p>OTHER: <input type="checkbox"/></p> |
|---|---|

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Set CIBP at 4800'.
Circulate 120 bbls of mud
25 sx Spot ~~20~~ sks of cmt on top of CIBP
P&S 50 sx Spot ~~20~~ sks of cmt at 2500'. Tag top of cement.
25 sx Spot ~~20~~ sks of cmt at 1100'.
Fill from 465' to surface with 65 sx of cmt.
Cut off wellhead and mark location.

Note changes to procedure

4" diameter 4' tall Above Ground Marker

SEE ATTACHED CONDITIONS OF APPROVAL

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE

TECH

DATE

11/15/2021

Type or print name

Holly Pankratz

E-mail address:

holly.pankratz@stewardenergy.net

PHONE:

214-297-0524

For State Use Only

APPROVED BY:

Kerry Fortner

TITLE

Compliance Officer A

DATE

2/8/22

Conditions of Approval (if any):

575-263-6633

Steward Energy Plugging Plan

Pinkman Fee #4H

30-025-43592

Estimated to begin 12/1/2021

1. Set CIBP at 4800'
2. Circulate 120 bbls of mud
3. Spot 20 sks of cement on top of CIBP
4. Spot 20 sks of cement at 2500'. Tag top of cement
5. Spot 20 sks of cement at 1100'
6. Fill from 465' to surface with 65 sacks of cement
7. Cut off wellhead and mark location

| | | | | | | |
|-----------------------|--|--|---|-------------------|------------------------|--|
| General | Company: Steward Energy II, LLC | | Prospect: Bronco | | | |
| | Well Name: Pinkman 4H | | TD (MD/TVD): 10,804' MD/5353' TVD | | | |
| | County: Lea | | Elevation: 3763' GL & 3782' KB | | | |
| | State: New Mexico | | Latitude & longitude: 33.097433/103.075094 | | | |
| | API Number: 30-025-43592 | | Section-Township-Range: Sec 23, T14S, R38E | | | |
| | | | Surface Location: 470' FNL & 330' FWL | | | |
| | | Bottom Hole Location: 100' FNL & 330' FWL | | | | |
| Formation | Depth MD TVD | | Casing Profile | Hole Size | Casing Specifications | Mud & Cement Program |
| | | | | 12 1/4" | 9 5/8" 36#/ft J-55 | 1000' / 650sx "C" (6% gel, 5% salt, .0125 pps Celloflake, 0.4 pps Defoamer) + 200sx "C" () |
| 9 5/8" Casing @ 2410' | | | | | | |
| | | | | 8 3/4" | 5 1/2" 20#/ft L-80 BTC | Cement w/ 660sx "C" () + 1630sx C () |
| | | | | | | 6 Deg DL @ 4864' |
| | | | | | | 2-7/8" tbg to 4685.7'. ESP intake at 4774.1'. Sensor at 4817.0'. |
| | | | | CURVE 8 3/4" | 5 1/2" 20#/ft L-80 BTC | Curve: 4864' - 5730' |
| | | | | LATERAL 8 3/4" | 5 1/2" 20#/ft L-80 BTC | TD Lateral @ 10,804' MD/5353' TVD Lateral: 5730' - 10,804' |
| Comments | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Released to Imaging: 2/9/2022 7:44:26 AM

**CONDITIONS OF APPROVAL
FOR PLUGGING AND ABANDONMENT
OCD - Southern District**

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office I (Hobbs) at (575)-263-6633 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down.

Company representative will be on location during plugging procedures.

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal - commercial or private- shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water will not be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.
16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).

19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
- A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Potash---(In the R-111-P Area (Potash Mine Area),
A solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing.

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name
2. Lease and Well Number
3. API Number
4. Unit letter
5. Quarter Section (feet from the North, South, East or West)
6. Section, Township and Range
7. Plugging Date
8. County

SPECIAL CASES -----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

Steward Energy Plugging Plan


Pinkman Fee #4H

30-025-43592

Estimated to begin 12/1/2021

1. Set CIBP at 4800'
2. Circulate 120 bbls of mud
3. Spot 20 sks of cement on top of CIBP
4. Spot 20 sks of cement at 2500'. Tag top of cement
5. Spot 20 sks of cement at 1100'
6. Fill from 465' to surface with 65 sacks of cement
7. Cut off wellhead and mark location

| | | | | | | |
|-----------------------|--|--|---|-------------------|------------------------|---|
| General | Company: Steward Energy II, LLC | | Prospect: Bronco | | | |
| | Well Name: Pinkman 4H | | TD (MD/TVD): 10,804' MD/5353' TVD | | | |
| | County: Lea | | Elevation: 3763' GL & 3782' KB | | | |
| | State: New Mexico | | Latitude & longitude: 33.097433/103.075094 | | | |
| | API Number: 30-025-43592 | | Section-Township-Range: Sec 23, T14S, R38E | | | |
| | | | Surface Location: 470' FNL & 330' FWL | | | |
| | | Bottom Hole Location: 100' FNL & 330' FWL | | | | |
| Formation | Depth MD TVD | | Casing Profile | Hole Size | Casing Specifications | Mud & Cement Program |
| | | | | 12 1/4" | 9 5/8" 36#/ft J-55 | 1000' / 650sx "C" (6% gel, 5% salt, .0125 pps Celloflake, 0.4 pps Defoamer) + 200sx "C" () |
| 9 5/8" Casing @ 2410' | | | | | | |
| | | | | 8 3/4" | 5 1/2" 20#/ft L-80 BTC | Cement w/ 660sx "C" () + 1630sx C () |
| | | | | | | 6 Deg DL @ 4864' |
| | | | | | | 2-7/8" tbg to 4685.7'. ESP intake at 4774.1'. Sensor at 4817.0'. |
| | | | | CURVE 8 3/4" | 5 1/2" 20#/ft L-80 BTC | Curve: 4864' - 5730' |
| | | | | LATERAL 8 3/4" | 5 1/2" 20#/ft L-80 BTC | TD Lateral @ 10,804' MD/5353' TVD Lateral: 5730' - 10,804' |
| Comments | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

| | | | | | | | | |
|----------------------|---|-------|------------------------|--|------------------------|------------------------|---|--|
| General | Company: | | Steward Energy II, LLC | | Prospect: | | Bronco | |
| | Well Name: | | Pinkman 4H | | TD (MD/TVD): | | 10,804' MD/5353' TVD | |
| | County: | | Lea | | Elevation: | | 3763' GL & 3782' KB | |
| | State: | | New Mexico | | Latitude & longitude: | | 33.097433/103.075094 | |
| | API Number: | | 30-025-43592 | | Section-Township-Range | | Sec 23, T14S, R38E | |
| | | | | | Surface Location: | | 470' FNL & 330' FWL | |
| | | | | | Bottom Hole Location: | | 100' FNL & 330' FWL | |
| Formation | | Depth | | Casing Profile | Hole Size | Casing Specificaitons | Mud & Cement Program | |
| | | MD | TVD | | | | | |
| | | | |  | 12 1/4" | 9 5/8" 36#/ft J-55 | Cement w/650sx "C" (6% gel, 5% salt, .0125 pps Celloflake, 0.4 pps Defoamer) + 200 sx "C" | |
| | | | | | 8 3/4" | 5 1/2" 20#/ft L-80 BTC | Cement w/660sx "C" () + 1630 sx "C" | |
| 9 5/8"Casing @ 2410' | | | | | | | 6 Deg DL @ 4864' | |
| | | | | CURVE | 8 3/4" | 5 1/2" 20#/ft L-80 BTC | Curve: 4864' - 5730' | |
| | | | | | | | | |
| | | | | LATERAL | 8 3/4" | 5 1/2" 20#/ft L-80 BTC | TD Lateral @ 10,804' MD/5353' TVD | |
| | | | | | | | Lateral: 5730' - 10,804' | |
| Comments | Proposed CIBP and 20 sacks of cement at 4800' | | | | | | | |
| | Proposed 20 sacks of cement at 2500' | | | | | | | |
| | Proposed 20 sacks of cement at 1100' | | | | | | | |
| | Proposed 65 sacks of cement at 500' | | | | | | | |

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 61751

CONDITIONS

| | |
|--|---|
| Operator: STEWARD ENERGY II, LLC 2600 Dallas Parkway Frisco, TX 75034 | OGRID: 371682 |
| | Action Number: 61751 |
| | Action Type: [C-103] NOI Plug & Abandon (C-103F) |

CONDITIONS

| Created By | Condition | Condition Date |
|------------|---|----------------|
| kfortner | See attached conditions of approval Note changes to procedure | 2/8/2022 |