

Submit 3 Copies To Appropriate District Office  
 District I  
 1625 N. French Dr., Hobbs, NM 88240  
 District II  
 1301 W. Grand Ave., Artesia, NM 88210  
 District III  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV  
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 May 27, 2004

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. 30-025-23452
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name SFPRR
8. Well Number 1
9. OGRID Number 371484
10. Pool name or Wildcat Sawyer, SA

**SUNDRY NOTICES AND REPORTS ON WELLS**  
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other ☐

2. Name of Operator  
Rover Operating, LLC

3. Address of Operator  
17304 Preston Rd., Ste. 300 Dallas, Tx 75252

4. Well Location  
 Unit Letter N : 660 feet from the S line and 1980 feet from the W line  
 Section 33 Township 9S Range 37E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3967.8 KB

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

<b>NOTICE OF INTENTION TO:</b>		<b>SUBSEQUENT REPORT OF:</b>	
PERFORM REMEDIAL WORK <input type="checkbox"/>	<b>PLUG AND ABANDON</b> <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Notify Regulatory 575-393-6161

- CIBP @ 4850' w/35' cmt. Circ P&A mud test to 500psi. **Spot 25 sx Class C 4100 Top San Andres**
- 200sx 2980' - 2285' P.S. Tag.
- 125sx 457' - Surf. P.S. Verify. Install DHM.

**LPC Area Below ground marker send pics before backfilling hole**

All fluids to licensed facility. P&A mud between all plugs.

**SEE ATTACHED CONDITIONS OF APPROVAL**

**Note changes to procedure**

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Ryan Sandmann

TITLE P. Eng.

DATE 2/15/22

Type or print name Ryan Sandmann

E-mail address: rsandmann@roverpetro.com

Telephone No 214-334-9115

For State Use Only

APPROVED BY: Kerry Fortner

TITLE Compliance Officer A

DATE 2/18/22

Conditions of Approval (if any):

575-263-6633

**Work Plan P&A SFPRR #1**

1. CIBP @ 4850' w/35' cmt. Circ P&A mud test to 500 psi. **Spot 25 sx Class C 4100 Top San Andres**
2. 200 sx 2980' - 2258' P.S. Tag.
3. 125 sx 457' - Surf. P.S. Verify. Install DHM.

WELL NAME:	SFPRR #1			FIELD:	West Sawyer		
LOCATION:	S33 T9S R37E			API #:	30-025-23452		
COUNTY:	Lea		ST:	NM		SPUD DATE:	03/09/70
KB:	3968	GL:	3960'	TD:	5003'	PBTD:	4992'
LAST UPDATED:	06/09/14			BY:	C. Fowler		

8 5/8" @ 407' cmt'd w/ 250 sx

**CASING DETAILS**

PURPOSE	SIZE	WEIGHT	GRADE	SET DEPTH
SURFACE	8 5/8"			407'
INTERMEDIATE				
PRODUCTION	4 1/2"			5002'
LINER				

**TUBING DETAILS**

DESCRIPTION	SIZE	WEIGHT	GRADE	SET DEPTH
	2 3/8"			4989'

**ROD DETAILS**

DESCRIPTION	SIZE	WEIGHT	GRADE	SET DEPTH
117	5/8"			
78	3/4"			
pump	1" x 1 1/2" x 16'			

TOC @ 3655'

**TOPS**

FORMATION	TOP	BOTTOM
San Andres		

Perfs 4936-4956'  
 Perfs 4975-4993', 9 holes

4 1/2" @5002' cmt'd w/ 250 sx

WELL NAME:	<b>SFPRR #1</b>		FIELD:	<b>West Sawyer</b>	
LOCATION:	<b>S33 T9S R37E</b>		API #:	<b>30-025-23452</b>	
COUNTY:	<b>Lea</b>	ST:	<b>NM</b>	SPUD DATE:	<b>03/09/70</b>
KB:	<b>3968</b>	GL:	<b>3960'</b>	TD:	<b>5003'</b>
		PBTD:	<b>4992'</b>		
LAST UPDATED:	<b>02/15/22</b>		BY:	<b>R. Sandmann</b>	

8 5/8" @ 407' cmt'd w/ 250 sx

**CASING DETAILS**

PURPOSE	SIZE	WEIGHT	GRADE	SET DEPTH
SURFACE	8 5/8"			407'
INTERMEDIATE				
PRODUCTION	4 1/2"			5002'
LINER				

125 sx 457' - Surf

**TUBING DETAILS**

DESCRIPTION	SIZE	WEIGHT	GRADE	SET DEPTH

200 sx 2980'-2285'

**ROD DETAILS**

DESCRIPTION	SIZE	WEIGHT	GRADE	SET DEPTH

TOC @ 3655'

**Spot 25 sx Class C 4100 Top San Andres**

CIBP @ 4850' w/ 35' cmt

Perfs 4936-4956'

Perfs 4975-4993', 9 holes

**TOPS**

FORMATION	TOP	BOTTOM
San Andres		

4 1/2" @ 5002' cmt'd w/ 250 sx

**CONDITIONS OF APPROVAL  
FOR PLUGGING AND ABANDONMENT  
OCD - Southern District**

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office I (Hobbs) at (575)-263-6633 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down.

**Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal - commercial or private- shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water will not be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.
16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).

19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
- A) Fusselman
  - B) Devonian
  - C) Morrow
  - D) Wolfcamp
  - E) Bone Springs
  - F) Delaware
  - G) Any salt sections
  - H) Abo
  - I) Glorieta
  - J) Yates.
  - K) Potash---(In the R-111-P Area (Potash Mine Area),  
A solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing.

### **DRY HOLE MARKER REQUIREMENTS**

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name
2. Lease and Well Number
3. API Number
4. Unit letter
5. Quarter Section (feet from the North, South, East or West)
6. Section, Township and Range
7. Plugging Date
8. County

### **SPECIAL CASES -----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS**

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

### **SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION**

**Work Plan P&A SFPRR #1**

1. CIBP @ 4850' w/35' cmt. Circ P&A mud test to 500 psi.
2. 200 sx 2980' - 2258' P.S. Tag.
3. 125 sx 457' - Surf. P.S. Verify. Install DHM.



WELL NAME:	SFPRR #1			FIELD:	West Sawyer		
LOCATION:	S33 T9S R37E			API #:	30-025-23452		
COUNTY:	Lea		ST:	NM		SPUD DATE:	03/09/70
KB:	3968	GL:	3960'	TD:	5003'	PBTD:	4992'
LAST UPDATED:	06/09/14			BY:	C. Fowler		

8 5/8" @ 407' cmt'd w/ 250 sx

**CASING DETAILS**

PURPOSE	SIZE	WEIGHT	GRADE	SET DEPTH
SURFACE	8 5/8"			407'
INTERMEDIATE				
PRODUCTION	4 1/2"			5002'
LINER				

**TUBING DETAILS**

DESCRIPTION	SIZE	WEIGHT	GRADE	SET DEPTH
	2 3/8"			4989'

**ROD DETAILS**

DESCRIPTION	SIZE	WEIGHT	GRADE	SET DEPTH
117	5/8"			
78	3/4"			
pump	1" x 1 1/2" x 16'			

TOC @ 3655'

**TOPS**

FORMATION	TOP	BOTTOM
San Andres		

Perfs 4936-4956'  
 Perfs 4975-4993', 9 holes

4 1/2" @5002' cmt'd w/ 250 sx



WELL NAME:	<b>SFPRR #1</b>		FIELD:	<b>West Sawyer</b>	
LOCATION:	<b>S33 T9S R37E</b>		API #:	<b>30-025-23452</b>	
COUNTY:	<b>Lea</b>	ST:	<b>NM</b>	SPUD DATE:	<b>03/09/70</b>
KB:	<b>3968</b>	GL:	<b>3960'</b>	TD:	<b>5003'</b>
		PBTD:	<b>4992'</b>		
LAST UPDATED:	<b>02/15/22</b>		BY:	<b>R. Sandmann</b>	

8 5/8" @ 407' cmt'd w/ 250 sx

**CASING DETAILS**

PURPOSE	SIZE	WEIGHT	GRADE	SET DEPTH
SURFACE	8 5/8"			407'
INTERMEDIATE				
PRODUCTION	4 1/2"			5002'
LINER				

**TUBING DETAILS**

DESCRIPTION	SIZE	WEIGHT	GRADE	SET DEPTH

**ROD DETAILS**

DESCRIPTION	SIZE	WEIGHT	GRADE	SET DEPTH

125 sx 457' - Surf

200 sx 2980'-2285'

TOC @ 3655'

CIBP @ 4850' w/ 35' cmt

Perfs 4936-4956'

Perfs 4975-4993', 9 holes

4 1/2" @ 5002' cmt'd w/ 250 sx

**TOPS**

FORMATION	TOP	BOTTOM
San Andres		

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
  
Action 81720

CONDITIONS

Operator: ROVER OPERATING, LLC 17304 Preston Road Dallas, TX 75252	OGRID: 371484
	Action Number: 81720
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
kfortner	See attached conditions of approval Note changes to procedure	2/18/2022