

Submit 1 Copy To Appropriate District Office

District I – (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II – (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III – (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV – (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-103

Revised July 18, 2013

WELL API NO. 30-025-49600	
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name BEAZA SWD	
8. Well Number 1	
9. OGRID Number 328435	
10. Pool name or Wildcat SWD; BELL CANYON-CHERRY CANYON	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other SWD 2. Name of Operator MILESTONE ENVIRONMENTAL SERVICES LLC 3. Address of Operator 15721 PARK ROW, SUITE 150 4. Well Location Unit Letter H : 2480 feet from the N line and 160 feet from the E line Section 25 Township 24S Range 34E NMPM County LEA 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3360.1	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: Proposed STep-rate Test Procedures <input checked="" type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Milestone is submitting an updated step-rate test procedure, requesting a maximum test rate of 26 bpm. An analysis of an initial injection test performed 3/22 indicates that three steps above the fracture parting pressure may not be achieved at 20 bpm. A chart of this test is attached.

Changes noted

Spud Date:

12/16/2021

Rig Release Date:

3/19/2022

I hereby certify that the information above is true and complete to the best of my knowledge and belief.


SIGNATURE Ramona K Hovey TITLE CONSULTING ENGINEER DATE 3/24/22

Type or print name RAMONA HOVEY E-mail address: ramona@longquist.com PHONE: 512 600 1777

For State Use Only

APPROVED BY: Phillip R. Lutz TITLE UIC Manager DATE 04/04/2022

Conditions of Approval (if any):



<b>LONQUIST &amp; CO. LLC</b> PETROLEUM ENGINEERS ENERGY ADVISORS		<b>Step Rate Test Procedure</b>			Project No.: 2375	
		<b>Milestone Environmental Services LLC</b>			Date: March 24, 2022 Page: 1 of 5	
Well: Beaza SWD No. 1		State: NM	County: Lea	API: 30-025-49600	District: 1 (Hobbs)	
<b>INTRODUCTION:</b>  Milestone Environmental Services LLC ("Milestone") has requested Lonquist & Co, LLC ("LCO") prepare procedures for a Step Rate Test ("SRT") on Beaza SWD No. 1. This test is being performed to support an application for injection pressure increase at the subject well. This procedure will follow the draft guidance document for the Application Process for Injection Pressure Increases provided by the Oil Conservation Division of the New Mexico Energy, Minerals and Natural Resources Department ("OCD").  The general scope of the work is as follows: <ul style="list-style-type: none"> <li>• If required by the District, a bradenhead test and mechanical integrity test (MIT) will be performed. The well must pass both tests before a SRT can be performed.</li> <li>• Prior to testing, shut in the well long enough, but not less than 48 hours to ensure that the bottom hole pressure is at or near the shut-in formation pressure.</li> <li>• Procure a minimum of nine (9) 500-bbl frac tanks</li> <li>• Fill tanks with clean brine water from a client facility or third-party source</li> <li>• MIRU pumps and iron</li> <li>• MIRU WL unit and Perform gauge ring run</li> <li>• TIH with BHP gauge to the mid-perf depth</li> <li>• If wellbore is not full, fill with brine at 0.5 BPM</li> <li>• Allow pressure to stabilize</li> <li>• Step up rates as detailed in the Rate Schedule table</li> <li>• Shut in well completely and record pressures for 30 minutes</li> <li>• Conclude test and RDMO pumps and WL unit</li> </ul>						
<b>OBJECTIVES</b>  Perform a step-rate test that: <ol style="list-style-type: none"> <li>1. Adheres precisely to the flow rates and durations included in the Rate Schedule below</li> <li>2. Includes a minimum of three steps below and three steps above the formation fracture pressure</li> </ol>						
PREPARED BY	DATE	REVIEWED BY	DATE	APPROVED BY	DATE	Client Signature
JAM	03/24/2022	NLB	03/24/2022	WHG	03/24/2022	

<b>LONQUIST &amp; CO. LLC</b> PETROLEUM ENGINEERS ENERGY ADVISORS		<b>Step Rate Test Procedure</b>			Project No.: 2375	
		<b>Milestone Environmental Services LLC</b>			Date: March 24, 2022 Page: 2 of 5	
Well: Beaza SWD No. 1		State: NM	County: Lea	API: 30-025-49600	District: 1 (Hobbs)	
<b>REGULATORY INFORMATION:</b>  <p>The Beaza SWD No. 1 is regulated by the New Mexico OCD. The operator must submit Division Form C-103 to the OCD District office with the description of the procedure for the SRT prior to the test. Once the operator has an approved Sundry Notice, the operator shall notify the appropriate OCD District office at least 72 hours prior to the scheduled SRT so that OCD personnel may be present to witness the test. A bradenhead test (if required by the District) and mechanical integrity test (MIT) will be performed before the SRT. If the subject well fails either test, then the SRT will be suspended until the mechanical integrity issue(s) has been remediated. The mechanical integrity testing may be modified at the discretion of the District Supervisor.</p> <p>The completed SRT results are to be submitted to the Engineering Bureau in Santa Fe and should include the following information:</p> <ul style="list-style-type: none"> <li>• Administrative application checklist (available on OCD website under Unnumbered Forms on Form webpage).</li> <li>• Cover letter with contact information, general description of test and pressure increase being proposed.</li> <li>• Complete data summary including injection rates, duration of each step, pressure measurements (surface and bottom hole) and the ISIP.</li> <li>• SRT-specific information: location of pressure gauges (depth); initial bottomhole pressure; injection fluid type and specific gravity.</li> <li>• Graph summary of pressure versus injection rate with interpretation.</li> <li>• Current well completion diagram.</li> <li>• Copy of the order authorizing the injection into the well.</li> </ul> <p>If a pressure increase is granted, it shall be limited for use in the well with the same tubing, size, length, and type of interior coating as present for the SRT. If these components are changed, the operator must ask the Engineering Bureau to recalculate the surface pressure limit, which may require another SRT.</p>						
PREPARED BY	DATE	REVIEWED BY	DATE	APPROVED BY	DATE	Client Signature
JAM	03/24/2022	NLB	03/24/2022	WHG	03/24/2022	

<b>LONQUIST &amp; CO. LLC</b> PETROLEUM ENGINEERS ENERGY ADVISORS		<b>Step Rate Test Procedure</b>			Project No.: 2375	
		<b>Milestone Environmental Services LLC</b>			Date: March 24, 2022 Page: 3 of 5	
Well: Beaza SWD No. 1		State: NM	County: Lea	API: 30-025-49600	District: 1 (Hobbs)	
<b>STEP-RATE TEST DETAILED PROCEDURE:</b> <ol style="list-style-type: none"> <li>Once the operator has an approved Sundry Notice, notify appropriate OCD District office at least 72 hours prior to the scheduled SRT so that OCD personnel may be present to witness the test.</li> <li>If required by the District, a bradenhead test and mechanical integrity test (MIT) will be performed. The well must pass both tests before an SRT can begin.</li> <li>Prior to testing, shut in the well long enough, but not less than 48 hours to ensure that the bottom hole pressure is at or near the shut-in formation pressure           <ol style="list-style-type: none"> <li>Pressure should be recorded for the duration of the shut in to confirm stabilization</li> </ol> </li> <li>Set a minimum of nine (9) 500-bbl frac tanks (Enough to complete the planned test with contingency brine)           <ol style="list-style-type: none"> <li>Fill with a minimum of 4,500 bbls of clean brine water from a client facility or third-party source</li> </ol> </li> <li>RU pumps and iron           <ol style="list-style-type: none"> <li>MIRU kill trucks/frac pumps and lay iron</li> <li>Pumps, iron and flow control should be sized so that steps in rate will not create pressure or rate transients, other than those caused by the intended steps</li> </ol> </li> <li>If not already present, install flow meter(s) and surface pressure gauge capable of digitally recording injection rates and pressures           <ol style="list-style-type: none"> <li>Recording frequency of one second or less is ideal</li> <li>Pressure gauges and flow meters should have continuous readout for observation throughout test</li> <li>Ensure pressure gauges are recently calibrated and able to accommodate the full range of expected rates and pressures</li> </ol> </li> <li>MIRU WL</li> <li>Perform gauge ring run</li> <li>PU BHP gauge and RIH to the mid-perf depth, ensure the gauge is calibrated</li> <li>Ensure the wellbore is full of brine before initiating the test           <ol style="list-style-type: none"> <li>If necessary, fill hole with brine at a constant rate of 0.5 BPM</li> <li>Once the well is full, stop pumping and allow the pressure to stabilize</li> </ol> </li> <li>Begin test at an injection rate of 0.5 BPM for 30 minutes           <ol style="list-style-type: none"> <li><b>Surface injection pressure, bottomhole pressure, and injection rate must be digitally recorded for the duration of the test</b></li> </ol> </li> <li>Step up rates per the table included below           <ol style="list-style-type: none"> <li>Surface pressure should not exceed 80% of the maximum pressure rating of the wellhead at any time</li> <li>Changes in flow rate must occur over as short of intervals as possible</li> <li>Injection rates should be controlled with a constant flow regulator</li> <li>All injection flow rates, including hole conditioning treatments prior to the test, must be documented on service company forms</li> <li>Re-fill frac tanks as needed</li> <li>A minimum of three fluid samples should be caught throughout the test, at the beginning, middle and end               <ol style="list-style-type: none"> <li>The density of the samples will be read by an in-house method</li> <li>Fluid density will be reported to the OCD with SRT results</li> </ol> </li> </ol> </li> </ol>						
PREPARED BY	DATE	REVIEWED BY	DATE	APPROVED BY	DATE	Client Signature
JAM	03/24/2022	NLB	03/24/2022	WHG	03/24/2022	

<b>LONQUIST &amp; CO. LLC</b> PETROLEUM ENGINEERS ENERGY ADVISORS		<b>Step Rate Test Procedure</b>			Project No.: 2375	
		<b>Milestone Environmental Services LLC</b>			Date: March 24, 2022 Page: 4 of 5	
Well: Beaza SWD No. 1		State: NM	County: Lea	API: 30-025-49600	District: 1 (Hobbs)	
<p>13. Upon completion of the final injection stage, the line valve must be closed to stop injection immediately. This will allow the pressure to bleed off into the formation.</p> <ul style="list-style-type: none"> <li>a. Ensure that pressure values are recorded at the highest obtainable frequency during shut-in</li> <li>b. Continue to capture falloff pressure data for 30 minutes</li> </ul> <p>14. Conclude test</p> <ul style="list-style-type: none"> <li>a. POOH with BHP gauge</li> <li>b. RDMO WL</li> </ul> <p>15. The completed SRT results are to be submitted to the Engineering Bureau in Santa Fe and should include the following information:</p> <ul style="list-style-type: none"> <li>a. Administrative application checklist (available on OCD website under Unnumbered Forms on Form webpage).</li> <li>b. Cover letter with contact information, general description of test and pressure increase being proposed.</li> <li>c. Complete data summary including injection rates, duration of each step, pressure measurements (surface and bottom hole) and the ISIP.</li> <li>d. SRT-specific information: location of pressure gauges (depth) initial bottomhole pressure; injection fluid type and specific gravity.</li> <li>e. Graph summary of pressure versus injection rate with interpretation.</li> <li>f. Current well completion diagram.</li> <li>g. Copy of the order authorizing the injection into the well.</li> </ul>						
<b>EQUIPMENT DESCRIPTION</b> <ul style="list-style-type: none"> <li>• Surface Pressure Gauge with continuous readout and digital data recording</li> <li>• Bottomhole Pressure Gauge with live surface readout and digital data recording</li> <li>• In-line Flow Meter with a rate range that includes 0.5 BPM to 26 BPM</li> </ul>						
PREPARED BY	DATE	REVIEWED BY	DATE	APPROVED BY	DATE	Client Signature
JAM	03/24/2022	NLB	03/24/2022	WHG	03/24/2022	



<b>LONQUIST &amp; CO. LLC</b> <b>PETROLEUM ENGINEERS</b> <b>ENERGY ADVISORS</b>	<b>Step Rate Test Procedure</b>			<b>Project No.:</b> 2375
	<b>Milestone Environmental Services LLC</b>			<b>Date:</b> March 24, 2022
				<b>Page:</b> 5 of 5
<b>Well:</b> Beaza SWD No. 1	<b>State:</b> NM	<b>County:</b> Lea	<b>API:</b> 30-025-49600	<b>District:</b> 1 (Hobbs)

**RATE SCHEDULE**

- Schedule is subject to change. Durations may increase to accommodate pressure stabilization and rates may change based on pressure behavior indicative of formation fracture.

Step No.	Injection Rate			Duration (minutes)	Stage Volume (BBL)	Cumulative Volume (BBL)
	BPM	GPM	BPD			
1	0.5	21	720	30	15	15
2	1	42	1,440	30	30	45
3	2	84	2,880	30	60	105
4	5	210	7,200	30	150	255
5	8	336	11,520	30	240	495
6	11	462	15,840	30	330	825
7	14	588	20,160	30	420	1,245
8	17	714	24,480	30	510	1,755
9	20	840	28,800	30	600	2,355
10	23	966	33,120	30	690	3,045
11	26	1092	37,440	30	780	3,825

**INJECTION HISTORY**

This is a new well that has not yet commenced injection

**WELL TREATMENT HISTORY**

The Beaza SWD No. 1 was acidized in February 2022 with approximately 700 bbls of 15% HCL at a maximum pressure of 1,100 psi. The daily reports for the acid treatment are attached.


**ATTACHMENTS**

- Wellbore Diagram
- Acid Treatment Daily Reports

PREPARED BY	DATE	REVIEWED BY	DATE	APPROVED BY	DATE	Client Signature
JAM	03/24/2022	NLB	03/24/2022	WHG	03/24/2022	

Attachment No. 1  
Wellbore Diagram





<b>LONQUIST &amp; CO. LLC</b> <b>PETROLEUM ENGINEERS</b> <b>ENERGY ADVISORS</b>	Milestone Environmental		Beaza SWD No. 1	
	Country: USA		State/Province: New Mexico	County/Parish: Lea
	Location: 160' FEL & 2,480' FNL of Unit H, Section 25, Township 24S, Range 34E			District: 1 (Hobbs)
	API No: 30-025-49600		Field:	Well Type/Status: Disposal / New Drill
	Texas License F-9147		Project No: 1761	Date: 03/16/2022
12912 Hill Country Blvd. Ste F-200 Austin, Texas 78738 Tel: 512.732.9812 Fax: 512.732.9816	Drawn: WHG		Reviewed: RH	Approved: RSC
	Rev No: 3		Notes:	

Attachment No. 2  
Acid Treatment Daily Reports

# Beaza SWD No. 1

<b>Operator:</b> Milestone Environmental	<b>Project Number:</b> F2131	<b>Rig Contractor:</b>
<b>Well API/SN:</b> 30-025-49600	<b>PO Number:</b>	<b>Days on Location:</b> 12
<b>Field:</b>	<b>Spud Date:</b>	<b>Days from Spud:</b>
<b>County/Parish:</b> Lea	<b>Report Number:</b> 12	<b>RKB:</b>
<b>State:</b> NM	<b>Report Date:</b> 02-20-2022	<b>Current Depth:</b>
<b>Company Man:</b> Mike Zaunbrecher	<b>Cell Phone:</b> 337-581-6514	<b>Rig Phone:</b>

### ACTIVITY LAST 24 HOURS

		Footage:	Rotary Hours:	ROP:	FPH
FROM	TO	HOURS	DESCRIPTION		
7:00	8:00	1:00	OFFLOAD RENTAL EQUIPMENT; RIG UP FLOWBACK IRON & PUMP TRUCK		
8:00	12:30	4:30	SAFETY MEETING WITH CUDD PERSONEL ON RIGGING UP; SPOT AND RIG UP COIL TUBING UNIT; PUMP TRUCKS AND SUPPORT EQUIPMENT		
		0:00	PRESSURE TEST LINES TO 3000 PSI		
12:30	16:00	3:30	RIH W/ 2-3/8" COIL TUBING @ 50-60 FT/MIN. PUMPING 4 BPM WASHING OVER PERFORATIONS F/6271' T/7208'		
		0:00	(STOPPING EVERY 250' AND WORKING COIL TUBING UP 100') TAGGED SLIGHT BRIDGE @ 7135' TAKKING ABOUT 2K WEIGHT.		
16:00	19:00	3:00	CIRCULATE HOLE CLEAN; PUMP 10 BBL 65 VIS. SWEEP AND CIRCULATE AT 4 BBL/MIN AND 350 SCFM NITROGEN.		
19:00	21:00	2:00	STOP NITROGEN INJECTION AND CIRCULATE OUT		
21:00	22:30	1:30	POSITION WASH NOZZLE @ 7208' PUMP 178 BBLS (7500 GAL) OF 15% HCL SPOTTING ACROSS PERF'S F/7030' T/7208' @ 3 BBL/MIN		
		0:00	1100 PSI AT START OF STAGE; 500 PSI AT END OF STAGE.		
22:30	23:30	1:00	SHUT IN WELL FOR 1 HOUR; PRESSURE BLED DOWN TO 0 PSI		
23:30	23:45	0:15	BULLHEAD 10 BBLS OF BRINE @ 3 BBL/MIN AND 500 PSI		
23:45	1:30	1:45	POSITION WASH NOZZLE @ 6910' PUMP 178 BBLS (7500 GAL) OF 15% HCL SPOTTING ACROSS PERF'S F/6686' T/6910' @ 3 BBL/MIN		
		0:00	500 PSI AT START OF STAGE; 400 PSI AT END OF STAGE.		
1:30	2:30	1:00	SHUT IN WELL FOR 1 HOUR; PRESSURE BLED DOWN TO 0 PSI		
2:30	2:45	0:15	BULLHEAD 10 BBLS OF BRINE @ 3 BBL/MIN AND 500 PSI		
2:45	4:30	1:45	POSITION WASH NOZZLE @ 6626' PUMP 178 BBLS (7500 GAL) OF 15% HCL SPOTTING ACROSS PERF'S F/6480' T/6626' @ 3 BBL/MIN		
4:30	6:00	1:30	500 PSI AT START OF STAGE; 400 PSI AT END OF STAGE.		
		0:00	SHUT IN WELL FOR 1 HOUR; PRESSURE BLED DOWN TO 0 PSI		
		0:00	HAUL BRINE PRIOR TO FINAL ACID STAGE		
		0:00			
		0:00			
		0:00			
		0:00			
		0:00			
		0:00			
		0:00			
		0:00			
		23:00	TOTAL HOURS		

**PLANNED ACTIVITY NEXT 24 HRS**

PUMP ACID STAGE 4. PUMP BRINE TO FLUSH WELLBORE AND MONITOR INJECTION RATE/PRESSURE RESPONSE. RDMO COIL TUBING AND SUPPORT EQUIPMENT.

## Beaza SWD No. 1

<b>Operator:</b> Milestone Environmental	<b>Project Number:</b> F2131	<b>Rig Contractor:</b>
<b>Well API/SN:</b> 30-025-49600	<b>PO Number:</b>	<b>Days on Location:</b> 13
<b>Field:</b>	<b>Spud Date:</b>	<b>Days from Spud:</b>
<b>County/Parish:</b> Lea	<b>Report Number:</b> 13	<b>RKB:</b>
<b>State:</b> NM	<b>Report Date:</b> 02-21-2022	<b>Current Depth:</b>
<b>Company Man:</b> Mike Zaunbrecher	<b>Cell Phone:</b> 337-581-6514	<b>Rig Phone:</b>

### ACTIVITY LAST 24 HOURS

			Footage:	Rotary Hours:	ROP:	FPH
FROM	TO	HOURS	DESCRIPTION			
6:00	11:30	5:30	WAIT FOR BRINE TO ARRIVE ON LOCATION PRIOR TO PUMPING LAST ACID STAGE			
11:30	12:00	0:30	BEGIN PUMPING FINAL ACID STAGE			
12:00	12:30	0:30	SHUT DOWN DUE TO LEAKING SEAL ON 2" 1502 UNION. PURGE LINE WITH BRINE SODA ASH MIXTURE. REPLACE BAD SEAL.			
		0:00	ABOUT 1 BBL OF 15% HCL SPILLED. (REPORTED TO MILESTONE, LONQUIST AND CUDD HSE)			
12:30	14:00	1:30	CONTINUE PUMPING 178 BBLS (7500 GAL) OF 15% HCL SPOTTING ACROSS PERF'S F/6271' T/6440' @ 3 BBL/MIN AND 300 PSI			
14:00	16:00	2:00	P.O.O.H. W/COIL TUBING; PURGE REEL WITH NITROGEN			
16:00	17:00	1:00	RIG DOWN COIL TUBING AND BOP'S; INSTALL AND TORQUE BLIND FLANGE ON FLOW CROSS			
17:00	17:30	0:30	PERFORM ABBREVIATED INJECTION TEST PUMPING DOWN 7" CSG HOLDING EACH RATE FOR 5 MIN.			
		0:00	2BPM @ 130-130PSI / 4BPM @ 130-163PSI / 6BPM @ 261-774 PSI / 9BPM @ 960 - 980 PSI			
17:30	18:30	1:00	RIG DOWN PUMP TRUCK AND FLOWBACK IRON. MOVE OUT EQUIPMENT. WELLBORE PRESSURE 350 PSI.			
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		0:00				
		12:30	<b>TOTAL HOURS</b>			

**PLANNED ACTIVITY NEXT 24 HRS**

RELEASE ACID TANKS, OPEN TOP, BOOSTER PUMP AND FLOWBACK. DETERMINE PATH FORWARD FOR COMPLETION AND TESTING.

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
  
Action 93027

CONDITIONS

Operator: Milestone Environmental Services, LLC 15721 Park Row Houston, TX 77084	OGRID: 328435
	Action Number: 93027
	Action Type: [C-103] NOI General Sundry (C-103X)

CONDITIONS

Created By	Condition	Condition Date
pgoetze	None	4/4/2022