KB = 12 ft GL = 6,295 ft API# 30-045-11676

Prepared by: JRyza

Date: 02/14/2022

Spud Date: 05/05/1966

Ready to produce: 05/20/1966

## MorningStar Operating, LLC

## Tibbar Federal #1 San Juan County, NM

TD - 6,646 ft MD

12-1/4" hole to 296' KB Surface Csg: 9 jts 8-5/8" 24# J55 STC Setting Depth: 296 ft

Cement 175sx Reg cement WOC & test

7-7/8" hole to 6646' Prod Csg: 206 jts 4-1/2" 10.5# J55 STC Setting Depth: 6,646 ft DV tools @ 2100' & 4663'

Cement

1<sup>st</sup> stage lead: 175sx 50/50 Pozmix

1<sup>st</sup> stage tail: 100sx reg cement

2<sup>nd</sup> stage: 250sx 50/50 Pozmix

3<sup>rd</sup> stage: 500sx 50/50 Pozmix

<u>Perfs: (Dakota): (4 spf):</u> 6,388'-98', 6,426'-30', 6,480'-90', 6,564'-68', 6,584'-97'

Casing squeeze (1/27/1986): Set RBP @ 6250', Determine casing leak between 2103' to 3590' w/ pkr. Squeeze w/ 450sx Class H (561 ft<sup>3</sup>) Drillout and test to 1500 psi good 6/19/2001 - test same to 650 psi, good 5/27/2015 - Pull tbg & packer from well Prod Tbg run 05/28/2015: 2-3/8" 4.7# J-55 tbg: 148 jts tbg, Model R pkr, 59 jts tbg, SN, 1 jt tbg EOT=6,605' KB; Pkr @ 4,695' KB Dakota Perfs: 6,388' - 6,597' (overall)

PBTD: 6,624 ft MD

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505** 

CONDITIONS

Action 81510

## **CONDITIONS**

Operator:	OGRID:
MorningStar Operating LLC	330132
400 W 7th St	Action Number:
Fort Worth, TX 76102	81510
	Action Type:
	[UF-WBS] Wellbore Schematic (WELLBORE SCHEMATICS)

## CONDITIONS

Created By		Condition Date
mkuehling	None	4/29/2022