I of										
Page 1 of	Form 3160-5 UNITED STATES (June 2019) DEPARTMENT OF THE INTERIOR			RIOR			FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021			
	BUREAU OF LAND MANAGEMENT						5. Lease Serial No. NN	1NM03619	1	
	SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name					
	SUBMIT IN TRIPLICATE - Other instructions on page 2						7. If Unit of CA/Agreement, Name and/or No.			
	1. Type of Well ☐ Gas Well ☐ Other						8. Well Name and No. FEDERALES BO/5			
	2. Name of Operator SILVERBACK OPERATING II LLC						9. API Well No. 3001521153			
		707 IH 10 WEST SUITE 2	01, SAN ANTONIO, 3b. F	Phone No. <i>(inch</i> 3) 585-3316						
	4. Location of W SEC 23/T17S	ell <i>(Footage, Sec., T.,R.,M., d</i> /R25E/NMP	2	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			11. Country or Parish, State EDDY/NM			
		12. CHECK TI	HE APPROPRIATE BOX(E	S) TO INDICA	TE NATURE	OF NOTIO	CE, REPORT OR OTH	ER DATA		
	TYPE OF	SUBMISSION			TYP	E OF ACT	TION			
	✓ Notice of	Intent	Acidize Alter Casing	Deepen Deepen Hydraulic	Fracturing		uction (Start/Resume)		r Shut-Off Integrity	
	Subseque	nt Report	Casing Repair Change Plans	New Cons		_	mplete oorarily Abandon	✓ Other	r .	
	Final Aba	ndonment Notice	Convert to Injection	Plug Back			r Disposal			
	the Bond under which the work will be performed or provide the Bond No. on file with BLM/BL completion of the involved operations. If the operation results in a multiple completion or recom completed. Final Abandonment Notices must be filed only after all requirements, including recla is ready for final inspection.) Plug and Abandon the Federales BO #5. See attached.						new interval, a Form 31	60-4 must b	e filed once testing has been	
2	No attachments included.									
	14. I hereby certify that the foregoing is true and correct. Name ( <i>Printed/Typed</i> ) RUDY WILDENSTEIN / Ph: (713) 829-0362				Reservoir Engineer Title					
0 AM	Signature AppA				Date 07/01/2022					
	epted for record – NMOCD gc 7/6/2022 THE SPACE FOR FEDERAL OR					ATE OF	ICE USE			
2 8:	Approved by				ENG	NEER			04/27/2022	
7/6/2022	KEITH P IMMATTY / Ph: (575) 988-4722 / Approved				Title		[ [	late	0412112022	
	Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.					RLSBAD	(			
i by OC		ection 1001 and Title 43 U.S. us or fraudulent statements o				y and will	fully to make to any de	partment or a	agency of the United States	
Received by OCD:	(Instructions on page 2)									

•

**Released to Imaging:** 7/7/2022 9:10:28 AM

#### **GENERAL INSTRUCTIONS**

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

#### SPECIFIC INSTRUCTIONS

*Item 4* - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

*Item 13:* Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

#### NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Released to Imaging: 7/7/2022 9:10:28 AM

## **Additional Information**

### Location of Well

0. SHL: NWNW / 330 FNL / 330 FWL / TWSP: 17S / RANGE: 25E / SECTION: 23 / LAT: 0.0 / LONG: 0.0 ( TVD: 0 feet, MD: 0 feet ) BHL: NWNW / 330 FNL / 330 FWL / TWSP: 17S / SECTION: / LAT: 0.0 / LONG: 0.0 ( TVD: 0 feet, MD: 0 feet )

(Form 3160-5, page 3)

**Federales BO #5** 300152115300S01 T17S-R25E-Section 23 UNIT D NWNW


Silverback Operating II, LLC plans to plug and abandon this well as follows:

- 1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
- 2. Set a CIBP at 1218 ft and perforate at 1184 ft. Perfs not necessary when there is cement in the annulus behind casing. Pump 42 sx Class C cement on top of CIBP to 654 ft. WOC and tag. This will cover San Andres perfs and top and casing shoe. Pressure test to 500psi for 30mins.
- 3. Perforate at 350 ft. Spot a 25 30sx Class C cement plug from 350 410ft up to surface. WOC and tag. Back fill as needed. Corrected for top of salt plug.
- 4. Cut off wellhead and install dry hole marker. Clean location as per regulated.

Wellbore schematics attached

Eadar	ales BO #5	Current				23-17S-2				30-015-2	
reuen	ales DU #5	Current	F	ootage	e Calls:	330' FNL	& 330'	FWL		Elev 350	6' GR
COMMENTS											
A	A		CAS	ING DET	AIL						
			#	HOLE	CSG	WGHT	GRADE	Тор	Depth	TOC	SX
			А	14	10.75	32	J-55	0	300	Circ	175
			В	9 1/2	7	23	J-55	0	1,134	Circ	450
			С	6 1/4	5.5	15.5	J-55	0	724	Circ	
			C	6 1/8	4.5	9.5	J-55	724	1,454	Circ	125
									.,		
											1
			FOR	MATION	TOPS						
res at 704'				FORM/		TOP	F	ORMATIO	אר		TOP
			QAN	ANDRES		704					TUF
			SAN		,	104					1
						+					
	В					1	I				1
			TUB	ING DET		•	•				
				OD	GRADE	WGHT	TOP	BASE			
			2	2 3/8			0	1401			
									]		
									]	TDEA	
					FORMATI		ТОР	BASE			TMENT
							TOP 1268			TREA 15% ACID 8	
			PER		FORMATI						
			PER		FORMATI						
			PER		FORMATI						
			PER		FORMATI						
			PER		FORMATI						
			PER		FORMATI						
			PER		FORMATI						
395'			PER		FORMATI						
-1395'	W		PER		FORMATI						
268'-1395'	W		PER		FORMATI						
1268'-1395'	W		PER		FORMATI						
'-1395'			PER		FORMATI						
7	с 1454'		PER		FORMATI						

Page 5 of 13



Page 6 of 13

•

Sundry ID	2668079					
Plug Type	Тор	Bottom	Length	Tag	Sacks	Notes
Curfeee Dive	0.00	100.00	100.00	TogAlority	20.00	410' to surface. Covers TOS, shoe
Surface Plug	0.00	100.00	100.00	Tag/Verify	30.00	and surface 410' to surface.
Shoe Plug	247.00	350.00	103.00	Tag/Verify	30.00	Covers TOS, shoe and surface
				If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio		410' to surface. Covers TOS, shoe
Fresh Water @ 340	286.60	390.00	103.40	ns	30.00	and surface 410' to surface.
	000 40	440.00	400.00	TerAlerifi	20.00	Covers TOS, shoe
Top of Salt @ 360	306.40	410.00	103.60	Tag/Verify	30.00	and surface Covered by CIBP
Base of Salt @ 780	722.20	830.00	107.80	Tag/Verify	42.00	-
Shoe Plug	1072.66	1184.00	111.34	Tag/Verify	42.00	
				If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio		Pressure test to
CIBP Plug	1183.00	1218.00	35.00	ns	42.00	500psi for 30mins

No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole. Class H >7500' Class C<7500' Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible. Critical, High, Medium, Secretary : Top of salt to surface If no salt take the deepest fresh water. R111P: 50' from bottom of salt to surface

Class C: 1.32 ft^3/sx	
Class H: 1.06 ft^3/sx	

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement	Low		
Shaa @	200.00		
Shoe @	300.00		
Shoe @	1134.00		
Shoe @	1454.00		
Perforatons Top @	1268.00	Perforations	1395.00
		CIBP @	1218.00

## BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

## Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.** 

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.** 

8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



# **United States Department of the Interior**

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

#### **Reclamation Objectives and Procedures**

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech/Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Jose Martinez-Colon Environmental Protection Specialist 575-234-5951

Mark Mattozzi Environmental Protection Specialist 575-234-5713

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612

District I 1625 N. French Dr., Hobbs, NM 88240 Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

## **State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:		
Silverback Operating II, LLC	330968		
IH10 West, Suite 201	Action Number:		
San Antonio, TX 78257	122969		
	Action Type:		
	[C-103] NOI Plug & Abandon (C-103F)		
CONDITIONS			

Created By	Condition	Condition Date
jagarcia	This well was plugged in violation of 19.15.25.9 NMAC, as the well was plugged without a required Division approved notice of intention sundry. Because this is a federal well the filing is required pursuant to 19.15.7.11 NMAC which requires "For wells located on land that the United States or a native American nation, tribe or pueblo owns, an operator shall file applications for permit to drill, deepen or plug back, BLM form no. 3160-3; sundry notices and reports on wells, BLM form no. 3160-5; and well completion or recompletion report and log, BLM form no. 3160-4 with the BLM in lieu of filing the corresponding division forms with the division. All such forms are, however, subject to division approval in the same manner and to the same extent as the corresponding division forms."	7/7/2022

CONDITIONS

Page 13 of 13

Action 122969