

| | | |
|--------------------------------------------------|--------------------------------------------------------------|-----------------------------------------------------|
| Well Name: FLOOFY CAT 21-16 FED STATE COM | Well Location: T23S / R32E / SEC 21 / SESW / | County or Parish/State: |
| Well Number: 524H | Type of Well: OIL WELL | Allottee or Tribe Name: |
| Lease Number: NMNM86153 | Unit or CA Name: | Unit or CA Number: |
| US Well Number: 3002550046 | Well Status: Approved Application for Permit to Drill | Operator: DEVON ENERGY PRODUCTION COMPANY LP |

Notice of Intent

Sundry ID: 2692055

| | |
|-------------------------------------------------------|-------------------------------------|
| Type of Submission: Notice of Intent | Type of Action: APD Change |
| Date Sundry Submitted: 09/12/2022 | Time Sundry Submitted: 08:45 |
| Date proposed operation will begin: 09/12/2022 | |

Procedure Description: PILOT HOLE SUNDRY: Devon Energy Production Co., L.P. (Devon) respectfully requests to run a pilot hole on the subject well. Pilot Hole:9,300ft-11,900ft; Procedure for Abandonment: 1. Finish coring and logging 2. Spot 1st Bone Spring Balanced Plug (10,286-10,491), tag and verfiy 3. Spot 2nd Bone Lime Balanced Plug (9,706-9,896), tag and verify 4. Prep well for whip stock 5. Run, orient, and set whip stock 6. KOP for Avalon B Production Curve/Lateral

NOI Attachments

Procedure Description

- FLOOFY_CAT_21_16_FED_STATE_COM_524H_Sundry_20220912204505.pdf
- 9.625_40lb_J_55_20220912204502.pdf
- 9.625_40.00_L80HC___BTC_20220912204501.pdf

| | | |
|--------------------------------------------------|--------------------------------------------------------------|-----------------------------------------------------|
| Well Name: FLOOFY CAT 21-16 FED STATE COM | Well Location: T23S / R32E / SEC 21 / SESW / | County or Parish/State: |
| Well Number: 524H | Type of Well: OIL WELL | Allottee or Tribe Name: |
| Lease Number: NMNM86153 | Unit or CA Name: | Unit or CA Number: |
| US Well Number: 3002550046 | Well Status: Approved Application for Permit to Drill | Operator: DEVON ENERGY PRODUCTION COMPANY LP |

Conditions of Approval

Additional

Floofy_Cat_21_16_Fed_State_Com_524H_Sundry_ID_2692055_Pilot_Hole_20221007130239.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

| | |
|---------------------------------------------------|-----------------------------------------|
| Operator Electronic Signature: JENNY HARMS | Signed on: SEP 12, 2022 08:45 PM |
| Name: DEVON ENERGY PRODUCTION COMPANY LP | |
| Title: Regulatory Compliance Professional | |
| Street Address: 333 West Sheridan Avenue | |
| City: Oklahoma City | State: OK |
| Phone: (405) 552-6560 | |
| Email address: jennifer.harms@dvn.com | |

Field

| | | |
|-----------------------------|---------------|-------------|
| Representative Name: | | |
| Street Address: | | |
| City: | State: | Zip: |
| Phone: | | |
| Email address: | | |

BLM Point of Contact

| | |
|----------------------------------------|----------------------------------------------|
| BLM POC Name: CHRISTOPHER WALLS | BLM POC Title: Petroleum Engineer |
| BLM POC Phone: 5752342234 | BLM POC Email Address: cwalls@blm.gov |
| Disposition: Approved | Disposition Date: 10/20/2022 |
| Signature: Chris Walls | |



Technical Data Sheet

9 5/8" 40.00 lbs/ft. L80HC - BTC

Mechanical Properties

| | | |
|--------------------------|------|--------|
| Minimum Yield Strength | psi. | 80,000 |
| Maximum Yield Strength | psi. | 95,000 |
| Minimum Tensile Strength | psi. | 95,000 |

Dimensions

| | | Pipe | BTC | LTC | STC |
|-----------------------|---------|-------|--------|-----|-----|
| Outside Diameter | in. | 9.625 | 10.625 | - | - |
| Wall Thickness | in. | 0.395 | - | - | - |
| Inside Diameter | in. | 8.835 | - | - | - |
| Standard Drift | in. | - | - | - | - |
| Alternate Drift | in. | 8.750 | - | - | - |
| Plain End Weight | lbs/ft. | - | - | - | - |
| Nominal Linear Weight | lbs/ft. | 40.00 | - | - | - |

Performance

| | | Pipe | BTC | LTC | STC |
|----------------------------------|------|-------------|-------------|-----|-----|
| Minimum Collapse Pressure | psi. | 3,870 | - | - | - |
| Minimum Internal Yield Pressure | psi. | 5,750 | 5,750 | - | - |
| Minimum Pipe Body Yield Strength | lbs. | 916 x 1,000 | - | - | - |
| Joint Strength | lbs. | - | 947 x 1,000 | - | - |

Make-Up Torques

| | | Pipe | BTC | LTC | STC |
|------------------------------------|---------|------|-----|-----|-----|
| Make-Up Loss | in. | - | - | - | - |
| Optimum Make-Up Torque | ft/lbs. | - | - | - | - |
| Maximum Operational Make-Up Torque | ft/lbs. | - | - | - | - |

Disclaimer: The content of this Technical Data Sheet is for general information only and does not guarantee performance and/or accuracy, which can only be determined by a professional expert with the specific installation and operation parameters. Information printed or downloaded may not be current and no longer in control by Axis Pipe and Tube. Anyone using the information herein does so at his or her own risk. To verify that you have the latest technical information, please contact Axis Pipe and Tube Technical Sales +1 (979) 599-7600, www.axispipeandtube.com



U. S. Steel Tubular Products

9.625" 40.00lbs/ft (0.395" Wall) J55

1/24/2019 2:45:24 PM

| MECHANICAL PROPERTIES | Pipe | BTC | LTC | STC | |
|----------------------------------|--------|--------|--------|--------|-----------|
| Minimum Yield Strength | 55,000 | -- | -- | -- | psi |
| Maximum Yield Strength | 80,000 | -- | -- | -- | psi |
| Minimum Tensile Strength | 75,000 | -- | -- | -- | psi |
| DIMENSIONS | Pipe | BTC | LTC | STC | |
| Outside Diameter | 9.625 | 10.625 | 10.625 | 10.625 | in. |
| Wall Thickness | 0.395 | -- | -- | -- | in. |
| Inside Diameter | 8.835 | 8.835 | 8.835 | 8.835 | in. |
| Standard Drift | 8.679 | 8.679 | 8.679 | 8.679 | in. |
| Alternate Drift | 8.750 | 8.750 | 8.750 | 8.750 | in. |
| Nominal Linear Weight, T&C | 40.00 | -- | -- | -- | lbs/ft |
| Plain End Weight | 38.97 | -- | -- | -- | lbs/ft |
| PERFORMANCE | Pipe | BTC | LTC | STC | |
| Minimum Collapse Pressure | 2,570 | 2,570 | 2,570 | 2,570 | psi |
| Minimum Internal Yield Pressure | 3,950 | 3,950 | 3,950 | 3,950 | psi |
| Minimum Pipe Body Yield Strength | 630 | -- | -- | -- | 1,000 lbs |
| Joint Strength | -- | 714 | 520 | 452 | 1,000 lbs |
| Reference Length | -- | 11,898 | 8,665 | 7,529 | ft |
| MAKE-UP DATA | Pipe | BTC | LTC | STC | |
| Make-Up Loss | -- | 4.81 | 4.75 | 3.38 | in. |
| Minimum Make-Up Torque | -- | -- | 3,900 | 3,390 | ft-lbs |
| Maximum Make-Up Torque | -- | -- | 6,500 | 5,650 | ft-lbs |

Legal Notice

All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products
460 Wildwood Forest Drive, Suite 300S
Spring, Texas 77380

1-877-893-9461
connections@uss.com
www.usstubular.com

FLOOFY CAT 21-16 FED STATE COM 524H

1. Geologic Formations

| | | | |
|---------------|-------|------------------------------|-------|
| TVD of target | 9650 | Pilot hole depth | 11900 |
| MD at TD: | 19902 | Deepest expected fresh water | |

Basin

| Formation | Depth (TVD) from KB | Water/Mineral Bearing/Target Zone? | Hazards* |
|----------------------|---------------------------|------------------------------------------|----------|
| Rustler | 1160 | | |
| Salt | 2600 | | |
| Base of Salt | 4805 | | |
| Delaware | 4840 | | |
| Cherry Canyon | 5970 | | |
| Brushy Canyon | 6300 | | |
| 1st Bone Spring Lime | 8640 | | |
| Avalon | 9160 | | |
| 1st Bone Spring Sand | 9846 | | |
| 2nd Bone Spring Lime | 10139 | | |
| 2nd Bone Spring Sand | 10441 | | |
| 3rd Bone Spring Lime | 10963 | | |
| 3rd Bone Spring Sand | 11749 | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

*H2S, water flows, loss of circulation, abnormal pressures, etc.

FLOOFY CAT 21-16 FED STATE COM 524H

2. Casing Program

| Hole Size | Csg. Size | Wt (PPF) | Grade | Conn | Casing Interval | | Casing Interval | |
|-----------|-----------|-------------|----------------|------|-----------------|--------------|-----------------|--------------|
| | | | | | From (MD) | To (MD) | From (TVD) | To (TVD) |
| 17 1/2 | 13 3/8 | 48 | H40 | BTC | 0 | 1185 | 0 | 1185 |
| 12 1/4 | 9 5/8 | 40 | J-55 L-80HC | BTC | 0 4500 | 4500 8400 | 0 | 4400 8300 |
| 8 3/4 | 5 1/2 | 17 | P110 | BTC | 0 | 19902 | 0 | 9650 |

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.

FLOOFY CAT 21-16 FED STATE COM 524H

3. Cementing Program (3-String Primary Design)

| Casing | # Sks | TOC | Wt. (lb/gal) | Yld (ft ³ /sack) | Slurry Description |
|------------|-------|--------------|-----------------|--------------------------------|----------------------------------------------------------------|
| Surface | 896 | Surf | 13.2 | 1.4 | Lead: Class C Cement + additives |
| Int 1 | 777 | Surf | 9.0 | 3.3 | 2nd Stage Bradenhead Squeeze - Lead: Class C Cement + additive |
| | 727 | Brushy' | 13.2 | 1.4 | Tail: Class H / C + additives |
| | | | | | |
| | | | | | |
| | | | | | |
| Production | 399 | 500' tieback | 9.0 | 3.3 | Lead: Class H / C + additives |
| | 2089 | KOP | 13.2 | 1.4 | Tail: Class H / C + additives |

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Assuming no returns are established while drilling, Devon requests to pump a two stage cement job on the 9-5/8" intermediate casing string with the first stage being pumped conventionally with the calculated top of cement at the Brushy Canyon and the second stage performed as a bradenhead squeeze with planned cement from the Brushy Canyon to surface. If necessary, a top out of Class C cement + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (2.30 yld, 12.91 ppg) will be executed as a contingency. The final cement top will be verified by Echo-meter.

Devon will include the Echo-meter verified fluid top and the volume of displacement fluid above the cement slurry in the annulus in all post-drill sundries on wells utilizing this cement program. Devon will report to the BLM the volume of fluid (limited to 1 bbls) used to flush intermediate casing valves following backside cementing procedures.

| Casing String | % Excess |
|---------------|----------|
| Surface | 50% |
| Intermediate | 30% |
| Production | 10% |

FLOOFY CAT 21-16 FED STATE COM 524H

4. Pressure Control Equipment (Three String Design)

| BOP installed and tested before drilling which hole? | Size? | Min. Required WP | Type | ✓ | Tested to: |
|------------------------------------------------------|---------|------------------|------------|---|-------------------------------|
| Int 1 | 13-58" | 5M | Annular | X | 50% of rated working pressure |
| | | | Blind Ram | X | 5M |
| | | | Pipe Ram | | |
| | | | Double Ram | X | |
| | | | Other* | | |
| Production | 13-5/8" | 5M | Annular | X | 50% of rated working pressure |
| | | | Blind Ram | X | 5M |
| | | | Pipe Ram | | |
| | | | Double Ram | X | |
| | | | Other* | | |
| Pilot Hole | 13-5/8" | 5M | Annular | X | 50% of rated working pressure |
| | | | Blind Ram | X | 5M |
| | | | Pipe Ram | | |
| | | | Double Ram | X | |
| | | | Other* | | |

FLOOFY CAT 21-16 FED STATE COM 524H

5. Mud Program (Three String Design)

| Section | Type | Weight (ppg) |
|--------------|--------|--------------|
| Surface | FW Gel | 8.5-9 |
| Intermediate | Brine | 10-10.5 |
| Production | WBM | 8.5-9 |
| Pilot Hole | WBM | 8.5-9 |

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

| | |
|---------------------------------------------------------|-----------------------------|
| What will be used to monitor the loss or gain of fluid? | PVT/Pason/Visual Monitoring |
|---------------------------------------------------------|-----------------------------|

Logging, Coring and Testing

| | |
|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| X | Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM. |
| X | Formation logging is planned |
| | Drill stem test? If yes, explain. |
| X | Coring? Coring planned from 1st Bone Sand to 2nd Bone Lime, ~9,805-10,360, approximately 600ft |

| Additional logs planned | | Interval |
|-------------------------|-------------------|--------------------------|
| X | Resistivity | Surface to 3rd Bone Lime |
| X | Density and Sonic | Surface to 3rd Bone Lime |
| X | Litho Scanner | Surface to 3rd Bone Lime |
| X | Mud log | Surface to 3rd Bone Lime |
| X | PEX | Surface to 3rd Bone Lime |

7. Drilling Conditions

| Condition | Specify what type and where? |
|----------------------------|------------------------------|
| BH pressure at deepest TVD | 7150 |
| Abnormal temperature | No |

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H₂S) monitors will be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

| | |
|---|---------------------------------|
| N | H ₂ S is present |
| Y | H ₂ S plan attached. |

FLOOFY CAT 21-16 FED STATE COM 524H

8. Other facets of operation

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
 - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pad.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments

X Directional Plan
 Other, describe

FLOOFY CAT 21-16 FED STATE COM 524H

9. Pilot Hole

| Hole Size 8 3/4" | |
|---------------------|--------------------|
| From | To |
| 9,300 (Pilot Begin) | 11,900 (Pilot end) |

- Pilot hole will be plugged back per NMOCD P&A requirements with a **cement plug**.
- Plug depths will be verified and tagged on the plug back.
- Devon will contact the NMOCD and give notice before performing any of the aforementioned procedures including the tagging of the cement plug.
- Additional cement coverage will be placed during Production Casing Cement job

| WHIP & CMT PLUG - 1st B Sand | |
|------------------------------|--------|
| Slurry Top: | 9,706' |
| Slurry Base: | 9,896' |
| Slurry Weight: | 15.6 |
| Cement Plug Height: | 190' |
| Estimated Whip | 8900' |

| CMT PLUG - 2nd Bone Spring Sand | |
|---------------------------------|---------|
| Slurry Top: | 10,286' |
| Slurry Base: | 10,491' |
| Slurry Weight: | 15.6 |
| Cement Plug Height: | 205' |

| | TOC | Wt. (lb/gal) | H ₂ O (gal/sk) | Yld (ft ³ /sack) | Slurry Description |
|----------|--------|-----------------|------------------------------|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Plug - 1 | 9,706' | 15.6 | 5.24 | 1.18 | <ul style="list-style-type: none"> • Lead: Class H Cement + Retarder – HR-601 – 0.1% BWOC • Suspension Agent – SA-1015 – 0.05% BWOC • Fluid Loss Additive – Halad-322 – 0.5% BWOC |

| | TOC | Wt. (lb/gal) | H ₂ O (gal/sk) | Yld (ft ³ /sack) | Slurry Description |
|----------|---------|-----------------|------------------------------|--------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Plug - 2 | 10,286' | 15.6 | 5.24 | 1.18 | <ul style="list-style-type: none"> • Lead: Class H Cement + Retarder – HR-601 – 0.1% BWOC • Suspension Agent – SA-1015 – 0.05% BWOC • Fluid Loss Additive – Halad-322 – 0.5% BWOC |

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

| | |
|-------------------------|--------------------------------------------|
| OPERATOR'S NAME: | Devon Energy Production Company LP |
| LEASE NO.: | Floofy Cat 21-16 Fed State Com 524H |
| LOCATION: | Section 21, T.23 S., R.32 E., NMPM |
| COUNTY: | Lea County, New Mexico |

| | |
|------------------------------|-------------------------------------|
| WELL NAME & NO.: | Cutbow 36 1 Federal Com 603H |
| SURFACE HOLE FOOTAGE: | 500'/S & 2340'/W |
| BOTTOM HOLE FOOTAGE: | 20'/N & 2310'/W |
| ATS/API ID: | ATS-22-1509 |
| Sundry ID: | 2692055 |

COA

| | | | |
|-------------------------------|----------------------------------------------------|------------------------------------------------|------------------------------------------|
| H2S | <input checked="" type="checkbox"/> Yes | <input type="checkbox"/> No | |
| Potash | <input checked="" type="checkbox"/> None | <input type="checkbox"/> Secretary | <input type="checkbox"/> R-111-P |
| Cave/Karst Potential | <input checked="" type="checkbox"/> Low | <input type="checkbox"/> Medium | <input type="checkbox"/> High |
| Cave/Karst Potential | <input type="checkbox"/> Critical | | |
| Variance | <input type="checkbox"/> None | <input checked="" type="checkbox"/> Flex Hose | <input type="checkbox"/> Other |
| Wellhead | <input type="checkbox"/> Conventional | <input type="checkbox"/> Multibowl | <input checked="" type="checkbox"/> Both |
| Wellhead Variance | <input type="checkbox"/> Diverter | | |
| Other | <input type="checkbox"/> 4 String | <input type="checkbox"/> Capitan Reef | <input type="checkbox"/> WIPP |
| Other | <input checked="" type="checkbox"/> Fluid Filled | <input checked="" type="checkbox"/> Pilot Hole | <input type="checkbox"/> Open Annulus |
| Cementing | <input checked="" type="checkbox"/> Cement Squeeze | <input type="checkbox"/> EchoMeter | |
| Special Requirements | <input type="checkbox"/> Water Disposal | <input checked="" type="checkbox"/> COM | <input type="checkbox"/> Unit |
| Special Requirements Variance | <input type="checkbox"/> Break Testing | <input type="checkbox"/> Offline Cementing | |

All Previous COAs Still Apply.

The pilot hole plugging procedure is approved as written. Note plug tops on subsequent drilling report. The BLM is to be contacted 24 hours prior to the commencement of any plugging operations (**575-689-5981 Lea County**) and when tagging the plugs. The 1st Bone Spring Sand formation top plug shall be **254'** in length from **9896' to 9638'** with a minimum of **92 sx** Class H cement.

- ❖ Mud Requirement: Mud shall be placed between all or below plugs. Minimum consistency of plugging mud shall be obtained by mixing at a rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

- ❖ Cement requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.
- ❖ Subsequent Plugging Reporting: Within 30 days after plugging work is completed to the BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date pilot hole was plugged and tagged.**

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
689-5981

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not

hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

LVO 10/7/2022

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 152508

CONDITIONS

| | |
|-------------------------------------------------------------------------------------------------------|------------------------------------------------------|
| Operator: DEVON ENERGY PRODUCTION COMPANY, LP 333 West Sheridan Ave. Oklahoma City, OK 73102 | OGRID: 6137 |
| | Action Number: 152508 |
| | Action Type: [C-103] NOI Change of Plans (C-103A) |

CONDITIONS

| Created By | Condition | Condition Date |
|------------|-----------|----------------|
| pkautz | None | 10/21/2022 |