

Well Name: JICARILLA M	Well Location: T23N / R2W / SEC 8 / NESW /	County or Parish/State: RIO ARRIBA / NM
Well Number: 3	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name: JICARILLA APACHE
Lease Number: JIC157	Unit or CA Name:	Unit or CA Number:
US Well Number: 3003908146	Well Status: Producing Gas Well	Operator: DJR OPERATING LLC

Notice of Intent

Sundry ID: 2697754

Type of Submission: Notice of Intent	Type of Action: Plug and Abandonment
Date Sundry Submitted: 10/12/2022	Time Sundry Submitted: 12:08
Date proposed operation will begin: 10/12/2022	

**Procedure Description:** This request is being submitted for engineering & geological review prior to onsite inspection as approved by Dave M. of the BLM. DJR Operating, LLC requests permission to Plug & Abandon the subject well according to the attached Procedure, Current & Proposed Wellbore Diagram.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

NOI\_PA\_BLM\_Submittal\_20221012120807.pdf

Well Name: JICARILLA M	Well Location: T23N / R2W / SEC 8 / NESW /	County or Parish/State: RIO ARRIBA / NM
Well Number: 3	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name: JICARILLA APACHE
Lease Number: JIC157	Unit or CA Name:	Unit or CA Number:
US Well Number: 3003908146	Well Status: Producing Gas Well	Operator: DJR OPERATING LLC

Conditions of Approval

Specialist Review

General\_Requirement\_PxA\_20221024162614.pdf  
23N2W8\_Jicarilla\_M\_3\_Geo\_KGR\_20221024162550.pdf  
2697754\_NOIA\_M\_3\_3003908146\_KR\_10242022\_20221024162540.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: SHAW-MARIE FORD  
Signed on: OCT 12, 2022 12:08 PM  
Name: DJR OPERATING LLC  
Title: Regulatory Specialist  
Street Address: 1 Road 3263  
City: Aztec State: NM  
Phone: (505) 632-3476  
Email address: sford@djrlc.com

Field

Representative Name:  
Street Address:  
City: State: Zip:  
Phone:  
Email address:

BLM Point of Contact

BLM POC Name: KENNETH G RENNICK  
BLM POC Title: Petroleum Engineer  
BLM POC Phone: 5055647742  
BLM POC Email Address: krennick@blm.gov  
Disposition: Approved  
Disposition Date: 10/24/2022  
Signature: Kenneth Rennick

**DJR Operating, LLC**  
**Plug and Abandonment Procedure**  
**Jicarilla M 157 3**  
**API # 30-039-08146**  
**NE/SW, Unit K, Sec. 8, T23N, R2W**  
**Rio Arriba County, NM**

1. Hold Pre job meeting, comply with all NMOCD, BLM, and environmental regulations.
2. MIRU rig.
3. Check and record tubing, casing and bradenhead pressures.
4. Remove existing piping from casing valve, RU blow lines from casing valves and blow down casing pressure. Kill well as necessary. Ensure that well is dead or on a vacuum.
5. ND WH, NU BOP, function test BOP.
6. TOOH with 1-1/4" tubing. LD tubing to be sent in for storage/salvage.
7. PU bit and 4-1/2" casing scraper on workstring and make sure it will go past 2960'. TOOH.
8. Plug 1. Pictured Cliffs perforations: PU and TIH with 4-1/2" CR and set near 2960'. Pressure test tubing to 1000 psi. Sting out and pressure test casing to 600 psi. Sting back into CR and attempt to squeeze below CR with 10 sx. TOOH.
9. MIRU logging truck. Roll hole. Run CBL log from CR to surface. Hold 600 psi on casing if possible. Electronic copy of CBL to be sent to; Monica Kuehling, NMOCD [mkuehling@state.nm.us](mailto:mkuehling@state.nm.us), Kenneth Renneck, BLM [krenneck@blm.gov](mailto:krenneck@blm.gov), Scott Lindsay, DJR [slindsay@djrlc.com](mailto:slindsay@djrlc.com), and Loren Diede, DJR [ldiede@djrlc.com](mailto:ldiede@djrlc.com).
10. Plug 2. Pictured Cliffs, Fruitland, Kirtland, and Ojo Alamo tops: Spot blind plug from CR to 2550'. Pump water to ensure that tubing is clear. TOOH.
11. Plug 3. Nacimiento: Perforate holes at 1828'. PU and TIH with 4-1/2" CR. Set CR near 1778'. Mix and pump sufficient volume to bring TOC to 1728', inside and outside. Pump water to ensure tubing is clear. TOOH.
12. Plug 4. Surface casing shoe and surface plug: Perforate holes at 151'. Tie on to 4 1/2" casing and mix and pump cement inside and outside from 151' to surface.
13. RD cementing equipment. Cut off wellhead, fill any exposed annulus with cement, as necessary. **Install P&A marker as per BIA requirements.** Record GPS coordinates

for P&A marker and the Final P&A Report. Photograph the P&A marker and attach to the report.

14. RD and MO all rig and cement equipment. Assure that location is free of trash and contamination before moving off.

15. Send all reports and attachments to DJR Aztec office for regulatory filings.

**Note: All cement is to be Class G mixed at 15.8 ppg, yield 1.15 cu ft / sx. Cement volumes are based on inside capacities + 50' excess and outside capacities + 100% excess.**

**PxA marker is to be 12"x18" with rounded corners and installed below grade no deeper than 2'.**

## Current Wellbore Diagram

DJR Operating, LLC

Jicarilla M 157 3

API # 30-039-08146

NE/SW, Unit K, Sec 8, T23N, R2W

Rio Arriba County, NM

GL	7192'
KB	7197'
Spud Date	6/15/1964

SURF CSG

Hole size	10.75"
Csg Size:	8.625"
Wt:	24#
Grade:	N/A
ID:	8.097"
Depth	101'
cap cf/ft:	0.3575
TOC:	Surface

FORMATION TOPS

San Jose	Surf
Nacimiento	1778'
Ojo Alamo	2600'
Kirtland	2780'
Fruitland	2900'
Pictured Cliffs	2976'


PROD TBG

1-1/4" @ 2985'

PROD CSG

Hole size	6.75"
Csg Size:	4.5"
Wt:	9.5"
Grade:	N/A
ID:	4.090"
Depth	3054'
cap cf/ft:	0.0912
Csg/Csg Ann, cf/ft:	0.2318
Csg/OH Ann, cf/ft:	0.2278
TOC: (Calc.)	2413'

Perfs	2977-3002'
PBTD	N/A
TD	3085'



**Proposed Wellbore Diagram**  
**DJR Operating, LLC**  
**Jicarilla M 157 3**  
**API # 30-039-08146**  
**NE/SW, Unit K, Sec 8, T23N, R2W**  
**Rio Arriba County, NM**

GL            7192'  
 KB            7197'  
 Spud Date      6/15/1964

SURF CSG

Hole size      10.75"  
 Csg Size:      8.625"  
 Wt:            24#  
 Grade:        N/A  
 ID:            8.097"  
 Depth        101'  
 cap cf/ft:     0.3575  
 TOC:          Surface

FORMATION TOPS

San Jose	Surf
Nacimiento	1778'
Ojo Alamo	2600'
Kirtland	2780'
Fruitland	2900'
Pictured Cliffs	2976'

PROD CSG

Hole size      6.75"  
 Csg Size:      4.5"  
 Wt:            9.5"  
 Grade:        N/A  
 ID:            4.090"  
 Depth        3054'  
 cap cf/ft:     0.0912  
 Csg/Csg Ann, cf/ft: 0.2471  
 Csg/OH Ann, cf/ft: 0.1381  
 TOC: (Calc.)   2413'

**Note: Inside plugs will include 50' excess, while outside plugs will include 100% excess.**

CR near 2960'  
 Perfs 2977-3002'  
 PBDT N/A  
 TD 3085'

Plug 4: Surface shoe and surface plug: Perf holes at 151'. Tie onto 4-1/2" casing and mix and pump sufficient cement to bring TOC to surface, inside and outside.

Plug 3: Nacimiento: Perf holes at 1828'. Set CR near 1778'. Mix and pump sufficient volume to bring TOC to 1728', inside and outside.

Plug 2: Pictured Cliffs, Fruitland, Kirtland, and Ojo Alamo: Spot blind plug from CR to 2550'.

Plug 1: Pictured Cliffs perfs: Set CR near 2960'. Sqz below CR with 10 sx. Run CBL.

**UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
FARMINGTON DISTRICT OFFICE  
6251 COLLEGE BLVD.  
FARMINGTON, NEW MEXICO 87402**

AFMSS 2 Sundry ID 2697754

Attachment to notice of Intention to Abandon

Well: Jicarilla M 3

**CONDITIONS OF APPROVAL**

1. Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
2. Farmington Office is to be notified at least 24 hours before the plugging operations commence at (505) 564-7750.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.

K. Rennick 10/24/2022

**GENERAL REQUIREMENTS FOR  
PERMANENT ABANDONMENT OF WELLS ON FEDERAL AND INDIAN LEASES  
FARMINGTON FIELD OFFICE**

- 1.0 The approved plugging plans may contain variances from the following minimum general requirements.
- 1.1 Modification of the approved plugging procedure is allowed only with the prior approval of the Authorized Officer, Farmington Field Office.
  - 1.2 Requirements may be added to address specific well conditions.
- 2.0 Materials used must be accurately measured. (densometer/scales)
- 3.0 A tank or lined pit must be used for containment of any fluids from the wellbore during plugging operations and all pits are to be fenced with woven wire. These pits will be fenced on three sides and once the rig leaves location, the fourth side will be fenced.
- 3.1 Pits are not to be used for disposal of any hydrocarbons. If hydrocarbons are present in the pit, the fluids must be removed prior to filling in.
- 4.0 All cement plugs are to be placed through a work string. Cement may be bull-headed down the casing with prior approval. Cement caps on top of bridge plugs or cement retainers may be placed by dump bailer.
- 4.1 The cement shall be as specified in the approved plugging plan.
  - 4.2 All cement plugs placed inside casing shall have sufficient volume to fill a minimum of 100' of the casing, or annular void(s) between casings, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug.
  - 4.3 Surface plugs may be no less than 50' in length.
  - 4.4 All cement plugs placed to fill annular void(s) between casing and the formation shall be of sufficient volume to fill a minimum of 100' of the annular space plus 100% excess, calculated using the bit size, or 100' of annular capacity, determined from a caliper log, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug.
  - 4.5 All cement plugs placed to fill an open hole shall be of sufficient volume to fill a minimum of 100' of hole, as calculated from a caliper log, plus an excess volume sufficient to provide for 50 linear feet of fill above the plug. In the absence of a caliper log, an excess of 100% shall be required.
  - 4.6 **A cement bond log or other accepted cement evaluation tool is required to be run if one had not been previously ran or cement did not circulate to surface during the original casing cementing job or subsequent cementing jobs.**



5.0 All cement plugs spotted across, or above, any exposed zone(s), when; the wellbore is not full of fluid or the fluid level will not remain static, and in the case of lost circulation or partial returns during cement placement, shall be tested by tagging with the work string.

- 5.1 The top of any cement plug verified by tagging must be at or above the depth specified in the approved plan, without regard to any excess.
- 5.2 Testing will not be required for any cement plug that is mechanically contained by use of a bridge plug and/or cement retainer, if casing integrity has been established.
- 5.3 Any cement plug which is the only isolating medium, for a fresh water interval or a zone containing a prospectively valuable deposit of minerals, shall be tested by tagging.
- 5.4 If perforations are required below the surface casing shoe, a 30 minute minimum wait time will be required to determine if gas and/or water flows are present. If flow is present, the well will be shut-in for a minimum of one hour and the pressure recorded. Short or long term venting may be necessary to evacuate trapped gas. **If only a water flow occurs with no associated gas, shut well in and record the pressures. Contact the Engineer as it may be necessary to change the cement weight and additives.**

6.0 Before setting any cement plugs the hole needs to be rolled. All wells are to be controlled by means of a fluid that is to be of a weight and consistency necessary to stabilize the wellbore. This fluid shall be left in place as filler between all plugs.

- 6.1 Drilling mud may be used as the wellbore fluid in open hole plugging operations.
- 6.2 The wellbore fluid used in cased holes shall be of sufficient weight to balance known pore pressures in all exposed formations.

7.0 A blowout preventer and related equipment (BOPE) shall be installed and tested prior to working in a wellbore with any exposed zone(s); (1) that are over pressured, (2) where the pressures are unknown, or (3) known to contain H<sub>2</sub>S.

8.0 Within 30 days after plugging work is completed, file a Sundry Notice, Subsequent Report of Abandonment (Form 3160-5), five copies, with the Field Manager, Bureau of Land Management, 6251 College Blvd., Suite A, Farmington, NM 87402. The report should show the manner in which the plugging work was carried out, the extent, by depth(s), of cement plugs placed, and the size and location, by depth(s), of casing left in the well. Show date well was plugged.

9.0 All permanently abandoned wells are to be marked with a permanent monument as specified in 43 CFR 3162.6(d). Unless otherwise approved.

10.0 If this well is located in a Specially Designated Area (SDA), compliance with the appropriate seasonal closure requirements will be necessary.

All of the above are minimum requirements. Failure to comply with the above conditions of approval may result in an assessment for noncompliance and/or a Shut-in Order being issued pursuant to 43 CFR 3163.1. You are further advised that any instructions, orders or decisions issued by the Bureau of Land Management are subject to administrative review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4 and 43 CFR 4.700.

(October 2012 Revision)

# BLM FLUID MINERALS P&A Geologic Report

**Date Completed:** 10/24/2022

Well No. Jicarilla M 3 (API# 30-039-08146)	Location	NESW			
Lease No. JIC157	Sec. 8	T23N			R2W
Operator DJR Operating, LLC	County	Rio Arriba	State		New Mexico
Total Depth 3085'	PBTD NA	Formation	Pictured Cliffs		
Elevation (GL) 7192'		Elevation (KB)	7197'		

Geologic Formations	Est. Top	Est. Bottom	Log Top	Log Bottom	Remarks
San Jose Fm					Surface/freshwater sands
Nacimiento Fm			1778		Possible freshwater sands
Ojo Alamo Ss			2600		Aquifer (possible freshwater)
Kirtland Shale			2780		
Fruitland Fm			2900		Coal/Gas/Possible water
Pictured Cliffs Ss			2976		Gas
Lewis Shale					
Chacra					Gas
Cliff House Ss					Water/Possible gas
Menefee Fm					Coal/Ss/Water/Possible O&G
Point Lookout Ss					Probable water/Possible O&G
Mancos Shale					
Gallup					O&G/Water
Greenhorn					
Graneros Shale					
Dakota Ss					O&G/Water

Remarks:

P & A

Reference Well:

- Pictured Cliffs perforations 2977 - 3002'.

**Prepared by: Kenneth Rennick**

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
  
Action 153441

CONDITIONS

Operator: DJR OPERATING, LLC 1 Road 3263 Aztec, NM 87410	OGRID: 371838
	Action Number: 153441
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
kpickford	CBL required	10/27/2022
kpickford	Notify NMOCD 24 Hours Prior to beginning operations	10/27/2022
kpickford	Adhere to BLM approved COAs and plugs. See BLM COAs and GEO report.	10/27/2022