Sundry Print Report

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Number: 1

Well Name: MALJAMAR SWD 29 Well Location: T17S / R32E / SEC 29 / County or Parish/State: LEA /

SWSE /

Type of Well: OTHER Allottee or Tribe Name:

Lease Number: NMLC029410A Unit or CA Name: Unit or CA Number:

US Well Number: 3002539519 Well Status: Water Disposal Well Operator: SPUR ENERGY

PARTNERS LLC

Notice of Intent

Sundry ID: 2694015

Type of Submission: Notice of Intent

Type of Action: Workover Operations

Date Sundry Submitted: 09/21/2022 Time Sundry Submitted: 01:38

Date proposed operation will begin: 10/01/2022

Procedure Description: This is a revision to the Sundry ID: 2646726 that was approved on 01/10/2022. Please find revised procedure and WBD attached for your use. Thank you.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Maljamar_SWD_29___1_Revised_Procedure_20221017073616.pdf

Page 1 of 2

eived by OCD: 10/19/2022 7:34:56 AM Well Name: MALJAMAR SWD 29

Well Location: T17S / R32E / SEC 29 /

SWSE /

County or Parish/State: LEA/ 2 of

Zip:

Well Number: 1

Type of Well: OTHER

Allottee or Tribe Name:

Lease Number: NMLC029410A

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002539519

Well Status: Water Disposal Well

Operator: SPUR ENERGY

PARTNERS LLC

Conditions of Approval

Specialist Review

Workover or Vertical Deepen COA 20221018155931.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: SARAH CHAPMAN Signed on: OCT 17, 2022 07:36 AM

Name: SPUR ENERGY PARTNERS LLC

Title: Regulatory Directory

Street Address: 9655 KATY FREEWAY, SUITE 500

City: Houston State: TX

Phone: (832) 930-8613

Email address: SCHAPMAN@SPUREPLLC.COM

Field

Representative Name:

Street Address:

City: State:

Phone:

Email address:

BLM Point of Contact

Signature: Jonathon Shepard

BLM POC Name: Jonathon W Shepard **BLM POC Title:** Petroleum Engineer

BLM POC Phone: 5752345972 BLM POC Email Address: jshepard@blm.gov


Disposition: Approved Disposition Date: 10/18/2022

Page 2 of 2

Maljamar SWD 29 #1

30-025-39519

- 1. Notify BLM and OCD 24 hrs before rigging up
- 2. MIRU Pulling unit
- 3. Blow well down to 0
- 4. ND WH and NU Hydraulic BOP
- 5. Spot LD machine and work string
- 6. MI and RU snubbing unit
- 7. PU RBP retrieval tool and retrieve first RBP at 6,950'
- 8. POOH and LD RB
- 9. RIH and retrieve second RBP at 9,774'
- 10. Send both RBPs in to be inspected
- 11. MI tested RBP and set at 2,500'
- 12. Blow down well pressure and perform a negative pressure test for 30 mins
- 13. Pressure up on well to 500 psi and pressure test for 30 mins
- 14. If both pressure tests are successful, unset the RBP and move it to 9,740' and set RBP
- 15. Blow down well pressure and perform a negative pressure test for 30 mins
- 16. Pressure up on well to 500 psi and pressure test for 30 mins
- 17. If both pressure tests are successful at 9,740, unset RBP and POOH while LD WS
- 18. MI polycore injection tubing, injection packer and BHA
- 19. RIH while snubbing and hydrotesting
- 20. Set packer at 9,776' and get off on/off tool
- 21. Circulate packer fluid
- 22. Latch back onto packer and test to 500 psi
- 23. ND Snubbing unit and BOP, NU wellhead
- 24. Notify OCD/BLM 24 hrs before performing MIT
- 25. Conduct MIT test before resuming injection




CREATED ON 6/24/2021 UPDATED ON

Maljamar SWD 29 #1

30-025-39519

- 1. Notify BLM and OCD 24 hrs before rigging up
- 2. MIRU Pulling unit
- 3. Blow well down to 0
- 4. ND WH and NU Hydraulic BOP
- 5. Spot LD machine and work string
- 6. MI and RU snubbing unit
- 7. PU RBP retrieval tool and retrieve first RBP at 6,950'
- 8. POOH and LD RB
- 9. RIH and retrieve second RBP at 9,774'
- 10. Send both RBPs in to be inspected
- 11. MI tested RBP and set at 2,500'
- 12. Blow down well pressure and perform a negative pressure test for 30 mins
- 13. Pressure up on well to 500 psi and pressure test for 30 mins
- 14. If both pressure tests are successful, unset the RBP and move it to 9,740' and set RBP
- 15. Blow down well pressure and perform a negative pressure test for 30 mins
- 16. Pressure up on well to 500 psi and pressure test for 30 mins
- 17. If both pressure tests are successful at 9,740, unset RBP and POOH while LD WS
- 18. MI polycore injection tubing, injection packer and BHA
- 19. RIH while snubbing and hydrotesting
- 20. Set packer at 9,776' and get off on/off tool
- 21. Circulate packer fluid
- 22. Latch back onto packer and test to 500 psi
- 23. ND Snubbing unit and BOP, NU wellhead
- 24. Notify OCD/BLM 24 hrs before performing MIT
- 25. Conduct MIT test before resuming injection




CREATED ON 6/24/2021 UPDATED ON

Maljamar SWD 29 #1

30-025-39519

- 1. Notify BLM and OCD 24 hrs before rigging up
- 2. MIRU Pulling unit
- 3. Blow well down to 0
- 4. ND WH and NU Hydraulic BOP
- 5. Spot LD machine and work string
- 6. MI and RU snubbing unit
- 7. PU RBP retrieval tool and retrieve first RBP at 6,950'
- 8. POOH and LD RB
- 9. RIH and retrieve second RBP at 9,774'
- 10. Send both RBPs in to be inspected
- 11. MI tested RBP and set at 2,500'
- 12. Blow down well pressure and perform a negative pressure test for 30 mins
- 13. Pressure up on well to 500 psi and pressure test for 30 mins
- 14. If both pressure tests are successful, unset the RBP and move it to 9,740' and set RBP
- 15. Blow down well pressure and perform a negative pressure test for 30 mins
- 16. Pressure up on well to 500 psi and pressure test for 30 mins
- 17. If both pressure tests are successful at 9,740, unset RBP and POOH while LD WS
- 18. MI polycore injection tubing, injection packer and BHA
- 19. RIH while snubbing and hydrotesting
- 20. Set packer at 9,776' and get off on/off tool
- 21. Circulate packer fluid
- 22. Latch back onto packer and test to 500 psi
- 23. ND Snubbing unit and BOP, NU wellhead
- 24. Notify OCD/BLM 24 hrs before performing MIT
- 25. Conduct MIT test before resuming injection



CREATED ON 6/24/2021 UPDATED ON

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 151851

COMMENTS

Operator:		OGRID:
	Spur Energy Partners LLC	328947
	9655 Katy Freeway	Action Number:
	Houston, TX 77024	151851
		Action Type:
		[C-103] NOI Workover (C-103G)

COMMENTS

Created By	Comment	Comment Date
mgebremichael	To resume injection, the well has to pass MIT based on proposed plan.	10/28/2022

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 151851

CONDITIONS

Operator:	OGRID:
Spur Energy Partners LLC	328947
9655 Katy Freeway	Action Number:
Houston, TX 77024	151851
	Action Type:
	[C-103] NOI Workover (C-103G)

CONDITIONS

Created By	Condition	Condition Date
mgebremichael	None	10/28/2022