Received by OCDA 1977/2022 1:28:36 PM State of New Mexico	Form C-Pose 1 of		
District I – (575) 393-6161 Energy, Minerals and Natural Resources	Revised July 18, 2013		
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283	WELL API NO. 30-015-22860		
811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION	5. Indicate Type of Lease		
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 1220 South St. Francis Dr.	STATE FEE		
<u>District IV</u> – (505) 476-3460 Santa Fe, NM 87505	6. State Oil & Gas Lease No.		
1220 S. St. Francis Dr., Santa Fe, NM 87505	309395		
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Gillespie State		
PROPOSALS.)	8. Well Number #014		
1. Type of Well: Oil Well X Gas Well Other 2. Name of Operator Off Operator	9. OGRID Number 280554		
CFM Oil Company LLC 3. Address of Operator	10. Pool name or Wildcat		
BOX 1176 Artesia, NM 88211	Empire; Yates - Seven Rivers East		
4. Well Location	1		
Unit Letter C :990 feet from the N line and 2	310feet from theline		
Section 27 Township 17 S Range 28 E	NMPM County Eddy		
11. Elevation (Show whether DR, RKB, RT, GR, etc.,			
12. Check Appropriate Box to Indicate Nature of Notice,	Report or Other Data		
NOTICE OF INTENTION TO: SUB	SEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR			
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DR			
PULL OR ALTER CASING DIMULTIPLE COMPL CASING/CEMEN	т јов		
CLOSED-LOOP SYSTEM	OCD 24hrs prior to any work done		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and			
	d give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Co			
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Copproposed completion or recompletion.			
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 			
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Coproposed completion or recompletion.	mpletions: Attach wellbore diagram of		
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hole with fresh water 4. Fill hole with 60 sacks cement slurry. WOC 	mpletions: Attach wellbore diagram of		
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hole with freeh water 4. Fill below with freeh water 	mpletions: Attach wellbore diagram of		
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hole with fresh water 4. Fill hole with 60 sacks cement slurry. WOC 	mpletions: Attach wellbore diagram of		
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hole with fresh water 4. Fill hole with 60 sacks cement slurry. WOC 	mpletions: Attach wellbore diagram of		
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Circulate hele with fresh water 4. Fill hole with 60 sacks cement slurry. 	mpletions: Attach wellbore diagram of		
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hole with fresh water 4. Fill hole with 60 sacks cement slurry. 	mpletions: Attach wellbore diagram of		
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Circulate hele with fresh water 4. Fill hole with 60 sacks cement slurry. 	mpletions: Attach wellbore diagram of		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Giroulate hele with fresh water Dump bail well dry - if well makes 4. Fill hole with 60 sacks cement slurry. WOC 5. Install regulation abandonment marker.	mpletions: Attach wellbore diagram of		
 of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hole with fresh water 4. Fill hole with 60 sacks cement slurry. 	mpletions: Attach wellbore diagram of		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Circulate hele with freeh water 4. Fill hole with 60 sacks cement slurry. 5. Install regulation abandonment marker. WOC 5. Install regulation abandonment marker. Rig Release Date:	fluid set CIBP @ 700'		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hele with freeh water. 4. Fill hole with 60 sacks cement slurry. 5. Install regulation abandonment marker. Spud Date: ****SEE ATTACHED COA's**** MUST BE PL	fluid set CIBP @ 700' UGGED BY 11/8/2023		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Circulate hele with freeh water 4. Fill hole with 60 sacks cement slurry. 5. Install regulation abandonment marker. WOC 5. Install regulation abandonment marker. Rig Release Date:	fluid set CIBP @ 700' UGGED BY 11/8/2023		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hele with freeh water. 4. Fill hole with 60 sacks cement slurry. 5. Install regulation abandonment marker. Spud Date: ****SEE ATTACHED COA's**** MUST BE PL	fluid set CIBP @ 700' UGGED BY 11/8/2023 re and belief.		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hele with freeh water. 4. Fill hole with 60 sacks cement slurry. 5. Install regulation abandonment marker. Spud Date: ****SEE ATTACHED COA's**** MUST BE PL	fluid set CIBP @ 700' UGGED BY 11/8/2023		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Circulate hele with fresh water 4. Fill hole with 60 sacks cement slury. WOC 5. Install regulation abandonment marker. Spud Date: ****SEE ATTACHED COA's**** MUST BE PL Thereby certify that the information above is true and complete to the best of my knowledg SIGNATURE May Add	fluid set CIBP @ 700' UGGED BY 11/8/2023 re and belief.		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Circulate hele with freeh water 4. Fill hole with 60 sacks cement slurry. WOC 5. Install regulation abandonment marker. Spud Date: ****SEE ATTACHED COA's**** MUST BE PL Thereby certify that the information above is true and complete to the best of my knowledg SIGNATURE Cumpdate	fluid set CIBP @ 700' fluid set CIBP @ 700' UGGED BY 11/8/2023 ge and belief. DATE _//-3-33		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Girculate hole with fresh water 4. Fill hole with 60 sacks cement slurry. WOC 5. Install regulation abandonment marker. Spud Date: ****SEE ATTACHED COA's**** MUST BE PL I hereby certify that the information above is true and complete to the best of my knowledg SIGNATURE Muffed Amy Pohl Type or print name Amy Pohl For State Use Only	fluid set CIBP @ 700' fluid set CIBP @ 700' UGGED BY 11/8/2023 te and belief. DATE //-3-33 DATE //-3-33		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Corproposed completion or recompletion. 1. POOH with Rods and Pump if necessary. 2. Clean well out to TD of 800. 3. Circulate hele with fresh water 4. Fill hole with 60 sacks cement slurry. WOC 5. Install regulation abandonment marker. MUST BE PL Thereby certify that the information above is true and complete to the best of my knowledg SIGNATURE	fluid set CIBP @ 700' fluid set CIBP @ 700' UGGED BY 11/8/2023 te and belief. DATE //-3-33 DATE //-3-33		

Released	to	Imaging:	11	/9/	2022	11:1	9:36	AM
nereusen		1	* */			****		X M L V M

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.

- 1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
- 2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
- 3. Trucking companies being used to haul oilfield waste fluids to a disposal commercial or private shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
- 4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
- 5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
- 6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
- 7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
- 8. Produced water will not be used during any part of the plugging operation.
- 9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
- 10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
- 11. Class 'C' cement will be used above 7500 feet.
- 12. Class 'H' cement will be used below 7500 feet.
- 13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
- 14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

- 16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
- 17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
- 18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
- 19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
- 20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E)Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K)Potash---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
- 21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIRMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name2. Lease and Well Number3. API Number4. Unit Letter5. QuarterSection (feet from the North, South, East or West)6. Section, Township and Range7. Plugging Date8. County(SPECIAL CASES)------AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S – R 30E

Sec 1 – Sec 36

T 21S – R 31E

Sec 1 – Sec 36

T 22S – R 28E

Sec 36 Unit A,H,I,P.

T 22S – R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S – R 30E

Sec 1 – Sec 36

T 22S – R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,B,C,D,G,H. Sec 27 – Sec 34.

T 23S – R 28E

Sec 1 Unit A

T 23S – R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S – R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S – R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S – R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S – R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S – R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

<i>Received by OCD: 11/7/2022 1:28:36</i> CFM OIL, LLC - 280554		
PO BOX 1176		
	GILLESPIE	
Artesia, NM 88211	<u>STATE #014 API #</u>	30-015-22860
	CURRENT WELLBORE	WELL HISTORY
		LOCATION: 990' FNL & 2310' FWL OF
	Surface:"	SECTION: 27: T-17-S, R-28-E, Eddy Co., NM
	@ Gr Cmt. w/	SPUD DATE: 3/21/79 COMPL. DATE: 5/31/7
	Hole Size"	T.D. 800' PBTD 797'
	Max Mud Wt #/G	TYPE: Oil FIELD: East Empire
		ZONES: Yates Seven Rivers
	Intermediate:	PERFS: 747'-751.5'
	",# Gr@#	
	Gr@Sx.	TOTAL HOLES: 10 shots
	TOC @, Hole Size", Max Mud	STIMULATION: 1,000 gal. 6% WIA
	Wt#/G	<u>1 gal. RD-11</u> 31 gal. LST-34
		900# QF-3
		30 gal. Adomall 30,000# 20/40 sand
		-
	1	
	a.	
	Production:4_1/2",	
	<u>9.5</u> #,Gr. @797 *, Cmt. w/	
	275Sx, TOC @	
a	<u> </u>	
	TD,	

Released to Imaging: 11/9/2022 11:19:36 AM

Received by OCD: 11/7/202. CFM OIL, LLC PO BOX 1176	- 280554	GILLESPIE	Pa
Artesia, NM 8	0411	<u>STATE #014 API #</u>	<u>30-015-22860</u>
		AFTER WELLBORE	SPUD DATE: 3/21/79 COMPL. DATE: 5/31/7 T.D. 800' PBTD 797' TYPE: Oil FIELD: East Empire ZONES: Yates Seven Rivers
		Intermediate: 	IP: 36 BOPD: 35 BWPD: 1 PERFS: 747'-751.5' TOTAL HOLES: 10 shots STIMULATION: 1,000 gal. 6% WIA 1 gal. RD-11 31 gal. LST-34 900# QF-3 30 gal. Adomall 30,000# 20/40 sand
		Production: 4 1/2 ", 9.5 #, Gr. @797' Cmt. w/ 275 Sx, TOC @	

Page 7 of 8

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:		
CFM OIL, LLC	280554		
P.O. Box 1176	Action Number:		
Artesia, NM 88210	156696		
	Action Type:		
	[C-103] NOI Plug & Abandon (C-103F)		
CONDITIONS			

CONDITIONS

Created By		Condition Date
gcordero	None	11/8/2022

Page 8 of 8

.

Action 156696