Office	10 Appropriate Distric	Q6:09 AM	State of New				Form C		
District I - (575	5) 393-6161 1 Dr., Hobbs, NM 88240	•	y, Minerals and N	Natural Resou	rces WELL A		evised July 18	, 2013	
District II – (57	/	OIL	CONSERVATI	ON DIVISIO		-49945			
011 D. 1 list St., Altesia, Will 00210				Francis Dr.	5. Indica	5. Indicate Type of Lease			
1000 Rio Brazo District IV – (5	os Rd., Aztec, NM 8741		Santa Fe, NM			ГАТЕ  ✓ Oil & Gas Lease	FEE		
	ncis Dr., Santa Fe, NM						. 110.		
87505	SUNDDV N	OTICES AND I	REPORTS ON WE			540001 Name or Unit A	graamant No	ma	
<b>(</b>	E THIS FORM FOR PR	OPOSALS TO DRI	LL OR TO DEEPEN OI PERMIT" (FORM C-10	R PLUG BACK TO	) A	nza 22/15 W2F	-		
PROPOSALS.) 1. Type of Well: Oil Well Gas Well 🗹 Other						Number 1H			
2. Name of Mewbou	Operator Irne Oil Company	1			9. OGR 1474	ID Number 4			
3. Address of						name or Wildca	ıt		
PO Box	5270 Hobbs, NM	1 88240			PUR	PLE SAGE; WO		SAS	
4. Well Loc	cation								
Uni	it LetterJ	: <u>2480</u> i	feet from the <u>S</u>	outh line	and <u>1600</u>	_feet from the _	East	line	
Sec	ction 22		Township 25S	Range 28E		Coun	ty Eddy		
			tion (Show whether	DR, RKB, RT,	GR, etc.)				
		2961'	GL						
		ck Appropriat	e Box to Indicat	e Nature of I	Notice, Report o SUBSEQUE		OF.		
PERFORM F	REMEDIAL WORK		D ABANDON	REMEDI	AL WORK		RING CASING	G 🗌	
TEMPORAR	RILY ABANDON	CHANGE	PLANS	COMME	NCE DRILLING OP	NS. 🗌 🛛 P AND	A		
	LTER CASING		E COMPL	CASING/	CEMENT JOB				
OTHER:	DOP SYSTEM			OTHER:					
	cribe proposed or c	ompleted operation	ions. (Clearly state	••••	tails, and give pert	inent dates, inclu	ding estimate	ed date	
			ULE 19.15.7.14 N	MAC. For Mul	tiple Completions:	Attach wellbore	diagram of		
of sta	arting any proposed completion of	r recompletion.							
of sta prop Mewbou	osed completion of	Ĩ	ved APD for the a	bove well. MC	C would like to c	hange the 13 3	/8" surface	csg	
of sta prop Mewbou setting d Cementi	urne Oil Company depth to 475'.	/ has an approv ollows: Lead w	/190 sx Class C v			-		-	
of sta prop Mewbou setting d Cementi 1.34 cuff	urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg.	/ has an approv ollows: Lead w TOC @ 0' w/2	/190 sx Class C v 5% excess.	v/yield 2.12 cu	ıft/sk @ 12.5 ppg	-		-	
of sta prop Mewbou setting d Cementi 1.34 cuff	urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg.	/ has an approv ollows: Lead w TOC @ 0' w/2	/190 sx Class C v	v/yield 2.12 cu	ıft/sk @ 12.5 ppg	-		-	
of sta prop Mewbou setting d Cementi 1.34 cuff	urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg.	/ has an approv ollows: Lead w TOC @ 0' w/2	/190 sx Class C v 5% excess.	v/yield 2.12 cu	ıft/sk @ 12.5 ppg	-		-	
of sta prop Mewbou setting d Cementi 1.34 cuff	urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg.	/ has an approv ollows: Lead w TOC @ 0' w/2	/190 sx Class C v 5% excess.	v/yield 2.12 cu	ıft/sk @ 12.5 ppg	-		-	
of sta prop Mewbou setting d Cementi 1.34 cuff	urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg.	/ has an approv ollows: Lead w TOC @ 0' w/2	/190 sx Class C v 5% excess.	v/yield 2.12 cu	ıft/sk @ 12.5 ppg	-		-	
of sta prop Mewbou setting d Cementi 1.34 cuff	urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg.	/ has an approv ollows: Lead w TOC @ 0' w/2	/190 sx Class C v 5% excess.	v/yield 2.12 cu	ıft/sk @ 12.5 ppg	-		-	
of sta prop Mewbou setting d Cementi 1.34 cuft Attachec	urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg.	/ has an approv ollows: Lead w TOC @ 0' w/2	/190 sx Class C v 5% excess.	v/yield 2.12 cu	ıft/sk @ 12.5 ppg	-		-	
of sta prop Mewbou setting d Cementi 1.34 cuft Attachec	osed completion of urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg. d are necessary o	/ has an approv ollows: Lead w TOC @ 0' w/2	/190 sx Class C v 5% excess. csg and cmt desig	v/yield 2.12 cu	ift/sk @ 12.5 ppg surface portion.	-		-	
of sta prop Mewbou setting d Cementi 1.34 cuff Attachec	osed completion of urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg. d are necessary of 3/15/2023	/ has an approv ollows: Lead w TOC @ 0' w/2 documents for o	/190 sx Class C v 5% excess. csg and cmt desig	v/yield 2.12 cu gn change for e Date: 4/1	ift/sk @ 12.5 ppg surface portion.	Tail w/200 sx		-	
of sta prop Mewbou setting d Cementi 1.34 cuff Attachec	osed completion of urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg. d are necessary of 3/15/2023	/ has an approv ollows: Lead w TOC @ 0' w/2 documents for o	/190 sx Class C v 5% excess. csg and cmt desig	v/yield 2.12 cu gn change for e Date: 4/1	ift/sk @ 12.5 ppg surface portion.	Tail w/200 sx		-	
of sta prop Mewbou setting d Cementi 1.34 cuft Attached	osed completion of urne Oil Company depth to 475'. ing would be as f t/sk @ 14.8 ppg. d are necessary of 3/15/2023	/ has an approvious: Lead w TOC @ 0' w/28 documents for o	/190 sx Class C v 5% excess. csg and cmt desig Rig Releas	v/yield 2.12 cu gn change for e Date: 4/1	ift/sk @ 12.5 ppg surface portion.	Tail w/200 sx (		ield	
of sta prop Mewbou setting d Cementi 1.34 cuff Attached Spud Date: hereby certif SIGNATURE	ing would be as for the formation of the	tion above is true	/190 sx Class C v 5% excess. csg and cmt desig Rig Releas e and complete to th 	v/yield 2.12 cu gn change for e Date: 4/1 he best of my k Engineer	ift/sk @ 12.5 ppg surface portion.	Tail w/200 sx of	Class C w/y	ield	
of sta prop Mewbou setting d Cementi 1.34 cuff Attached Spud Date: hereby certif SIGNATURE Fype or print For State Use	ing would be as for the formation of the	tion above is true	/190 sx Class C v 5% excess. csg and cmt desig Rig Releas e and complete to th 	v/yield 2.12 cu gn change for e Date: 4/1 he best of my k Engineer	Ift/sk @ 12.5 ppg surface portion. 1/2023	Tail w/200 sx of	Class C w/y	ield	

•

.

ъ

## Mewbourne Oil Company, Bonanza 22/15 W2HA State Com #1H Sec 22, T25S, R28E SHL: 2480' FSL & 1600' FEL, Sec 22 BHL: 330' FNL & 330' FEL, Sec 15

	Casing Pi	rogram								
Hole	Casing	Interval	Csg.	Weight	Grade	Conn.	SF	SF	SF Jt	SF Body
Size	From	То	Size	(lbs)			Collapse	Burst	Tension	Tension
17.5"	0'	475'	13.375"	48	H40	STC	3.54	7.96	14.12	23.73
12.25"	0'	2440'	9.625"	36	J55	LTC	1.59	2.77	5.16	6.42
8.75"	0'	10850'	7"	26	P110	LTC	1.16	1.86	2.27	2.94
6.125"	10650'	18370'	4.5"	13.5	P110	LTC	1.61	1.87	3.24	4.05
				BLM Minimum Safety		1.125	1	1.6 Dry	1.6 Dry	
				Factor					1.8 Wet	1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Bonanza 22/15 W2HA State Com #1H								
SHL: 2480' FSL & 1600' FEL (Sec 22)								
BHL: 330' FNL & 330' FEL (Sec 15)								
Casing Type	Fluid Type	Hole Size	Casing Descripion	Casing Weight	Top MD	Setting Depth	Sacks Cement	TOL/TOT
Surface	Spud Mud	17.5"	13.375" 48# H40 STC	48.0 lb/ft	0'	475'	390	0'/285'
Intermediate	Brine	12.25"	9.625" 36# J55 LTC	36.0 lb/ft	0'	2440'	530	0'/1764'
Production	Cut-Brine	8.75"	7" 26# P110 LTC	26.0 lb/ft	0'	10850'	950	2200'/8357'
Liner	OBM	6.125"	4.5" 13.5# P110 LTC	13.5 lb/ft	10650'	18370'	490	10650'

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:
MEWBOURNE OIL CO	14744
P.O. Box 5270	Action Number:
Hobbs, NM 88241	176334
	Action Type:
	[C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By		Condition Date					
kpickford	Adhere to previous NMOCD Conditions of Approval	1/19/2023					

CONDITIONS

Page 4 of 4

Action 176334