

Well Name: BETONNIE TSOSIE WASH UNIT	Well Location: T23N / R8W / SEC 15 / SESW / 36.221984 / -107.672225	County or Parish/State: SAN JUAN / NM
Well Number: 207H	Type of Well: OIL WELL	Allottee or Tribe Name: NAVAJO NATION
Lease Number: NMNM50999	Unit or CA Name:	Unit or CA Number: NMNM135219a
US Well Number: 3004538244	Well Status: Drilling Well	Operator: DJR OPERATING LLC

Subsequent Report

Sundry ID: 2706235

Type of Submission: Subsequent Report

Type of Action: Drilling Operations

Date Sundry Submitted: 12/07/2022

Time Sundry Submitted: 07:47

Date Operation Actually Began: 11/25/2022

Actual Procedure: Intermediate Casing & Cement. Depth have been adjusted for 26' KB of production rig -11/25/22: NU BOPE. Full function PT L250 (5min) H5000 (10min). PT pre-set 9.625" 36# J55 STC casing 1500 (30min). All tests good & recorded on chart. No regulatory agencies onsite to witness. Drill 8.75" hole from 388' to 2899'. -11/26/22: Drill 8.75" to 5318'. -11/27/22: Drill 8.75" hole to 6026' TD. -11/28/22: Wash & Ream through tight spots. -11/29/22. Wash & Ream through tight spots. Decision made to pause operations & skid to next well. ND BOPE. Install well cap. -12/02/22: NU BOPE. Full function PT L250 (5min) H5000 (10min). PT pre-set 9.625" 36# J55 STC casing 1500 (30min). All test good & recorded on chart. No regulatory agencies onsite to witness. TIH. Wash & Ream. TOH. -12/03 & 04/22: RU CRTs. RIH with 137 jts of 7" 26# J55 LTC casing set from surface to 6022'. -12/05/22: RU to cement. 5k test on lines, test good. Cement LEAD: Type G, 211 bbls (507 sx), 12.3 ppg, 2.32 yield, 13.2 gps (surface – 4085') TAIL: Type G, 42 bbls (154 sx), 13.5 ppg, 1.51 yield, 7.13 gps (4085' – 6022'). Bump plug 1540 FCP, pressure up to 2545 & hold for 5min. Check floats, floats held. Circulate. No cement back to surface. No regulatory agencies onsite to witness. CBL will be ran & submitted at a later date. Install packoff, test to 5k, test good. ND BOPE & cap well. PT of 7" casing will be provided in next report.

Well Name: BETONNIE TSOSIE WASH UNIT	Well Location: T23N / R8W / SEC 15 / SESW / 36.221984 / -107.672225	County or Parish/State: SAN JUAN / NM
Well Number: 207H	Type of Well: OIL WELL	Allottee or Tribe Name: NAVAJO NATION
Lease Number: NMNM50999	Unit or CA Name:	Unit or CA Number: NMNM135219a
US Well Number: 3004538244	Well Status: Drilling Well	Operator: DJR OPERATING LLC

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: SHAW-MARIE FORD	Signed on: DEC 07, 2022 07:46 AM
Name: DJR OPERATING LLC	
Title: Regulatory Specialist	
Street Address: 1 Road 3263	
City: Aztec	State: NM
Phone: (505) 632-3476	
Email address: sford@djrlc.com	

Field

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

BLM Point of Contact

BLM POC Name: KENNETH G RENNICK	BLM POC Title: Petroleum Engineer
BLM POC Phone: 5055647742	BLM POC Email Address: krennick@blm.gov
Disposition: Accepted	Disposition Date: 12/07/2022
Signature: Kenneth Rennick	

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 164834

CONDITIONS

Operator: DJR OPERATING, LLC 1 Road 3263 Aztec, NM 87410	OGRID: 371838
	Action Number: 164834
	Action Type: [C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
gramirez	Cement is required to circulate on both surface and intermediate1 strings of casing. Perform a top down job.	2/7/2023