Received by OCD: 2/3/2023 10:06:42 AM Office State of New Me	xico Form C ^{Page 1 of 8}
District I – (575) 393-6161 Energy, Minerals and Natur	ral Resources Revised July 18, 2013 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283 811 S. First St. Artosia NM 88210 OIL CONSERVATION	30-015-32438
811 S. First St., Artesia, NM 88210 OIL CONSERVATION District III – (505) 334-6178 1220 South St. Fran	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 Sonto Eq. NM 87	SIAIE V FEE
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	0. State Off & Gas Lease NO.
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLU DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FO PROPOSALS.)	R SUCH Shugart State Com
1. Type of Well: Oil Well Gas Well X Other Disposal	8. Well Number 002
2. Name of Operator Select Agua Libre Midstream, LLC	9. OGRID Number 246368
3. Address of Operator	10. Pool name or Wildcat
12515 Carriage Way Oklahoma City, OK 73142 4. Well Location	Delaware, SWD
4. Well Location Unit Letter K : 1850 feet from the Sout	h line and 1650 feet from the West line
	nge 31E NMPM County Eddy
11. Elevation (Show whether DR,	6 51E 5 5
3659' GR	
12 Check Appropriate Poy to Indicate N	ature of Notice Bapart or Other Data
12. Check Appropriate Box to Indicate N	ature of Notice, Report of Other Data
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON FEMPORARILY ABANDON CHANGE PLANS	REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. P AND A
	Notify OCD 24 hrs. prior to any work
OTHER: 13. Describe proposed or completed operations. (Clearly state all p	OTHER: done
of starting any proposed work). SEE RULE 19.15.7.14 NMAC	
proposed completion or recompletion.	
	L or have CBL on location
 MIRU. POOH w/ Inj. Tbg RIH EL - Set CIBP @ 5,100'. Circ hole. Pressure 	csg 500psi / 30 min A test eaging Spot 25 ex emt to 5 075' WOC. Tag
3. Spot 32 sx cmt @ $4,616'$ - $4,416'$. WOC. Tag	
4. Spot 32 sx cmt @ 725'- 525'. WOC. Tag	Spot 25 sx cmt 2168' - 2000' - T. Yates
5. Spot XSX cmt @ 10X-3' Spot 25 sx cmt 2	200' - Surface
6. RDMO. Cut off WH & anchors - Install P&A ma	Verify cmt to surface on all strings
SWD - Failed MIT 12/2018	
Spud Date: Rig Release Da	te:
****SEE ATTACHED COA's****	MUST BE PLUGGED BY 9/8/2023
I hereby certify that the information above is true and complete to the be	st of my knowledge and bener.
SIGNATURE WD Trile Cons	sultant DATE 2/1/2023
SIGNATURE IIILE_CON	DATEDATE
Type or print name <u>William Fegley</u> E-mail address For State Use Only	: <u>wfegley@lokienv.com</u> PHONE: <u>318-572-7315</u>
	SU 117.4 0/0/0000
APPROVED BY:	_Staff ManagerDATE_2/8/2023
Conditions of Approval (II any).	

•

Released	to	Imaging:	2/8/2023	3:03:55 PM
nereusen		1111181181		0.00.00 1 111

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.

- 1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
- 2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
- 3. Trucking companies being used to haul oilfield waste fluids to a disposal commercial or private shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
- 4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
- 5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
- 6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
- 7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
- 8. Produced water will not be used during any part of the plugging operation.
- 9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
- 10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
- 11. Class 'C' cement will be used above 7500 feet.
- 12. Class 'H' cement will be used below 7500 feet.
- 13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
- 14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

- 16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
- 17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
- 18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
- 19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
- 20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Cherry Canyon Eddy County
 - L) Potash----(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
- 21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIRMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name2. Lease and Well Number3. API Number4. Unit Letter5. QuarterSection (feet from the North, South, East or West)6. Section, Township and Range7. Plugging Date8. County(SPECIAL CASES)------AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S – R 30E

Sec 1 – Sec 36

T 21S – R 31E

Sec 1 – Sec 36

T 22S – R 28E

Sec 36 Unit A,H,I,P.

T 22S – R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S – R 30E

Sec 1 – Sec 36

T 22S – R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,B,C,D,G,H. Sec 27 – Sec 34.

T 23S – R 28E

Sec 1 Unit A

T 23S – R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S – R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S – R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S – R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S – R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S – R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

.

Proposal

.

Basic Energy Services LP Shugart State Com # 2 1850" FSL, 1650' FWL, Unit (K), Sec 16, T18S, R31E API # 30-015-32438 Eddy County

J.

			Tree Connection	2 7/8 J-55 PCT
			Surface Casing:	13 3/8" 48#
Surface Hol Bit Size	e 17 1/2"		Setting Depth @	674' 580sx TOC Surf.
DIL SIZE	CIBP @ 3900' + 35' CMT		Setting Deptin @	674 5005X 10C 5un.
Inter. Hole			Interm. Casing:	8 5/8" 32#
Bit Size	<u>11"</u>		Setting Depth:	4 516' 1410ev
	Pkr. set @ 5100'		Setting Depth.	4,516' 1410sx Circulated to Surface
			Perf Intervals @ (5340'-5550'), (5560'- (5700'-5740')	(5150'-5180'), (5260'-5320'), 5570'), (5600'-5610'), (5640'-5660')
Cement Dat	a:	CIE	IP @ 5840' + 35'	
Lead - Tail -		CIE	3P @ 7,170' + 35' CMT	
Note -		CIE	3P @ 9,550' + 35' CMT	
	CIBP @ 11,650' + 35' CMT		PBTD:	11,913'
			Production Csg.:	5 1/2" 17#
Bit size	7 7/8"		Setting Depth @	
		and the second secon		Circulated to Surface

TD @ 11,970'

.

.

Proposal

.

Basic Energy Services LP <u>Shugart State Com # 2</u> 1850" FSL, 1650' FWL, Unit (K), Sec 16, T18S, R31E API # 30-015-32438 Eddy County

J

Surface Hole Surface Casing: 13 3/8" 48# Bit Size 17 1/2" Set Plug @ 725 to 525 + 32 sx Set Ing Depth @ 574' 580sx TOC Surf. Interr. Hole Interrm. Casing: 85/8" 32# Bit Size 11" Set Plug @ 4616 to 4416' + 32 sx Setting Depth: 4,516' 1410sx Circulated to Surface Circulated to Surface Perf Intervals @ (5150'-5180'), (5260'-5320'), (530'-5510'), (560'-5510'	Se	t Surface Plug @ 100 to 3 + 32 sx			Tree Connection	<u>2 7/8 J-55 PCT</u>
Bit Size 17 1/2" Set Plug @ 725 to 525 + 32 sx Inter. Hole Interm. Casing: 8 5/8" 32# Bit Size 11" Set Plug @ 4616 to 4416' + 32 sx Set CIBP @ 5100' + 25' CMT Circulated to Surface Cement Data: (510'-5180'), (550'-5570'), (560'-5570'), (560'-5610'), (5640'-5660') Lead - CIBP @ 5100' + 25' CMT Cilep @ 5100' + 25' CMT CIBP @ 7,170' + 35' CMT Cilep @ 11,550' + 35' CMT CIBP @ 9,550' + 35' CMT Bit size 7.78"					Surface Casing:	13 3/8" 48#
Set Plug @ 726 to 526 + 32 sx Inter. Hole Bit Size 11" Set Plug @ 4616 to 4416' + 32 sx Set Plug @ 4616 to 4416' + 32 sx Set CIBP @ 5100' + 25' CMT Cement Data: Lead - Tail - Note - CIBP @ 11,650' + 35' CMT CIBP @ 11,650' + 35' CMT Bit size 7.78" Set set ing Depth (@ 11,970' 2000sx)						
Inter. Hole Bit Size 11" Bit Size 11" Set Plug @ 4616 to 4416' + 32 sx Setting Depth: 4,516' 1410sx Circulated to Surface Perf Intervals @ (5150'-5180'), (5560'-5520'), (5540'-5560') Set CIBP @ 5100' + 25' CMT Circulated to Surface Cement Data: CIBP @ 5140' + 35' Lead -	Bit Size				Setting Depth @	674' 580sx TOC Surf.
Bit Size 11" Set Plug @ 4616 to 4416' + 32 sx Setting Depth: 4,516' 1410sx Circulated to Surface Perf Intervals @ (5150'-5180'), (5260'-5320'), (5340'-5550'), (5560'-5570'), (5660'-5610'), (5640'-5660' Set CIBP @ 5100' + 25' CMT CIBP @ 5840' + 35' Lead -		Set Plug @ 725 to 525 + 32 sx				
Set Plug @ 4616 to 4416' + 32 sx Setting Depth: 4,516' 1410sx Circulated to Surface Perf Intervals @ (5150'-5180'), (5260'-5320'), (5340'-5550'), (5560'-5570'), (5600'-5610'), (5640'-5660'') (5130'-5570'), (5600'-5610'), (5640'-5660'') Cement Data: CIBP @ 5840' + 35' CIBP @ 5840' + 35' Lead - CIBP @ 7,170' + 35' CMT CIBP @ 7,170' + 35' CMT Tail - CIBP @ 11,650' + 35' CMT CIBP @ 9,550' + 35' CMT Bit size 77/8'' Setting Depth @	Inter. Hole				nterm. Casing:	8 5/8" 32#
Set Plug @ 4616 to 4416' + 32 sx Circulated to Surface Perf Intervals @ (5150'-5180'), (5260'-5320'), (5340'-5550'), (5660'-5570'), (5660'-5610'), (5640'-5660'', (5700'-5740') Cement Data: CiBP @ 5840' + 35' Lead -	Bit Size	<u></u>				
Set CIBP @ 5100' + 25' CMT Perf Intervals @ (5150'-5180'), (5260'-5320'), (5340'-5560'' (5700'-5740') Cement Data: CIBP @ 5840' + 35' Lead -					Setting Depth:	
Set CIBP @ 5100' + 25' CMT (5340'-5550'), (5600'-5610'), (5640'-5660'' Cement Data: CIBP @ 5840' + 35' Lead -		Set Plug @ 4616 to 4416 + 32 sx	•			Circulated to Surface
Set CIBP @ 5100' + 25' CMT (5340'-5550'), (5600'-5610'), (5640'-5660'' Cement Data: CIBP @ 5840' + 35' Lead -					Perf Intervals @	(5150'-5180'), (5260'-5320'),
Cement Data:				1 224	•	
Lead -		SetCIBP @ 5100' + 25' CMT	· · · · · · · · · · · · · · · · · · ·		(5700'-5740')	
Lead -						
Lead -	Cement Dat	a:		CIPD	@ 5940' + 25'	
Tail - Image: Classing Depth @170' + 35' CMT Note - Classing Depth @11,913' Classing Depth @11,970' 2000sx	Lead -				@ 5640 + 55	
Tail -				СІВР	@ 7,170' + 35' CMT	
CIBP @ 11,650' + 35' CMT PBTD: 11,913' Production Csg.: 5 1/2" 17# Bit size 7 7/8" Setting Depth @ 11,970' 2000sx	Tail -				-	
CIBP @ 11,650' + 35' CMT PBTD: 11,913' Production Csg.: 5 1/2" 17# Bit size 7 7/8" Setting Depth @ 11,970' 2000sx				i i		
CIBP @ 11,650' + 35' CMT Production Csg.: <u>5 1/2" 17#</u> Bit size <u>7 7/8"</u> Setting Depth @ <u>11,970' 2000sx</u>	Note -		-	CIBP	@ 9,550' + 35' CMT	
CIBP @ 11,650' + 35' CMT Production Csg.: <u>5 1/2" 17#</u> Bit size <u>7 7/8"</u> Setting Depth @ <u>11,970' 2000sx</u>						
CIBP @ 11,650' + 35' CMT Production Csg.: <u>5 1/2" 17#</u> Bit size <u>7 7/8"</u> Setting Depth @ <u>11,970' 2000sx</u>			-		PBTD:	11.913'
Bit size <u>7 7/8"</u> Setting Depth @ <u>11,970' 2000sx</u>		CIBP @ 11,650' + 35' CMT				
					Production Csg.:	<u>5 1/2" 17#</u>
	Bit size	7 7/8"	!)		Setting Denth @	11.970' 2000sx
			A REAL PROPERTY AND INCOME.			

TD @ 11,970'

.

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:
SELECT AGUA LIBRE MIDSTREAM, LLC	331031
12515 Carriage Way	Action Number:
Oklahoma City, OK 73142	182408
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By		Condition Date
gcordero	None	2/8/2023

Page 8 of 8

Action 182408