State of New Mexico State of New New Mexico State of New Mexico State of New Mexico State of New New Mexico State of New Mexico State of New Mexico State of New New Mexico State of New New Mexico State of New
District II - (375) 748-1283 District III - (375) 748-1283 District III - (375) 748-1283 District III - (305) 334-1678 District III - (305) 334-678 District III - (305) 344-678 District IV - (305) 476-3460 District IV - (305) 476-3
1220 South St. Francis Dr. S. Indicate Type of Lease STATE ST
Santa Fe, NM 87505 Santa Fe, NM 87505 Santa Fe, NM 87505 State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 1220 S. St. Sc. Class H. cmt on CIBP (10,161'-10,361'). WOC. Tag Dr., Santa Fe, NM 1220 S. St. Sc. Sc. Sc. Sc. Sc. Sc. Sc. Sc. Sc. Sc
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other 2. Name of Operator
1. Type of Well: Oil Well
2. Name of Operator CONTANGO RESOURCES, INC 3. Address of Operator 717 TEXAS AVE, SUITE 2900, HOUSTON, TX 77002 4. Well Location Unit Letter A : 330 feet from the NORTH line and 700 feet from the EAST line Section 20 Township 168 Range 36E NMPM County LEA 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,919' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350 - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10
3. Address of Operator 717 TEXAS AVE, SUITE 2900, HOUSTON, TX 77002 4. Well Location Unit Letter A : 330 feet from the NORTH line and 700 feet from the EAST line Section 20 Township 16S Range 36E NMPM County LEA 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,919' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON STEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A STEMPORARILY ABANDON NULTIPLE COMPL CASING CASING CASING CASING CASING CASING COMMENCE DRILLING OPNS. PAND A STATEM OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35
4. Well Location Unit Letter A : 330 feet from the NORTH line and 700 feet from the EAST line Section 20 Township 168 Range 36E NMPM County LEA 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,919' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM MULTIPLE COMPL CASING/CEMENT JOB OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 1036
Unit Letter A : 330 feet from the NORTH line and 700 feet from the EAST line Section 20 Township 168 Range 36E NMPM County LEA 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,919' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK □ PLUG AND ABANDON □ CHANGE PLANS □ COMMENCE DRILLING OPNS.□ P AND A □ PULL OR ALTER CASING □ MULTIPLE COMPL □ CASING/CEMENT JOB □ Notify OCD 24 hrs. prior to any work done 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CICRULATE CASING □ CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CICRULATE CASING □ CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @
Section 20 Township 16S Range 36E NMPM County LEA 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,919' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK □ PLUG AND ABANDON □ CHANGE PLANS □ COMMENCE DRILLING OPNS.□ P AND A □ PULL OR ALTER CASING □ MULTIPLE COMPL □ CASING/CEMENT JOB □ DOWNHOLE COMMINGLE □ CLOSED-LOOP SYSTEM □ OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 1350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag 2. Pull rods & tubing. Set 5-1/2" CIBP @ +/-10.62'. Spot 25 sxs Class H cmt on CIBP (10,161'-10,361'). WOC. Tag TOC. 3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. Run CBL to surface. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp).
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,919' GR 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB Notify OCD 24 hrs. prior to any work done OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC &
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB Notify OCD 24 hrs. prior to any work done OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dump
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. P AND A PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB Notify OCD 24 hrs. prior to any work done OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag 2. Pull rods & tubing. Set 5-1/2" CIBP @ +/-10\subseteq 62'. Spot 25 sxs Class H cmt on CIBP (10,161'-10,361'). WOC. Tag TOC. 3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp).
PULL OR ALTER CASING
DOWNHOLE COMMINGLE CLOSED-LOOP SYSTEM OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' c
CLOSED-LOOP SYSTEM OTHER: OTHER: OTHER: Notify OCD 24 hrs. prior to any work done Indicates the proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WO
OTHER: OTHER: done 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag 2. Pull rods & tubing. Set 5-1/2" CIBP @ +/-10.362'. Spot 25 sxs Class H cmt on CIBP (10,161'-10,361'). WOC. Tag TOC. 3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp).
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. CIBP @ 12350' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 11400' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag CIBP @ 10360' - Dumpbail 35' cl H cmt - WOC & Tag 2. Pull rods & tubing. Set 5-1/2" CIBP @ +/-10 62'. Spot 25 sxs Class H cmt on CIBP (10,161'-10,361'). WOC. Tag TOC. 3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp).
Description of Procedure: 1. Notify OCD 24 hours prior to MIRU to P&A. 2. Pull rods & tubing. Set 5-1/2" CMP @ +/-10 262'. Spot 25 sxs Class H cmt on CIBP (10,161'-10,361'). WOC. Tag TOC. 3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp).
Description of Procedure: 1. Notify OCD 24 hours prior to MIRU to P&A. 2. Pull rods & tubing. Set 5-1/2" CMP @ +/-10 62'. Spot 25 sxs Class H cmt on CIBP (10,161'-10,361'). WOC. Tag TOC. 3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp).
Description of Procedure: 1. Notify OCD 24 hours prior to MIRU to P&A. 2. Pull rods & tubing. Set 5-1/2" CPSP @ +/-10 62'. Spot 25 sxs Class H cmt on CIBP (10,161'-10,361'). WOC. Tag TOC. 3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp).
2. Pull rods & tubing. Set 5-1/2" CIBP @ +/-10.662'. Spot 25 sxs Class H cmt on CIBP (10,161'-10,361'). WOC. Tag TOC. 3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp).
3. Circulate well w/ water-based mud, pressure test csg to 500 psi for 30 minutes. 4. Spot 25 sxs Class H cmt @ 9,480'-9,670' (Wolfcamp). Spot 25 sx @ 8050' - 7950' - TOC
5. Perf @ +/-6,385', Circ/sqz 40 sxs Class C cmt @ 6,225' - 6,385' (Glorieta).
6. Perf @ +/-5,026', Circ/sqz 60 sxs Class C cmt @ 4,795' - 5,026' (San Andres & Int. Csg Shoe). WOC. Tag TOC.
7. Perf @ +/-3,242', Circ/sqz 35 sxs Class C cmt @ 3,112' - 3,242' (Yates). WOC. Tag TOC.
8. Perf @ +/-2,055', Circ/sqz 30 sxs Class C cmt @ 1,935' - 2,055' (Rustler). WOC. Tag TOC. 9. Perf @ +/-479', Circ/sqz 120 sxs Class C cmt @ surface – 479' (Surf Csg Shoe).
10. Cut off wellhead, verify cmt to surface, weld on dry hole marker.
Spud Date: Rig Release Date:
****SEE ATTACHED COA's**** MUST BE PLUGGED BY 8/9/2023
I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE SIGNATURE PART / TITLE Regulatory Analyst DATE 2/08/2023
kristy.polk@contango.com
Type or print name E-mail address: PHONE:
101 State Coc Only
APPROVED BY:

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.

- A notice of intent to plug and abandon a wellbore is required to be approved before plugging
 operations are conducted. A cement evaluation tool is required in order to ensure isolation of
 producing formations, protection of water and correlative rights. A cement bond log or other
 accepted cement evaluation tool is to be provided to the division for evaluation if one has not
 been previously run or if the well did not have cement circulated to surface during the original
 casing cementing job or subsequent cementing jobs. Insure all bradenheads have been
 exposed, identified and valves are operational prior to rig up.
- 2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
- 3. Trucking companies being used to haul oilfield waste fluids to a disposal commercial or private shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
- 4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
- 5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
- 6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
- 7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
- 8. Produced water will not be used during any part of the plugging operation.
- 9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
- 10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
- 11. Class 'C' cement will be used above 7500 feet.
- 12. Class 'H' cement will be used below 7500 feet.
- 13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
- 14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

- 16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
- 17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
- 18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
- 19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
- 20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - 1) Glorieta
 - J) Yates.
 - K) Cherry Canyon Eddy County
 - L) Potash---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
- 21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIRMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3.API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)------AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S - R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S - R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A-F. Sec 27 Unit A,B,C,F,G,H.

T 19S - R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S - R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S - R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S - R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S - R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S - R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S - R 30E

Sec 1 – Sec 36

T 21S - R 31E

Sec 1 – Sec 36

T 22S - R 28E

Sec 36 Unit A,H,I,P.

T 22S - R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S - R 30E

Sec 1 – Sec 36

T 22S - R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

T 23S - R 28E

Sec 1 Unit A

T 23S - R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S - R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S - R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S - R 30E


Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.


T 24S - R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S - R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.





District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 184040

COMMENTS

Operator:	OGRID:
Contango Resources, LLC	330447
111 E. 5TH STREET	Action Number:
FORT WORTH, TX 76102	184040
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM	2/9/2023

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 184040

CONDITIONS

Operator:	OGRID:
Contango Resources, LLC	330447
111 E. 5TH STREET	Action Number:
FORT WORTH, TX 76102	184040
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By		Condition Date
gcordero	None	2/9/2023